GENERAL INFORMATION

General Information in accordance with the Federal Communica-tions Commission Rules and Regulations, Volume II, Part 2.

1. Applicant:

Uniden America Corporation Engineering Services Office 216 John Street, P.O. Box 580 Lake City, South Carolina 29560 Mr. James R. Haynes, Chief Engineer

2. Equipment Identification:

FCC ID: AMWUT871 MODEL: HH985

3. Quantity: Quantity Production is planned.

4. Emission Type: 16K0F3E

5. Frequency Range: 156.025 - 157.425 MHz (TX) 156.025 - 163.275 MHz (RX)

6. Operating Power: 5/1 W

7. Max. Power Rating:

According to the section 80.215 of the FCC Rules.

8. DC voltage and current into Final Amplifying Device:

Refer to test data

9. Solid State Devices: Refer to Parts List/Tune-up Info

10. Circuit & Block Diagrams: Refer to EXHIBITS

11. Instruction Manual: Refer to User Manual

12. Tune-up Procedures: Refer to Parts List/Tune-up Info

13. Circuit Descriptions: Refer to Operational Description

Means for Frequency Stabilization Means for Attenuation of Spurious Emissions Means for Limiting Modulation

14. Description of Digital Modulation Techniques:

Not Applicable

15. Standard Test Conditions:

The following conditions and procedures were followed during testing of the equipment.

Room Temperature: 23 - 27 Degrees Celsius

Room Humidity: 40 - 60 %

Power Supply Voltage: 7.2 V DC

Note: Prior to testing, the unit is tuned-up according to the manufacturer's alignment procedure.

All presented data will represent the "worst case" parameter being measured.

16. Equipment Identification:

A drawing of the equipment's Identification Label and, its location are as shown in ID Label/Location Info.

17. Photographs:

External photographs of the unit as well as internal photos of the printed circuit boards are found in External Photos and Internal photographs.