## FCC ID: 2BDEUHP-330

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

## EDR:

| Modulation   | Channel<br>Freq.<br>(GHz) | Conduct<br>ed<br>power<br>(dBm) | Conducte<br>d power<br>(mW) | Tune-up<br>power<br>(dBm) | Max<br>tune-up<br>power<br>(dBm) | Max<br>tune-up<br>power<br>(mW) | Distance<br>(mm) | Result<br>calculatio<br>n | SAR<br>Exclusion<br>threshold | SAR test exclusion |
|--------------|---------------------------|---------------------------------|-----------------------------|---------------------------|----------------------------------|---------------------------------|------------------|---------------------------|-------------------------------|--------------------|
| GFSK         | 2.402                     | -0.633                          | 0.86                        | 0±1                       | 1.00                             | 1.26                            | <5               | 0.39023                   | 3.00                          | YES                |
|              | 2.441                     | -1.2                            | 0.76                        | -1±1                      | 0.00                             | 1.00                            | <5               | 0.31247                   | 3.00                          | YES                |
|              | 2.480                     | -0.33                           | 0.93                        | 0±1                       | 1.00                             | 1.26                            | <5               | 0.39651                   | 3.00                          | YES                |
| π<br>/4DQPSK | 2.402                     | 0.203                           | 1.05                        | 0±1                       | 1.00                             | 1.26                            | <5               | 0.39023                   | 3.00                          | YES                |
|              | 2.441                     | -0.415                          | 0.91                        | 0±1                       | 1.00                             | 1.26                            | <5               | 0.39338                   | 3.00                          | YES                |
|              | 2.480                     | 0.567                           | 1.14                        | 0±1                       | 1.00                             | 1.26                            | <5               | 0.39651                   | 3.00                          | YES                |

## Conclusion:

For the max result: 0.39651≤ FCC Limit 3.0 for 1g SAR.