

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.82	68.91	15.77	0.00	150.0	± 9.6 %
		Y	0.90	68.29	16.15		150.0	
		Z	0.77	68.38	15.37		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.32	75.39	17.14	3.29	80.0	± 9.6 %
		Y	100.00	131.59	34.49		80.0	
		Z	100.00	129.59	32.92		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.76	60.00	7.09	3.23	80.0	± 9.6 %
		Y	4.63	77.57	16.00		80.0	
		Z	0.74	60.00	7.79		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.79	60.00	6.50	3.23	80.0	± 9.6 %
		Y	1.49	65.34	10.90		80.0	
		Z	0.76	60.00	7.16		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.48	69.57	14.21	3.23	80.0	± 9.6 %
		Y	100.00	128.72	32.98		80.0	
		Z	100.00	125.35	30.81		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.76	60.00	7.02	3.23	80.0	± 9.6 %
		Y	2.92	72.75	14.31		80.0	
		Z	0.74	60.00	7.72		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.79	60.00	6.46	3.23	80.0	± 9.6 %
		Y	1.30	63.97	10.25		80.0	
		Z	0.76	60.00	7.11		80.0	
10467-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.57	70.35	14.56	3.23	80.0	± 9.6 %
		Y	100.00	129.06	33.13		80.0	
		Z	100.00	125.82	31.02		80.0	
10468-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.76	60.00	7.04	3.23	80.0	± 9.6 %
		Y	3.25	73.90	14.73		80.0	
		Z	0.74	60.00	7.74		80.0	
10469-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.79	60.00	6.46	3.23	80.0	± 9.6 %
		Y	1.30	64.00	10.26		80.0	
		Z	0.76	60.00	7.11		80.0	
10470-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.56	70.33	14.55	3.23	80.0	± 9.6 %
		Y	100.00	129.11	33.14		80.0	
		Z	100.00	125.84	31.01		80.0	
10471-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.76	60.00	7.03	3.23	80.0	± 9.6 %
		Y	3.21	73.75	14.66		80.0	
		Z	0.74	60.00	7.73		80.0	
10472-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.79	60.00	6.44	3.23	80.0	± 9.6 %
		Y	1.29	63.92	10.21		80.0	
		Z	0.76	60.00	7.09		80.0	
10473-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.56	70.28	14.52	3.23	80.0	± 9.6 %
		Y	100.00	129.06	33.12		80.0	
		Z	100.00	125.78	30.99		80.0	
10474-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.76	60.00	7.02	3.23	80.0	± 9.6 %
		Y	3.17	73.64	14.62		80.0	
		Z	0.74	60.00	7.73		80.0	
10475-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.78	60.00	6.45	3.23	80.0	± 9.6 %
		Y	1.29	63.89	10.20		80.0	
		Z	0.76	60.00	7.09		80.0	

10477-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.76	60.00	7.00	3.23	80.0	± 9.6 %
		Y	2.91	72.72	14.27		80.0	
		Z	0.74	60.00	7.70		80.0	
10478-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.79	60.00	6.43	3.23	80.0	± 9.6 %
		Y	1.28	63.82	10.16		80.0	
		Z	0.76	60.00	7.08		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.36	78.87	19.25	3.23	80.0	± 9.6 %
		Y	6.72	85.93	23.37		80.0	
		Z	31.53	108.71	28.80		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.01	65.44	11.92	3.23	80.0	± 9.6 %
		Y	7.23	81.86	20.03		80.0	
		Z	6.32	79.43	17.87		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.64	62.93	10.36	3.23	80.0	± 9.6 %
		Y	5.72	78.02	18.32		80.0	
		Z	3.41	71.49	14.62		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.29	62.41	10.80	2.23	80.0	± 9.6 %
		Y	3.64	76.21	18.93		80.0	
		Z	1.66	65.83	12.91		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.52	61.14	9.55	2.23	80.0	± 9.6 %
		Y	4.09	73.43	17.03		80.0	
		Z	2.32	66.35	12.70		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.52	60.89	9.42	2.23	80.0	± 9.6 %
		Y	3.80	72.18	16.53		80.0	
		Z	2.19	65.41	12.27		80.0	
10485-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.96	67.14	14.58	2.23	80.0	± 9.6 %
		Y	3.64	76.20	19.95		80.0	
		Z	2.47	70.93	16.63		80.0	
10486-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.93	63.65	12.21	2.23	80.0	± 9.6 %
		Y	3.34	71.00	17.20		80.0	
		Z	2.25	65.99	13.71		80.0	
10487-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.95	63.41	12.07	2.23	80.0	± 9.6 %
		Y	3.31	70.45	16.94		80.0	
		Z	2.25	65.61	13.50		80.0	
10488-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.57	68.84	16.72	2.23	80.0	± 9.6 %
		Y	3.64	73.87	19.67		80.0	
		Z	2.88	71.05	17.92		80.0	
10489-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.71	66.42	15.54	2.23	80.0	± 9.6 %
		Y	3.41	69.51	17.78		80.0	
		Z	2.89	67.77	16.40		80.0	
10490-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.80	66.35	15.53	2.23	80.0	± 9.6 %
		Y	3.50	69.28	17.68		80.0	
		Z	2.97	67.63	16.34		80.0	
10491-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.93	68.13	16.75	2.23	80.0	± 9.6 %
		Y	3.79	71.78	18.88		80.0	
		Z	3.14	69.61	17.57		80.0	
10492-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.14	66.26	16.05	2.23	80.0	± 9.6 %
		Y	3.72	68.46	17.58		80.0	
		Z	3.26	67.14	16.60		80.0	

10493-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.20	66.19	16.02	2.23	80.0	± 9.6 %
		Y	3.78	68.30	17.52		80.0	
		Z	3.32	67.03	16.55		80.0	
10494-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.09	69.16	17.09	2.23	80.0	± 9.6 %
		Y	4.18	73.66	19.49		80.0	
		Z	3.38	70.96	18.01		80.0	
10495-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.16	66.52	16.26	2.23	80.0	± 9.6 %
		Y	3.75	68.86	17.79		80.0	
		Z	3.28	67.44	16.81		80.0	
10496-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.25	66.39	16.25	2.23	80.0	± 9.6 %
		Y	3.82	68.54	17.67		80.0	
		Z	3.36	67.23	16.76		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	0.98	60.00	8.08	2.23	80.0	± 9.6 %
		Y	2.67	71.65	16.05		80.0	
		Z	0.96	60.00	8.56		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.18	60.00	7.01	2.23	80.0	± 9.6 %
		Y	1.73	63.28	11.10		80.0	
		Z	1.15	60.00	7.42		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.20	60.00	6.87	2.23	80.0	± 9.6 %
		Y	1.65	62.50	10.55		80.0	
		Z	1.17	60.00	7.27		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.22	67.95	15.51	2.23	80.0	± 9.6 %
		Y	3.54	74.72	19.65		80.0	
		Z	2.63	70.95	17.16		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.29	65.10	13.66	2.23	80.0	± 9.6 %
		Y	3.38	70.39	17.41		80.0	
		Z	2.58	67.13	14.94		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.32	64.94	13.52	2.23	80.0	± 9.6 %
		Y	3.43	70.21	17.27		80.0	
		Z	2.61	66.92	14.77		80.0	
10503-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.54	68.66	16.62	2.23	80.0	± 9.6 %
		Y	3.60	73.66	19.57		80.0	
		Z	2.84	70.82	17.80		80.0	
10504-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.69	66.32	15.48	2.23	80.0	± 9.6 %
		Y	3.40	69.42	17.73		80.0	
		Z	2.87	67.65	16.32		80.0	
10505-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.78	66.26	15.46	2.23	80.0	± 9.6 %
		Y	3.48	69.19	17.63		80.0	
		Z	2.96	67.52	16.27		80.0	
10506-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.07	69.03	17.01	2.23	80.0	± 9.6 %
		Y	4.15	73.51	19.42		80.0	
		Z	3.35	70.80	17.93		80.0	
10507-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.15	66.46	16.22	2.23	80.0	± 9.6 %
		Y	3.73	68.80	17.76		80.0	
		Z	3.26	67.37	16.77		80.0	

10508-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.24	66.32	16.20	2.23	80.0	± 9.6 %
		Y	3.81	68.47	17.63		80.0	
		Z	3.35	67.15	16.71		80.0	
10509-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.51	68.36	16.83	2.23	80.0	± 9.6 %
		Y	4.41	71.84	18.68		80.0	
		Z	3.72	69.67	17.51		80.0	
10510-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.65	66.40	16.44	2.23	80.0	± 9.6 %
		Y	4.20	68.42	17.64		80.0	
		Z	3.74	67.11	16.83		80.0	
10511-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.72	66.27	16.42	2.23	80.0	± 9.6 %
		Y	4.25	68.13	17.55		80.0	
		Z	3.81	66.92	16.79		80.0	
10512-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.53	69.27	17.06	2.23	80.0	± 9.6 %
		Y	4.71	73.81	19.35		80.0	
		Z	3.83	70.97	17.89		80.0	
10513-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.53	66.49	16.47	2.23	80.0	± 9.6 %
		Y	4.09	68.73	17.78		80.0	
		Z	3.62	67.27	16.91		80.0	
10514-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.58	66.23	16.41	2.23	80.0	± 9.6 %
		Y	4.11	68.25	17.62		80.0	
		Z	3.67	66.92	16.81		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.86	62.95	14.53	0.00	150.0	± 9.6 %
		Y	0.96	63.14	14.68		150.0	
		Z	0.84	62.85	14.32		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.68	75.09	17.93	0.00	150.0	± 9.6 %
		Y	0.60	70.79	17.39		150.0	
		Z	0.59	73.58	17.02		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.71	65.13	15.13	0.00	150.0	± 9.6 %
		Y	0.81	65.08	15.31		150.0	
		Z	0.69	64.87	14.81		150.0	
10518-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.31	66.61	16.23	0.00	150.0	± 9.6 %
		Y	4.51	66.70	16.19		150.0	
		Z	4.30	66.61	16.12		150.0	
10519-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.46	66.79	16.33	0.00	150.0	± 9.6 %
		Y	4.69	66.93	16.31		150.0	
		Z	4.45	66.80	16.22		150.0	
10520-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.32	66.72	16.24	0.00	150.0	± 9.6 %
		Y	4.55	66.89	16.23		150.0	
		Z	4.31	66.74	16.13		150.0	
10521-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.25	66.68	16.22	0.00	150.0	± 9.6 %
		Y	4.48	66.88	16.21		150.0	
		Z	4.24	66.71	16.11		150.0	
10522-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.30	66.84	16.33	0.00	150.0	± 9.6 %
		Y	4.54	66.98	16.30		150.0	
		Z	4.30	66.85	16.22		150.0	

10523-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.22	66.79	16.22	0.00	150.0	± 9.6 %
		Y	4.42	66.85	16.15		150.0	
		Z	4.21	66.79	16.10		150.0	
10524-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.25	66.78	16.31	0.00	150.0	± 9.6 %
		Y	4.48	66.90	16.27		150.0	
		Z	4.24	66.79	16.19		150.0	
10525-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.28	65.85	15.93	0.00	150.0	± 9.6 %
		Y	4.47	65.95	15.86		150.0	
		Z	4.27	65.86	15.81		150.0	
10526-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.41	66.15	16.05	0.00	150.0	± 9.6 %
		Y	4.64	66.31	16.00		150.0	
		Z	4.40	66.17	15.93		150.0	
10527-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.34	66.11	15.98	0.00	150.0	± 9.6 %
		Y	4.56	66.27	15.95		150.0	
		Z	4.33	66.13	15.87		150.0	
10528-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.35	66.13	16.02	0.00	150.0	± 9.6 %
		Y	4.58	66.29	15.98		150.0	
		Z	4.34	66.15	15.90		150.0	
10529-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.35	66.13	16.02	0.00	150.0	± 9.6 %
		Y	4.58	66.29	15.98		150.0	
		Z	4.34	66.15	15.90		150.0	
10531-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.32	66.16	16.00	0.00	150.0	± 9.6 %
		Y	4.57	66.39	15.99		150.0	
		Z	4.31	66.19	15.89		150.0	
10532-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.20	66.01	15.92	0.00	150.0	± 9.6 %
		Y	4.43	66.24	15.92		150.0	
		Z	4.19	66.04	15.81		150.0	
10533-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.36	66.21	16.02	0.00	150.0	± 9.6 %
		Y	4.59	66.34	15.97		150.0	
		Z	4.35	66.22	15.90		150.0	
10534-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	4.94	66.18	16.13	0.00	150.0	± 9.6 %
		Y	5.11	66.38	16.03		150.0	
		Z	4.91	66.20	15.99		150.0	
10535-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	4.99	66.35	16.21	0.00	150.0	± 9.6 %
		Y	5.18	66.56	16.12		150.0	
		Z	4.97	66.36	16.07		150.0	
10536-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.87	66.32	16.17	0.00	150.0	± 9.6 %
		Y	5.05	66.51	16.07		150.0	
		Z	4.85	66.34	16.04		150.0	
10537-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	4.94	66.34	16.18	0.00	150.0	± 9.6 %
		Y	5.10	66.48	16.06		150.0	
		Z	4.91	66.31	16.03		150.0	
10538-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.01	66.30	16.21	0.00	150.0	± 9.6 %
		Y	5.19	66.49	16.11		150.0	
		Z	4.98	66.30	16.06		150.0	
10540-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	4.93	66.22	16.18	0.00	150.0	± 9.6 %
		Y	5.13	66.52	16.13		150.0	
		Z	4.91	66.26	16.06		150.0	

10541-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	4.90	66.09	16.10	0.00	150.0	± 9.6 %
		Y	5.10	66.38	16.06		150.0	
		Z	4.88	66.13	15.98		150.0	
10542-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.07	66.24	16.19	0.00	150.0	± 9.6 %
		Y	5.25	66.45	16.11		150.0	
		Z	5.04	66.26	16.06		150.0	
10543-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.16	66.37	16.29	0.00	150.0	± 9.6 %
		Y	5.33	66.48	16.14		150.0	
		Z	5.12	66.32	16.12		150.0	
10544-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.28	66.21	16.10	0.00	150.0	± 9.6 %
		Y	5.42	66.50	16.03		150.0	
		Z	5.25	66.26	15.98		150.0	
10545-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.51	66.84	16.38	0.00	150.0	± 9.6 %
		Y	5.61	66.90	16.18		150.0	
		Z	5.45	66.77	16.19		150.0	
10546-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.32	66.36	16.14	0.00	150.0	± 9.6 %
		Y	5.48	66.70	16.10		150.0	
		Z	5.29	66.40	16.02		150.0	
10547-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.43	66.58	16.25	0.00	150.0	± 9.6 %
		Y	5.55	66.74	16.11		150.0	
		Z	5.37	66.52	16.07		150.0	
10548-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.67	67.49	16.67	0.00	150.0	± 9.6 %
		Y	5.79	67.62	16.52		150.0	
		Z	5.59	67.37	16.46		150.0	
10550-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.44	66.73	16.35	0.00	150.0	± 9.6 %
		Y	5.51	66.72	16.12		150.0	
		Z	5.36	66.62	16.14		150.0	
10551-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.31	66.31	16.10	0.00	150.0	± 9.6 %
		Y	5.52	66.76	16.10		150.0	
		Z	5.30	66.41	15.99		150.0	
10552-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.28	66.30	16.09	0.00	150.0	± 9.6 %
		Y	5.44	66.57	16.01		150.0	
		Z	5.25	66.34	15.96		150.0	
10553-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.34	66.26	16.10	0.00	150.0	± 9.6 %
		Y	5.52	66.60	16.06		150.0	
		Z	5.31	66.32	15.98		150.0	
10554-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.72	66.58	16.20	0.00	150.0	± 9.6 %
		Y	5.83	66.86	16.12		150.0	
		Z	5.67	66.61	16.06		150.0	
10555-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.84	66.90	16.34	0.00	150.0	± 9.6 %
		Y	5.95	67.15	16.24		150.0	
		Z	5.79	66.90	16.19		150.0	
10556-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.87	66.98	16.38	0.00	150.0	± 9.6 %
		Y	5.98	67.20	16.26		150.0	
		Z	5.82	66.99	16.23		150.0	
10557-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.81	66.79	16.30	0.00	150.0	± 9.6 %
		Y	5.94	67.10	16.23		150.0	
		Z	5.77	66.83	16.17		150.0	

10558-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.82	66.86	16.35	0.00	150.0	± 9.6 %
		Y	5.99	67.26	16.33		150.0	
		Z	5.79	66.94	16.24		150.0	
10560-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.84	66.78	16.35	0.00	150.0	± 9.6 %
		Y	5.98	67.11	16.29		150.0	
		Z	5.80	66.82	16.22		150.0	
10561-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.78	66.81	16.39	0.00	150.0	± 9.6 %
		Y	5.91	67.08	16.31		150.0	
		Z	5.74	66.84	16.26		150.0	
10562-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.83	66.94	16.46	0.00	150.0	± 9.6 %
		Y	6.02	67.44	16.49		150.0	
		Z	5.80	67.03	16.35		150.0	
10563-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	5.98	67.08	16.50	0.00	150.0	± 9.6 %
		Y	6.21	67.62	16.54		150.0	
		Z	5.91	67.01	16.31		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.63	66.62	16.36	0.46	150.0	± 9.6 %
		Y	4.84	66.79	16.36		150.0	
		Z	4.61	66.63	16.24		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.83	67.05	16.69	0.46	150.0	± 9.6 %
		Y	5.06	67.22	16.67		150.0	
		Z	4.82	67.07	16.58		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.66	66.85	16.48	0.46	150.0	± 9.6 %
		Y	4.90	67.07	16.49		150.0	
		Z	4.65	66.88	16.38		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.70	67.27	16.87	0.46	150.0	± 9.6 %
		Y	4.93	67.45	16.84		150.0	
		Z	4.69	67.33	16.78		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.56	66.58	16.20	0.46	150.0	± 9.6 %
		Y	4.81	66.86	16.28		150.0	
		Z	4.55	66.62	16.10		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.68	67.48	17.00	0.46	150.0	± 9.6 %
		Y	4.88	67.55	16.91		150.0	
		Z	4.67	67.53	16.91		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.69	67.30	16.91	0.46	150.0	± 9.6 %
		Y	4.92	67.39	16.83		150.0	
		Z	4.68	67.31	16.79		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.00	63.45	14.91	0.46	130.0	± 9.6 %
		Y	1.13	64.20	15.58		130.0	
		Z	0.98	63.57	14.96		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.01	64.01	15.28	0.46	130.0	± 9.6 %
		Y	1.14	64.75	15.94		130.0	
		Z	0.99	64.16	15.34		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	1.87	85.75	21.98	0.46	130.0	± 9.6 %
		Y	1.92	86.55	24.04		130.0	
		Z	2.25	89.51	23.31		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.08	70.06	18.36	0.46	130.0	± 9.6 %
		Y	1.22	70.33	18.86		130.0	
		Z	1.09	70.58	18.62		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.39	66.32	16.32	0.46	130.0	± 9.6 %
		Y	4.62	66.58	16.43		130.0	
		Z	4.39	66.40	16.27		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.42	66.53	16.41	0.46	130.0	± 9.6 %
		Y	4.65	66.74	16.49		130.0	
		Z	4.42	66.60	16.36		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.59	66.78	16.57	0.46	130.0	± 9.6 %
		Y	4.85	67.03	16.66		130.0	
		Z	4.59	66.86	16.52		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.49	66.94	16.68	0.46	130.0	± 9.6 %
		Y	4.74	67.18	16.75		130.0	
		Z	4.50	67.02	16.64		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.24	66.07	15.88	0.46	130.0	± 9.6 %
		Y	4.51	66.48	16.08		130.0	
		Z	4.24	66.15	15.83		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.28	66.14	15.91	0.46	130.0	± 9.6 %
		Y	4.56	66.53	16.11		130.0	
		Z	4.29	66.22	15.86		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.40	66.99	16.63	0.46	130.0	± 9.6 %
		Y	4.64	67.22	16.70		130.0	
		Z	4.40	67.08	16.59		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.17	65.84	15.66	0.46	130.0	± 9.6 %
		Y	4.45	66.25	15.88		130.0	
		Z	4.18	65.90	15.60		130.0	
10583-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.39	66.32	16.32	0.46	130.0	± 9.6 %
		Y	4.62	66.58	16.43		130.0	
		Z	4.39	66.40	16.27		130.0	
10584-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.42	66.53	16.41	0.46	130.0	± 9.6 %
		Y	4.65	66.74	16.49		130.0	
		Z	4.42	66.60	16.36		130.0	
10585-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.59	66.78	16.57	0.46	130.0	± 9.6 %
		Y	4.85	67.03	16.66		130.0	
		Z	4.59	66.86	16.52		130.0	
10586-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.49	66.94	16.68	0.46	130.0	± 9.6 %
		Y	4.74	67.18	16.75		130.0	
		Z	4.50	67.02	16.64		130.0	
10587-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.24	66.07	15.88	0.46	130.0	± 9.6 %
		Y	4.51	66.48	16.08		130.0	
		Z	4.24	66.15	15.83		130.0	
10588-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.28	66.14	15.91	0.46	130.0	± 9.6 %
		Y	4.56	66.53	16.11		130.0	
		Z	4.29	66.22	15.86		130.0	
10589-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.40	66.99	16.63	0.46	130.0	± 9.6 %
		Y	4.64	67.22	16.70		130.0	
		Z	4.40	67.08	16.59		130.0	
10590-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.17	65.84	15.66	0.46	130.0	± 9.6 %
		Y	4.45	66.25	15.88		130.0	
		Z	4.18	65.90	15.60		130.0	

10591-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.55	66.42	16.46	0.46	130.0	± 9.6 %
		Y	4.78	66.64	16.53		130.0	
		Z	4.55	66.49	16.40		130.0	
10592-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.67	66.72	16.59	0.46	130.0	± 9.6 %
		Y	4.93	66.98	16.66		130.0	
		Z	4.68	66.80	16.53		130.0	
10593-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.59	66.59	16.43	0.46	130.0	± 9.6 %
		Y	4.85	66.88	16.54		130.0	
		Z	4.59	66.67	16.38		130.0	
10594-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.64	66.77	16.61	0.46	130.0	± 9.6 %
		Y	4.90	67.05	16.69		130.0	
		Z	4.65	66.86	16.56		130.0	
10595-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.61	66.75	16.51	0.46	130.0	± 9.6 %
		Y	4.87	67.00	16.59		130.0	
		Z	4.61	66.82	16.45		130.0	
10596-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.54	66.71	16.50	0.46	130.0	± 9.6 %
		Y	4.80	67.00	16.60		130.0	
		Z	4.54	66.79	16.44		130.0	
10597-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.49	66.57	16.34	0.46	130.0	± 9.6 %
		Y	4.75	66.90	16.48		130.0	
		Z	4.49	66.65	16.29		130.0	
10598-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.48	66.81	16.63	0.46	130.0	± 9.6 %
		Y	4.73	67.12	16.73		130.0	
		Z	4.49	66.91	16.58		130.0	
10599-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.31	67.13	16.85	0.46	130.0	± 9.6 %
		Y	5.45	67.20	16.74		130.0	
		Z	5.25	67.05	16.69		130.0	
10600-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.48	67.76	17.14	0.46	130.0	± 9.6 %
		Y	5.57	67.58	16.91		130.0	
		Z	5.39	67.54	16.90		130.0	
10601-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.31	67.28	16.91	0.46	130.0	± 9.6 %
		Y	5.47	67.34	16.80		130.0	
		Z	5.27	67.22	16.76		130.0	
10602-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.43	67.41	16.89	0.46	130.0	± 9.6 %
		Y	5.56	67.39	16.75		130.0	
		Z	5.40	67.36	16.75		130.0	
10603-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.54	67.82	17.25	0.46	130.0	± 9.6 %
		Y	5.64	67.67	17.02		130.0	
		Z	5.49	67.76	17.09		130.0	
10604-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.42	67.47	17.05	0.46	130.0	± 9.6 %
		Y	5.46	67.19	16.76		130.0	
		Z	5.37	67.38	16.88		130.0	
10605-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.43	67.47	17.04	0.46	130.0	± 9.6 %
		Y	5.56	67.49	16.91		130.0	
		Z	5.37	67.38	16.87		130.0	
10606-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.17	66.77	16.54	0.46	130.0	± 9.6 %
		Y	5.31	66.83	16.45		130.0	
		Z	5.12	66.68	16.37		130.0	

10607-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.40	65.75	16.09	0.46	130.0	± 9.6 %
		Y	4.62	65.97	16.16		130.0	
		Z	4.40	65.83	16.04		130.0	
10608-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.54	66.09	16.24	0.46	130.0	± 9.6 %
		Y	4.80	66.37	16.32		130.0	
		Z	4.55	66.18	16.20		130.0	
10609-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.43	65.91	16.05	0.46	130.0	± 9.6 %
		Y	4.69	66.22	16.16		130.0	
		Z	4.44	66.00	16.00		130.0	
10610-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.49	66.09	16.23	0.46	130.0	± 9.6 %
		Y	4.74	66.38	16.32		130.0	
		Z	4.49	66.18	16.19		130.0	
10611-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.40	65.88	16.06	0.46	130.0	± 9.6 %
		Y	4.66	66.19	16.17		130.0	
		Z	4.40	65.97	16.02		130.0	
10612-AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.39	66.01	16.10	0.46	130.0	± 9.6 %
		Y	4.66	66.35	16.22		130.0	
		Z	4.40	66.10	16.06		130.0	
10613-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.38	65.82	15.94	0.46	130.0	± 9.6 %
		Y	4.67	66.22	16.10		130.0	
		Z	4.39	65.92	15.90		130.0	
10614-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.35	66.06	16.21	0.46	130.0	± 9.6 %
		Y	4.61	66.40	16.32		130.0	
		Z	4.36	66.17	16.17		130.0	
10615-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.39	65.69	15.81	0.46	130.0	± 9.6 %
		Y	4.66	66.03	15.96		130.0	
		Z	4.39	65.77	15.76		130.0	
10616-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.07	66.15	16.34	0.46	130.0	± 9.6 %
		Y	5.27	66.44	16.35		130.0	
		Z	5.05	66.21	16.25		130.0	
10617-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.14	66.37	16.43	0.46	130.0	± 9.6 %
		Y	5.34	66.62	16.41		130.0	
		Z	5.12	66.42	16.33		130.0	
10618-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.03	66.38	16.45	0.46	130.0	± 9.6 %
		Y	5.22	66.62	16.43		130.0	
		Z	5.02	66.45	16.36		130.0	
10619-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.07	66.24	16.31	0.46	130.0	± 9.6 %
		Y	5.24	66.43	16.27		130.0	
		Z	5.03	66.23	16.18		130.0	
10620-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.13	66.23	16.35	0.46	130.0	± 9.6 %
		Y	5.33	66.47	16.34		130.0	
		Z	5.11	66.25	16.24		130.0	
10621-AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.12	66.28	16.51	0.46	130.0	± 9.6 %
		Y	5.33	66.60	16.51		130.0	
		Z	5.11	66.38	16.44		130.0	
10622-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.11	66.38	16.55	0.46	130.0	± 9.6 %
		Y	5.34	66.76	16.59		130.0	
		Z	5.11	66.50	16.49		130.0	

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	4.99	65.86	16.14	0.46	130.0	± 9.6 %
		Y	5.22	66.30	16.24		130.0	
		Z	4.98	65.96	16.08		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.20	66.20	16.38	0.46	130.0	± 9.6 %
		Y	5.41	66.49	16.39		130.0	
		Z	5.19	66.26	16.30		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.30	66.37	16.54	0.46	130.0	± 9.6 %
		Y	5.75	67.41	16.90		130.0	
		Z	5.33	66.58	16.52		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.40	66.14	16.28	0.46	130.0	± 9.6 %
		Y	5.57	66.51	16.31		130.0	
		Z	5.38	66.23	16.21		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.71	67.03	16.70	0.46	130.0	± 9.6 %
		Y	5.80	67.06	16.54		130.0	
		Z	5.65	66.96	16.54		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.40	66.15	16.18	0.46	130.0	± 9.6 %
		Y	5.60	66.59	16.25		130.0	
		Z	5.38	66.23	16.10		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.55	66.49	16.35	0.46	130.0	± 9.6 %
		Y	5.67	66.64	16.26		130.0	
		Z	5.49	66.42	16.19		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	5.95	67.89	17.05	0.46	130.0	± 9.6 %
		Y	6.08	68.07	16.98		130.0	
		Z	5.84	67.71	16.83		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.77	67.48	17.05	0.46	130.0	± 9.6 %
		Y	5.99	67.89	17.07		130.0	
		Z	5.74	67.53	16.95		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.72	67.25	16.96	0.46	130.0	± 9.6 %
		Y	5.77	67.11	16.70		130.0	
		Z	5.64	67.12	16.77		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.44	66.28	16.29	0.46	130.0	± 9.6 %
		Y	5.66	66.76	16.36		130.0	
		Z	5.44	66.43	16.24		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.44	66.38	16.39	0.46	130.0	± 9.6 %
		Y	5.64	66.78	16.43		130.0	
		Z	5.43	66.48	16.32		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.30	65.61	15.72	0.46	130.0	± 9.6 %
		Y	5.53	66.14	15.85		130.0	
		Z	5.29	65.70	15.64		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.86	66.55	16.40	0.46	130.0	± 9.6 %
		Y	5.98	66.87	16.39		130.0	
		Z	5.82	66.61	16.30		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.02	66.98	16.61	0.46	130.0	± 9.6 %
		Y	6.13	67.25	16.56		130.0	
		Z	5.97	67.00	16.48		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.03	67.01	16.60	0.46	130.0	± 9.6 %
		Y	6.13	67.22	16.53		130.0	
		Z	5.97	67.00	16.46		130.0	

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	5.96	66.80	16.53	0.46	130.0	± 9.6 %
		Y	6.11	67.17	16.55		130.0	
		Z	5.93	66.87	16.44		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	5.92	66.70	16.42	0.46	130.0	± 9.6 %
		Y	6.12	67.19	16.50		130.0	
		Z	5.91	66.82	16.35		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.06	66.91	16.55	0.46	130.0	± 9.6 %
		Y	6.16	67.10	16.47		130.0	
		Z	6.01	66.89	16.41		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.04	66.98	16.76	0.46	130.0	± 9.6 %
		Y	6.20	67.33	16.75		130.0	
		Z	6.02	67.07	16.68		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.90	66.69	16.50	0.46	130.0	± 9.6 %
		Y	6.04	67.03	16.51		130.0	
		Z	5.87	66.78	16.42		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	5.95	66.86	16.60	0.46	130.0	± 9.6 %
		Y	6.19	67.50	16.76		130.0	
		Z	5.94	66.99	16.54		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.44	67.99	17.14	0.46	130.0	± 9.6 %
		Y	6.47	67.94	16.94		130.0	
		Z	6.16	67.33	16.68		130.0	
10646-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	7.50	90.48	30.44	9.30	60.0	± 9.6 %
		Y	17.43	112.38	39.34		60.0	
		Z	9.26	96.56	33.29		60.0	
10647-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	6.74	88.72	29.93	9.30	60.0	± 9.6 %
		Y	14.54	108.61	38.31		60.0	
		Z	8.10	94.14	32.60		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.39	60.00	6.32	0.00	150.0	± 9.6 %
		Y	0.67	63.31	10.55		150.0	
		Z	0.38	60.00	6.43		150.0	
10652-AAB	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.10	65.49	15.51	2.23	80.0	± 9.6 %
		Y	3.52	66.85	16.73		80.0	
		Z	3.18	66.07	15.91		80.0	
10653-AAB	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.70	65.11	16.04	2.23	80.0	± 9.6 %
		Y	4.03	66.07	16.78		80.0	
		Z	3.73	65.44	16.24		80.0	
10654-AAB	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	3.73	64.77	16.12	2.23	80.0	± 9.6 %
		Y	4.00	65.69	16.76		80.0	
		Z	3.74	65.07	16.28		80.0	
10655-AAB	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	3.81	64.71	16.17	2.23	80.0	± 9.6 %
		Y	4.06	65.68	16.79		80.0	
		Z	3.81	65.01	16.32		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	3.06	66.59	11.16	10.00	50.0	± 9.6 %
		Y	100.00	111.68	26.09		50.0	
		Z	3.93	69.81	12.66		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	1.63	63.81	8.65	6.99	60.0	± 9.6 %
		Y	100.00	113.13	25.67		60.0	
		Z	2.52	68.36	10.82		60.0	

10660-AAA	Pulse Waveform (200Hz, 40%)	X	0.57	60.00	5.26	3.98	80.0	± 9.6 %
		Y	100.00	118.24	26.52		80.0	
		Z	0.68	61.70	6.30		80.0	
10661-AAA	Pulse Waveform (200Hz, 60%)	X	0.32	60.00	3.83	2.22	100.0	± 9.6 %
		Y	100.00	125.46	28.15		100.0	
		Z	0.29	60.00	3.83		100.0	
10662-AAA	Pulse Waveform (200Hz, 80%)	X	7.43	367.15	53.93	0.97	120.0	± 9.6 %
		Y	100.00	135.73	30.13		120.0	
		Z	0.00	228.51	107.76		120.0	

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

APPENDIX D: SAR TISSUE SPECIFICATIONS

Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity ϵ' can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

Table D-I
Composition of the Tissue Equivalent Matter

Frequency (MHz)	750	750	835	835	1750	1750	1900	1900	2450	2450	5200-5800	5200-5800
Tissue	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Ingredients (% by weight)												
Bactericide	See page 2-3	See page 2	0.1	0.1					See page 4		See page 5	
DGBE					47	31	44.92	29.44		26.7		
HEC			1	1								
NaCl			1.45	0.94	0.4	0.2	0.18	0.39		0.1		
Sucrose			57	44.9								
Polysorbate (Tween) 80												20
Water			40.45	53.06	52.6	68.8	54.9	70.17		73.2		80

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 07/08/18 - 07/23/18	DUT Type: Portable Handset			APPENDIX D: Page 1 of 5

2 Composition / Information on ingredients

The Item is composed of the following ingredients:

H ₂ O	Water, 35 – 58%
Sucrose	Sugar, white, refined, 40 – 60%
NaCl	Sodium Chloride, 0 – 6%
Hydroxyethyl-cellulose	Medium Viscosity (CAS# 9004-62-0), <0.3%
Preventol-D7	Preservative: aqueous preparation, (CAS# 55965-84-9), containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyl-3(2H)-isothiazolone, 0.1 – 0.7%
Relevant for safety; Refer to the respective Safety Data Sheet*.	

Figure D-1

Composition of 750 MHz Head and Body Tissue Equivalent Matter

Note: 750MHz liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland
Phone +41 44 245 9700, Fax +41 44 245 9779
info@speag.com, http://www.speag.com

Measurement Certificate / Material Test

Item Name	Body Tissue Simulating Liquid (MSL750V2)
Product No.	SL AAM 075 AA (Batch: 170608-1)
Manufacturer	SPEAG

Measurement Method

TSL dielectric parameters measured using calibrated DAK probe.

Setup Validation

Validation results were within $\pm 2.5\%$ towards the target values of Methanol.

Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

Test Condition

Ambient	Environment temperatur (22 ± 3)°C and humidity < 70%.
TSL Temperature	22°C
Test Date	20-Jun-17
Operator	CL

Additional Information

TSL Density	1.212 g/cm ³
TSL Heat-capacity	3.006 kJ/(kg·K)

f [MHz]	Measured			Target		Diff.to Target [%]	
	e'	e''	sigma	eps	sigma	Δ-eps	Δ-sigma
600	57.3	25.02	0.84	56.1	0.95	2.2	-12.2
625	57.1	24.67	0.86	56.0	0.95	1.9	-10.1
650	56.8	24.32	0.88	55.9	0.96	1.6	-8.0
675	56.6	24.02	0.90	55.8	0.96	1.3	-5.8
700	56.3	23.71	0.92	55.7	0.96	1.1	-3.8
725	56.1	23.48	0.95	55.6	0.96	0.8	-1.5
750	55.9	23.25	0.97	55.5	0.96	0.6	0.7
775	55.6	23.04	0.99	55.4	0.97	0.3	2.9
800	55.4	22.82	1.02	55.3	0.97	0.1	5.0
825	55.2	22.65	1.04	55.2	0.98	-0.1	6.3
838	55.1	22.56	1.05	55.2	0.98	-0.3	6.9
850	54.9	22.47	1.06	55.2	0.99	-0.4	7.5
875	54.7	22.34	1.09	55.1	1.02	-0.7	6.7
900	54.5	22.21	1.11	55.0	1.05	-0.9	5.9
925	54.3	22.08	1.14	55.0	1.06	-1.3	6.9
950	54.1	21.95	1.16	54.9	1.08	-1.6	7.9
975	53.8	21.86	1.19	54.9	1.09	-1.9	9.1
1000	53.6	21.76	1.21	54.8	1.10	-2.2	10.2





Figure D-2

750MHz Body Tissue Equivalent Matter

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 07/08/18 - 07/23/18	DUT Type: Portable Handset			APPENDIX D: Page 2 of 5

Measurement Certificate / Material Test

Item Name **Head Tissue Simulating Liquid (HSL750V2)**
 Product No. SL AAH 075 AA (Batch: 170612-4)
 Manufacturer **SPEAG**

Measurement Method

TSL dielectric parameters measured using calibrated DAK probe.

Setup Validation

Validation results were within $\pm 2.5\%$ towards the target values of Methanol.

Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

Test Condition

Ambient Environment temperatur ($22 \pm 3^\circ\text{C}$ and humidity $< 70\%$).
 TSL Temperature 22°C
 Test Date 20-Jun-17
 Operator CL

Additional Information

TSL Density 1.284 g/cm^3
 TSL Heat-capacity $2.701 \text{ kJ/(kg}^\circ\text{K)}$

f [MHz]	Measured			Target		Diff.to Target [%]	
	e'	e''	sigma	eps	sigma	$\Delta\text{-eps}$	$\Delta\text{-sigma}$
600	45.6	22.97	0.77	42.7	0.88	6.7	-13.1
625	45.2	22.73	0.79	42.6	0.88	6.2	-10.6
650	44.9	22.49	0.81	42.5	0.89	5.6	-8.2
675	44.5	22.27	0.84	42.3	0.89	5.1	-5.8
700	44.2	22.05	0.86	42.2	0.89	4.6	-3.5
725	43.8	21.88	0.88	42.1	0.89	4.2	-1.0
750	43.5	21.72	0.91	41.9	0.89	3.8	1.4
775	43.2	21.55	0.93	41.8	0.90	3.4	3.7
800	42.9	21.38	0.95	41.7	0.90	2.9	6.0
825	42.6	21.24	0.97	41.6	0.91	2.4	7.5
838	42.5	21.17	0.99	41.5	0.91	2.2	8.2
850	42.3	21.09	1.00	41.5	0.92	2.0	8.9
875	42.0	20.98	1.02	41.5	0.94	1.2	8.3
900	41.7	20.87	1.05	41.5	0.97	0.5	7.7
925	41.5	20.76	1.07	41.5	0.98	0.0	8.7
950	41.2	20.64	1.09	41.4	0.99	-0.6	9.7
975	40.9	20.55	1.11	41.4	1.00	-1.1	10.9
1000	40.6	20.46	1.14	41.3	1.01	-1.7	12.1





Figure D-3
750MHz Head Tissue Equivalent Matter

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 07/08/18 - 07/23/18	DUT Type: Portable Handset			APPENDIX D: Page 3 of 5

3 Composition / Information on ingredients

The Item is composed of the following ingredients:

Water	50 – 73 %	
Non-ionic detergents	25 – 50 %	polyoxyethylenesorbitan monolaurate
NaCl	0 – 2 %	
Preservative	0.05 – 0.1 %	Preventol-D7

Safety relevant ingredients:

CAS-No. 55965-84-9	< 0.1 %	aqueous preparation, containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyl-3(2H)-isothiazolone
--------------------	---------	--

CAS-No. 9005-64-5	< 50 %	polyoxyethylenesorbitan monolaurate
-------------------	--------	-------------------------------------

According to international guidelines, the product is not a dangerous mixture and therefore not required to be marked by symbols.

Figure D-4
Composition of 2.4 GHz Head Tissue Equivalent Matter

Note: 2.4 GHz head liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.




Figure D-5
2.4 GHz Head Tissue Equivalent Matter

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 07/08/18 - 07/23/18	DUT Type: Portable Handset			APPENDIX D: Page 4 of 5

2 Composition / Information on ingredients

The Item is composed of the following ingredients:

Water	50 – 65%
Mineral oil	10 – 30%
Emulsifiers	8 – 25%
Sodium salt	0 – 1.5%

Figure D-6

Composition of 5 GHz Head Tissue Equivalent Matter

Note: 5GHz head liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland
Phone +41 44 245 9700, Fax +41 44 245 9779
info@speag.com, http://www.speag.com

Measurement Certificate / Material Test

Item Name Head Tissue Simulating Liquid (HBBL3500-5800V5)
Product No. SL AAH 502 AG (Batch: 170613-1)
Manufacturer SPEAG

Measurement Method

TSL dielectric parameters measured using calibrated DAK probe.

Setup Validation

Validation results were within $\pm 2.5\%$ towards the target values of Methanol.

Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

Test Condition

Ambient Environment temperatur (22 ± 3)°C and humidity < 70%.
TSL Temperature 22°C
Test Date 20-Jun-17
Operator CL

Additional Information

TSL Density 0.985 g/cm³
TSL Heat-capacity 3.383 kJ/(kg*K)

f [MHz]	Measured			Target			Diff to Target [%]		
	ϵ'	ϵ''	σ_{sig}	ϵ'	ϵ''	σ_{sig}	$\Delta\epsilon'$	$\Delta\epsilon''$	$\Delta\sigma_{\text{sig}}$
3400	38.6	15.03	2.84	38.0	2.81	1.5	1.1		
3500	38.5	15.00	2.92	37.9	2.91	1.5	0.3		
3600	38.3	14.98	3.00	37.8	3.02	1.3	-0.5		
3700	38.2	14.96	3.08	37.7	3.12	1.3	-1.2		
3800	38.1	14.96	3.16	37.6	3.22	1.4	-1.9		
3900	38.0	14.95	3.24	37.5	3.32	1.4	-2.5		
4000	37.9	14.95	3.33	37.4	3.43	1.5	-2.8		
4100	37.8	14.96	3.41	37.2	3.53	1.5	-3.3		
4200	37.6	15.00	3.50	37.1	3.63	1.3	-3.6		
4300	37.5	15.05	3.60	37.0	3.73	1.3	-3.5		
4400	37.4	15.11	3.70	36.9	3.84	1.4	-3.5		
4500	37.2	15.18	3.80	36.8	3.94	1.1	-3.5		
4600	37.1	15.24	3.90	36.7	4.04	1.2	-3.5		
4700	37.0	15.29	4.00	36.6	4.14	1.2	-3.4		
4800	36.8	15.35	4.10	36.4	4.25	1.0	-3.4		
4850	36.8	15.35	4.14	36.4	4.30	1.1	-3.6		
4900	36.7	15.38	4.19	36.3	4.35	1.0	-3.6		
4950	36.6	15.39	4.24	36.3	4.40	0.9	-3.6		
5000	36.5	15.42	4.29	36.2	4.45	0.8	-3.6		
5050	36.5	15.43	4.34	36.2	4.50	0.9	-3.6		
5100	36.4	15.46	4.39	36.1	4.55	0.8	-3.6		
5150	36.3	15.48	4.43	36.0	4.60	0.7	-3.8		
5200	36.2	15.50	4.48	36.0	4.66	0.6	-3.8		
5250	36.1	15.53	4.54	35.9	4.71	0.5	-3.5		
5300	36.1	15.55	4.58	35.9	4.76	0.6	-3.7		
5350	36.0	15.56	4.63	35.8	4.81	0.5	-3.7		
5400	35.9	15.57	4.68	35.8	4.86	0.4	-3.7		
5450	35.9	15.59	4.73	35.7	4.91	0.6	-3.7		
5500	35.8	15.61	4.78	35.6	4.96	0.4	-3.7		
5550	35.7	15.65	4.83	35.6	5.01	0.3	-3.7		
5600	35.6	15.66	4.88	35.5	5.07	0.2	-3.7		
5650	35.6	15.70	4.93	35.5	5.12	0.4	-3.6		
5700	35.5	15.72	4.98	35.4	5.17	0.2	-3.6		
5750	35.4	15.76	5.04	35.4	5.22	0.1	-3.4		
5800	35.4	15.78	5.09	35.3	5.27	0.3	-3.4		
5850	35.3	15.81	5.14	35.3	5.34	0.0	-3.7		
5900	35.3	15.82	5.19	35.3	5.40	0.0	-3.9		





Figure D-7

5GHz Head Tissue Equivalent Matter

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 07/08/18 - 07/23/18	DUT Type: Portable Handset			APPENDIX D: Page 5 of 5

APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-1
SAR System Validation Summary – 1g

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE TYPE	PROBE CAL. POINT		COND.	PERM.	CW VALIDATION			MOD. VALIDATION		
							(σ)	(ε _r)	SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
E	750	3/11/2018	3213	ES3DV3	750	Head	0.890	40.788	PASS	PASS	PASS	N/A	N/A	N/A
E	835	3/5/2018	3213	ES3DV3	835	Head	0.925	43.335	PASS	PASS	PASS	GMSK	PASS	N/A
E	1750	3/2/2018	3213	ES3DV3	1750	Head	1.397	38.415	PASS	PASS	PASS	N/A	N/A	N/A
E	1900	5/22/2018	3213	ES3DV3	1900	Head	1.447	38.909	PASS	PASS	PASS	GMSK	PASS	N/A
H	1900	7/16/2018	7409	EX3DV4	1900	Head	1.425	40.935	PASS	PASS	PASS	GMSK	PASS	N/A
G	2300	10/16/2017	3332	ES3DV3	2300	Head	1.715	39.101	PASS	PASS	PASS	N/A	N/A	N/A
G	2450	10/16/2017	3332	ES3DV3	2450	Head	1.880	38.615	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
G	2600	10/16/2017	3332	ES3DV3	2600	Head	2.051	38.039	PASS	PASS	PASS	TDD	PASS	N/A
H	5250	7/5/2018	7409	EX3DV4	5250	Head	4.492	34.994	PASS	PASS	PASS	OFDM	N/A	PASS
H	5600	7/5/2018	7409	EX3DV4	5600	Head	4.839	34.496	PASS	PASS	PASS	OFDM	N/A	PASS
H	5750	7/5/2018	7409	EX3DV4	5750	Head	4.995	34.288	PASS	PASS	PASS	OFDM	N/A	PASS
I	750	7/19/2018	7406	EX3DV4	750	Body	0.969	53.451	PASS	PASS	PASS	N/A	N/A	N/A
J	835	5/26/2018	3347	ES3DV3	835	Body	0.973	54.458	PASS	PASS	PASS	GMSK	PASS	N/A
J	1750	5/14/2018	3347	ES3DV3	1750	Body	1.516	52.662	PASS	PASS	PASS	N/A	N/A	N/A
I	1900	6/18/2018	7406	EX3DV4	1900	Body	1.575	51.579	PASS	PASS	PASS	GMSK	PASS	N/A
K	2300	4/3/2018	3319	ES3DV3	2300	Body	1.871	51.575	PASS	PASS	PASS	N/A	N/A	N/A
K	2450	4/3/2018	3319	ES3DV3	2450	Body	2.043	51.130	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
K	2600	4/3/2018	3319	ES3DV3	2600	Body	2.225	50.665	PASS	PASS	PASS	TDD	PASS	N/A
D	5250	6/11/2018	7357	EX3DV4	5250	Body	5.529	48.096	PASS	PASS	PASS	OFDM	N/A	PASS
D	5600	6/11/2018	7357	EX3DV4	5600	Body	6.007	47.521	PASS	PASS	PASS	OFDM	N/A	PASS
D	5750	6/11/2018	7357	EX3DV4	5750	Body	6.214	47.275	PASS	PASS	PASS	OFDM	N/A	PASS

Table E-2
SAR System Validation Summary – 10g

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE TYPE	PROBE CAL. POINT		COND.	PERM.	CW VALIDATION			MOD. VALIDATION		
							(σ)	(ε _r)	SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
J	1750	5/14/2018	3347	ES3DV3	1750	Body	1.516	52.662	PASS	PASS	PASS	N/A	N/A	N/A
I	1900	6/18/2018	7406	EX3DV4	1900	Body	1.575	51.579	PASS	PASS	PASS	GMSK	PASS	N/A
D	5250	6/11/2018	7357	EX3DV4	5250	Body	5.529	48.096	PASS	PASS	PASS	OFDM	N/A	PASS
D	5600	6/11/2018	7357	EX3DV4	5600	Body	6.007	47.521	PASS	PASS	PASS	OFDM	N/A	PASS
D	5750	6/11/2018	7357	EX3DV4	5750	Body	6.214	47.275	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 07/08/18 - 07/23/18	DUT Type: Portable Handset			APPENDIX E: Page 1 of 1

APPENDIX G: POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process was divided into two parts: (1) evaluation of output power levels for individual or multiple triggering mechanisms and (2) evaluation of the triggering distances for proximity-based sensors.

1.1 Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

1.2 Distance Verification Procedure

The distance verification procedure was performed according to the following procedure:

1. A base station simulator was used to establish an RF connection and to monitor the power levels. The device being tested was placed below the relevant section of the phantom with the relevant side or edge of the device facing toward the phantom.
2. The device was moved toward and away from the phantom to determine the distance at which the mechanism triggers and the output power is reduced, per KDB Publication 616217 D04v01r02 and FCC Guidance. Each applicable test position was evaluated. The distances were confirmed to be the same or larger (more conservative) than the minimum distances provided by the manufacturer.
3. Steps 1 and 2 were repeated for low, mid, and high bands, as appropriate (see note below Table G-2 for more details).
4. Steps 1 through 3 were repeated for all distance-based power reduction mechanisms.

FCC ID: ZNFQ910QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset			APPENDIX G: Page 1 of 2

1.3 Main Antenna Verification Summary

Table G-1
Power Measurement Verification for Main Antenna

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered (Max)	Mechanism #1 (Reduced)
Proximity Sensor	UMTS B4	24.68	23
Proximity Sensor	UMTS B2	23.8	21.93
Proximity Sensor	CDMA BC1	24.39	21.92
Proximity Sensor	LTE B4	23.73	22.78
Proximity Sensor	LTE B66	23.82	22.62
Proximity Sensor	LTE B2	23.37	21.14
Proximity Sensor	LTE B25	23.3	21.12

Table G-2
Distance Measurement Verification for Main Antenna

Mechanism(s)	Test Condition	Band	Distance Measurements (mm)		Minimum Distance per Manufacturer (mm)
			Moving Toward	Moving Away	
Proximity Sensor	Phablet - Back Side	Mid	6	7	4
Proximity Sensor	Phablet - Front Side	Mid	4	5	3
Proximity Sensor	Phablet - Bottom Edge	Mid	7	8	6

*Note: Mid band refers to: CDMA BC1, UMTS B2/4, LTE B2/4/25/66

1.4 WIFI Verification Summary

Table G-3
Power Measurement Verification WIFI

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered (Max)	Mechanism #1 (Reduced)
Held-to-Ear	802.11b	20.28	17.58
Held-to-Ear	802.11g	18.94	17.29
Held-to-Ear	802.11n (2.4GHz)	17.39	16.96

*Note: 802.11ac (2.4 GHz) was not capable of being measured due to equipment limitations.

FCC ID: ZNFQ910QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset			APPENDIX G: Page 2 of 2

APPENDIX H: DOWNLINK LTE CA RF CONDUCTED POWERS

1.1 LTE Downlink Only Carrier Aggregation Test Reduction Methodology

SAR test exclusion for LTE downlink Carrier Aggregation is determined by power measurements according to the number of component carriers (CCs) supported by the product implementation. Per April 2018 TCBC Workshop Notes, the following test reduction methodology was applied to determine the combinations required for conducted power measurements.

LTE DLCA Test Reduction Methodology:

- The supported combinations were arranged by the number of component carriers in columns.
- Any limitations on the PCC or SCC for each combination were identified alongside the combination (e.g. CA_2A-2A-4A-12A, but B12 can only be configured as a SCC).
- Power measurements were performed for "supersets" (LTE CA combinations with multiple components carriers) and any "subsets" (LTE CA combinations with fewer component carriers) that were not completely covered by the supersets.
- Only subsets that have the exact same components as a superset were excluded for measurement.
- When there were certain restrictions on component carriers that existed in the superset that were not applied for the subset, the subset configuration was additionally evaluated.
- Both inter-band and intra-band downlink carrier aggregation scenarios were considered.

Table 1 – Example of Exclusion Table for SISO Configurations

Index	SCC	Supported Component Carriers (SCCs)	Restrictions	Completely Covered by Measurement Superset
SCC-01	CA_2A	5, 10, 15, 20	SCC-01	Yes
SCC-02	CA_2A	5, 10, 15, 20	SCC-02	Yes
SCC-03	CA_2A	5, 10, 15, 20	SCC-03	Yes
SCC-04	CA_2A	5, 10, 15, 20	SCC-04	Yes
SCC-05	CA_2A	5, 10, 15, 20	SCC-05	Yes
SCC-06	CA_2A	5, 10, 15, 20	SCC-06	Yes
SCC-07	CA_2A	5, 10, 15, 20	SCC-07	Yes
SCC-08	CA_2A	5, 10, 15, 20	SCC-08	Yes
SCC-09	CA_2A	5, 10, 15, 20	SCC-09	Yes
SCC-10	CA_2A	5, 10, 15, 20	SCC-10	Yes
SCC-11	CA_2A	5, 10, 15, 20	SCC-11	Yes
SCC-12	CA_2A	5, 10, 15, 20	SCC-12	Yes
SCC-13	CA_2A	5, 10, 15, 20	SCC-13	Yes
SCC-14	CA_2A	5, 10, 15, 20	SCC-14	Yes
SCC-15	CA_2A	5, 10, 15, 20	SCC-15	Yes
SCC-16	CA_2A	5, 10, 15, 20	SCC-16	Yes
SCC-17	CA_2A	5, 10, 15, 20	SCC-17	Yes
SCC-18	CA_2A	5, 10, 15, 20	SCC-18	Yes
SCC-19	CA_2A	5, 10, 15, 20	SCC-19	Yes
SCC-20	CA_2A	5, 10, 15, 20	SCC-20	Yes
SCC-21	CA_2A	5, 10, 15, 20	SCC-21	Yes
SCC-22	CA_2A	5, 10, 15, 20	SCC-22	Yes
SCC-23	CA_2A	5, 10, 15, 20	SCC-23	Yes
SCC-24	CA_2A	5, 10, 15, 20	SCC-24	Yes
SCC-25	CA_2A	5, 10, 15, 20	SCC-25	Yes
SCC-26	CA_2A	5, 10, 15, 20	SCC-26	Yes
SCC-27	CA_2A	5, 10, 15, 20	SCC-27	Yes
SCC-28	CA_2A	5, 10, 15, 20	SCC-28	Yes
SCC-29	CA_2A	5, 10, 15, 20	SCC-29	Yes
SCC-30	CA_2A	5, 10, 15, 20	SCC-30	Yes
SCC-31	CA_2A	5, 10, 15, 20	SCC-31	Yes
SCC-32	CA_2A	5, 10, 15, 20	SCC-32	Yes
SCC-33	CA_2A	5, 10, 15, 20	SCC-33	Yes
SCC-34	CA_2A	5, 10, 15, 20	SCC-34	Yes
SCC-35	CA_2A	5, 10, 15, 20	SCC-35	Yes
SCC-36	CA_2A	5, 10, 15, 20	SCC-36	Yes
SCC-37	CA_2A	5, 10, 15, 20	SCC-37	Yes
SCC-38	CA_2A	5, 10, 15, 20	SCC-38	Yes
SCC-39	CA_2A	5, 10, 15, 20	SCC-39	Yes
SCC-40	CA_2A	5, 10, 15, 20	SCC-40	Yes
SCC-41	CA_2A	5, 10, 15, 20	SCC-41	Yes
SCC-42	CA_2A	5, 10, 15, 20	SCC-42	Yes
SCC-43	CA_2A	5, 10, 15, 20	SCC-43	Yes
SCC-44	CA_2A	5, 10, 15, 20	SCC-44	Yes
SCC-45	CA_2A	5, 10, 15, 20	SCC-45	Yes
SCC-46	CA_2A	5, 10, 15, 20	SCC-46	Yes
SCC-47	CA_2A	5, 10, 15, 20	SCC-47	Yes
SCC-48	CA_2A	5, 10, 15, 20	SCC-48	Yes
SCC-49	CA_2A	5, 10, 15, 20	SCC-49	Yes
SCC-50	CA_2A	5, 10, 15, 20	SCC-50	Yes
SCC-51	CA_2A	5, 10, 15, 20	SCC-51	Yes
SCC-52	CA_2A	5, 10, 15, 20	SCC-52	Yes
SCC-53	CA_2A	5, 10, 15, 20	SCC-53	Yes
SCC-54	CA_2A	5, 10, 15, 20	SCC-54	Yes
SCC-55	CA_2A	5, 10, 15, 20	SCC-55	Yes
SCC-56	CA_2A	5, 10, 15, 20	SCC-56	Yes
SCC-57	CA_2A	5, 10, 15, 20	SCC-57	Yes
SCC-58	CA_2A	5, 10, 15, 20	SCC-58	Yes
SCC-59	CA_2A	5, 10, 15, 20	SCC-59	Yes
SCC-60	CA_2A	5, 10, 15, 20	SCC-60	Yes
SCC-61	CA_2A	5, 10, 15, 20	SCC-61	Yes
SCC-62	CA_2A	5, 10, 15, 20	SCC-62	Yes
SCC-63	CA_2A	5, 10, 15, 20	SCC-63	Yes
SCC-64	CA_2A	5, 10, 15, 20	SCC-64	Yes
SCC-65	CA_2A	5, 10, 15, 20	SCC-65	Yes
SCC-66	CA_2A	5, 10, 15, 20	SCC-66	Yes
SCC-67	CA_2A	5, 10, 15, 20	SCC-67	Yes
SCC-68	CA_2A	5, 10, 15, 20	SCC-68	Yes
SCC-69	CA_2A	5, 10, 15, 20	SCC-69	Yes
SCC-70	CA_2A	5, 10, 15, 20	SCC-70	Yes
SCC-71	CA_2A	5, 10, 15, 20	SCC-71	Yes
SCC-72	CA_2A	5, 10, 15, 20	SCC-72	Yes
SCC-73	CA_2A	5, 10, 15, 20	SCC-73	Yes
SCC-74	CA_2A	5, 10, 15, 20	SCC-74	Yes
SCC-75	CA_2A	5, 10, 15, 20	SCC-75	Yes
SCC-76	CA_2A	5, 10, 15, 20	SCC-76	Yes
SCC-77	CA_2A	5, 10, 15, 20	SCC-77	Yes
SCC-78	CA_2A	5, 10, 15, 20	SCC-78	Yes
SCC-79	CA_2A	5, 10, 15, 20	SCC-79	Yes
SCC-80	CA_2A	5, 10, 15, 20	SCC-80	Yes
SCC-81	CA_2A	5, 10, 15, 20	SCC-81	Yes
SCC-82	CA_2A	5, 10, 15, 20	SCC-82	Yes
SCC-83	CA_2A	5, 10, 15, 20	SCC-83	Yes
SCC-84	CA_2A	5, 10, 15, 20	SCC-84	Yes
SCC-85	CA_2A	5, 10, 15, 20	SCC-85	Yes
SCC-86	CA_2A	5, 10, 15, 20	SCC-86	Yes
SCC-87	CA_2A	5, 10, 15, 20	SCC-87	Yes
SCC-88	CA_2A	5, 10, 15, 20	SCC-88	Yes
SCC-89	CA_2A	5, 10, 15, 20	SCC-89	Yes
SCC-90	CA_2A	5, 10, 15, 20	SCC-90	Yes
SCC-91	CA_2A	5, 10, 15, 20	SCC-91	Yes
SCC-92	CA_2A	5, 10, 15, 20	SCC-92	Yes
SCC-93	CA_2A	5, 10, 15, 20	SCC-93	Yes
SCC-94	CA_2A	5, 10, 15, 20	SCC-94	Yes
SCC-95	CA_2A	5, 10, 15, 20	SCC-95	Yes
SCC-96	CA_2A	5, 10, 15, 20	SCC-96	Yes
SCC-97	CA_2A	5, 10, 15, 20	SCC-97	Yes
SCC-98	CA_2A	5, 10, 15, 20	SCC-98	Yes
SCC-99	CA_2A	5, 10, 15, 20	SCC-99	Yes
SCC-100	CA_2A	5, 10, 15, 20	SCC-100	Yes

FCC ID: ZNFQ910QM	 SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset		APPENDIX H: Page 1 of 7

1.2 LTE Downlink Only Carrier Aggregation Test Selection and Setup

SAR test exclusion for LTE downlink Carrier Aggregation is determined by power measurements according to the number component carriers (CCs) supported by the product implementation. For those configurations required by April 2018 TCBC Workshop Notes, conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.

Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

General PCC and SCC configuration selection procedure

- PCC uplink channel, channel bandwidth, modulation and RB configurations were selected based on section C)3)b)ii) of KDB 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation.
- To maximize aggregated bandwidth, highest channel bandwidth available for that CA combination was selected for SCC. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers.
- All selected PCC and SCC(s) remained fully within the uplink/downlink transmission band of the respective component carrier.
- When a device supports LTE capabilities with overlapping transmission frequency ranges, the standalone powers from the band with a larger transmission frequency range can be used to select measurement configurations for the band with the fully covered transmission frequency range.




Figure 1
DL CA Power Measurement Setup

FCC ID: ZNFQ910QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset			APPENDIX H: Page 2 of 7

1.3 Downlink Carrier Aggregation RF Conducted Powers

1.3.1 LTE Band 12 as PCC

Table 1
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC						SCC 1				SCC 2				SCC 3				Power				
			PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]		
CA 12A-25A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B25	20	8365	1962.5	-	-	-	-	-	-	-	-	-	-	25.35	25.35
CA 12A-66A (1)	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	-	-	25.34	25.35
CA 12A-66A (2)	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	-	-	25.34	25.35
CA 2A-12A (1)	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B2	20	900	1960	-	-	-	-	-	-	-	-	-	-	25.32	25.35
CA 4A-12A (1)	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B4	20	2175	2132.5	-	-	-	-	-	-	-	-	-	-	25.34	25.35
CA 12A-12A (1)	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B2	20	2175	2132.5	-	-	-	-	-	-	-	-	-	-	25.34	25.35
CA 12A-66A-66A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B66	20	66786	2145	LTE B66	20	67236	2190	-	-	-	-	-	-	25.32	25.35
CA 12A-66C	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	-	-	-	-	-	-	25.33	25.35
CA 2A-12B	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B12	10	5107	738.7	LTE B2	20	900	1960	-	-	-	-	-	-	25.35	25.35
CA 4A-12B	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B12	10	5107	738.7	LTE B4	20	2175	2132.5	-	-	-	-	-	-	25.35	25.35
CA 4A-7A-12A (1)	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	-	-	-	-	-	-	25.32	25.35
CA 2A-12A-30A-66A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	LTE B66	20	66786	2145	-	-	25.22	25.35
CA 2A-2A-12A-30A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B30	10	9820	2355	-	-	25.26	25.35
CA 2A-12A-12A-66A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B66	20	66786	2145	-	-	25.24	25.35
CA 2A-4A-12A-12A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	-	-	25.32	25.35
CA 4A-4A-12A-30A	LTE B12	5	23035	701.5	QPSK	1	24	5035	731.5	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	LTE B30	10	9820	2355	-	-	25.31	25.35

1.3.2 LTE Band 17 as PCC

Table 2
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC				Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC 1			Power	
				PCC (UL) Freq. [MHz]	PCC (UL) RB	PCC (UL) RB Offset	PCC (DL) Freq. [MHz]						SCC Band	SCC BW [MHz]	SCC (DL) Channel	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 2A-17A	LTE B17	5	23755	706.5	QPSK	1	24	5755	736.5	LTE B2	10	900	1960	2175	2132.5	25.35	25.35
CA 4A-17A	LTE B17	5	23755	706.5	QPSK	1	24	5755	736.5	LTE B4	10	2175	2132.5	2175	2132.5	25.37	25.36

1.3.3 LTE Band 13 as PCC

Table 3
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC						SCC 1				SCC 2			SCC 3			Power						
				PCC (UL) Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)			
CA 13A-46A	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B46	20	50665	5537.5	-	-	-	-	-	-	-	-	-	-	-	25.29	
CA 13A-46C	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	-	-	-	25.30	25.29
CA 13A-66A-66A	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B66	20	66786	2145	LTE B66	20	67236	2190	-	-	-	-	-	-	-	25.32	25.29
CA 13A-66B	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B66	15	66786	2145	LTE B66	5	66879	2154.3	-	-	-	-	-	-	-	25.30	25.29
CA 13A-66C	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	-	-	-	-	-	-	-	25.34	25.29
CA 2A-13A-66A	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B2	20	900	1960	LTE B66	20	66786	2145	-	-	-	-	-	-	-	25.31	25.29
CA 2A-2A-13A	LTE B13	10	23230	782	QPSK	1	0	5230	751	LTE B2	20	900	1960	LTE B2	20	700	1940	-	-	-	-	-	-	-	25.13	25.22
CA 2A-4A-13A	LTE B13	10	23230	782	QPSK	1	0	5230	751	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	-	-	-	-	-	-	-	25.16	25.22
CA 4A-4A-13A	LTE B13	10	23230	782	QPSK	1	0	5230	751	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	-	-	-	-	-	-	-	25.13	25.22
CA 4C-13A	LTE B13	10	23230	782	QPSK	1	0	5230	751	LTE B4	20	2175	2132.5	LTE B4	10	2031	2118.1	-	-	-	-	-	-	-	25.15	25.22
CA 13A-46D	LTE B13	5	23230	782	QPSK	1	0	5230	751	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	-	-	-	25.32	25.29

1.3.4 LTE Band 5 as PCC

Table 4
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC						SCC 1				SCC 2				Power	
				PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_5A-25A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B25	20	8365	1962.5	-	-	-	-	25.44	25.41
CA_5A-46A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B46	20	50665	5537.5	-	-	-	-	25.36	25.41
CA_5B	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B5	10	2453	874.3	-	-	-	-	25.39	25.41
CA_2A-4A-5A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	25.40	25.41
CA_2A-5A-30A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	25.43	25.41
CA_2A-5A-66A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B2	20	900	1960	LTE B66	20	66786	2145	25.35	25.41
CA_4A-5A-30A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	25.38	25.41
CA_5A-30A-66A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B30	10	9820	2355	LTE B66	20	66786	2145	25.40	25.41
CA_5A-46C (1)	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	25.38	25.41
CA_5A-66A-66A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B66	20	66786	2145	LTE B66	20	67236	2190	25.41	25.41
CA_5A-66B	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B66	15	66786	2145	LTE B66	5	66879	2154.3	25.40	25.41
CA_5A-66C	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	25.43	25.41
CA_4C-5A	LTE B5	5	20525	836.5	QPSK	1	12	2525	881.5	LTE B4	20	2175	2132.5	LTE B4	10	2031	2118.1	25.45	25.41

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset	APPENDIX H: Page 3 of 7		

1.3.5 LTE Band 26 as PCC

Table 5
Maximum Output Powers

Combination	PCC									SCC 1				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 25A-26A	LTE B26	3	26865	831.5	QPSK	1	7	8865	876.5	LTE B25	20	8365	1962.5	25.42	25.43
CA 26A-41A	LTE B26	5	26865	831.5	QPSK	1	0	8865	876.5	LTE B41	20	40620	2593	25.49	25.42

1.3.6 LTE Band 4 as PCC

Table 6
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC				PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
				Mod.	PCC UL# RB	PCC UL RB Offset	Mod.																
CA 2A-4A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	-	-	-	-	-	-	-	-	24.20	24.18
CA 4A-12A (1)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	24.18	24.18
CA 4A-12A (2)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	24.18	24.18
CA 4A-17A	LTE B4	5	19975	1712.5	QPSK	1	0	1975	2112.5	LTE B17	10	5790	740	-	-	-	-	-	-	-	-	24.09	24.07
CA 4A-29A	LTE B4	5	19975	1712.5	QPSK	1	0	1975	2112.5	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	24.08	24.07
CA 4A-29A (2)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	24.19	24.18
CA 2A-2A-4A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B2	20	700	1940	-	-	-	-	24.19	24.18
CA 2A-4A-13A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B13	10	5230	751	-	-	-	-	24.19	24.18
CA 2A-4A-29A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B29	10	9715	722.5	-	-	-	-	24.20	24.18
CA 2A-4A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B30	10	9820	2355	-	-	-	-	24.18	24.18
CA 2A-4A-4A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	20	2050	2120	LTE B2	20	900	1960	-	-	-	-	24.18	24.18
CA 2A-4A-5A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B5	10	2525	881.5	-	-	-	-	24.19	24.18
CA 4A-12B	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	-	-	-	-	24.15	24.18
CA 4A-46A-46A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B46	20	50665	5537.5	LTE B46	20	47090	5180	-	-	-	-	24.18	24.18
CA 4A-4A-13A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	20	2050	2120	LTE B13	10	5230	751	-	-	-	-	24.17	24.18
CA 4A-4A-7A (1)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	20	2050	2120	LTE B7	20	3100	2655	-	-	-	-	24.16	24.18
CA 4A-5A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	-	-	-	-	24.15	24.18
CA 4A-7A-12A (1)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	-	-	-	-	24.20	24.18
CA 4A-7A-7A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B7	20	3100	2655	LTE B7	20	2850	2630	-	-	-	-	24.20	24.18
CA 4C-13A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	20	2102	2125.2	LTE B13	10	5230	751	-	-	-	-	24.18	24.18
CA 4C-5A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	20	2102	2125.2	LTE B5	10	2525	881.5	-	-	-	-	24.19	24.18
CA 2A-4A-7A-12A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	24.20	24.18
CA 4A-4A-46C	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	24.08	24.18
CA 4A-46D	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	24.07	24.18
CA 4A-4A-12A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	20	2050	2120	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.12	24.18

Table 7
Reduced Output Powers

Combination	PCC									SCC 1				SCC 2			SCC 3				Power			
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA 2A-4A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	-	-	-	-	-	-	-	-	-	23.03	23.03
CA 4A-12A (1)	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	-	23.03	23.03
CA 4A-12A (2)	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	-	23.03	23.03
CA 4A-17A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B17	10	5790	740	-	-	-	-	-	-	-	-	-	23.03	23.03
CA 4A-29A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	-	23.03	23.03
CA 4A-29A (2)	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	-	23.03	23.03
CA 2A-2A-4A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	LTE B2	20	730	1940	-	-	-	-	-	22.91	23.03
CA 2A-4A-13A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	LTE B13	10	5230	751	-	-	-	-	-	22.89	23.03
CA 2A-4A-29A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	LTE B29	10	9715	722.5	-	-	-	-	-	22.88	23.03
CA 2A-4A-30A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	LTE B30	10	9820	2355	-	-	-	-	-	22.90	23.03
CA 2A-4A-4A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B4	20	2300	2145	LTE B2	20	900	1960	-	-	-	-	-	22.87	23.03
CA 2A-4A-5A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	LTE B5	10	2525	881.5	-	-	-	-	-	22.89	23.03
CA 4A-12B	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	-	-	-	-	-	22.86	23.03
CA 4A-46A-46A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B46	20	50665	5537.5	LTE B46	20	47090	5180	-	-	-	-	-	22.87	23.03
CA 4A-4A-13A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B4	20	2300	2145	LTE B13	10	5230	751	-	-	-	-	-	22.86	23.03
CA 4A-4A-7A (1)	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B4	20	2300	2145	LTE B7	20	3100	2655	-	-	-	-	-	22.89	23.03
CA 4A-5A-30A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	-	-	-	-	-	22.90	23.03
CA 4A-7A-12A (1)	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	-	-	-	-	-	22.89	23.03
CA 4A-7A-7A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B7	20	3100	2655	LTE B7	20	2850	2630	-	-	-	-	-	22.88	23.03
CA 4C-13A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B4	20	2144	2129.4	LTE B13	10	5230	751	-	-	-	-	-	22.86	23.03
CA 4C-5A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B4	20	2144	2129.4	LTE B5	10	2525	881.5	-	-	-	-	-	22.89	23.03
CA 2A-4A-7A-12A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B2	20	900	1960	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	22.86	23.03	
CA 4A-46A-46C	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	22.84	23.03	
CA 4A-46D	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	22.89	23.03	
CA 4A-4A-12A-30A	LTE B4	10	20000	1715	16QAM	1	49	2000	2115	LTE B4	20	2300	2145	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	22.83	23.03	

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT	
-------------------	---	-----------------------	--

1.3.7 LTE Band 66 as PCC

Table 8
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC				PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC 1			SCC Band	SCC 2			SCC Band	SCC 3			Power	
				Mod.	PCC UL RB	PCC UL RB Offset					SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]		SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]		SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12A-66A (1)	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	24.15	24.18
CA 12A-66A (2)	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	24.15	24.18
CA 29A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	24.14	24.18
CA 2A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B2	20	900	1960	-	-	-	-	-	-	-	-	24.20	24.18
CA 12A-66A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	67236	2190	LTE B12	10	5095	737.5	-	-	-	-	24.20	24.18
CA 12A-66C	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	66588	2125.2	LTE B12	10	5095	737.5	-	-	-	-	24.17	24.18
CA 13A-66A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	67236	2190	LTE B13	10	5230	751	-	-	-	-	24.20	24.18
CA 13A-66B	LTE B66	5	131997	1712.5	QPSK	1	0	66461	2112.5	LTE B66	15	66554	2121.8	LTE B13	10	5230	751	-	-	-	-	24.10	24.07
CA 13A-66C	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	66588	2125.2	LTE B13	10	5230	751	-	-	-	-	24.20	24.18
CA 2A-13A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B2	20	900	1960	LTE B13	10	5230	751	-	-	-	-	24.19	24.18
CA 2A-5A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	900	1960	LTE B5	10	2525	881.5	-	-	-	-	24.20	24.18
CA 2A-66B	LTE B66	5	131997	1712.5	QPSK	1	0	66461	2112.5	LTE B66	15	66554	2121.8	LTE B2	20	900	1960	-	-	-	-	24.03	24.07
CA 2A-66C	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	66588	2125.2	LTE B2	20	900	1960	-	-	-	-	24.15	24.18
CA 46A-46A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B46	20	50605	5537.5	LTE B46	20	47090	5180	-	-	-	-	24.06	24.18
CA 5A-30A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	-	-	-	-	24.17	24.18
CA 5A-66A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	67236	2190	LTE B5	10	2525	881.5	-	-	-	-	24.18	24.18
CA 5A-66B	LTE B66	5	131997	1712.5	QPSK	1	0	66461	2112.5	LTE B66	15	66554	2121.8	LTE B5	10	2525	881.5	-	-	-	-	24.09	24.07
CA 5A-66C	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	66588	2125.2	LTE B5	10	2525	881.5	-	-	-	-	24.16	24.18
CA 66A-66C	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	67038	2170.2	LTE B66	20	67236	2190	-	-	-	-	24.19	24.18
CA 66C-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	66588	2125.2	LTE B66	20	67236	2190	-	-	-	-	24.20	24.18
CA 2A-12A-30A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B2	20	900	1960	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.20	24.18
CA 2A-2A-12A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B12	10	5095	737.5	24.17	24.18
CA 2A-2A-66A-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B66	20	67236	2190	LTE B2	20	900	1960	LTE B2	20	700	1940	24.18	24.18
CA 46A-46C-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B46	20	50605	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	24.05	24.18
CA 46D-66A	LTE B66	20	132322	1745	QPSK	1	0	66786	2145	LTE B46	20	50605	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	24.04	24.18

Table 9
Reduced Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC				PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC 1			SCC Band	SCC 2			SCC Band	SCC 3			Power	
				Mod.	PCC UL RB	PCC UL RB Offset					SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]		SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]		SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12A-66A (1)	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	23.17	23.03
CA 12A-66A (2)	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	23.17	23.03
CA 29A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	23.20	23.03
CA 2A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B2	20	900	1960	-	-	-	-	-	-	-	-	23.15	23.03
CA 12A-66A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	67236	2190	LTE B12	10	5095	737.5	-	-	-	-	22.97	23.03
CA 12A-66C	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66630	2129.4	LTE B12	10	5095	737.5	-	-	-	-	22.95	23.03
CA 13A-66A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66585	2129.4	LTE B13	10	5230	751	-	-	-	-	23.01	23.03
CA 13A-66B	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66585	2129.4	LTE B13	10	5230	751	-	-	-	-	22.93	23.03
CA 2A-13A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B2	20	900	1960	LTE B13	10	5230	751	-	-	-	-	22.93	23.03
CA 2A-5A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66630	2129.4	LTE B5	10	2525	881.5	-	-	-	-	22.89	23.03
CA 2A-66B	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66585	2129.4	LTE B2	20	900	1960	-	-	-	-	22.98	23.03
CA 2A-66C	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66630	2129.4	LTE B2	20	900	1960	-	-	-	-	22.94	23.03
CA 46A-46A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B46	20	50605	5537.5	LTE B46	20	47090	5180	-	-	-	-	22.95	23.03
CA 5A-30A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	-	-	-	-	22.91	23.03
CA 5A-66A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	67236	2190	LTE B5	10	2525	881.5	-	-	-	-	22.89	23.03
CA 5A-66B	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66585	2129.4	LTE B5	10	2525	881.5	-	-	-	-	22.96	23.03
CA 5A-66C	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66630	2129.4	LTE B5	10	2525	881.5	-	-	-	-	22.92	23.03
CA 66A-66C	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	67038	2170.2	LTE B66	20	67236	2190	-	-	-	-	22.91	23.03
CA 66C-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	66630	2129.4	LTE B66	20	67236	2190	-	-	-	-	22.91	23.03
CA 2A-12A-30A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B2	20	900	1960	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	22.95	23.03
CA 2A-2A-12A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B12	10	5095	737.5	22.98	23.03
CA 2A-2A-66A-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B66	20	67236	2190	LTE B2	20	900	1960	LTE B2	20	700	1940	22.92	23.03
CA 46A-46C-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B46	20	50605	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	22.96	23.03
CA 46D-66A	LTE B66	10	132022	1715	16QAM	1	49	66486	2115	LTE B46	20	50605	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	22.93	23.03

1.3.8 LTE Band 2 as PCC

Table 10
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC				PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC 1			SCC Band	SCC 2			SCC Band	SCC 3			Power		
				Mod.	PCC UL RB	PCC UL RB Offset					SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]		SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]		SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA 2A-12A (1)	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	24.32	24.38	
CA 2A-17A	LTE B2	10	19125	1905	QPSK	1	0	1150	1985	LTE B17	10	5790	740	-	-	-	-	-	-	-	-	24.29	24.29	
CA 2A-29A	LTE B2	10	19125	1905	QPSK	1	0	1150	1985	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	24.30	24.29	
CA 2A-24A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	2175	722.5	-	-	-	-	-	-	-	-	24.30	24.29	
CA 2A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	24.40	24.38	
CA 2C	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B2	20	954	766.5	-	-	-	-	-	-	-	-	24.40	24.38	
CA 2A-12B	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	-	-	-	-	-	24.31	24.38
CA 2A-13A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B13	10	5230	751	LTE B66	20	66786	2145	-	-	-	-	-	24.39	24.38
CA 2A-29A-30A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	-	-	-	-	-	24.40	24.38
CA 2A-24A-13A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B2	20	700	1540	LTE B13	10	5230	751	-	-	-	-	-	24.37	24.38
CA 2A-24A-1A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	700	1540	LTE B4	20	2175	722.5	-	-	-	-	-	24.36	24.38
CA 2A-66A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B46	20	50665	5517.5	LTE B46	20	47090	5180	-	-	-	-	-	24.37	24.38
CA 2A-4A-13A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	2175	2132.5	LTE B13	10	5230	751	-	-	-	-	-	24.39	24.38
CA 2A-4A-29A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	2175	2132.5	LTE B29	10	9715	722.5	-	-	-	-	-	24.36	24.38
CA 2A-4A-30A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	-	-	-	-	-	24.38	24.38
CA 2A-4A-5A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	2175	2132.5	LTE B4	20	2130	2150	-	-	-	-	-	24.30	24.38
CA 2A-5A-5A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B5	10	2525	881.5	LTE B5	10	2525	881.5	-	-	-	-	-	24.35	24.38
CA 2A-5A-30A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	-	-	-	-	-	24.37	24.38
CA 2A-5A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B5	10	2525	881.5	LTE B66	20	66786	2145	-	-	-	-	-	24.36	24.38
CA 2A-66B	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B66	15	66786	2145	LTE B66	5	66879	2154.3	-	-	-	-	-	24.40	24.38
CA 2A-66C	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	-	-	-	-	-	24.40	24.38
CA 2A-7A-7A	LTE B2	15	19125	1902.5	QPSK	1	0	1127	1982.5	LTE B7	20	3100	2655	LTE B7	20	2850	2655	-	-	-	-	-	24.32	24.38
CA 2A-12A-30A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	LTE B66	20	66786	2145	-	24.29	24.38
CA 2A-2A-12A-30A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B2	20	700	1540	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	-	24.31	24.38
CA 2A-2A-12A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B2	20	700	1540	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	-	24.30	24.38
CA 2A-2A-66A-66A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B2	20	700	1540	LTE B66	20	66786	2145	LTE B66	20	66786	2145	-	24.30	24.38
CA 2A-4A-66A-66C	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B46	20	50665	5517.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	-	24.37	24.38
CA 2A-4A-66A-66C	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B46	20	50665	5517.5	LTE B46	20	50467	5517.7	LTE B46	20	52065	5752.3	-	24.37	24.38
CA 2A-4A-7A-12A	LTE B2	15	19125	1902.5	QPSK	1	0	1125	1982.5	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	-	24.31	24.38

Table 11
Reduced Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC				SCC 1				SCC 2				SCC 3				Power					
			PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA 2A-12A (1)	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	-	22.10	22.10
CA 2A-17A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B17	10	5790	740	-	-	-	-	-	-	-	-	-	22.10	22.10
CA 2A-29A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B29	10	9715	722.5	-	-	-	-	-	-	-	-	-	22.10	22.10
CA 2A-4A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	-	-	-	-	-	-	-	-	-	22.10	22.10
CA 2A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	-	22.10	22.10
CA 2C	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B2	20	1058	1975.8	-	-	-	-	-	-	-	-	-	22.10	22.10
CA 2A-12B	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	-	-	-	-	-	22.07	22.10
CA 2A-13A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B13	10	5230	751	LTE B66	20	66786	2145	-	-	-	-	-	22.09	22.10
CA 2A-29A-30A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	-	-	-	-	-	22.07	22.10
CA 2A-2A-13A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B2	20	700	1940	LTE B13	10	5230	751	-	-	-	-	-	22.10	22.10
CA 2A-2A-4A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B2	20	700	1940	LTE B4	20	2175	2132.5	-	-	-	-	-	22.08	22.10
CA 2A-4A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B46	20	50665	5537.5	LTE B46	20	47090	5180	-	-	-	-	-	22.09	22.10
CA 2A-4A-13A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	LTE B13	10	5230	751	-	-	-	-	-	22.07	22.10
CA 2A-4A-29A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	LTE B29	10	9715	722.5	-	-	-	-	-	22.09	22.10
CA 2A-4A-30A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	-	-	-	-	-	22.08	22.10
CA 2A-4A-4A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	LTE B4	10	2250	2150	-	-	-	-	-	22.07	22.10
CA 2A-4A-5A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	-	-	-	-	-	22.06	22.10
CA 2A-5A-30A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	-	-	-	-	-	22.08	22.10
CA 2A-5A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B5	10	2525	881.5	LTE B66	20	66786	2145	-	-	-	-	-	22.06	22.10
CA 2A-66B	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B66	15	66786	2145	LTE B66	5	66879	2154.3	-	-	-	-	-	22.09	22.10
CA 2A-66C	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	-	-	-	-	-	22.07	22.10
CA 2A-7A-7A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B7	20	3100	2655	LTE B7	20	2850	2630	-	-	-	-	-	22.09	22.10
CA 2A-12A-30A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	LTE B66	20	66786	2145	22.06	22.10	
CA 2A-2A-12A-30A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B2	20	700	1940	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	22.08	22.10	
CA 2A-2A-12A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B2	20	700	1940	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	22.07	22.10	
CA 2A-2A-66A-66A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B2	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	67236	2190	22.03	22.10	
CA 2A-4A-46C	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	22.07	22.10	
CA 2A-46D	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50963	5557.3	22.08	22.10	
CA 2A-4A-7A-12A	LTE B2	5	19175	1907.5	QPSK	12	6	1175	1987.5	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	22.08	22.10	

1.3.9 LTE Band 25 as PCC

Table 12
Maximum Output Powers

Combination	PCC										SCC 1			Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12A-25A	LTE B25	15	26615	1907.5	QPSK	1	0	8615	1987.5	LTE B12	10	5095	737.5	24.36	24.38
CA 25A-25A (1)	LTE B25	15	26615	1907.5	QPSK	1	0	8615	1987.5	LTE B25	20	8140	1940	24.34	24.38
CA 25A-26A	LTE B25	15	26615	1907.5	QPSK	1	0	8615	1987.5	LTE B26	15	8865	876.5	24.38	24.38
CA 25A-41A	LTE B25	15	26615	1907.5	QPSK	1	0	8615	1987.5	LTE B41	20	40620	2593	24.34	24.38
CA 5A-25A	LTE B25	15	26615	1907.5	QPSK	1	0	8615	1987.5	LTE B5	10	2525	881.5	24.39	24.38

Table 13
Reduced Output Powers

Combination	PCC										SCC 1			Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12A-25A	LTE B25	5	26665	1912.5	QPSK	12	6	8665	1992.5	LTE B12	10	5095	737.5	22.10	22.10
CA 25A-25A (1)	LTE B25	5	26665	1912.5	QPSK	12	6	8665	1992.5	LTE B25	20	8140	1940	22.09	22.10
CA 25A-26A	LTE B25	5	26665	1912.5	QPSK	12	6	8665	1992.5	LTE B26	15	8865	876.5	22.10	22.10
CA 25A-41A	LTE B25	5	26665	1912.5	QPSK	12	6	8665	1992.5	LTE B41	20	40620	2593	22.10	22.10
CA 5A-25A	LTE B25	5	26665	1912.5	QPSK	12	6	8665	1992.5	LTE B5	10	2525	881.5	22.10	22.10

1.3.10 LTE Band 30 as PCC

Table 14
Maximum Output Powers

Combination	PCC										SCC 1			SCC 2			SCC 3			Power				
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL# RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA 2A-29A-30A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B2	20	900	1960	LTE B29	10	9715	722.5	-	-	-	-	-	22.99	22.83
CA 2A-4A-30A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	-	-	-	-	-	22.00	22.83
CA 2A-5A-30A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B2	20	900	1960	LTE B5	10	2525	881.5	-	-	-	-	-	22.97	22.83
CA 4A-5A-30A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	-	-	-	-	-	22.98	22.83
CA 5A-30A-66A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B5	10	2525	881.5	LTE B66	20	66786	2145	-	-	-	-	-	22.96	22.83
CA 2A-12A-30A-66A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B2	20	900	1960	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	22.89	22.83	
CA 2A-2A-12A-30A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B12	10	5095	737.5	22.00	22.83	
CA 4A-4A-12A-30A	LTE B30	10	27710	2310	QPSK	1	25	9820	2355	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	LTE B12	10	5095	737.5	22.82	22.83	

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset	APPENDIX H: Page 6 of 7		

1.3.11 LTE Band 7 as PCC

Table 15
Maximum Output Powers

Combination	PCC								SCC 1				SCC 2				SCC 3				Power		
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 7A-46A (1)	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B46	20	50665	5537.5	-	-	-	-	-	-	-	-	23.68	23.62
CA 7B	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B7	5	3282	2673.2	-	-	-	-	-	-	-	-	23.66	23.62
CA 7C (1)	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B7	20	3204	2665.4	-	-	-	-	-	-	-	-	23.68	23.62
CA 2A-7A-7A	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B7	20	2850	2630	LTE B2	20	900	1960	-	-	-	-	23.60	23.62
CA 4A-4A-7A (1)	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B4	20	2175	2182.5	LTE B4	10	2350	2150	-	-	-	-	23.62	23.62
CA 4A-7A-12A (1)	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B4	20	2175	2182.5	LTE B12	10	5095	737.5	-	-	-	-	23.64	23.62
CA 4A-7A-7A	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B7	20	2850	2630	LTE B4	20	2175	2132.5	-	-	-	-	23.59	23.62
CA 7A-46C (1)	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	23.69	23.62
CA 7A-46A-46A	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B46	20	50665	5537.5	LTE B46	20	47090	5180	-	-	-	-	23.66	23.62
CA 2A-4A-7A-12A	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	23.69	23.62
CA 7A-48D (1)	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50869	5557.3	23.67	23.62
CA 7A-46A-46C	LTE B7	15	21375	2562.5	QPSK	1	0	3375	2682.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	53540	5825	23.65	23.62

1.3.12 LTE Band 41 as PCC

Table 16
Maximum Output Powers

Combination	PCC								SCC1				SCC2				SCC3				Power		
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 41A-41A (1)	LTE B41	20	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	39750	2506	-	-	-	-	-	-	-	-	24.88	24.90
CA 41A-41C	LTE B41	20	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	-	-	-	-	24.88	24.90
CA 41C-41A	LTE B41	20	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41292	2660.2	LTE B41	20	39750	2506	-	-	-	-	24.90	24.90
CA 41A-41D	LTE B41	20	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	40146	2545.6	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	24.86	24.90
CA 41C-41C	LTE B41	20	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41292	2660.2	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	24.88	24.90
CA 41D-41A	LTE B41	20	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41292	2660.2	LTE B41	20	41054	2640.4	LTE B41	20	39750	2506	24.89	24.90

FCC ID: ZNFQ910QM		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 07/08/18 – 07/23/18	DUT Type: Portable Handset			APPENDIX H: Page 7 of 7