



FCC CERTIFICATION TEST REPORT

Applicant	:	Cooler Master Technology Inc.
Address of Applicant	:	7F., No.398, Xinhua 1st Rd., Neihu Dist., Taipei City 114065, Taiwan
Manufacturer	:	Dong Guan IONE Electronic Technology Co., Ltd.
Address of Manufacturer	:	Building 3 No.76, Yongjun 2nd, Road, HuangJiang Town, DongGuan City, GuangDong Province, China
Equipment under Test	:	Gaming Headset
Model No.	:	CH351, CH-351, CH-351-MC, CH-351-*****, CH351-***** The symbol "*" can be may be any alphanumeric character, symbol, or blank. When "*" is blank, "-" can be optional, for marketing usage)
FCC ID	:	2AR8X-CH351
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
Report No.	:	DDT-RE24050708-2E01
Issue Date	:	2024/08/07
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions.....	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	20 dB Bandwidth.....	13
4.1.	Block diagram of test setup	13
4.2.	Limits.....	13
4.3.	Test procedure.....	13
4.4.	Test result	14
4.5.	Test graphs	15
5.	Maximum Peak Output Power.....	21
5.1.	Block diagram of test setup	21
5.2.	Limits.....	21
5.3.	Test procedure.....	21
5.4.	Test result	22
5.5.	Test graphs	23
6.	Carrier Frequency Separation	29
6.1.	Block diagram of test setup	29
6.2.	Limits.....	29
6.3.	Test procedure.....	29
6.4.	Test result	30
6.5.	Test graphs	31
7.	Dwell Time	33
7.1.	Block diagram of test setup	33
7.2.	Limits.....	33
7.3.	Test procedure.....	33
7.4.	Test result	34
7.5.	Test graphs	35
8.	Number of Hopping Channel	47

8.1.	Block diagram of test setup	47
8.2.	Limits.....	47
8.3.	Test procedure.....	47
8.4.	Test result	48
8.5.	Test graphs.....	49
9.	Band Edge Compliance (Conducted Method).....	51
9.1.	Block diagram of test setup	51
9.2.	Limit.....	51
9.3.	Test procedure.....	51
9.4.	Test result	52
9.5.	Test graphs.....	53
10.	RF Conducted Spurious Emissions.....	61
10.1.	Block diagram of test setup	61
10.2.	Limits.....	61
10.3.	Test procedure.....	61
10.4.	Test result	62
10.5.	Test graphs.....	63
11.	Duty cycle	81
11.1.	Block diagram of test setup	81
11.2.	Limit.....	81
11.3.	Test procedure.....	81
11.4.	Test result	82
11.5.	Test graphs.....	83
12.	Antenna Requirements	89
12.1.	Limit.....	89
12.2.	Result.....	89
13.	Radiated Emission.....	90
13.1.	Test equipment.....	90
13.2.	Block diagram of test setup	91
13.3.	Limits.....	92
13.4.	Assistant equipment used for test	94
13.5.	Test procedure.....	94
13.6.	Test result	95
13.7.	Test data	96
14.	Band Edge Compliance	112
14.1.	Test equipment.....	112
14.2.	Block diagram of test setup	113
14.3.	Limits.....	113

14.4.	Assistant equipment used for test	113
14.5.	Test procedure.....	113
14.6.	Test result	113
14.7.	Test data	114
15.	Power Line Conducted Emissions.....	138
15.1.	Test equipment.....	138
15.2.	Block diagram of test setup	138
15.3.	Limits.....	138
15.4.	Assistant equipment used for test	138
15.5.	Test procedure.....	138
15.6.	Test result	139
15.7.	Test data	140
16.	Test Setup Photograph.....	142
17.	Photos of the EUT	144

Test Report Declare

Applicant	:	Cooler Master Technology Inc.
Address of Applicant	:	7F., No.398, Xinhua 1st Rd., Neihu Dist., Taipei City 114065, Taiwan
Equipment under Test	:	Gaming Headset
Model No.	:	CH351, CH-351, CH-351-MC, CH-351-*****, CH351-***** The symbol "*" can be may be any alphanumeric character, symbol, or blank. When "*" is blank, "-" can be optional, for marketing usage)
Manufacturer	:	Dong Guan IONE Electronic Technology Co., Ltd.
Address of Manufacturer	:	Building 3 No.76, Yongjun 2nd, Road, HuangJiang Town, DongGuan City, GuangDong Province, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10:2013

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24050708-2E01		
Date of Receipt:	2024/07/16	Date of Test:	2024/07/16~2024/08/07

Prepared By:**Bobo Chen/Engineer****Approved By:****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/08/07	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	Maximum Peak Output Power	FCC Part 15: 15.247(b)(1)	/	Pass
2	20 dB Bandwidth	FCC Part 15: 15.247(a)(1)	/	Pass
3	Carrier Frequency Separation	FCC Part 15: 15.247(a)(1)	/	Pass
4	Number of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii)	/	Pass
5	Dwell Time	FCC Part 15: 15.247(a)(1)(iii)	/	Pass
6	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d)	/	Pass
7	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d)	/	Pass
8	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d)	/	Pass
9	Power Line Conducted Emissions	FCC Part 15: 15.207(a)	/	Pass
10	Antenna Requirement	FCC Part 15: 15.203	/	Pass

Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

2. General Test Information

2.1. Description of EUT

EUT Name	: Gaming Headset
Model Number	: CH351, CH-351, CH-351-MC, CH-351-*****, CH351-***** The symbol "*" can be may be any alphanumeric character, symbol, or blank. When "*" is blank, "-" can be optional, for marketing usage)
Difference of model number	: All models circuits share the same electrical, mechanical and physical structure, with the only difference being the model number of the prototype. Therefore, the test model is CH351.
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V from USB cable DC 3.7V Polymer Li-ion built-in battery

Note: This EUT support Bluetooth BR/EDR, 2.4 GHz SRD, this report only for Bluetooth BR/EDR.

Radio Specification	: Bluetooth BR/EDR
Operation Frequency	: 2402 MHz-2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK

Antenna information	
Antenna Type	: Chip
Ant 1 Max Antenna Gain(dBi)	: 2.2
Ant 2 Max Antenna Gain(dBi)	: 2.2

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472

17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Dongle	Dong Guan IONE Electronic Technology Co., Ltd.	CMHS-D	/
USB cable	/	/	Length: 180cm
Aux cable	/	/	178cm

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: Upgrade_tool_25xx_v1.2.7.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK hopping on Tx mode	11	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	11	CH0 to CH78	2402 to 2480
8DPSK hopping on Tx mode	11	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	11	CH0	2402
	11	CH39	2441
	11	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	11	CH0	2402
	11	CH39	2441
	11	CH78	2480
8DPSK hopping off Tx mode	11	CH0	2402
	11	CH39	2441
	11	CH78	2480
Worst-case data rates were: GFSK mode: DH5, $\pi/4$ -DQPSK mode: 2DH5, 8DPSK mode: 3DH5			

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 4#)				
Signal &Spectrum Analyzer	R&S	FSV3044	101173	2025/03/31
Wideband Radio Communication Tester	R&S	CMW500	168801	2025/03/31
MXG Vector Signal Generator	Agilent	N5182A	MY48180737	2025/03/31
PSG Vector Signal Generator	Agilent	E8267D	US49060192	2024/09/05
RF Control Unit	Tonsend	JS0806-2	21I8060485	2025/03/31
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4. 20 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 6.9.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 20 dB bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 2 times and 5 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Measure and record the results in the report.


4.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	26.2℃,44.8%RH	Test Date:	2024.07.23~2024.07.24
Test Power Supply:	Battery	Sample Number:	S24050708-005


Test Mode	Antenna	Frequency [MHz]	20dB EBW[MHz]
DH5	Ant1	2402	0.96
	Ant2	2402	0.99
	Ant1	2441	0.97
	Ant2	2441	0.97
	Ant1	2480	0.97
	Ant2	2480	0.96
2DH5	Ant1	2402	1.24
	Ant2	2402	1.28
	Ant1	2441	1.26
	Ant2	2441	1.25
	Ant1	2480	1.28
	Ant2	2480	1.27
3DH5	Ant1	2402	1.30
	Ant2	2402	1.28
	Ant1	2441	1.25
	Ant2	2441	1.26
	Ant1	2480	1.26
	Ant2	2480	1.27

4.5.Test graphs







DH5_Ant1_2480




DH5_Ant2_2480



2DH5_Ant1_2402







2DH5_Ant1_2480




2DH5_Ant2_2480




3DH5_Ant1_2402




3DH5_Ant2_2402




3DH5_Ant1_2441




3DH5_Ant2_2441



3DH5_Ant1_2480




3DH5_Ant2_2480



5. Maximum Peak Output Power

5.1. Block diagram of test setup



5.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

5.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	> 20 dB bandwidth of the emission being measured.
VBW:	$VBW \geq RBW$.
Span:	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-to-peak function to set the marker to the peak of the emission and record the results in the report.


5.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	26.2℃,44.8%RH	Test Date:	2024.07.23~2024.07.24
Test Power Supply:	Battery	Sample Number:	S24050708-005


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
DH5	Ant1	2402	4.50	≤20.97	6.70	≤30	PASS
	Ant2	2402	4.98	≤20.97	7.18	≤30	PASS
	Ant1	2441	4.26	≤20.97	6.46	≤30	PASS
	Ant2	2441	4.90	≤20.97	7.10	≤30	PASS
	Ant1	2480	4.23	≤20.97	6.43	≤30	PASS
	Ant2	2480	4.79	≤20.97	6.99	≤30	PASS
2DH5	Ant1	2402	4.43	≤20.97	6.63	≤30	PASS
	Ant2	2402	4.91	≤20.97	7.11	≤30	PASS
	Ant1	2441	4.24	≤20.97	6.44	≤30	PASS
	Ant2	2441	4.85	≤20.97	7.05	≤30	PASS
	Ant1	2480	4.20	≤20.97	6.40	≤30	PASS
	Ant2	2480	4.77	≤20.97	6.97	≤30	PASS
3DH5	Ant1	2402	4.43	≤20.97	6.63	≤30	PASS
	Ant2	2402	4.94	≤20.97	7.14	≤30	PASS
	Ant1	2441	4.26	≤20.97	6.46	≤30	PASS
	Ant2	2441	4.83	≤20.97	7.03	≤30	PASS
	Ant1	2480	4.18	≤20.97	6.38	≤30	PASS
	Ant2	2480	4.75	≤20.97	6.95	≤30	PASS

5.5.Test graphs







DH5_Ant1_2480




DH5_Ant2_2480




2DH5_Ant1_2402




2DH5_Ant2_2402




2DH5_Ant1_2441




2DH5_Ant2_2441




2DH5_Ant1_2480




2DH5_Ant2_2480




3DH5_Ant1_2402




3DH5_Ant2_2402




3DH5_Ant1_2441




3DH5_Ant2_2441



3DH5_Ant1_2480




3DH5_Ant2_2480



6. Carrier Frequency Separation

6.1. Block diagram of test setup



6.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	approximately 30% of the channel spacing
VBW:	VBW $\geq$ RBW.
Span:	Wide enough to capture the peaks of two adjacent channels.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-delta function to determine the separation between the peaks of the adjacent channels and record the results in the report.


6.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	26.2℃,44.8%RH	Test Date:	2024.07.23~2024.07.24
Test Power Supply:	Battery	Sample Number:	S24050708-005


Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	1.000	≥0.970	PASS
	Ant2	Hop	0.992	≥0.970	PASS
2DH5	Ant1	Hop	1.000	≥0.853	PASS
	Ant2	Hop	1.010	≥0.853	PASS
3DH5	Ant1	Hop	1.002	≥0.867	PASS
	Ant2	Hop	1.006	≥0.867	PASS

6.5.Test graphs






3DH5_Ant1_Hop




3DH5_Ant2_Hop



7. Dwell Time

7.1. Block diagram of test setup



7.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.4.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	$\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$
VBW:	$VBW \geq RBW$.
Span:	Zero span, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Clear Write.
- (5) The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (6) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = total hops * pulse's on time.
- (7) Measure and record the results in the report.

7.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	26.2℃,44.8%RH	Test Date:	2024.07.23~2024.07.24
Test Power Supply:	Battery	Sample Number:	S24050708-005

Test Mode	Antenna	Frequency [MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.400	319	0.128	≤0.4	PASS
	Ant2	Hop	0.400	307	0.123	≤0.4	PASS
DH3	Ant1	Hop	1.650	155	0.256	≤0.4	PASS
	Ant2	Hop	1.650	160	0.264	≤0.4	PASS
DH5	Ant1	Hop	2.900	108	0.313	≤0.4	PASS
	Ant2	Hop	2.900	113	0.328	≤0.4	PASS
2DH1	Ant1	Hop	0.390	312	0.122	≤0.4	PASS
	Ant2	Hop	0.390	315	0.123	≤0.4	PASS
2DH3	Ant1	Hop	1.650	151	0.249	≤0.4	PASS
	Ant2	Hop	1.640	148	0.243	≤0.4	PASS
2DH5	Ant1	Hop	2.890	110	0.318	≤0.4	PASS
	Ant2	Hop	2.900	100	0.29	≤0.4	PASS
3DH1	Ant1	Hop	0.390	310	0.121	≤0.4	PASS
	Ant2	Hop	0.390	310	0.121	≤0.4	PASS
3DH3	Ant1	Hop	1.640	151	0.248	≤0.4	PASS
	Ant2	Hop	1.640	147	0.241	≤0.4	PASS
3DH5	Ant1	Hop	2.890	114	0.329	≤0.4	PASS
	Ant2	Hop	2.890	101	0.292	≤0.4	PASS

DH1_Ant1_Hop

The figure consists of three screenshots of a spectrum analyzer interface, showing signal capture and analysis for two different antennas.

Screenshot 1: DH1_Ant1_Hop (Top)


- MultiView / Spectrum**: Shows a spectrum plot with a peak at approximately 2.441 GHz.
- Ref Level**: 20.00 dBm, **Offset**: 12.48 dB, **RBW**: 1 MHz.
- Att**: 20 dB, **SWT**: 10 ms, **VBW**: 3 MHz.
- TRG:VID**: 1 Zero Span.
- Scale**: 10 dBm to -70 dBm.
- Frequency**: CF 2.441 GHz, 1001 pts.
- Time**: 20:14:09 23.07.2024.
- Peak Data**: M1[1] 3.83 dBm, 0 s; S2[1] -9.02 dB, 400.00 μ s.
- Trigger**: TRG -9.800 dBm.

Screenshot 2: DH1_Ant1_Hop (Middle)



- MultiView / Spectrum**: Shows a spectrum plot with a peak at approximately 2.441 GHz.
- Ref Level**: 20.00 dBm, **Offset**: 12.48 dB, **RBW**: 500 kHz.
- Att**: 20 dB, **SWT**: 31.6 s, **VBW**: 3 MHz.
- TRG:VID**: 1 Zero Span.
- Scale**: 10 dBm to -70 dBm.
- Frequency**: CF 2.441 GHz, 30001 pts.
- Time**: 20:14:45 23.07.2024.
- Peak Data**: M1[1] 4.15 dBm, 0 s; S2[1] -9.44 dB, 400.00 μ s.
- Trigger**: TRG -9.800 dBm.

Screenshot 3: DH1_Ant2_Hop (Bottom)


- MultiView / Spectrum**: Shows a spectrum plot with a peak at approximately 2.441 GHz.
- Ref Level**: 20.00 dBm, **Offset**: 12.48 dB, **RBW**: 1 MHz.
- Att**: 20 dB, **SWT**: 10 ms, **VBW**: 3 MHz.
- TRG:VID**: 1 Zero Span.
- Scale**: 10 dBm to -70 dBm.
- Frequency**: CF 2.441 GHz, 1001 pts.
- Time**: 21:00:02 23.07.2024.
- Peak Data**: M1[1] 4.15 dBm, 0 s; S2[1] -9.44 dB, 400.00 μ s.
- Trigger**: TRG -9.100 dBm.




DH3_Ant1_Hop





DH3_Ant2_Hop







DH5_Ant2_Hop





2DH1_Ant1_Hop










2DH3_Ant1_Hop




2DH3_Ant2_Hop













3DH3_Ant1_Hop




3DH3_Ant2_Hop





8. Number of Hopping Channel

8.1. Block diagram of test setup



8.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

8.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW:	VBW $\geq$ RBW.
Span:	The frequency band of operation
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (5) Measure the hopping number and record the results in the report.
- (6) Measure and record the results in the report.

8.4. Test result

Test Engineer:	Haofeng	Test Site:	RF Measurement System 4#
Ambient Condition:	26.2℃,44.8%RH	Test Date:	2024.07.23~2024.07.24
Test Power Supply:	Battery	Sample Number:	S24050708-005

Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
	Ant2	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
	Ant2	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS
	Ant2	Hop	79	≥15	PASS