

Made in Germany, 79689 Maulburg

Micropilot

Order code: 12345678901234

Ser. no.: 12345678901234

Ext. ord. cd.:NMR84-FC1AA1A2A1AC+ACAABA1ADJICRAAEA+HAJALAN1PA0123456789012345678901234567890

24...62 V AC / DC (50...60 Hz) ..VA

MWP: 1bar / 14.5psi

Tp max.: 200°C

Ta > 60 °C: 

>85°C

M20x1.5

Mat.: FFKM, PTFE, 316L

DeviceID: 452B481005-A91234010AB

FW: 01.00.00 Dev.Rev.: 1 ex works

20.14

TC 72222

89.01

Tank ID: 505

Tank ref.height: 505

Zero point: 1

Ta: -20...~+60 °C

0700

CE

0044

Endress+Hauser

IP68 / 66 Type 4X / 6P Encl.

FM

US

APPROVED

FM16US0006X

XP-IS / I / 1 / A - D / T6-T1

XP-AIS / I / 1 / A - D / T6-T1;

CL I Zone 0/1 AEx ia/d IIC T6-T1 Ga/Gb

CL I Zone 1 AEx d[ia Ga] IIC T6-T1 Gb

FM16CA0006X

XP / I / 1 / B - D / T6-T1

IS / I / 1 / A - D / T6-T1

AIS / I / 1 / A - D / T6-T1;

1 / Ex db IIC T6-T1 Gb

0 / Ex ia IIC T6-T1 Ga

1 / Ex db [ia Ga] IIC / T6-T1 Gb

FCC ID LCGNMR8XC

Dual seal

Z-65.16-xyz

→

X = if modification see sep. label

Date: 2016-02