



SPECIFICATION

APPLICATION FOR APPROVAL

客户名称 CUSTOMER : 上海英众信息科技有限公司
客户案号 CS P/N : XB22-Aux
零件名称 PART NAME : AUK02130B-Aux
耀登案号 DEVE NO. : B52462-00

承认日期 DATE : Jul. 8, 2021

客户确认:			
射频工程师	结构工程师	研发经理	产品经理
耀登电通科技(昆山)有限公司			
电气工程师	结构工程师	研发经理	项目经理
陈金马	张海洋	钱磊	王显文

总部

耀登电通科技(昆山)有限公司
江苏省昆山市周市镇迎宾路 15 号
TEL: 0512-57646998
FAX: 0512-57646168

Head Quarter

Auden Techno(KUNSHAN)CO.LTD
NO.15 YING-BIN ROAD, LUYANGTOWN, KUNSHAN, JIANGSU
CHINA

分公司:

耀登电通科技(昆山)有限公司西安分公司
西安市 高新区 唐延南路 10 号 中兴产业园 E1-04
TEL: 13382157879

Branch

Auden Techno(KUNSHAN)CO.LTD. Xi 'an branch
E1-04, zhongxing industrial park, no.10 tangyan south road,
high-tech zone, xi 'an

耀登电通科技(昆山)有限公司深圳分公司
地址: 深圳市南山区桃源街道红花岭工业区第五区 A 栋二楼
201-202 (南区)
TEL: 185 8845 5257

Auden Techno(KUNSHAN)CO.LTD. Shenzhen branch
Address: 201-202, 2nd floor, building A, zone 5, honghualing
industrial zone, taoyuan street, nanshan district, shenzhen
(southern district)

CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.


INDEX

- 一、规格书封面 (Cover)
- 二、规格书目录 (Index)
- 三、天线基本参数 (The Basic Parameters)
- 四、电气测试报告 (RF Performance Test Report)
- 五、工程图纸 (Product Drawing)
- 六、尺寸报告 (Dimensional check reports)
- 七、可靠性测试报告 (Reliability test report)

CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.

天线基本参数 (The Basic Parameters)


项目 (Item)	特性 (Specifications)
天线结构组成	FPC+CABLE
频率 (Frequency)	2.4g~5.8g
驻波比 (V. S. W. R)	≤ 3
增益 (Gain)	≤ 7
极化方式 (Polarization)	线极化
特性阻抗 (Impedance)	50Ω
塑胶材质 (Plastic material)	无
接头形式 (joint type)	4 代端子+Cable
工作温度 (Operation temperature)	-40°C to 85°C
储存温度 (Storage temperature)	-40°C to 85°C
湿度 (humidity)	Non-condensing 65°C 95% RH
天线图片	

CONFIDENTIAL


This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.

电气测试报告（RF Performance Test Report）

组装位置



V.S.W.R



CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.




Aux-无源测试数据

Frequency	Efficiency(%)	Gain(dBi)	Frequency	Efficiency(%)	Gain(dBi)
2.4G	54.33	2.23	5.15G	79.98	6.41
2.41G	53.46	2.21	5.2G	76.91	6.15
2.42G	53.58	2.34	5.25G	73.11	5.83
2.43G	51.05	2.14	5.3G	77.27	6.24
2.44G	51.17	2.12	5.35G	69.5	5.89
2.45G	54.58	2.34	5.4G	72.11	6.19
2.46G	54.95	2.14	5.45G	68.39	5.95
2.47G	54.58	2.19	5.5G	67.14	5.96
2.48G	57.15	2.41	5.55G	53.95	5.15
2.49G	55.34	2.33	5.6G	54.45	5.23
2.5G	52.24	2.13	5.65G	53.21	5.28
			5.7G	63.24	5.8
			5.75G	60.53	5.26
			5.8G	62.37	5.36
			5.85G	64.27	5.25

CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.

工程图纸 (Product Drawing)



尺寸报告 (Dimensional check reports)

CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message.

Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.



Auden Techno(KUNSHAN)CO.LTD ANTENNA SPECIFICATION

No perfect status,Always seek for better !

全尺寸测量报告

Vendor(供应商)		材质名称		天线		Part NO(料号)		B52462-00								Tool Number(模号)		Cav. Number(穴数)		Unit(单位)				Comments(设计者签字)							
耀登						Part Name (零件名称)		总装												INCHES ■MILLIMETERS											
日期		2021/7/7														AUK02130B-AUX		Rev(版本)	V1.0												
MEASURED DIMENSION(实测尺寸)																% TOLERANCE USED(公差使用百分比)		DISPOSITION						ACCEPTABLE VARIANCE							
DIM. #	DIMENSION		DRAWING ZONE	+ TOL.	- TOL.	NOTE	SAMPLE 1	SAMPLE 2	SAMPLE 3	SAMPLE 4	SAMPLE 5	SAMPLE 6	SAMPLE 7	SAMPLE 8	SAMPLE 9	SAMPLE 10	UPPER	LOWER	0%-25%	25%-50%	50%-75%	75%-100%	100%+	Re-Measure	Accept	Fix Tool	Accept	With Variance	DIMENSION	+ TOL.	- TOL.
1	23.78	1A	0.15	0.15			23.78	23.79	23.77	23.78	23.79	23.79	23.77	23.78	23.79	23.78	7%	7%	X												
2	25.40	2A	0.15	0.15			25.40	25.41	25.39	25.40	25.41	25.41	25.39	25.40	25.41	25.40	7%	7%	X												
3	154.20	3A	2.00	2.00			154.20	154.30	154.40	154.20	154.30	154.30	154.40	154.20	154.30	154.20	10%	0%	X												
4	0.81	4A	0.05	0.05			0.81	0.81	0.80	0.80	0.81	0.81	0.80	0.80	0.81	0.80	0%	20%	X												
5	170.00	1	2.00	2.00			170.10	170.00	170.20	170.30	170.10	170.00	170.20	170.30	170.10	170.30	15%	0%	X												
6	0.15	2	0.05	0.05			0.15	0.16	0.14	0.15	0.15	0.16	0.14	0.15	0.15	0.15	20%	20%	X												
核准: 李金			审核: 麦建国												制表: 孙贊贊																

CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.



可靠性测试报告(Reliability test report)

NO.	ITEM	TEST CONDITION	SPECIFICATION
1	Low Temperature Test	1.Temperature: $-40\pm 2^{\circ}\text{C}$ 2.Time: 48hrs	No material deformation is allowed.
2	High Temperature Test	1.Temperature: $+85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 2.Time: 48hrs	
3	High Temperature/Humidity Storage Test(non operating)	1.Temperature: $+60 \pm 2^{\circ}\text{C}$ 2.Humidity: $93\% \pm 2\% \text{RH}$ 3.Time: 48hrs	
4	Salt-Spray Test	35°C , 85%RH, 48Hours(According to MIL-STD-810E) The salt-spray is generated from a 5% salt(NaCl) solution.,	NO appear rusting phenomenon is allowed

耀登电通科技(昆山)有限公司

可靠性测试汇总报告

客户		客户机种		耀登机种	AUK02130B-AUX					
可靠性测试项目及要求						测试结果				
序号	测试项目	测试时间	测试仪器	测试条件	判定标准	1	2	3	4	5
1	盐雾试验	2021/6/30	盐雾测试机	将产品放于盐雾试验机中, 在 $35^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 的密闭环境中, PH值在6.5-7.2范围内, 用5% $\pm 1\%$ 的NaCl溶液连续48h盐水喷雾后, 将样品用清水冲洗干净后检查天线外观;	表面无锈蚀、镀层剥落、起泡等不良现象, RF测试通过为合格。	OK	OK	OK	OK	OK
2	低温试验	2021/6/30	恒温恒湿机	将产品放置在温度为 $-40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 的低温环境存储48h, 试验完成后在常温环境下放置2小时后检查产品外观。	部件无裂痕、明显的变形、脱落, RF测试通过为合格。	OK	OK	OK	OK	OK
3	高温试验	2021/7/2	恒温恒湿机	将产品放置在温度为 $85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 的高温环境存储48h, 试验完成后在常温环境下放置2 h后检查产品外观。	部件无裂痕、明显的变形、脱落, RF测试通过为合格。	OK	OK	OK	OK	OK
4	高温高湿试验	2021/7/4	恒温恒湿机	将产品放置在温度为 $60^{\circ}\text{C} \pm 2^{\circ}\text{C}$; 湿度: $93\% \pm 2\% \text{RH}$ 环境存储48h, 试验完成后在常温环境下放置2小时后检查产品外观。	部件无裂痕、明显的变形、脱落, RF测试通过为合格。	OK	OK	OK	OK	OK
试验结果判定				可靠性试验合格						
核准: 李金				审核: 麦建国			测试员: 孙赞赞			

CONFIDENTIAL

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.