

# **FCC RF EXPOSURE REPORT**

**FCC ID: Q3N-2564MR**

**Project No. : 1612075**  
**Equipment : BT Scanner**  
**Model : 2564MR**  
**Applicant : CIPHERLAB CO., LTD.**  
**Address : 12F, 333, Dunhua S. Rd., Sec. 2, Taipei, Taiwan**

**According: : FCC Guidelines for Human Exposure IEEE  
C95.1**

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.  
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Quietek	2560MB_2015 0830A	Printed	N/A	3.54

**GENERAL CONCLUSION:**

Maximum measured transmitter power:

BT

OutputPower (dBm)	Output Power (mW)	Limit (mW)
2.08	1.61	10

LE

OutputPower (dBm)	Output Power (mW)	Limit (mW)
3.74	2.37	10

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm

The maximum measured output peak power of this EUT is 2.37 less than 10mW at 5mm distance.

**Conclusion: No SAR evaluation required since transmitter power is below FCC threshold**