

*February 1, 2002*

*Tandy Electronics (China) Ltd.  
6/F. & 7/F., M.C. Packaging Bldg.,  
9th District Lian Tang Ind. District,  
Shenzhen, Guangdong, China*

*Dear Mr. Tan Hui:*

*Enclosed you will find your file copy of a Part 15 report (FCC ID: AAO3301196T).*

*For your reference, TCB will normally take another 15-20 days for reviewing the report.  
Approval will then be granted when no query is sorted.*

*Please contact me if you have any questions regarding the enclosed material.*

*Sincerely,*

*Alfred Lo  
Senior Technical Supervisor*

*Enclosure*

*FCC ID: AAO3301196T*

**Tandy Electronics (China) Ltd.**

Application  
For  
Certification  
**(FCC ID: AAO3301196T)**

Transmitter

WO# 0200048  
AL/sa  
February 1, 2002

FCC ID: AAO3301196T

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited
- For Terms And Conditions of the services, it can be provided upon request.

# INTERTEK TESTING SERVICES

---

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information

# INTERTEK TESTING SERVICES

## MEASUREMENT/TECHNICAL REPORT

**Tandy Electronics (China) Ltd. - MODEL: 33-1196 Transmitter**  
**FCC ID: AAO3301196T**

This report concerns (check one):      Original Grant       Class II Change

Equipment Type: Low Power Transmitter (example: computer, printer, modem, etc.)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes       No

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?      Yes       No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [5-24-01 Edition] provision.

Report prepared by:

Alfred Lo  
Intertek Testing Services  
Hong Kong Ltd.  
2/F., Garment Centre,  
576, Castle Peak Road,  
Kowloon, Hong Kong  
Phone: 852-2173-8545  
Fax: 852-2371-0914

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0 <b>General Description</b> .....	3
1.1 Product Description.....	3
1.2 Related Submittal(s) Grants.....	3
1.3 Test Methodology.....	4
1.4 Test Facility .....	4
2.0 <b>System Test Configuration</b> .....	6
2.1 Justification.....	6
2.2 EUT Exercising Software .....	6
2.3 Special Accessories .....	6
2.4 Equipment Modification.....	7
2.5 Support Equipment List and Description .....	7
3.0 <b>Emission Results</b> .....	9
3.1 Field Strength Calculation .....	10
3.1 Field Strength Calculation (cont'd) .....	11
3.2 Radiated Emission Configuration Photograph .....	12
3.3 Radiated Emission Data .....	13
3.4 Conducted emission Configuration Photograph.....	16
3.5 Conducted Emission Data .....	18
4.0 <b>Equipment Photographs</b> .....	20
5.0 <b>Product Labelling</b> .....	22
6.0 <b>Technical Specifications</b> .....	24
7.0 <b>Instruction Manual</b> .....	26
8.0 <b>Miscellaneous Information</b> .....	28
8.1 Measured Bandwidth.....	29
8.2 Discussion of Pulse Desensitization .....	30
8.3 Calculation of Average Factor .....	31
8.4 Emissions Test Procedures .....	32
8.4 Emissions Test Procedures (cont'd).....	33

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit type	File Description	filename
Cover Letter	Letter of Agency	letter.pdf
Test Report	Test Report	report.doc
Operation Description	Technical Description	descri1.pdf, descri2.pdf and descri3.pdf
Test Setup Photo	Radiated Emission	radiated1.jpg, radiated2.jpg
Test Setup Photo	Conduct Emission	conduct1.jpg, conduct2.jpg, conduct3.jpg
Test Report	Conducted Emission Test Result	conduct.pdf
Test Report	Bandwidth Plot	bw.pdf
External Photo	External Photo	ophoto1.jpg, ophoto2.jpg, ophoto3.jpg and ophoto4.jpg
Internal Photo	Internal Photo	iphoto1.jpg, iphoto2.jpg, iphoto3.jpg, iphoto4.jpg, iphoto5.jpg, iphoto6.jpg and iphoto7.jpg
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual1.pdf, manual2.pdf and manual3.pdf

**EXHIBIT 1**

**GENERAL DESCRIPTION**

# INTERTEK TESTING SERVICES

---

## 1.0 General Description

### 1.1 Product Description

The Equipment Under Test (EUT) is a transmitter for wireless headphone (single channel) operating at 900MHz. The EUT is powered by AC/DC adaptor which provided by the applicant (model U120025D; 120VAC/12VDC). It consists the power switch for switch "on" or "off" the transmitter. On the hand, the DC jack and the AUDIO IN jacks (phono type) are use the DC power connection and connecting to an audio source respectively. Moreover, this transmitter includes an additional lead for headphone's batteries charging process which covered by the plastic cover at the back of EUT. The bare wire type antenna was equipped inside the plastic case and its photo was shown on the following pages. The mains function of this product is use to transmit the modulated signal to it's corresponding received.

For electronic filing, the brief circuit description is saved with filename: descri1.pdf to descri3.pdf

### 1.2 Related Submittal(s) Grants

The receiver for this transmitter was authorized by Certification procedure. The FCC ID of the associated receiver is AAO3301196 and has been filed at the same time as this application.

## INTERTEK TESTING SERVICES

---

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (1992). Radiated Emission measurement was performed in Open Area Test Sites and Conducted Emission was performed in shield room. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

**EXHIBIT 2**

**SYSTEM TEST CONFIGURATION**

# INTERTEK TESTING SERVICES

---

## 2.0 **System Test Configuration**

### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSIC63.4 (1992).

The EUT was powered AC/DC Adaptor which provided by the applicant

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

For simplicity of testing, the unit was operated to transmit continuously.

### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the typical signal continuously.

### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

## INTERTEK TESTING SERVICES

---

### 2.4 Equipment Modification

Any modifications installed previous to testing by Tandy Electronics (China) Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services.

### 2.5 Support Equipment List and Description

Auxiliary input of EUT connected to a walkman through 1.8 mter cable  
(Provided by ITS)

All the items listed under section 2.0 of this report are:

*Confirmed by:*

*Alfred Lo  
Senior Technical Supervisor - Home Entertainment Electronics  
Intertek Testing Services Hong Kong Ltd.  
Agent for Tandy Electronics (China) Ltd.*

\_\_\_\_\_.Signature

\_\_\_\_\_February 1, 2002\_\_\_\_\_Date

**EXHIBIT 3**  
**EMISSION RESULTS**

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

### 3.1 Field Strength Calculation (cont'd)

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
at  
919.846 MHz

For electronic filing, the front view and back view of the test configuration photographs are saved with filename: radiated1.jpg and radiated2.jpg respectively.

## INTERTEK TESTING SERVICES

---

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 3.0 dB margin

#### ***TEST PERSONNEL:***

\_\_\_\_\_  
*Signature*

Lawrence H. C. Chow, Compliance Engineer  
*Typed/Printed Name*

February 1, 2002 \_\_\_\_\_

Date

# INTERTEK TESTING SERVICES

---

Company: Tandy Electronics (China) Ltd.  
 Model: 33-1196 Transmitter  
 Worst Case Operating Mode: Transmitting Mode

Date of Test: January 4, 2002

**Table 1**

**Radiated Emissions**

Polarity	Frequency	Reading	Antenna	Pre-Amp	Net	Limit	Margin
	(MHz)	(dB $\mu$ V)	Factor (dB)	Gain (dB)	3m at (dB $\mu$ m)	at 3m (dB $\mu$ V/m)	(dB)
H	907.243	35.0	22.6	16	41.6	46.0	-4.4
H	911.449	84.0	22.6	16	90.6	94.0	-3.4
H	915.646	84.2	22.6	16	90.8	94.0	-3.2
H	919.846	36.4	22.6	16	43.0	46.0	-3.0
H	1822.898	46.1	26.5	34	38.6	54.0	-15.4
H	1831.292	46.4	26.5	34	38.9	54.0	-15.1
H	*2734.347	43.3	29.1	34	38.4	54.0	-15.6
H	*2746.938	43.4	29.1	34	38.5	54.0	-15.5
H	*3654.796	39.1	32.8	34	37.9	54.0	-16.1
H	*3662.584	38.8	32.8	34	37.6	54.0	-16.4

- NOTES:
1. Peak Detector is used below 1000MHz unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative sign in the column shows value below limit.
  4. Horn antenna and average detector are used for the emission over 1000MHz.
  5. The radiated emission test was observed up to 40GHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Lawrence H. C. Chow

---

## INTERTEK TESTING SERVICES

---

Company: Tandy Electronics (China) Ltd.  
Model: 33-1196 Transmitter  
Worst Case Operating Mode: Charging Mode

Date of Test: January 4, 2002

**Table 2**

**Radiated Emissions**

Polarity	Frequency	Reading	Antenna	Pre-Amp	Net	Limit	Margin
	(MHz)	(dB $\mu$ V)	Factor (dB)	Gain (dB)	3m at (dB/m)	at 3m (dB $\mu$ V/m)	(dB)
H	32.841	30.2	11.6	16	25.8	40.0	-14.2
H	36.496	30.4	11.2	16	25.6	40.0	-14.4
H	48.341	29.0	11.9	16	24.9	40.0	-15.1
H	52.849	28.6	11.7	16	24.3	40.0	-15.7
H	58.764	29.0	11.0	16	24.0	40.0	-16.0
H	63.229	29.9	9.9	16	23.8	40.0	-16.2

- NOTES:
1. Peak Detector is used below 1000MHz unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative sign in the column shows value below limit.
  4. Horn antenna and average detector are used for the emission over 1000MHz.
  5. The radiated emission test was observed up to 40GHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Test Engineer

### 3.4 Conducted Emission Configuration Photograph

Worst Case Conducted Emission  
at  
0.45 MHz

For electronic filing, the front view, rear view and side view of the test configuration photographs are saved with filename: conduct1.jpg, conduct2.jpg and conduct3.jpg.

# INTERTEK TESTING SERVICES

---

Company: Tandy Electronics (China) Ltd.  
Model: 33-1196 Transmitter

Date of Test: January 4, 2002

## **Conducted Emissions Section 15.107 Requirements**

For Electronic filing, the conducted emission test result is saved with filename: conduct.pdf

## INTERTEK TESTING SERVICES

---

### 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission are saved with filename: conduct.pdf. The data table lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 21.7 dB margin

\* Peak Detector Data Unless otherwise stated.

### ***TEST PERSONNEL:***

\_\_\_\_\_  
*Signature*

Lawrence H. C. Chow, Compliance Engineer  
*Typed/Printed Name*

February 1, 2002 \_\_\_\_\_  
Date

**EXHIBIT 4**

**EQUIPMENT PHOTOGRAPHS**

### 4.0 **Equipment Photographs**

For electronic filing, photographs of the tested EUT are saved with filename: ophoto1.jpg to ophoto4.jpg for external photo, and iphoto1.jpg to iphoto7.jpg for internal photo.

**EXHIBIT 5**

**PRODUCT LABELLING**

### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

**EXHIBIT 6**

**TECHNICAL SPECIFICATIONS**

### 6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

**EXHIBIT 7**

**INSTRUCTION MANUAL**

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual1.pdf to manual3.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States. Moreover, it was said that the declaration which mention in following pages will also be committed at the time.

**EXHIBIT 8**

**MISCELLANEOUS INFORMATION**

## 8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

### 8.1 Measured Bandwidth

The plot on saved in bw.pdf shows the fundamental emission which are with/without applying modulation. From the plot, it shows the emission is within the band edge 902MHz and 928MHz (as the plotting shown that the start and stop frequencies of it are 910.14MHz and 916.144MHz respectively). The unit meets the FCC bandwidth requirements.

### 8.2 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device. Since the transmitter transmits the RF signal continuously.

### 8.3 Calculation of Average Factor

Since this device is a transmits signal continuously, it is not necessary to apply average factor to the measurement results.

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of Low Power Transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 1992.

The equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the groundplane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 450 kHz to 30 MHz.

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 1992.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Measurements are normally conducted at a measurement distance of three meters. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.