

RF Test Report

For


Applicant name: Shenzhen Yizhita Technology Co., Ltd
Address: Room 1901, Qianhai HOP Int'l, No. 19 Xinghua 1st Rd (Extension), Bao'an District, Shenzhen, Guangdong, China.
EUT name: ATK BLAZING SKY Z1 lightweight wireless mouse
Brand name: ATK
Model number: ATK BLAZING SKY Z1 Ultra
Series model number: N/A

Issued By

Company name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Report number: BTF240920R01901
Test standards: FCC CFR Title 47 Part 15 Subpart C (§15.247)
Test conclusion: Pass
FCC ID: 2BE9P-ATKZ1ULTRA
Test date: 2024-09-21 to 2024-09-26
Date of issue: 2024-09-29
Test by: Ssxx.guo
Ssxx.Guo / Tester

Prepared by: Ace Xie
Ace Xie Project engineer

Approved by: 
Ryan.C/EMC manager



Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue date	Revisions content
R_V0	2024-09-29	Original
<i>Note:</i> <i>Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1 Introduction	4
1.1 Laboratory Location	4
1.2 Laboratory Facility	4
1.3 Announcement	4
2 Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Technical Information	5
2.6 Channel list	6
3 Test Information	7
3.1 Test Standards	7
3.2 Summary of Test	7
3.3 Uncertainty of Test	8
3.4 Additions to, deviations, or exclusions from the method	8
3.5 Test Auxiliary Equipment	8
3.6 Test Equipment List	8
4 Test Configuration	10
4.1 Environment Condition	10
4.2 Test mode	10
4.3 Test Channel of EUT	10
4.4 Test procedure	11
4.5 Test Setup Block	12
5 Technical requirements specification	14
5.1 Summary of Test Result	14
5.2 Antenna Requirement	15
5.3 AC Power Line Conducted Emission	16
5.4 Emissions in Restricted Frequency Bands	18
5.5 Emissions in Non-restricted Frequency Bands	19
6 Test Setup Photos	23
7 EUT Constructional Details (EUT Photos)	25

1 Introduction

1.1 Laboratory Location

Test location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone number:	+86-0755-23146130
Fax number:	+86-0755-23146130

1.2 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1330**
BTF Testing Lab (Shenzhen) Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Registration No. is 518915.
- **ISED – CAB identifier.: CN0135**
The 3m Semi-anechoic chamber of BTF Testing Lab (Shenzhen) Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 27844.
- **CNAS - Registration No.: CNAS L17568**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L17568.
- **A2LA - Registration No.: 6660.01**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 Product Information

2.1 Application Information

Company name:	Shenzhen Yizhita Technology Co., Ltd
Address:	Room 1901, Qianhai HOP Int'l, No. 19 Xinghua 1st Rd (Extension), Bao'an District, Shenzhen, Guangdong, China.

2.2 Manufacturer Information

Company name:	Shenzhen Yizhita Technology Co., Ltd
Address:	Room 1901, Qianhai HOP Int'l, No. 19 Xinghua 1st Rd (Extension), Bao'an District, Shenzhen, Guangdong, China.

2.3 Factory Information

Company name:	Dongguan Dianxuntong Electronics Technology Co., Ltd.
Address:	Room 302, Building 1, No. 6 Wende Street, Xiabian, Chang'an Town, Dongguan City, Guangdong Province

2.4 General Description of Equipment under Test (EUT)

EUT name	ATK BLAZING SKY Z1 lightweight wireless mouse
Under test model name	ATK BLAZING SKY Z1 Ultra
Series model name	N/A
Description of model name differentiation	N/A
Power supply:	DC 5V
AC adapter:	N/A

2.5 Technical Information

Operation frequency:	2403MHz ~ 2480MHz
Channel numbers:	16
Channel separation:	1MHz
Modulation technology:	GFSK
Max. E.I.R.P Power:	-5.55 dBm
Antenna type:	Internal Antenna
Antenna gain:	-2.39 dBi (declare by Applicant)
Antenna transmit mode:	SISO (1TX, 1RX)

2.6 Channel list

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2403MHz	7	2452MHz	13	2470MHz
2	2424MHz	8	2458MHz	14	2472MHz
3	2442MHz	9	2462MHz	15	2474MHz
4	2444MHz	10	2464MHz	16	2480MHz
5	2446MHz	11	2466MHz		
6	2450MHz	12	2468MHz		

3 Test Information

3.1 Test Standards

Identity	Document Title
FCC CFR Title 47 Part 15 Subpart C (§15.247)	Intentional Radiators - Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of The FCC Rules

3.2 Summary of Test

Clauses	Test Items	Result
§ 15.203 § 15.247(b)(4)	Antenna Requirement	Pass
§ 15.207	AC Power Line Conducted Emission	Pass
§ 15.247(b)(1)	Conducted Output Power	Pass
§ 15.247(a)(1)	20dB Occupied Bandwidth	Pass
§ 15.247(a)(1)	Carrier Frequencies Separation	Pass
§ 15.247(a)(1)(iii)	Hopping Channel Number	Pass
§ 15.247(a)(1)(iii)	Dwell Time	Pass
§ 15.247(d)	Band-edge Emission Conduction Spurious Emission	Pass
§ 15.205 § 15.247(d)	Emissions in Restricted Frequency Bands	Pass
§ 15.209 § 15.247(d)	Emissions in Non-restricted Frequency Bands	Pass

Remark:

1. Pass: met the requirements.
2. N/A: not applicable.

3.3 Uncertainty of Test

Measurement	Value
Conducted Emission for LISN (9kHz ~ 150kHz)	±2.97 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.45 dB
Radiated Emission (30MHz ~ 1000MHz)	±4.80 dB
Radiated Emission (1GHz ~ 18GHz)	±5.25 dB
Radiated Emission (18GHz ~ 40GHz)	±5.35 dB
The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3.4 Additions to, deviations, or exclusions from the method

None

3.5 Test Auxiliary Equipment

The EUT has been tested as an independent unit.

3.6 Test Equipment List

Conducted Emission Test					
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EMI Receiver	Rohde & Schwarz	ESCI3	101422	2023/11/15	2024/11/14
V-LISN	Schwarzbeck	NSLK 8127	01073	2023/11/16	2024/11/15
Coaxial Switcher	Schwarzbeck	CX210	CX210	/	/
Pulse Limiter	Schwarzbeck	VTSD 9561-F	00953	/	/
Test Software	Frad	EZ_EM	Version: EMC-CON 3A1.1+		

Radiated test method					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EMI Receiver	Rohde & Schwarz	ESCI7	101032	2023/11/16	2024/11/15
Signal Analyzer	Rohde & Schwarz	FSQ40	100010	2023/11/16	2024/11/15
Log periodic antenna	Schwarzbeck	VULB 9168	01328	2023/11/13	2024/11/12
Preamplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9744	00246	2023/11/13	2024/11/12
Horn Antenna	Schwarzbeck	BBHA9120D	2597	2023/11/13	2024/11/12
Preamplifier (1GHz ~ 18GHz)	TST	LNA10180G45	TS2215007	2023/11/13	2024/11/12
Test Software	Frad	EZ_EM	Version: FA-03A2 RE+		

Conducted test method					
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020A	MY50410020	2023/11/16	2024/11/15
ESG Vector Signal Generator	Agilent	E4438C	MY45094854	2023/11/16	2024/11/15
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2023/11/16	2024/11/15
Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	161997	2023/11/16	2024/11/15
Temperature Humidity Chamber	ZZCKONG	ZZ-K02A	20210928007	2023/11/16	2024/11/15
DC Power Supply	Tongmen	etm-6050c	20211026123	2023-11-16	2024-11-15
RF Control Unit	Techy	TR1029-1	/	2023/11/11	2024/11/12
RF Sensor Unit	Techy	TR1029-2	/	2023/11/11	2024/11/12
Test Software	TST Pass	/	Version: 2.0		

4 Test Configuration

4.1 Environment Condition

Selected Values During Tests			
Temperature	Test Voltage	Relative Humidity	Ambient Pressure
Normal: +15°C to +35°C	120V/60Hz	20% to 75%	100 kPa to 102 kPa

4.2 Test mode

Transmitting mode:	Keep the EUT in continuously transmitting mode with modulation
Hopping mode:	Keep the EUT in normal hopping mode
Remark: Per-scan all kind of data rate, and report only reflects the test data of worst data rate mode.	

4.3 Test Channel of EUT

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2403	3	2442	16	2480

4.4 Test procedure

AC Power Line Conducted Emission

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Radiated test method

For below 1GHz:

1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

For above 1GHz:


1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

Conducted test method


1. The Bluetooth antenna port of EUT was connected to the test port of the test system through an RF cable.
2. The EUT is keeping in continuous transmission mode and tested in all modulation modes.
3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.


4.5 Test Setup Block

1) Conducted emission measurement:



2) Conducted test method:



3) Radiated test method:

5 Technical requirements specification

5.1 Summary of Test Result

Test Items	Limit	Test data	Verdict
Antenna Requirement	Please refer to §15.203 and §15.247(b)(4)	See Section 5.2	Pass
AC Power Line Conducted Emission	Please refer to §15.207	See Section 5.3	Pass
Conducted Output Power	Non-overlapping hopping channels: 1 watts (30dBm). All other frequency hopping systems: 0.125 watts (21dBm).	See Appendix-2.4G FHSS	Pass
20dB Occupied Bandwidth	Within authorization band	See Appendix-2.4G FHSS	Pass
Carrier Frequencies Separation	a) 0.025MHz or the 20dB bandwidth (whichever is greater). b) 0.025MHz or two-thirds of the 20dB bandwidth (whichever is greater).	See Appendix-2.4G FHSS	Pass
Hopping Channel Number	At least 15 channels.	See Appendix-2.4G FHSS	Pass
Dwell Time	Not be greater than 0.4 seconds.	See Appendix-2.4G FHSS	Pass
Band-edge Emission Conduction Spurious Emission	Please refer to §15.247(d)	See Appendix-2.4G FHSS	Pass
Emissions in Restricted Frequency Bands	Please refer to §15.205	See section 5.4	Pass
Emissions in Non-restricted Frequency Bands	Please refer to §15.209 and §15.247(d)	See section 5.5	Pass

5.2 Antenna Requirement

§15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

§15.247(b) (4) requirement:

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


E.U.T Antenna:

The Bluetooth antenna is an Internal antenna which permanently attached, and the best case gain of the antenna is -2.39 dBi. See product internal photos for details.

5.3 AC Power Line Conducted Emission


Remark: All modes are tested, and only the worst mode GFSK 2403MHz is showed in the report.

Test phase: L phase



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3300	19.56	10.57	30.13	59.45	-29.32	QP	P	
2	0.3524	7.11	10.57	17.68	48.91	-31.23	AVG	P	
3	0.5054	9.04	10.58	19.62	46.00	-26.38	AVG	P	
4	0.5324	21.90	10.60	32.50	56.00	-23.50	QP	P	
5 *	0.8880	27.11	10.68	37.79	56.00	-18.21	QP	P	
6	0.9104	13.83	10.67	24.50	46.00	-21.50	AVG	P	
7	1.2164	20.98	10.66	31.64	56.00	-24.36	QP	P	
8	1.2164	7.25	10.66	17.91	46.00	-28.09	AVG	P	
9	1.5945	6.02	10.66	16.68	46.00	-29.32	AVG	P	
10	1.7970	19.27	10.67	29.94	56.00	-26.06	QP	P	
11	3.1425	20.74	10.67	31.41	56.00	-24.59	QP	P	
12	3.1425	8.36	10.67	19.03	46.00	-26.97	AVG	P	

Test phase: N phase



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3300	18.91	10.57	29.48	59.45	-29.97	QP	P	
2	0.3300	6.96	10.57	17.53	49.45	-31.92	AVG	P	
3	0.5055	7.95	10.58	18.53	46.00	-27.47	AVG	P	
4	0.5325	21.06	10.60	31.66	56.00	-24.34	QP	P	
5	0.7080	22.42	10.69	33.11	56.00	-22.89	QP	P	
6	0.7080	9.21	10.69	19.90	46.00	-26.10	AVG	P	
7 *	0.8880	26.45	10.68	37.13	56.00	-18.87	QP	P	
8	0.8880	12.16	10.68	22.84	46.00	-23.16	AVG	P	
9	1.7745	3.18	10.67	13.85	46.00	-32.15	AVG	P	
10	1.7925	17.08	10.67	27.75	56.00	-28.25	QP	P	
11	3.0390	3.82	10.68	14.50	46.00	-31.50	AVG	P	
12	3.1920	18.00	10.66	28.66	56.00	-27.34	QP	P	

5.4 Emissions in Restricted Frequency Bands

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Detector	Polarization
GFSK-2403MHz TX mode							
2310.00	79.40	-30.59	48.81	74.00	-25.19	Peak	V
2310.00	71.42	-30.59	40.83	54.00	-13.17	AVG	V
2310.00	82.03	-30.59	51.44	74.00	-22.56	Peak	H
2310.00	73.38	-30.59	42.79	54.00	-11.21	AVG	H
2390.00	79.95	-30.49	49.46	74.00	-24.54	Peak	H
2390.00	70.97	-30.49	40.48	54.00	-13.52	AVG	H
2390.00	77.96	-30.49	47.47	74.00	-26.53	Peak	V
2390.00	68.01	-30.49	37.52	54.00	-16.48	AVG	V


Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Detector	Polarization
GFSK-2480MHz TX mode							
2483.50	80.88	-30.39	50.49	74.00	-23.51	Peak	V
2483.50	68.81	-30.39	38.42	54.00	-15.58	AVG	V
2483.50	82.41	-30.39	52.02	74.00	-21.98	Peak	H
2483.50	71.04	-30.39	40.65	54.00	-13.35	AVG	H
2500.00	81.36	-30.37	50.99	74.00	-23.01	Peak	H
2500.00	70.33	-30.37	39.96	54.00	-14.04	AVG	H
2500.00	78.91	-30.37	48.54	74.00	-25.46	Peak	V
2500.00	66.90	-30.37	36.53	54.00	-17.47	AVG	V

5.5 Emissions in Non-restricted Frequency Bands

For below 1GHz:


Remark: All modes are tested, and only the worst mode GFSK 2403MHz is showed in the report.

Test antenna polarization: Vertical (30 MHz to 1 GHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	33.3279	34.28	-9.68	24.60	40.00	-15.40	peak	P
2	65.3432	30.08	-9.41	20.67	40.00	-19.33	peak	P
3	159.5045	38.09	-14.38	23.71	43.50	-19.79	peak	P
4	239.5670	46.28	-14.06	32.22	46.00	-13.78	peak	P
5	368.7576	43.21	-12.48	30.73	46.00	-15.27	peak	P
6 *	561.6767	44.95	-11.81	33.14	46.00	-12.86	peak	P

Test antenna polarization: Horizontal (30 MHz to 1 GHz)



For above 1GHz:


Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Detector	Polarization
GFSK-2403MHz TX mode							
4806.00	70.78	-27.92	42.86	74.00	-31.14	Peak	V
4806.00	58.87	-27.92	30.95	54.00	-23.05	AVG	V
7209.00	71.73	-24.87	46.86	74.00	-27.14	Peak	V
7209.00	60.88	-24.87	36.01	54.00	-17.99	AVG	V
9612.00	70.74	-23.44	47.30	74.00	-26.70	Peak	V
9612.00	60.87	-23.44	37.43	54.00	-16.57	AVG	V
4806.00	71.35	-27.92	43.43	74.00	-30.57	Peak	H
4806.00	60.37	-27.92	32.45	54.00	-21.55	AVG	H
7209.00	73.07	-24.87	48.20	74.00	-25.80	Peak	H
7209.00	62.16	-24.87	37.29	54.00	-16.71	AVG	H
9612.00	69.27	-23.44	45.83	74.00	-28.17	Peak	H
9612.00	58.81	-23.44	35.37	54.00	-18.63	AVG	H

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Detector	Polarization
GFSK-2442MHz TX mode							
4884.00	70.47	-27.70	42.77	74.00	-31.23	Peak	V
4884.00	60.27	-27.70	32.57	54.00	-21.43	AVG	V
7326.00	71.11	-24.83	46.28	74.00	-27.72	Peak	V
7326.00	61.53	-24.83	36.70	54.00	-17.30	AVG	V
9768.00	68.36	-23.79	44.57	74.00	-29.43	Peak	V
9768.00	56.89	-23.79	33.10	54.00	-20.90	AVG	V
4884.00	71.04	-27.70	43.34	74.00	-30.66	Peak	H
4884.00	61.59	-27.70	33.89	54.00	-20.11	AVG	H
7326.00	73.45	-24.83	48.62	74.00	-25.38	Peak	H
7326.00	62.46	-24.83	37.63	54.00	-16.37	AVG	H
9768.00	69.59	-23.79	45.80	74.00	-28.20	Peak	H
9768.00	58.19	-23.79	34.40	54.00	-19.60	AVG	H

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Detector	Polarization
GFSK-2480MHz TX mode							
4960.00	70.21	-24.79	45.42	74.00	-28.58	Peak	V
4960.00	60.89	-24.79	36.10	54.00	-17.90	AVG	V
7440.00	71.88	-24.80	47.08	74.00	-26.92	Peak	V
7440.00	61.59	-24.80	36.79	54.00	-17.21	AVG	V
9920.00	67.56	-24.11	43.45	74.00	-30.55	Peak	V
9920.00	58.29	-24.11	34.18	54.00	-19.82	AVG	V
4960.00	71.61	-24.79	46.82	74.00	-27.18	Peak	H
4960.00	61.67	-24.79	36.88	54.00	-17.12	AVG	H
7440.00	73.94	-24.80	49.14	74.00	-24.86	Peak	H
7440.00	62.75	-24.80	37.95	54.00	-16.05	AVG	H
9920.00	69.01	-24.11	44.90	74.00	-29.10	Peak	H
9920.00	58.93	-24.11	34.82	54.00	-19.18	AVG	H

6 Test Setup Photos

Radiated test method



30 MHz – 1 GHz



Above 1 GHz

Conducted test method

7 EUT Constructional Details (EUT Photos)

Please see the attached photos.



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--