

FCC RF Exposure Report

FCC ID : 18811ACAP22

Equipment : 802.11ac Wave 2 Dual-Radio Ceiling Mount

PoE Access Point

(Refer to item 1.1.1 for more details)

Model No. : NWA1123ACv3

(Refer to item 1.1.1 for more details)

Brand Name : ZYXEL

Applicant : Zyxel Communications Corporation

Address : No.2 Industry East RD. IX, Hsinchu Science

Park, Hsinchu 30075, Taiwan, R.O.C

Testing Laboratory 2732

Standard : 47 CFR FCC Part 2.1091

Received Date : Jul. 07, 2020

Tested Date : Jul. 07 ~ Sep. 02, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen / Assistant Manager Gary Chang / Manager

Report No.: FA070801 Page : 1 of 7



Table of Contents

1	GENERAL DESCRIPTION	4
1.1	Information	
2	MPE EVALUATION OF MOBILE DEVICES	5
2.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	5
2.2	MPE EVALUATION FORMULA	5
2.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	5
2.4	MEASUREMENT UNCERTAINTY	
2.5	MPE EVALUATION RESULTS	6
2.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION	6
3	TEST LABORATORY INFORMATION	7



Release Record

Report No.	Version	Description	Issued Date
FA070801	Rev. 01	Initial issue	Sep. 24, 2020

Report No.: FA070801 Page: 3 of 7



1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Description	
ZYXEL	NWA1123ACv3	802.11ac Wave 2 Dual-Radio Ceiling Mount PoE Access Point	Cottugare difference
ZYXEL	WAC500	802.11ac Wave 2 Dual-Radio Unified Access Point	Software difference

[★] The above models, model NWA1123ACv3 was selected as a representative one for the final test and only its data was recorded in this report.

Report No.: FA070801 Page: 4 of 7



2 MPE EVALUATION OF MOBILE DEVICES

2.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

2.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

2.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

2.4 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FA070801 Page: 5 of 7



2.5 MPE EVALUATION RESULTS

Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	*Ratio	Pass / Fail
2412~2462	24.01	24.5	0	20	0.056	1	0.056	Pass
5180-5240	25.19	25.5	0	20	0.071	1	0.071	Pass
5745-5825	25.05	25.5	0	20	0.071	1	0.071	Pass

^{*}Ratio = Power density / Limit.

Beamforming mode

	Beaning mode								
	Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	*Ratio	Pass / Fail
	2412~2462	19.96	20	3.01	20	0.040	1	0.040	Pass
	5180-5240	24.72	25	3.01	20	0.126	1	0.126	Pass
Ī	5745-5825	24.28	24.5	3.01	20	0.112	1	0.112	Pass

^{*}Ratio = Power density / Limit.

For 2.4 GHz / 5 GHz

Directional gain = 0 + 2*log(2/1) = 3.01 dBi

2.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Non-beamforming mode

Mode	Max Ratio of Each Mode
WLAN 2.4GHz	0.056
WLAN 5GHz	0.071
Sum	0.127
Limit	1
Pass / Fail	Pass

Beamforming mode

Mode	Max Ratio of Each Mode
WLAN 2.4GHz	0.040
WLAN 5GHz	0.126
Sum	0.166
Limit	1
Pass / Fail	Pass

Report No.: FA070801 Page: 6 of 7



3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

___END___

Report No.: FA070801 Page: 7 of 7