

TEST REPORT

Reference No...... : WTX21D05042516W002
FCC ID : AUSCR8017B
Applicant..... : Modern Marketing Concepts, Inc.
Address..... : 1220 E Oak, St. Louisville, KY 40204 United States
Manufacturer : Timsen Development Limited
Address..... : 5F, 447# Tianhebei Road, Guangzhou, China
Product..... : Voyager Turntable
Model(s) : CR8017B-DU
Standards..... : FCC Part 2.1091
Date of Receipt sample : 2021-05-06
Date of Test : 2021-05-06 to 2021-05-12
Date of Issue..... : 2021-05-12
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:

Approved by:

Estel Qian

Estel Qian / Project Engineer



Daniel Liu

Daniel Liu / Designated Reviewer

2. Contents

	Page
1 COVER PAGE.....	1
2. CONTENTS	2
3. REVISION HISTORY	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.....	4
4.3. TEST FACILITY	4
5. TEST SUMMARY	5
6. RF EXPOSURE.....	6
6.1. REQUIREMENTS.....	6
6.2. THE PROCEDURES / LIMIT	6
6.3. MPE CALCULATION METHOD	7
6.4. RESULT: COMPLIANCE	7

3. Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTX21D05042516 W002	2021-05-06	2021-05-06 to 2021-05-12	2021-05-12	Original	-	Valid

4. General Information

4.1. General Description of E.U.T.

Product:	Voyager Turntable
Model(s):	CR8017B-DU
Additional model(s):	CR8017X-XXXX ("X-XXXX" can be replaced by letter from "A" to "Z", number from "0" to "9" or blank)
Operation Frequency:	2402-2480MHz, 79 Channels in total
Max. RF output power:	-1.47dBm
Antenna installation:	PCB Printed Antenna
Antenna Gain:	-0.58dBi
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Hardware Version:	1.0
Software Version:	1.0

4.2. Details of E.U.T.

Ratings:	DC 5V 1A from adapter
Adapter:	Model: ZWSP-050100US002 Input: 100-240V ~ 50/60Hz 0.5A Output: 5V $\equiv$ 1000mA

4.3. Test Facility

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.
ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1091	PASS

6. RF Exposure

Test Requirement: FCC Part 2.1091

Evaluation Method: KDB 447498 D01 General RF Exposure Guidance v06

6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

6.2. The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. conducted Output Power (dBm)	Max. conducted Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
-0.58	0.875	-1.47	0.71	0.000124	1	Compliance

6.4. Result: Compliance

No SAR measurement is required.

=====End of Report=====