FCC Test Report (Class II Permissive Change)

Product Name	Intel [®] Dual Band Wireless-AC 7260
Model No	7260NGW
FCC ID.	PD97260NG, PD97260NGU

* FCC ID: PD97260H (For OEM factory installation)

* FCC ID: PD97260HU (For user installation)

Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA

Date of Receipt	Mar. 10, 2014
Issue Date	Mar. 20, 2014
Report No.	1430182R-RFUSP25V00
Report Version	V1.0



The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation. This report must not be used to claim product endorsement by TAF or any agency of the U.S. Government

Test Report Certification

Issue Date: Mar. 20, 2014 Report No.: 1430182R-RFUSP25V00



Product Name	Intel® Dual Band Wireless-AC 7260	
Applicant	Intel Mobile Communications	
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA	
Manufacturer	Intel Mobile Communications	
Model No.	7260NGW	
FCC ID.	PD97260NG, PD97260NGU	
EUT Rated Voltage	DC 3.3V (via Mini-PCI Express slot)	
EUT Test Voltage	AC 120V/60Hz	
Trade Name	Intel	
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2012	
	ANSI C63.10: 2009, KDB 558074	
Test Result	Complied	

The Test Results relate only to the samples tested.

:

:

:

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation. This report must not be used to claim product endorsement by TAF or any agency of the U.S. Government

Documented By

Genie Chang

(Senior Adm. Specialist / Genie Chang)

Tested By

- chu. incent

(Engineer / Vincent Chu)

Approved By

(Director / Vincent Lin)

TABLE OF CONTENTS

Description Page 1. GENERAL INFORMATION4 1.1. 1.2. 1.3. 1.4. 1.5. 1.6. 2. Peak Power Output10 2.1. 2.2. 2.3. 2.4. 2.5. Uncertainty11 2.6. 3. 3.1. 3.2. 3.3. 3.4. 3.5. 3.6. 4. 4.1. 4.2. 4.3. 4.4. 4.5. 4.6. During Compliance Testing71 5. Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Intel® Dual Band Wireless-AC 7260
Trade Name	Intel
Model No.	7260NGW
FCC ID.	PD97260NG, PD97260NGU
Frequency Range	802.11b/g/n-20MHz: 2412-2462MHz, 802.11n-40MHz: 2422-2452MHz
	802.11a/n-20MHz: 5745-5825MHz, 802.11n-40MHz: 5755-5795MHz
	802.11ac-80MHz: 5775 MHz
Number of Channels	802.11b/g/n-20MHz: 11, n-40MHz: 7
	802.11a/n-20MHz: 5, n-40MHz: 2
	802.11ac-80MHz: 1
Data Speed	802.11b: 1-11Mbps, 802.11a/g: 6-54Mbps, 802.11n: up to 300Mbps
	802.11ac-80MHz: up to 866.7MHz
Channel separation	802.11b/g/n-20MHz: 5 MHz, 802.11a/n-20MHz: 20MHz
	802.11n-40MHz: 40MHz, 802.11ac-80MHz: 80MHz
Type of Modulation	802.11b:DSSS, DBPSK, DQPSK, CCK
	802.11a/g/n: OFDM, BPSK, QPSK, 16QAM, 64QAM, 256QAM
Antenna Type	Dipole Antenna
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto
Contain Module	Intel / 7260NGW

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Wistron Neweb	81XCAA15.G03 (497317-003) (Tx1/ Rx1)	Dipole	1.26dBi For 2.4GHz
	Corp.	81XCAA15.G03 (497317-003) (Tx2/ Rx2)		1.09dBi For 5725-5850GHz

Note: The antenna of EUT is conform to FCC 15.203

802.11b/g/n-20MHz Center Frequency of Each Channel: Channel Frequency Channel Frequency Channel Frequency Channel Frequency Channel 01: 2412 MHz Channel 02: 2417 MHz Channel 03: 2422 MHz Channel 04: 2427 MHz Channel 05: 2432 MHz Channel 06: Channel 07: 2442 MHz Channel 08: 2437 MHz 2447 MHz Channel 09: 2452 MHz Channel 10: 2457 MHz Channel 11: 2462 MHz 802.11a/n-20MHz Center Working Frequency of Each Channel: Channel Frequency Channel Frequency Channel Frequency Channel Frequency Channel 149: 5745 MHz Channel 153: 5765 MHz Channel 157: 5785 MHz Channel 161: 5805 MHz Channel 165: 5825 MHz 802.11n-40MHz (2.4G Band) Center Working Frequency of Each Channel: Channel Frequency Channel Frequency Channel Frequency Channel Frequency Channel 3: 2422 MHz Channel 4: 2427 MHz Channel 5: 2432 MHz Channel 6: 2437 MHz Channel 7: 2442 MHz Channel 8: 2447 MHz Channel 9: 2452 MHz 802.11n-40MHz (5G Band) Center Working Frequency of Each Channel: Channel Frequency Channel Frequency Channel 151: 5755 MHz Channel 159: 5795 MHz

802.11ac-80MHz Carrier Frequency of Each Channel:

Channel Frequency

Channel 155: 5775 MHz

- 2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
- Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps \$\cdot 802.11g is 6Mbps \$\cdot 802.11n(20M-BW) is 14.4Mbps \$\cdot 802.11n(40M-BW) is 30Mbps) and 802.11ac(80M-BW) is 65Mbps.
- 4. At result of pretests, module supports dual-channel transmission, only the worst case is shown in the report. (802.11b is chain B \$ 802.11g is chain B \$ 802.11a is chain A)
- 5. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11a/b/g/n transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.
- 6. This is to request a Class II permissive change for FCC ID: PD97260NG, PD97260NGU, originally granted on 04/22/2013.

The major change filed under this application is:

Change #1: Addition new antenna, antenna type is different with the original application.

(Antenna type: Dipole antenna)

Test Mode:	Mode 1: Transmit - 802.11b 1Mbps
	Mode 2: Transmit - 802.11g 6Mbps
	Mode 3: Transmit - 802.11a 6Mbps
	Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band)
	Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band)
	Mode 6: Transmit - 802.11n-20BW_14.4Mbps(5G Band)
	Mode 7: Transmit - 802.11n-40BW_30Mbps(5G Band)
	Mode 8: Transmit - 802.11ac-80BW_65Mbps(5G Band)

1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Test Fixture	Intel	N/A	N/A	N/A
2	Notebook PC	Intel	N/A	N/A	Non-Shielded, 1.8m

Signal Cable Type		Signal cable Description
1 Test Fixture Cable		Non-Shielded, 0.8m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4
- (2) Execute "DRTU Ver2.2.3.1" program on the Notebook PC.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Press "OK" to start the continuous Transmit.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site : <u>http://www.quietek.com/tw/ctg/cts/accreditations.htm</u> The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site : <u>http://www.quietek.com/</u>

Site Description: File on Federal Communications Commission FCC Engineering Laboratory 7435 Oakland Mills Road Columbia, MD 21046 Registration Number: 92195

Site Name:	Quietek Corporation
Site Address:	No.5-22, Ruishukeng Linkou Dist., New Taipei City
	24451, Taiwan, R.O.C.
	TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
	E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Peak Power Output

2.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Power Meter	Anritsu	ML2495A/6K00003357	May, 2013
	Power Sensor	Anritsu	MA2411B/0738448	Jun., 2013
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2013
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2013
Х	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2013
Note	- .			

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

2. The test instruments marked with "X" are used to measure the final test results.

2.2. Test Setup

Average Power For different Data Rate (Mbps)



Peak Power Measurement



2.3. Limits

The maximum peak power shall be less 1 Watt.

2.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 section 9.1.3 PKPM1 Peak power meter method.

2.5. Uncertainty

± 1.27 dB

2.6. Test Result of Peak Power Output

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 1: Transmit - 802.11b 1Mbps

CHAIN A

Channel No.	Frequency	Peak Power	Required	Popult
Chaimer No	(MHz)	Data Rate 1 Mbps	Limit	Kesuit
01	2412	17.64	<30dBm	Pass
06	2437	17.56	<30dBm	Pass
11	2462	17.33	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

Channel No	Frequency (MHz)	Peak Power Data Rate 1 Mbps	Required Limit	Result
01	2412	19.57	<30dBm	Pass
06	2437	19.38	<30dBm	Pass
11	2462	19.07	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product :	Intel [®] Dual Band Wireless-AC 7260
Test Item :	Peak Power Output Data
Test Site :	No.3 OATS
Test Mode :	Mode 2: Transmit - 802.11g 6Mbps

Channel No	Frequency (MHz)	Peak Power Data Rate 6 Mbps	Required Limit	Result
01	2412	20.11	<30dBm	Pass
06	2437	23.49	<30dBm	Pass
11	2462	21.95	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

Channel No	Frequency (MHz)	Peak Power Data Rate 6 Mbps	Required Limit	Result
01	2412	21.44	<30dBm	Pass
06	2437	24.68	<30dBm	Pass
11	2462	22.49	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 3: Transmit - 802.11a 6Mbps

Channel No	Frequency (MHz)	Peak Power Data Rate 6 Mbps	Required Limit	Result
149	5745	24.83	<30dBm	Pass
157	5785	25.06	<30dBm	Pass
165	5825	25.19	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

Channel No	Frequency (MHz)	Peak Power Data Rate 6 Mbps	Required Limit	Result
149	5745	24.08	<30dBm	Pass
157	5785	23.77	<30dBm	Pass
165	5825	23.52	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band)

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 14.4 Mbps	
01	2412	17.29	
06	2437	19.22	
11	2462	18.18	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 14.4 Mbps	
01	2412	16.12	
06	2437	18.25	
11	2462	17.24	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency	Data Rata	Chain A Power	Chain B Power	Chain A+B Power	Limit	Result
	(MHz)	(Mbps)	(dBm)	(dBm)	(dBm)	(dBm)	
1	2412	14.4	17.29	16.12	19.75	<30dBm	Pass
6	2437	14.4	19.22	18.25	21.77	<30dBm	Pass
11	2462	14.4	18.18	17.24	20.75	<30dBm	Pass

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band)

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 30 Mbps	
3	2422	14.09	
6	2437	19.24	
9	2452	18.18	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 30 Mbps	
3	2422	13.19	
6	2437	17.84	
9	2452	16.88	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency	Data Rata	Chain A Power	Chain B Power	Chain A+B Power	Limit	Result
	(MHz)	(Mbps)	(dBm)	(dBm)	(dBm)	(dBm)	
3	2422	30	14.09	13.19	16.67	<30dBm	Pass
6	2437	30	19.24	17.84	21.61	<30dBm	Pass
9	2452	30	18.18	16.88	20.59	<30dBm	Pass

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 6: Transmit - 802.11n-20BW_14.4Mbps(5G Band)

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 14.4 Mbps	
149	5745	23.88	
157	5785	23.97	
165	5825	23.25	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 14.4 Mbps	
149	5745	23.18	
157	5785	23.36	
165	5825	23.01	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency	Data Rata	Chain A Power	Chain B Power	Chain A+B Power	Limit	Result
	(MHz)	(Mbps)	(dBm)	(dBm)	(dBm)	(dBm)	
149	5745	14.4	23.88	23.18	26.55	<30dBm	Pass
157	5785	14.4	23.97	23.36	26.69	<30dBm	Pass
165	5825	14.4	23.25	23.01	26.14	<30dBm	Pass

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 7: Transmit - 802.11n-40BW_30Mbps(5G Band)

	Frequency	Peak Power
Channel No	(MHz)	Data Rate 30 Mbps
151	5755	19.52
159	5795	19.16

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 30 Mbps	
151	5755	19.04	
159	5795	18.93	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency	Data Rata	Chain A Power	Chain B Power	Chain A+B Power	Limit	Result
	(MHz)	(Mbps)	(dBm)	(dBm)	(dBm)	(dBm)	
151	5755	30	19.52	19.04	22.30	<30dBm	Pass
159	5795	30	19.16	18.93	22.06	<30dBm	Pass

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Peak Power Output Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 8: Transmit - 802.11ac-80BW_65Mbps(5G Band)

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 65 Mbps	
155	5775	19.83	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

	Frequency	Peak Power	
Channel No	(MHz)	Data Rate 65 Mbps	
155	5775	19.99	

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency	Data Rata	Chain A Power	Chain B Power	Chain A+B Power	Limit	Result
	(MHz)	(Mbps)	(dBm)	(dBm)	(dBm)	(dBm)	
155	5775	65	19.83	19.99	22.92	<30dBm	Pass

3. Radiated Emission

3.1. Test Equipment

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
\boxtimes Site # 3	Х	Loop Antenna	Teseq	HLA6120 / 26739	Jul., 2013
	Х	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2013
	Х	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2013
	Х	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2013
	Х	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2013
	Х	Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2013
	Х	Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2014
	Х	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2013
	Х	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2013
	Х	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2014
	Х	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	Х	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

The following test equipment are used during the radiated emission test:

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

2. The test instruments marked with "X" are used to measure the final test results.

3.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



3.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits					
Frequency MHz	Field strength	Measurement distance			
	(microvolts/meter)	(meter)			
0.009-0.490	2400/F(kHz)	300			
0.490-1.705	24000/F(kHz)	30			
1.705-30	30	30			
30-88	100	3			
88-216	150	3			
216-960	200	3			
Above 960	500	3			

Remarks: E field strength $(dBuV/m) = 20 \log E$ field strength (uV/m)

3.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2009 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas. The measurement is divided into the Preliminary Measurement and the Final Measurement. The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna. The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

3.5. Uncertainty

- ± 3.9 dB above 1GHz
- ± 3.8 dB below 1GHz

3.6. Test Result of Radiated Emission

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Harmonic Radiated Emission Data
Test Site	:	No.3 OATS
Test Mode	:	Mode 1: Transmit - 802.11b 1Mbps (2412MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
Peak Detector:					
4824.000	3.261	42.600	45.861	-28.139	74.000
7236.000	10.650	37.430	48.080	-25.920	74.000
9648.000	13.337	36.670	50.006	-23.994	74.000
Average					
Detector:					
Vertical					
Peak Detector:					
4824.000	6.421	40.770	47.191	-26.809	74.000
7236.000	11.495	37.870	49.365	-24.635	74.000
9648.000	13.807	36.320	50.126	-23.874	74.000
Average					
Detector:					

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260					
Test Item	: Harmonic Radiated Emission Data					
Test Site	: No.3 OATS					
Test Mode	: Mode 1:	Transmit - 802.1	1b 1Mbps (2437 MH	z)		
Frequency	Correct	Reading	Measurement	Margin	Limit	
	Factor	Level	Level			
MHz	dB	dBuV	dBuV/m	dB	dBuV/m	
Horizontal						
Peak Detector:						
4874.000	3.038	42.860	45.897	-28.103	74.000	
7311.000	11.795	36.750	48.544	-25.456	74.000	
9748.000	12.635	37.950	50.585	-23.415	74.000	
Average						
Detector:						
Vertical						
Peak Detector:						
4874.000	5.812	41.160	46.971	-27.029	74.000	
7311.000	12.630	36.680	49.309	-24.691	74.000	
9748.000	13.126	38.020	51.146	-22.854	74.000	
Average						
Detector:						

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260					
Test Item	: Harmonic Radiated Emission Data					
Test Site	: No.3 OATS					
Test Mode	: Mode 1:	Transmit - 802.1	1b 1Mbps (2462 MH	z)		
Frequency	Correct	Reading	Measurement	Margin	Limit	
	Factor	Level	Level			
MHz	dB	dBuV	dBuV/m	dB	dBuV/m	
Horizontal						
Peak Detector:						
4924.000	2.858	43.020	45.877	-28.123	74.000	
7386.000	12.127	37.410	49.538	-24.462	74.000	
9848.000	12.852	36.810	49.663	-24.337	74.000	
Average						
Detector:						
Vertical						
Peak Detector:						
4924.000	5.521	41.950	47.470	-26.530	74.000	
7386.000	13.254	36.430	49.684	-24.316	74.000	
9848.000	13.367	37.720	51.087	-22.913	74.000	
Average						
Detector:						

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260					
Test Item	: Harmonic Radiated Emission Data					
Test Site	: No.3 OATS					
Test Mode	: Mode 2:	Transmit - 802.1	1g 6Mbps (2412MHz)		
Frequency	Correct	Reading	Measurement	Margin	Limit	
	Factor	Level	Level			
MHz	dB	dBuV	dBuV/m	dB	dBuV/m	
Horizontal						
Peak Detector:						
4824.000	3.261	39.210	42.471	-31.529	74.000	
7236.000	10.650	37.020	47.670	-26.330	74.000	
9648.000	13.337	36.680	50.016	-23.984	74.000	
Average						
Detector:						
Vertical						
Peak Detector:						
4824.000	6.421	38.120	44.541	-29.459	74.000	
7236.000	11.495	36.770	48.265	-25.735	74.000	
9648.000	13.807	37.290	51.096	-22.904	74.000	
Average						
Detector:						

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Intel® Dual Band Wireless-AC 7260								
Test Item	Item : Harmonic Radiated Emission Data							
Test Site	 No.3 OATS Mode 2: Transmit - 802.11g 6Mbps (2437 MHz) 							
Test Mode								
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
Peak Detector:								
4874.000	3.038	39.930	42.967	-31.033	74.000			
7311.000	11.795	36.010	47.804	-26.196	74.000			
9748.000	12.635	37.460	50.095	-23.905	74.000			
Average								
Detector:								
Vertical								
Peak Detector:								
4874.000	5.812	38.850	44.661	-29.339	74.000			
7311.000	12.630	36.580	49.209	-24.791	74.000			
9748.000	13.126	37.520	50.646	-23.354	74.000			
Average								
Detector:								

Note:

=

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel [®] Dual Band Wireless-AC 7260						
Test Item	: Harmonic Radiated Emission Data						
Test Site	e : No.3 OATS						
Test Mode	: Mode 2: Transmit - 802.11g 6Mbps (2462 MHz)						
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
4924.000	2.858	39.760	42.617	-31.383	74.000		
7386.000	12.127	36.500	48.628	-25.372	74.000		
9848.000	12.852	37.350	50.203	-23.797	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
4924.000	5.521	38.930	44.450	-29.550	74.000		
7386.000	13.254	36.700	49.954	-24.046	74.000		
9848.000	13.367	37.540	50.907	-23.093	74.000		
Average							
Detector:							

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260							
Test Item	: Harmonic Radiated Emission Data							
Test Site	e : No.3 OATS							
Test Mode	: Mode 3: Transmit - 802.11a 6Mbps (5745 MHz)							
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
Peak Detector:								
11490.000	17.106	36.300	53.407	-20.593	74.000			
Average								
Detector:								
Vertical								
Peak Detector:								
11490.000	18.034	36.070	54.105	-19.895	74.000			
Average								
Detector:								
11490.000	18.034	22.730	40.765	-13.235	54.000			

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® D	ual Band Wireles	ss-AC 7260					
Test Item	: Harmon	: Harmonic Radiated Emission Data						
Test Site	: No.3 OA	No.3 OATS						
Test Mode	: Mode 3:	Transmit - 802.1	1a 6Mbps (5785 MHz	Z)				
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
Peak Detector:								
11570.000	16.809	36.680	53.489	-20.511	74.000			
Average								
Detector:								
Vertical								
Peak Detector:								
11570.000	17.698	36.070	53.768	-20.232	74.000			

Average

Detector:

--

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® D	: Intel® Dual Band Wireless-AC 7260						
Test Item	: Harmoni	: Harmonic Radiated Emission Data						
Test Site	: No.3 OA	: No.3 OATS						
Test Mode	: Mode 3:	Transmit - 802.1	1a 6Mbps (5825 MHz	z)				
Energy and and	Correct	Decding	Magazza	Manain	T :			
Frequency	Correct	Reading	Measurement	Margin	LIIIIIt			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
Peak Detector:								
11650.000	16.158	37.690	53.848	-20.152	74.000			
Average								
Detector:								
Vertical								
Peak Detector:								
11650.000	17.274	35.730	53.005	-20.995	74.000			

Average

Detector:

--

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260						
Test Item	: Harmonic Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band) (2412MHz)						
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
4824.000	3.261	40.010	43.271	-30.729	74.000		
7236.000	10.650	36.600	47.250	-26.750	74.000		
9648.000	13.337	37.890	51.226	-22.774	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
4824.000	6.421	38.960	45.381	-28.619	74.000		
7236.000	11.495	36.890	48.385	-25.615	74.000		
9648.000	13.807	36.990	50.796	-23.204	74.000		
Average							
Detector:							

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260						
Test Item	: Harmonic Radiated Emission Data						
Test Site	Test Site : No.3 OATS						
Test Mode	: Mode 4	: Transmit - 802.1	1n-20BW_14.4Mbps	(2.4G Band) (243	7 MHz)		
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
4874.000	3.038	37.730	40.767	-33.233	74.000		
7311.000	11.795	36.290	48.084	-25.916	74.000		
9748.000	12.635	36.980	49.615	-24.385	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
4874.000	5.812	38.710	44.521	-29.479	74.000		
7311.000	12.630	36.380	49.009	-24.991	74.000		
9748.000	13.126	37.660	50.786	-23.214	74.000		
Average							
Detector:							

Note:

=

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260						
Test Item	: Harmonic Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band) (2462 MHz)						
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
4924.000	2.858	39.920	42.777	-31.223	74.000		
7386.000	12.127	36.090	48.218	-25.782	74.000		
9848.000	12.852	36.820	49.673	-24.327	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
4924.000	5.521	38.870	44.390	-29.610	74.000		
7386.000	13.254	36.870	50.124	-23.876	74.000		
9848.000	13.367	37.980	51.347	-22.653	74.000		
Average							
Detector:							

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260							
Test Item	: Harmonic Radiated Emission Data							
Test Site	: No.3 OATS							
Test Mode	: Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band) (2422MHz)							
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
Peak Detector:								
4844.000	3.171	39.530	42.701	-31.299	74.000			
7266.000	11.162	36.720	47.882	-26.118	74.000			
9688.000	12.964	37.190	50.155	-23.845	74.000			
Average								
Detector:								
Vertical								
Peak Detector:								
4844.000	6.178	38.620	44.798	-29.202	74.000			
7266.000	11.982	37.100	49.082	-24.918	74.000			
9688.000	13.507	37.840	51.348	-22.652	74.000			
Average								
Detector:								

Note:

=

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260						
Test Item	: Harmonic Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band) (2437 MHz)						
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
4874.000	3.038	39.980	43.017	-30.983	74.000		
7311.000	11.795	36.140	47.934	-26.066	74.000		
9748.000	12.635	37.640	50.275	-23.725	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
4874.000	5.812	38.480	44.291	-29.709	74.000		
7311.000	12.630	36.890	49.519	-24.481	74.000		
9748.000	13.126	37.730	50.856	-23.144	74.000		
Average							
Detector:							

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260						
Test Item	: Harmonic Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band) (2452 MHz)						
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
4904.000	2.914	39.980	42.895	-31.105	74.000		
7356.000	11.995	36.100	48.094	-25.906	74.000		
9808.000	12.475	37.230	49.705	-24.295	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
4904.000	5.530	38.080	43.611	-30.389	74.000		
7356.000	13.005	36.930	49.934	-24.066	74.000		
9808.000	12.901	37.850	50.751	-23.249	74.000		
Average							
Detector:							

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® I	: Intel® Dual Band Wireless-AC 7260					
Test Item	: Harmonic Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 6	Transmit - 802.1	1n-20BW_14.4Mbps	(5G Band) (5745)	MHz)		
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
Peak Detector:							
11490.000	17.106	36.450	53.557	-20.443	74.000		
Average							
Detector:							
Vertical							
Peak Detector:							
11490.000	18.034	41.620	59.655	-14.345	74.000		
Average							
Detector:							
11490.000	18.034	25.700	43.735	-10.265	54.000		

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: Harmonic Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	: Mode 6: Transmit - 802.11n-20BW_14.4Mbps(5G Band) (5785 MHz)								
Frequency	Correct	Reading	Measurement	Margin	Limit				
	Factor	Level	Level						
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
Peak Detector:									
11570.000	16.809	36.410	53.219	-20.781	74.000				
Average									
Detector:									
Vertical									
Peak Detector:									
11570.000	17.698	41.000	58.698	-15.302	74.000				
Average									
Detector:									
11570.000	17.698	24.560	42.258	-11.742	54.000				

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: Harmonic Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	: Mode 6: Transmit - 802.11n-20BW_14.4Mbps(5G Band) (5825 MHz)								
Frequency	Correct	Reading	Measurement	Margin	Limit				
	Factor	Level	Level						
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
Peak Detector:									
11650.000	16.158	36.400	52.558	-21.442	74.000				
Average									
Detector:									
Vertical									
Peak Detector:									
11650.000	17.274	39.860	57.135	-16.865	74.000				
Average									
Detector:									
11650.000	17.274	24.160	41.435	-12.565	54.000				

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: Harmonic Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	Mode 7: Transmit - 802 11n-40BW 30Mbps(5G Band) (5755MHz)								
Frequency	Correct	Reading	Measurement	Margin	Limit				
1 2	Factor	Level	Level	C					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
Peak Detector:									
11510.000	17.124	37.900	55.024	-18.976	74.000				
Average									
Detector:									
11510.000	17.124	23.880	41.004	-12.996	54.000				
Vertical									
Peak Detector:									
11510.000	18.081	37.640	55.721	-18.279	74.000				
Average									
Detector:									
11510.000	18.081	23.450	41.531	-12.469	54.000				

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: Harmonic Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	: Mode 7: Transmit - 802.11n-40BW_30Mbps(5G Band) (5795 MHz)								
Frequency	Correct	Reading	Measurement	Margin	Limit				
	Factor	Level	Level						
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
Peak Detector:									
11590.000	16.701	36.860	53.560	-20.440	74.000				
Average									
Detector:									
Vertical									
Peak Detector:									
11590.000	17.567	37.120	54.686	-19.314	74.000				
Average									
Detector:									
11590.000	17.567	24.660	42.226	-11.774	54.000				

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: Harmonic Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	: Mode 8: Transmit - 802.11ac-80BW_65Mbps(5G Band) (5775 MHz)								
Frequency	Correct	Reading	Measurement	Margin	Limit				
	Factor	Level	Level						
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
Peak Detector:									
11550.000	16.914	35.470	52.384	-21.616	74.000				
Average									
Detector:									
Vertical									
Peak Detector:									
11550.000	17.826	35.565	53.390	-20.610	74.000				

Average

Detector:

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: General Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	: Mode 1: Transmit - 802.11b 1Mbps (2437 MHz)								
Frequency	Correct	Reading	Measurement	Margin	Limit				
	Factor	Level	Level						
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
175.500	-10.017	41.656	31.638	-11.862	43.500				
398.600	-2.268	37.691	35.423	-10.577	46.000				
540.220	2.551	30.859	33.410	-12.590	46.000				
615.880	3.215	28.631	31.846	-14.154	46.000				
780.780	4.230	27.206	31.436	-14.564	46.000				
961.200	6.450	33.681	40.131	-13.869	54.000				
Vertical									
239.520	-8.581	45.428	36.848	-9.152	46.000				
375.320	-2.029	38.265	36.236	-9.764	46.000				
499.480	-0.852	30.800	29.948	-16.052	46.000				
720.640	-0.099	43.062	42.963	-3.037	46.000				
798.240	2.808	28.220	31.028	-14.972	46.000				
961.200	7.260	34.438	41.698	-12.302	54.000				

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8 No emission found between lowest internal used/generated frequency to 30MHz.

Product	: Intel® Dual Band Wireless-AC 7260							
Test Item	: General Radiated Emission Data							
Test Site	: No.3 OATS							
Test Mode	: Mode 2:	Transmit - 802.1	lg 6Mbps (2437 MHz	z)				
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
154.160	-10.091	39.359	29.268	-14.232	43.500			
299.660	-3.585	32.014	28.429	-17.571	46.000			
375.320	-1.209	38.265	37.056	-8.944	46.000			
580.960	3.505	27.016	30.521	-15.479	46.000			
798.240	5.148	28.220	33.368	-12.632	46.000			
961.200	6.450	34.438	40.888	-13.112	54.000			
Vertical								
375.320	-2.029	39.984	37.955	-8.045	46.000			
499.480	-0.852	30.107	29.255	-16.745	46.000			
600.360	-2.833	30.014	27.181	-18.819	46.000			
699.300	0.695	28.861	29.556	-16.444	46.000			
796.300	2.831	28.113	30.944	-15.056	46.000			
961.200	7.260	34.899	42.159	-11.841	54.000			

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: General Radiated Emission Data								
Test Site	: No.3 OATS								
Test Mode	: Mode 3	: Transmit - 802.1	1a 6Mbps (5785MHz)					
Frequency	Correct	Reading	Measurement	Margin	Limit				
	Factor	Level	Level						
MHz	dB	dBuV	dBuV/m	dB	dBuV/m				
Horizontal									
239.520	-6.851	45.313	38.463	-7.537	46.000				
375.320	-1.209	39.705	38.496	-7.504	46.000				
497.540	-0.273	34.652	34.379	-11.621	46.000				
598.420	3.991	32.253	36.244	-9.756	46.000				
800.180	5.141	30.039	35.180	-10.820	46.000				
961.200	6.450	35.054	41.504	-12.496	54.000				
Vertical									
140.580	-6.241	39.783	33.542	-9.958	43.500				
239.520	-8.581	45.313	36.733	-9.267	46.000				
375.320	-2.029	39.705	37.676	-8.324	46.000				
480.080	-4.359	44.430	40.071	-5.929	46.000				
598.420	-2.979	32.253	29.274	-16.726	46.000				
800.180	2.801	30.039	32.840	-13.160	46.000				

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

Product	: Intel® Dual Band Wireless-AC 7260							
Test Item	: General Radiated Emission Data							
Test Site	: No.3 OATS							
Test Mode	: Mode 4	: Transmit - 802.1	1n-20BW_14.4Mbps	(2.4G Band) (243	7 MHz)			
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
125.060	-9.946	43.116	33.170	-10.330	43.500			
239.520	-6.851	46.012	39.162	-6.838	46.000			
375.320	-1.209	39.984	38.775	-7.225	46.000			
600.360	3.977	30.014	33.991	-12.009	46.000			
796.300	5.161	28.113	33.274	-12.726	46.000			
961.200	6.450	34.899	41.349	-12.651	54.000			
Vertical								
140.580	-6.241	39.239	32.998	-10.502	43.500			
299.660	-6.855	29.255	22.400	-23.600	46.000			
499.480	-0.852	30.107	29.255	-16.745	46.000			
600.360	-2.833	30.014	27.181	-18.819	46.000			
796.300	2.831	28.113	30.944	-15.056	46.000			
961.200	7.260	34.899	42.159	-11.841	54.000			

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

375.320

-1.209

46.000

Product	: Intel® Dual Band Wireless-AC 7260								
Test Item	: General	: General Radiated Emission Data							
Test Site	: No.3 O	No.3 OATS							
Test Mode	: Mode 5	: Transmit - 802.1	1n-40BW_30Mbps(2	.4G Band) (2437	MHz)				
Frequency MHz	Correct Factor dB	orrect Reading Measurement Margin L factor Level Level dB dBuV dBuV/m dB dB							
Horizontal									
125.060	-9.946	47.166	37.220	-6.280	43.500				
286.080	-4.687	32.617	27.930	-18.070	46.000				

42.178

-3.822

540.220	2.551	31.637	34.188	-11.812	46.000
600.360	3.977	30.812	34.789	-11.211	46.000
961.200	6.450	32.346	38.796	-15.204	54.000
Vertical					
154.160	-6.221	40.565	34.344	-9.156	43.500
239.520	-8.581	47.524	38.944	-7.056	46.000
375.320	-2.029	43.387	41.358	-4.642	46.000
540.220	0.121	31.637	31.758	-14.242	46.000
600.360	-2.833	30.812	27.979	-18.021	46.000
961.200	7.260	32.346	39.606	-14.394	54.000

43.387

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

Product	: Intel® Dual Band Wireless-AC 7260							
Test Item	: General Radiated Emission Data							
Test Site	: No.3 OATS							
Test Mode	: Mode 6	: Transmit - 802.1	1n-20BW_14.4Mbps	(5G Band) (5785	MHz)			
Frequency	Correct	Reading	Measurement	Margin	Limit			
	Factor	Level	Level					
MHz	dB	dBuV	dBuV/m	dB	dBuV/m			
Horizontal								
154.160	-10.091	40.993	30.902	-12.598	43.500			
375.320	-1.209	42.117	40.908	-5.092	46.000			
480.080	-0.329	41.893	41.564	-4.436	46.000			
540.220	2.551	31.430	33.981	-12.019	46.000			
600.360	3.977	30.322	34.299	-11.701	46.000			
961.200	6.450	32.234	38.684	-15.316	54.000			
Vertical								
154.160	-6.221	40.993	34.772	-8.728	43.500			
375.320	-2.029	42.117	40.088	-5.912	46.000			
480.080	-4.359	41.893	37.534	-8.466	46.000			
660.500	-2.233	27.614	25.381	-20.619	46.000			
780.780	3.060	26.324	29.384	-16.616	46.000			
961.200	7.260	32.234	39.494	-14.506	54.000			

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

Product	: Intel® Dual Band Wireless-AC 7260						
Test Item	: General Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 7	: Transmit - 802.1	1n-40BW_30Mbps(5	G Band) (5755M	Hz)		
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
125.060	-9.946	47.063	37.117	-6.383	43.500		
239.520	-6.851	47.496	40.646	-5.354	46.000		
375.320	-1.209	42.117	40.908	-5.092	46.000		
480.080	-0.329	41.893	41.564	-4.436	46.000		
600.360	3.977	30.322	34.299	-11.701	46.000		
961.200	6.450	32.234	38.684	-15.316	54.000		
Vertical							
154.160	-6.221	40.993	34.772	-8.728	43.500		
286.080	-8.097	32.292	24.195	-21.805	46.000		
398.600	-4.678	36.029	31.351	-14.649	46.000		
482.020	-3.985	38.011	34.026	-11.974	46.000		
540.220	0.121	31.430	31.551	-14.449	46.000		
961.200	7.260	32.234	39.494	-14.506	54.000		

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

Product	: Intel [®] Dual Band Wireless-AC 7260						
Test Item	: General Radiated Emission Data						
Test Site	: No.3 OATS						
Test Mode	: Mode 8	: Transmit - 802.1	1ac-80BW_65Mbps(5G Band) (5775N	(Hz)		
Frequency	Correct	Reading	Measurement	Margin	Limit		
	Factor	Level	Level				
MHz	dB	dBuV	dBuV/m	dB	dBuV/m		
Horizontal							
150.280	-10.194	36.514	26.320	-17.180	43.500		
373.380	-1.163	26.743	25.580	-20.420	46.000		
534.400	2.069	26.950	29.019	-16.981	46.000		
660.500	2.097	23.213	25.310	-20.690	46.000		
796.300	5.161	23.603	28.764	-17.236	46.000		
910.760	6.164	22.350	28.515	-17.485	46.000		
Vertical							
109.540	-0.418	27.041	26.623	-16.877	43.500		
220.120	-8.840	34.482	25.642	-20.358	46.000		
371.440	-2.737	28.826	26.089	-19.911	46.000		
522.760	-0.334	32.601	32.267	-13.733	46.000		
722.580	-0.114	28.070	27.956	-18.044	46.000		
879.720	2.335	28.570	30.905	-15.095	46.000		

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. Measurement Level = Reading Level + Correct Factor.
- 5. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.
- 7. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 8. No emission found between lowest internal used/generated frequency to 30MHz.

4. Band Edge

4.1. Test Equipment

RF Radiated Measurement:

The following test equipments are used during the band edge tests:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 3		Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2013
	Х	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2013
		Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2013
		Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2013
	Х	Pre-Amplifier	QTK	AP-180C / CHM_0906076	Sep., 2013
		Pre-Amplifier	MITEQ	AMF-4D-180400-45-6P/ 925975	Mar, 2014
	Х	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2013
		Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2013
	Х	Coaxial Cable	QuieTek	QTK-CABLE/ CAB5	Feb., 2014
	Х	Controller	QuieTek	QTK-CONTROLLER/ CTRL3	N/A
	Χ	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note: 1

: 1. All instruments are calibrated every one year.

2. The test instruments marked by "X" are used to measure the final test results.

4.2. Test Setup

RF Radiated Measurement:



4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

4.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2009. on radiated measurement.

4.5. Uncertainty

- ± 3.9 dB above 1GHz
- ± 3.8 dB below 1GHz

4.6. Test Result of Band Edge

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 1: Transmit - 802.11b 1Mbps

RF Radiated Measurement (Horizontal):

	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2390.000	-1.131	41.507	40.376	74.00	54.00	Pass
01 (Peak)	2400.000	-1.084	48.373	47.290			Pass
01 (Peak)	2413.000	-1.009	86.776	85.766			Pass
01 (Average)	2385.600	-1.148	31.788	30.640	74.00	54.00	Pass
01 (Average)	2390.000	-1.131	30.215	29.084	74.00	54.00	Pass
01 (Average)	2400.000	-1.084	42.898	41.815			Pass
01 (Average)	2409.400	-1.031	82.154	81.123			Pass

Horizontal (Peak)

Figure Channel 01:



Figure Channel 01:

Horizontal (Average)



Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.

- 2. Peak measurements: RBW = 1MHz, VBW = 3MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 1: Transmit - 802.11b 1Mbps

RF Radiated Measurement (Vertical):

Channal No	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2385.600	-1.704	55.700	53.996	74.00	54.00	Pass
01 (Peak)	2390.000	-1.725	55.045	53.320	74.00	54.00	Pass
01 (Peak)	2400.000	-1.733	65.817	64.085			Pass
01 (Peak)	2410.600	-1.712	103.081	101.370			Pass
01 (Average)	2386.000	-1.706	47.038	45.332	74.00	54.00	Pass
01 (Average)	2390.000	-1.725	44.983	43.258	74.00	54.00	Pass
01 (Average)	2400.000	-1.733	60.122	58.390			Pass
01 (Average)	2409.400	-1.713	98.383	96.669			Pass

Figure Channel 01:

Vertical (Peak)



Figure Channel 01:

Vertical (Average)



Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.

- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 1: Transmit - 802.11b 1Mbps

RF Radiated Measurement (Horizontal):

Channal No	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
11 (Peak)	2460.500	-0.704	91.173	90.469			Pass
11 (Peak)	2483.500	-0.558	40.380	39.822	74.00	54.00	Pass
11 (Peak)	2500.500	-0.492	40.925	40.433	74.00	54.00	Pass
11 (Average)	2459.300	-0.712	86.754	86.042			Pass
11 (Average)	2483.500	-0.558	29.410	28.852	74.00	54.00	Pass

Figure Channel 11:

Horizontal (Peak)



Figure Channel 11:

Horizontal (Average)



- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 1: Transmit - 802.11b 1Mbps

RF Radiated Measurement (Vertical):

Channal No	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
11 (Peak)	2460.500	-1.432	105.095	103.663			Pass
11 (Peak)	2483.500	-1.305	53.005	51.700	74.00	54.00	Pass
11 (Peak)	2488.700	-1.276	53.104	51.828	74.00	54.00	Pass
11 (Average)	2459.100	-1.440	100.439	98.999			Pass
11 (Average)	2483.500	-1.305	40.998	39.693	74.00	54.00	Pass

Figure Channel 11:

Vertical (Peak)



Figure Channel 11:

Vertical (Average)



Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.

- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 2: Transmit - 802.11g 6Mbps

RF Radiated Measurement (Horizontal):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Dogult
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2390.000	-1.131	50.272	49.141	74.00	54.00	Pass
01 (Peak)	2400.000	-1.084	66.837	65.754			Pass
01 (Peak)	2415.800	-0.992	86.776	85.784			Pass
01(Average)	2390.000	-1.131	32.589	31.458	74.00	54.00	Pass
01(Average)	2400.000	-1.084	46.750	45.667			Pass
01(Average)	2405.000	-1.055	76.216	75.160			Pass





Horizontal (Average)



Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.

- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.



Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 2: Transmit - 802.11g 6Mbps

RF Radiated Measurement (Vertical):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2390.000	-1.725	69.056	67.331	74.00	54.00	Pass
01 (Peak)	2400.000	-1.733	82.529	80.797			Pass
01 (Peak)	2415.600	-1.685	103.538	101.853			Pass
01 (Average)	2390.000	-1.725	48.893	47.168	74.00	54.00	Pass
01 (Average)	2400.000	-1.733	63.498	61.766			Pass
01 (Average)	2415.600	-1.685	92.216	90.531			Pass

Figure Channel 01:

Vertical (Peak)





Vertical (Average)



Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.

- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 2: Transmit - 802.11g 6Mbps

RF Radiated Measurement (Horizontal):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
11 (Peak)	2458.100	-0.719	92.387	91.667			Pass
11 (Peak)	2483.500	-0.558	44.212	43.654	74.00	54.00	Pass
11 (Average)	2458.500	-0.718	81.361	80.644			Pass
11 (Average)	2483.500	-0.558	31.090	30.532	74.00	54.00	Pass





Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.

- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 2: Transmit - 802.11g 6Mbps

RF Radiated Measurement (Vertical):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
11 (Peak)	2457.100	-1.452	106.366	104.915			Pass
11 (Peak)	2483.500	-1.305	68.196	66.891	74.00	54.00	Pass
11 (Average)	2458.100	-1.446	95.131	93.685			Pass
11 (Average)	2483.500	-1.305	48.943	47.638	74.00	54.00	Pass





- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2389.400	-1.133	61.661	60.528	74.00	54.00	Pass
01 (Peak)	2390.000	-1.131	59.534	58.403	74.00	54.00	Pass
01 (Peak)	2400.000	-1.084	76.913	75.830			Pass
01 (Peak)	2407.600	-1.042	98.014	96.973			Pass
01 (Average)	2390.000	-1.131	43.036	41.905	74.00	54.00	Pass
01 (Average)	2400.000	-1.084	55.175	54.092			Pass
01 (Average)	2408.200	-1.037	84.883	83.845			Pass





Horizontal (Average)



- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.



Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band)

RF Radiated Measurement (Vertical):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2389.400	-1.722	74.458	72.736	74.00	54.00	Pass
01 (Peak)	2390.000	-1.725	72.798	71.073	74.00	54.00	Pass
01 (Peak)	2400.000	-1.733	83.905	82.173			Pass
01 (Peak)	2409.000	-1.715	107.447	105.732			Pass
01 (Average)	2390.000	-1.725	53.345	51.620	74.00	54.00	Pass
01 (Average)	2400.000	-1.733	65.571	63.839			Pass
01 (Average)	2419.400	-1.664	93.245	91.581			Pass

Figure Channel 01:

Vertical (Peak)





Vertical (Average)



- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band)

RF Radiated Measurement (Horizontal):

Channal No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
11 (Peak)	2455.300	-0.737	100.857	100.120			Pass
11 (Peak)	2483.500	-0.558	72.066	71.508	74.00	54.00	Pass
11 (Peak)	2485.100	-0.548	72.850	72.302	74.00	54.00	Pass
11 (Average)	2458.300	-0.718	86.494	85.776			Pass
11 (Average)	2483.500	-0.558	44.712	44.154	74.00	54.00	Pass

Figure Channel 11:

Horizontal (Peak)





- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.



Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 4: Transmit - 802.11n-20BW_14.4Mbps(2.4G Band)

RF Radiated Measurement (Vertical):

Channal No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
11 (Peak)	2459.100	-1.440	107.478	106.038			Pass
11 (Peak)	2483.500	-1.305	68.661	67.356	74.00	54.00	Pass
11 (Peak)	2483.900	-1.302	70.363	69.060	74.00	54.00	Pass
11 (Average)	2454.700	-1.466	94.488	93.023			Pass
11 (Average)	2483.500	-1.305	51.824	50.519	74.00	54.00	Pass

Figure Channel 11:

Vertical (Peak)





Vertical (Average)



- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.



Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band)

RF Radiated Measurement (Horizontal):

Channal No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2390.000	-1.131	54.848	53.717	74.00	54.00	Pass
01 (Peak)	2400.000	-1.084	65.300	64.217			Pass
01 (Peak)	2430.000	-0.900	93.410	92.510			Pass
01 (Average)	2390.000	-1.131	41.867	40.736	74.00	54.00	Pass
01 (Average)	2400.000	-1.084	50.049	48.966			Pass
01 (Average)	2431.000	-0.894	79.561	78.667			Pass

Figure Channel 01:

Horizontal (Peak)





- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band)

RF Radiated Measurement (Vertical):

Channel No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Dogult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
01 (Peak)	2388.000	-1.715	65.019	63.304	74.00	54.00	Pass
01 (Peak)	2390.000	-1.725	64.356	62.631	74.00	54.00	Pass
01 (Peak)	2400.000	-1.733	73.587	71.855			Pass
01 (Peak)	2425.000	-1.633	102.426	100.793			Pass
01 (Average)	2390.000	-1.725	50.978	49.253	74.00	54.00	Pass
01 (Average)	2400.000	-1.733	58.981	57.249			Pass
01 (Average)	2430.800	-1.600	88.031	86.431			Pass



Vertical (Peak)





Vertical (Average)



- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.



: Intel® Dual Band wireless-AC /260

Product	:	Intel® Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 5: Transmit - 802.11n-40BW_30Mbps(2.4G Band)

RF Radiated Measurement (Horizontal):

Channal No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
07 (Peak)	2460.300	-0.706	97.971	97.266			Pass
07 (Peak)	2483.500	-0.558	73.445	72.887	74.00	54.00	Pass
07 (Average)	2445.500	-0.800	83.525	82.725			Pass
07 (Average)	2483.500	-0.558	48.171	47.613	74.00	54.00	Pass

Figure Channel 07:

Horizontal (Peak)





Horizontal (Average)



- All readings above 1GHz are performed with peak and/or average measurements as necessary. 1.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- "*", means this data is the worst emission level. 4.
- Measurement Level = Reading Level + Correct Factor. 5.
- The average measurement was not performed when the peak measured data under the limit of average 6. detection.

Product	:	Intel [®] Dual Band Wireless-AC 7260
Test Item	:	Band Edge
Test Site	:	No.3 OATS
Test Mode	:	Mode 5: Transmit - 802.11n-40BW 30Mbps(2.4G Band)

RF Radiated Measurement (Vertical):

Channal No.	Frequency	Correct Factor	Reading Level	Emission Level	Peak Limit	Average Limit	Docult
Channel No.	(MHz)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dBuV/m)	Result
07 (Peak)	2443.100	-1.532	105.827	104.296			Pass
07 (Peak)	2483.500	-1.305	70.395	69.090	74.00	54.00	Pass
07 (Peak)	2488.900	-1.275	71.650	70.375	74.00	54.00	Pass
07 (Average)	2444.900	-1.522	91.620	90.099			Pass
07 (Average)	2483.500	-1.305	53.468	52.163	74.00	54.00	Pass

Figure Channel 07:

Vertical (Peak)





Vertical (Average)



- 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
- 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
- 4. "*", means this data is the worst emission level.
- 5. Measurement Level = Reading Level + Correct Factor.
- 6. The average measurement was not performed when the peak measured data under the limit of average detection.

5. During Compliance Testing

No modification was made during testing.