

Heiko Posenauer

Project Manager R&D, Machine Control Division
 Leica Geosystems AG, part of Hexagon
 Heinrich-Wild-Strasse
 9435 Heerbrugg, Switzerland
 Phone: +41 71 727 3537

Explanation on similarity and differences of the iCA202 Family

To whom it may concern, the three variants:

- iCA202
- iCA202 400 MHz
- iCA202 900 MHz

Are identical with this difference:

- The iCA202 does not contain an UHF radio
- The iCA202 400/900 MHz variants contain an UHF radio, configured in the corresponding frequency.

Here a description on the feature set:

Product Variants	Article Number (Production)	Description
iCA202	889666	Machine Controller which supplies RTK positioning data to an earthmoving machine or paver. GNSS correction data can be supplied to the unit through a variety of interfaces. The positioning data and sensor data is supplied to the machine primarily through CAN bus. The machine controller can be accessed remotely through a variety of RF or wired interfaces. Features: • Multifrequency • GPS support • GLONASS support • Galileo support (optional) • Beidou support (optional) • High accuracy RTK Positioning • Precise Heading output • Dual Positioning • Unlimited Baseline length • RTK Network capability • 20 Hz Position update rate • NMEA Streaming (optional) • 1yr SmartLink Fill Support (optional)
iCA202 400 MHz	951568	In addition to "iCA202": • 400 Mhz UHF radio Integrated.
iCA202 900 MHz	951568	In addition to "iCA202": • 900 Mhz UHF radio Integrated.

Sincerely,

Heiko Posenauer