

## FCC RF Exposure

EUT Description: UnoQ Counter - Handset

Model No.: WH-Z4B, WH-Z4B-BL, WH-Z2B, WH-Z2B-BL, WT-HZ4B, WT-HZ2B, WT-HZ4B-BL, WT-HZ2B-BL, Button Handset, RSH-ZigBee-SC04, RSH-ZigBee-SC13, RSH-ZigBee-SC12, RSH-ZigBee-SC11, RSH-Zigbee, RSH-Zigbee-SC10, SR-ZS1, ESW-0ZAA-eu,

UnoQ Counter - Button Handset

FCC ID: 2AGQF-WT-UNOQ-HS

Equipment type: Portable equipment

According to KDB 447498 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numeric simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance in mm})] \cdot [f(\text{GHz})] < 3.0 \text{ for 1-g SAR, and } < 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

$$\text{EIRP} = \text{E}_{\text{Meas}} + 20 \log(d_{\text{meas}}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

E<sub>Meas</sub> in dBm is the field strength of the emission at the measurement distance, in dB u V/m

d<sub>meas</sub> is the measurement distance, in m

Field strength (dBuV/m)	EIRP (dBm)	Max tune-up (mW)	Frequency (MHz)	Min. distance (mm)	Calc. thresholds	limit
93.83	-1.3276	0.7366	2410	5	0.2287	3.0
92.36	-2.7976	0.5251	2443	5	0.1641	3.0
95.17	0.0124	1.0029	2475	5	0.3156	3.0

Conclusion: No SAR is required