



EMC

TEST REPORT

REPORT NO. : F89091507
MODEL NO. : 5112
DATE OF TEST : Sept. 18, 2000
DATE OF RECEIPT : Sept. 15, 2000

PREPARED FOR: BEHAVIOR TECH COMPUTER CORP.

ADDRESS : 2F, NO.51, TUNG HSING. RD.,
TAIPEI, TAIWAN, R.O.C.

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory

11F, NO.1, SEC.4, NAN-KING EAST RD.,
TAIPEI, TAIWAN, R.O.C.

This test report consists of 15 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



TABLE OF CONTENTS

| | |
|--|----|
| 1. CERTIFICATION | 3 |
| 2. GENERAL INFORMATION | 4 |
| 2.1 GENERAL DESCRIPTION OF EUT | 4 |
| 2.2 DESCRIPTION OF SUPPORT UNITS | 5 |
| 2.3 TEST METHODOLOGY AND CONFIGURATION | 5 |
| 3. TEST INSTRUMENTS | 6 |
| 3.1 TEST INSTRUMENTS (EMISSION) | 6 |
| 3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION | 7 |
| 4. TEST RESULTS (EMISSION) | 8 |
| 4.1 RADIO DISTURBANCE | 8 |
| 4.2 EUT OPERATION CONDITION | 8 |
| 4.3 TEST DATA OF CONDUCTED EMISSION | 9 |
| 4.4 TEST DATA OF RADIATED EMISSION | 11 |
| 5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN | 13 |
| 6. APPENDIX - INFORMATION OF THE TESTING LABORATORY | 15 |

**1. CERTIFICATION**

Issue Date: Sept. 26, 2000

Product : KEYBOARD
Trade Name : BTC
Model No. : 5112
Applicant : BEHAVIOR TECH COMPUTER CORP.
Standard : FCC Part 15, Subpart B, Class B
CISPR 22:1997, Class B
ANSI C63.4-1992

We hereby certify that one sample of the designation has been tested in our facility on Sept. 18, 2000. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

The test results show that the EUT as described in this report is in compliance with the Class B limits of conducted and radiated emission of applicable standards.

TESTED BY : J.W. Kuo , DATE: 9/26/2000
(J.W. Kuo)

CHECKED BY : Kathy Tseng , DATE: 09/26/2000
(Kathy Tseng)

APPROVED BY : Paul Yang , DATE: 9/26/2000
(Mike Su)

ADVANCE DATA TECHNOLOGY CORPORATION**NVLAP[®]**

Accredited Laboratory



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | | |
|--------------|---|------------------|
| Product | : | KEYBOARD |
| Model No. | : | BTC |
| Power Supply | : | DC 5V (from PC) |
| Data Cable | : | Shielded (1.8 m) |

Note: For more detailed features description, please refer to manufacturer's specification or User's Manual.



2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

| No. | Product | Brand | Model No. | Serial No. | FCC ID |
|-----|-------------------|----------|-----------|------------------|------------------|
| 1 | PERSONAL COMPUTER | IBM | 2187-12W | 1S218714ABNA0002 | FCC DoC APPROVED |
| 2 | 21"COLOR MONITOR | HP | D2846 | JP92233133 | FCC DoC APPROVED |
| 3 | PRINTER | HP | 2225C | 2923S47245 | DSI6XU2225 |
| 4 | MODEM | ACEEX | 1414 | 980020502 | IFAXDM1414 |
| 5 | SPEAKER | JAZZ | J-008 | J790537 | NA |
| 6 | MOUSE | LOGITECH | M-S43 | LZE000703132 | DZL211106 |

| No. | Signal cable description |
|-----|--|
| 1 | NA |
| 2 | 1.8 m braid shielded wire, terminated with VGA connector via metallic frame, w/o core. |
| 3 | 1.2m braid shielded wire, terminated with DB25 and Centronic connector via metallic frame, w/o core. |
| 4 | 1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core. |
| 5 | 1.5 m wrapped shielded wire, terminated via drain wire, with 3.5 mm phone plug , w/o core. |
| 6 | 1.5 m foil shielded wire, terminated with PS2 connector via drain wire, w/o core. |

Note: All power cords of the above support units are non shielded (1.8m).

2.3 TEST METHODOLOGY AND CONFIGURATION

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 1992. Radiated testing was performed at an antenna to EUT distance of 10 m on an open area test site.

Please refer to the photos of test configuration in Item 5.



3. TEST INSTRUMENTS

3.1 TEST INSTRUMENTS (EMISSION)

CONDUCTED EMISSION MEASUREMENT

| Description & Manufacturer | Model No. | Serial No. | Calibrated Until |
|--|-----------|------------|------------------|
| ROHDE & SCHWARZ Test Receiver | ESHS30 | 828109/007 | July 6, 2001 |
| ROHDE & SCHWARZ Artificial Mains Network | ESH3-Z5 | 839135/006 | July 9, 2001 |
| ROHDE & SCHWARZ 4-wire ISN | ENY41 | 835154/007 | Apr. 26, 2001 |
| EMCO-L.I.S.N. | 3825/2 | 9204-1964 | July 9, 2001 |
| Shielded Room | Site 2 | ADT-C02 | NA |

Note: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.

RADIATED EMISSION MEASUREMENT

| Description & Manufacturer | Model No. | Serial No. | Calibrated until |
|------------------------------------|----------------------|--------------------------|------------------|
| HP Spectrum Analyzer | 8590L | 3544A00941 | Dec. 05, 2000 |
| HP Pre-Amplifier | 8447D | 2944A08312 | March 12, 2001 |
| HP Preamplifier | 8449B | 3008A01201 | Dec. 14, 2000 |
| R&S Receiver | ESVS10 | 844594/010 | Sept. 29, 2000 |
| SCHWARZBECK Tunable Dipole Antenna | VHA 9103 UHA 9105 | E101051 E101055 | Nov. 23, 2000 |
| ROHDE & SCHWARZ TEST RECEIVER | ESMI | 839013/007 839379/002 | Aug. 3, 2001 |
| CHASE BILOG Antenna | CBL6111A | 1500 | Aug. 31, 2001 |
| EMCO Double Ridged Guide Antenna | 3115 | 9312-4192 | March 29, 2001 |
| EMCO Turn Table | 1060-04 | 1196 | NA |
| EMCO Tower | 1051 | 1264 | NA |
| Open Field Test Site | Site 1 | ADT-R01 | Aug. 25, 2001 |

Note: 1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.



3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION

LIMIT OF RADIATED EMISSION OF CISPR 22

| FREQUENCY (MHz) | Class A (at 10m) * | Class B (at 10m) * |
|--------------------|--------------------|--------------------|
| | dBuV/m | dBuV/m |
| 30 - 230 | 40 | 30 |
| 230 - 1000 | 47 | 37 |

* Detector Function: Quasi-Peak

LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

| FREQUENCY (MHz) | Class A (dBuV/m) (at 3m) | | Class B (dBuV/m) (at 3m) | |
|--------------------|--------------------------|---------|--------------------------|---------|
| | Peak | Average | Peak | Average |
| Above 1000 | 80.0 | 60.0 | 74.0 | 54.0 |

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

LIMIT OF CONDUCTED EMISSION OF CISPR 22

| FREQUENCY (MHz) | Class A (dBuV) | | Class B (dBuV) | |
|--------------------|----------------|---------|----------------|---------|
| | Quasi-peak | Average | Quasi-peak | Average |
| 0.15 - 0.5 | 79 | 66 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 73 | 60 | 56 | 46 |
| 5.0 - 30.0 | 73 | 60 | 60 | 50 |

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4. TEST RESULTS (EMISSION)

4.1 RADIO DISTURBANCE

Frequency Range : 0.15 - 30 MHz (Conducted Emission)
30 - 1000 MHz (Radiated Emission)
Input Voltage : 120 Vac, 60 Hz (from PC)
Temperature : 27 Degree C
Humidity : 80 %
Atmospheric Pressure : 1000 mbar

| TEST RESULT | Remarks |
|-------------|--|
| PASS | Minimum passing margin of conducted emission: -11.77 dB at 0.204 MHz Minimum passing margin of radiated emission:-7.7 dB at 42.05 MHz |

4.2 EUT OPERATION CONDITION

1. Turn on the power of all equipment.
2. PC reads a test program to enable all functions.
3. PC reads and writes messages from FDD and HDD.
4. EUT sends "H" character to PC.
5. PC sends "H" messages to monitor and monitor displays "H" patterns on screen.
6. PC sends "H" messages to modem.
7. PC sends "H" messages to printer, and the printer prints them on paper.
8. PC sends audio messages to speaker.
9. Repeat steps 3-9.




4.3 TEST DATA OF CONDUCTED EMISSION

EUT: **KEYBOARD**MODEL: **5112**6 dB Bandwidth: **10 kHz**PHASE: **LINE (L)**

| No | Freq. | Corr. | Reading Value | | Emission Level | | Limit | | Margin | |
|----|--------|--------|---------------|-----|----------------|-----|-----------|-------|--------|-----|
| | | Factor | [dB (uV)] | | [dB (uV)] | | [dB (uV)] | | (dB) | |
| | | (dB) | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.209 | 0.20 | 51.06 | - | 51.26 | - | 63.24 | 54.31 | -11.98 | - |
| 2 | 0.411 | 0.20 | 44.18 | - | 44.38 | - | 57.63 | 48.54 | -13.25 | - |
| 3 | 0.513 | 0.20 | 41.50 | - | 41.70 | - | 56.00 | 46.00 | -14.30 | - |
| 4 | 1.236 | 0.20 | 36.34 | - | 36.54 | - | 56.00 | 46.00 | -19.46 | - |
| 5 | 14.315 | 0.96 | 45.92 | - | 46.88 | - | 60.00 | 50.00 | -13.12 | - |
| 6 | 17.564 | 1.05 | 34.30 | - | 35.35 | - | 60.00 | 50.00 | -24.65 | - |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Correction Factor + Reading Value.






TEST DATA OF CONDUCTED EMISSION

EUT: **KEYBOARD**MODEL: **5112**6 dB Bandwidth: **10 kHz**PHASE: **NEUTRAL (N)**

| No | Freq. [MHz] | Corr. | Reading Value | | Emission Level | | Limit | | Margin | |
|----|----------------|--------|---------------|-----|----------------|-----|-----------|-------|--------|-----|
| | | Factor | [dB (uV)] | | [dB (uV)] | | [dB (uV)] | | (dB) | |
| | | (dB) | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.204 | 0.20 | 51.48 | - | 51.68 | - | 63.45 | 54.46 | -11.77 | - |
| 2 | 0.408 | 0.20 | 44.96 | - | 45.16 | - | 57.69 | 48.63 | -12.53 | - |
| 3 | 0.513 | 0.20 | 42.86 | - | 43.06 | - | 56.00 | 46.00 | -12.94 | - |
| 4 | 1.236 | 0.20 | 35.04 | - | 35.24 | - | 56.00 | 46.00 | -20.76 | - |
| 5 | 14.315 | 0.86 | 45.82 | - | 46.68 | - | 60.00 | 50.00 | -13.32 | - |
| 6 | 17.567 | 0.95 | 30.50 | - | 31.45 | - | 60.00 | 50.00 | -28.55 | - |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Correction Factor + Reading Value.





4.4 TEST DATA OF RADIATED EMISSION

EUT: **KEYBOARD**MODEL: **5112**ANT. POLARITY: HorizontalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M

| Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (cm) | Table Angle (Degree) |
|--------------------|---------------------------|-------------------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|
| 40.18 | 11.4 | 7.4 | 18.8 | 30.0 | -11.2 | 400 | 92 |
| 48.03 | 8.6 | 6.9 | 15.5 | 30.0 | -14.5 | 400 | 234 |
| 114.32 | 11.5 | 4.4 | 15.9 | 30.0 | -14.1 | 400 | 74 |
| 144.04 | 12.1 | 5.5 | 17.6 | 30.0 | -12.4 | 400 | 281 |
| 178.85 | 9.6 | 3.4 | 13.0 | 30.0 | -17.0 | 400 | 32 |
| 260.80 | 13.3 | 7.1 | 20.4 | 37.0 | -16.6 | 304 | 140 |

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)
+ Reading value (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION

EUT: **KEYBOARD**MODEL: **5112**ANT. POLARITY: VerticalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M


| Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (cm) | Table Angle (Degree) |
|--------------------|---------------------------|-------------------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|
| 42.05 | 10.7 | 11.6 | 22.3 | 30.0 | -7.7 | 100 | 265 |
| 85.96 | 8.1 | 11.8 | 19.9 | 30.0 | -10.1 | 100 | 355 |
| 114.46 | 11.5 | 6.5 | 18.0 | 30.0 | -12.0 | 100 | 242 |
| 144.02 | 12.1 | 7.9 | 20.0 | 30.0 | -10.0 | 100 | 98 |
| 178.84 | 9.6 | 12.2 | 21.8 | 30.0 | -8.2 | 100 | 267 |
| 229.11 | 11.5 | 7.1 | 18.6 | 30.0 | -11.4 | 100 | 209 |
| 249.43 | 12.9 | 6.3 | 19.2 | 37.0 | -17.8 | 100 | 139 |

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)
+ Reading value (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value




5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN

CONDUCTED EMISSION TEST





RADIATED EMISSION TEST





6. APPENDIX - INFORMATION OF THE TESTING LABORATORY

Information of the testing laboratory

We, ADT Corp., are founded in 1988, to provide our best service in EMC and Safety consultation. Our laboratory is accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

- | | |
|---------------|--------------------------------------|
| ● USA | FCC, UL, NVLAP |
| ● Germany | TUV Rheinland TUV Product Service |
| ● Japan | VCCI |
| ● New Zealand | RFS |
| ● Norway | NEMKO, DNV |
| ● U.K. | INCHCAPE |
| ● R.O.C. | BSMI |

Copies of accreditation certificates of our laboratory obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.
If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab.:
Tel: 886-2-26032180
Fax: 886-2-26022943

Hsin Chu EMC Lab:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab.:
Tel: 886-2-26093195
Fax: 886-2-26093184

Design Center:
Tel: 886-2-26093195
Fax: 886-2-26093184

E-mail: service@mail.adt.com.tw
<http://www.adt.com.tw>