4.6. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a. Set RBW = 100 kHz.
- b. Set the video bandwidth (VBW) \ge 3 × RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

<u>LIMIT</u>

For Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz

TEST RESULTS

Temperature	23.6 ℃	Humidity	55.7%		
Test Engineer	Oliver Ou	Configurations	IEEE 802.11a/n/ac		

Туре	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	149	16.400		
	157	157 16.400		Pass
	165	16.400		
	149	17.440		
802.11nHT20	157	16.960	>500	Pass
	165	17.320		
000 44-40	151	35.680	> 500	Deee
002.111140	159	36.240	>500	Pass
	149	17.200		
802.11ac20	157	17.200	>500	Pass
	165	17.200		
802.11ac40	151	36.080	> 500	Deee
	159	35.360	-500	rass
802.11ac80	155	75.520	>500	Pass







4.7. 26dBc Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for Emission Bandwidth (EBW) measurement:

- a. Set RBW = 220 kHz/430 kHz /820 kHz (approximately 1% of the emission bandwidth).
- b. Set the video bandwidth (VBW) = 3* RBW)
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

<u>LIMIT</u>

No Limits for 26dBc Bandwith

TEST RESULTS

Temperature	23.6 ℃	Humidity	55.7%
Test Engineer	Oliver Ou	Configurations	IEEE 802.11a/n/ac

Туре	Channel	99%Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (KHz)	Result
	36	17.111	25.320		
802.11a	40	17.332	27.440	-	Pass
	48	17.297	28.640		
	36	18.290	33.960		
802.11nHT20	40	18.199	33.080	-	Pass
	48	18.225	36.840		
000 11-10	38	36.635	52.880		Pass
002.111140	46	36.758	61.040	-	
	36	18.221	34.120		
802.11ac20	40	18.180	34.880	-	Pass
	48	18.194	33.720		
802.11ac40	38	36.647	61.200		Deee
	46	36.701	54.880	-	Pass
802.11ac80	42	76.490	123.520	-	Pass













4.8. Band Edge Compliance

TEST CONFIGURATION



<u>LIMIT</u>

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBµV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725 5950	-27 (beyond 10MHz of the bandedge)	68.2
5725-5850	-17 (within 10 MHz of band edge)	78.2

TEST PROCEDURE

- 1. The EUT was placed on a turn table which is 1.5m above 1GHz.
- 2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measurements have been completed..
- 5. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
rest requeitcy range	rest Antenna Type	r cor Distance
1GHz-18GHz	Double Ridged Horn Antenna	3

6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-18GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

TEST RESULTS

Remark:For radiated bandedge We measured at both mode, recorded worst case in antenna 0's 802.11 ac20 mode;

For Radiated Bandedge Measurement

Temperature	23.4 ℃	Humidity	54.5%	
Test Engineer	Oliver Ou	Configurations	IEEE 802.11a/n/ac	

	802.11 ac20/ Channel 36 :5180 MHz								
Frog	Read	Antenna	PRM	Cable	Result	Limit	Margin		
	Level	Factor	Factor	Loss	Level	Line		Detector	Polarization
(IVIHZ)	(dBµV)	(dB/m)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(ub)		
4500.0	35.07	35.58	29.04	8.28	49.89	74.00	-24.11	Peak	Horizontal
4500.0	30.02	35.58	29.04	8.28	44.84	54.00	-9.16	AV	Horizontal
5150.0	39.26	35.58	29.04	8.28	54.08	74.00	-19.92	Peak	Horizontal
5150.0	30.45	35.58	29.04	8.28	45.27	54.00	-8.73	AV	Horizontal

802.11 ac20/ Channel 48 :5240 MHz									
Frog	Read	Antenna	PRM	Cable	Result	Limit	Morgin		
	Level	Factor	Factor	Loss	Level	Line	(dD)	Detector	Polarization
(11112)	(dBµV)	(dB/m)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(UD)		
5350.0	35.04	35.42	29.06	8.39	49.79	74.00	-24.21	Peak	Horizontal
5350.0	30.38	35.42	29.06	8.39	45.13	54.00	-8.87	AV	Horizontal
5460.0	39.01	35.42	29.06	8.39	53.76	74.00	-20.24	Peak	Horizontal
5460.0	30.55	35.42	29.06	8.39	45.30	54.00	-8.70	AV	Horizontal

802.11 ac20/ Channel 149 :5745 MHz									
Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
5650.0	30.02	35.35	29.07	8.43	44.73	68.20	-23.47	Peak	Horizontal
5700.0	30.37	35.35	29.07	8.43	45.08	68.20	-23.12	Peak	Horizontal
5720.0	32.20	35.35	29.07	8.43	46.91	68.20	-21.29	Peak	Horizontal
5725.0	30.63	35.35	29.07	8.43	45.34	68.20	-22.86	Peak	Horizontal

802.11 ac20/ Channel 165 :5825 MHz									
Erea	Read	Antenna	PRM	Cable	Result	Limit	Margin		
	Level	Factor	Factor	Loss	Level	Line	(dP)	Detector	Polarization
(IVI⊓∠)	(dBµV)	(dB/m)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(ub)		
5850.0	30.07	35.3	29.11	8.51	44.77	68.20	-23.43	Peak	Horizontal
5855.0	30.32	35.3	29.11	8.51	45.02	68.20	-23.18	Peak	Horizontal
5875.0	32.09	35.3	29.11	8.51	46.79	68.20	-21.41	Peak	Horizontal
5925.0	30.53	35.3	29.11	8.51	45.23	68.20	-22.97	Peak	Horizontal

REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. Margin value = Result Level-Limit value.

2. The other emission levels were very low against the limit.

3. The average measurement was not performed when the peak measured data under the limit of average detection.

4. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;

For Conducted Band edge Measurement

Temperature	23.6 ℃	Humidity	55.7%
Test Engineer	Oliver Ou	Configurations	IEEE 802.11a/n/ac

The test results have included the antenna gain

5150-5250MHz:













5725-5850MHz:













4.9. Frequency Stability

Standard Applicable

According to FCC §15.407(g) "Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user manual."

According to FCC §2.1055(a) "The frequency stability shall be measured with variation of ambient temperature as follows:"

(1) From -30° to + 50° centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.

(2) From -20° to + 50° centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.

(3) From 0° to + 50° centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

Test Configuration



Variable Power Supply

Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low engouh to obtain the desired frequency resoluation and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure wuth 10 degree increased per stage until the highest temperature of +50 degree reached.

Temperature Chamber

Test Results

PASS

Remark:

1. Measured all conditions and recorded worst case.

IEEE 802.11a Mode / 5180 - 5240 MHz / 5180 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5180.014725	5150 – 5250	PASS
20	DC 21.6V	5180.000058	5150 – 5250	PASS
50	DC 24.0V	5179.983380	5150 – 5250	PASS
40	DC 24.0V	5179.998466	5150 – 5250	PASS
30	DC 24.0V	5180.030942	5150 – 5250	PASS
20	DC 24.0V	5179.992540	5150 – 5250	PASS
10	DC 24.0V	5180.006288	5150 – 5250	PASS
0	DC 24.0V	5179.995486	5150 – 5250	PASS
-10	DC 24.0V	5180.031401	5150 – 5250	PASS
-20	DC 24.0V	5179.982786	5150 – 5250	PASS
-30	DC 24.0V	5180.013452	5150 – 5250	PASS

IEEE 802.11a Mode / 5180 - 5240 MHz / 5240 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5240.010996	5150 – 5250	PASS
20	DC 21.6V	5239.969368	5150 – 5250	PASS
50	DC 24.0V	5239.975515	5150 – 5250	PASS
40	DC 24.0V	5240.043892	5150 – 5250	PASS
30	DC 24.0V	5239.974154	5150 – 5250	PASS
20	DC 24.0V	5240.009330	5150 – 5250	PASS
10	DC 24.0V	5239.984078	5150 – 5250	PASS
0	DC 24.0V	5239.979810	5150 – 5250	PASS
-10	DC 24.0V	5239.986327	5150 – 5250	PASS
-20	DC 24.0V	5239.990206	5150 – 5250	PASS
-30	DC 24.0V	5239.978379	5150 – 5250	PASS

IEEE 802.11a Mode / 5745 - 5825 MHz / 5745 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5745.000007	5725 – 5850	PASS
20	DC 21.6V	5744.997123	5725 – 5850	PASS
50	DC 24.0V	5744.981465	5725 – 5850	PASS
40	DC 24.0V	5744.993939	5725 – 5850	PASS
30	DC 24.0V	5744.997974	5725 – 5850	PASS
20	DC 24.0V	5744.987062	5725 – 5850	PASS
10	DC 24.0V	5744.995244	5725 – 5850	PASS
0	DC 24.0V	5745.024469	5725 – 5850	PASS
-10	DC 24.0V	5744.979982	5725 – 5850	PASS
-20	DC 24.0V	5745.007275	5725 – 5850	PASS
-30	DC 24.0V	5745.000954	5725 – 5850	PASS

IEEE 802.11a Mode / 5745 - 5825 MHz / 5825 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5824.969724	5725 – 5850	PASS
20	DC 21.6V	5825.028796	5725 – 5850	PASS
50	DC 24.0V	5825.018541	5725 – 5850	PASS
40	DC 24.0V	5825.010382	5725 – 5850	PASS
30	DC 24.0V	5824.969404	5725 – 5850	PASS
20	DC 24.0V	5824.994274	5725 – 5850	PASS
10	DC 24.0V	5825.021721	5725 – 5850	PASS
0	DC 24.0V	5825.020142	5725 – 5850	PASS
-10	DC 24.0V	5824.977305	5725 – 5850	PASS
-20	DC 24.0V	5825.040408	5725 – 5850	PASS
-30	DC 24.0V	5825.021381	5725 – 5850	PASS

4.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The antenna is Internal Aantenna, through the buckle stretched out, The directional gains of antenna used for transmitting is 0dBi.

Reference to the Test Report: GTS20210908006-1-1.

5. TEST SETUP PHOTOS OF THE EUT

Reference to the test report No. GTS20210908006-1-1.

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No. GTS20210908006-1-1.

.....End of Report.....