

RF Exposure Report

Report No.: SA150826C05A

FCC ID: PY315100319

Test Model: R7800

Received Date: Aug. 21, 2015

Test Date: Dec. 23, 2015 ~ May 26, 2016

Issued Date: Jun. 04, 2016

Applicant: NETGEAR INC.

Address: 350 East Plumeria Drive, San Jose, CA 95134, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150826C05A	Original release.	Jun. 04, 2016

1 Certificate of Conformity

Product: Nighthawk X4S AC2600 Smart WiFi Router

Brand: NETGEAR

Test Model: R7800

Sample Status: Engineering sample


Applicant: NETGEAR INC.

Test Date: Dec. 23, 2015 ~ May 26, 2016

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 (October 23, 2015)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Polly Chien / Specialist

Date:

Jun. 04, 2016

Approved by :


Ken Liu / Senior Manager

Date:

Jun. 04, 2016

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 29cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Band	Modulation type	Frequency Channel (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
CDD Mode							
2.4GHz	802.11b	2412	29.89	6.23	29	0.387	1
		2422	29.84	6.43	29	0.401	1
		2437	29.84	6.13	29	0.374	1
	802.11g	2412	27.35	6.23	29	0.216	1
		2422	29.84	6.43	29	0.401	1
		2437	27.13	6.13	29	0.200	1
	802.11n (HT20)	2412	27.35	6.23	29	0.216	1
		2437	29.84	6.43	29	0.401	1
		2462	27.35	6.13	29	0.211	1
	802.11n (HT40)	2422	23.79	6.43	29	0.100	1
		2437	26.76	6.43	29	0.197	1
		2452	25.51	6.23	29	0.141	1
5GHz (U-NII-2A)	802.11a	5260	22.83	6.93	29	0.090	1
		5300	22.85	7.13	29	0.094	1
		5320	22.77	7.13	29	0.092	1
	802.11n (HT20)	5260	22.68	6.93	29	0.086	1
		5300	22.70	7.13	29	0.091	1
		5320	22.74	7.13	29	0.092	1
	802.11n (HT40)	5270	23.60	7.03	29	0.109	1
		5310	23.85	7.13	29	0.119	1
	802.11ac (VHT80)	5290	20.46	7.13	29	0.054	1
5GHz (U-NII-2C)	802.11a	5500	22.86	7.53	29	0.104	1
		5580	22.72	7.53	29	0.100	1
		5700	22.73	7.53	29	0.100	1
	802.11n (HT20)	5500	22.97	7.53	29	0.106	1
		5580	22.65	7.53	29	0.099	1
		5700	22.68	7.53	29	0.099	1
	802.11n (HT40)	5510	23.86	7.63	29	0.133	1
		5550	23.80	7.53	29	0.129	1
		5670	23.81	7.63	29	0.132	1
	802.11ac (VHT80)	5530	22.37	7.63	29	0.095	1
		5610	23.71	7.53	29	0.126	1

Band	Modulation type	Frequency Channel (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Total Power Density (mW/cm ²)	Limit (mW/cm ²)
5GHz (U-NII-1 & U-NII-2A)	802.11ac (VHT80+VHT80)	5210	22.79	3.82	29	0.043	0.090	1
		5290	22.82	4.12		0.047		
5GHz (U-NII-2A & U-NII-2C)	802.11ac (VHT80+VHT80)	5530	20.59	4.62	29	0.031	0.031	1
		5610	20.56	4.52	29	0.030		
5690		17.58	4.52	29	0.015	0.015	1	
5690		4.84	4.52		0.001	0.031		
5775		20.49	4.52		0.030			

Note:

2412MHz: Directional gain = 0.21dBi + 10log(4) = 6.23dBi
2422MHz: Directional gain = 0.41dBi + 10log(4) = 6.43dBi
2437MHz: Directional gain = 0.41dBi + 10log(4) = 6.43dBi
2452MHz: Directional gain = 0.21dBi + 10log(4) = 6.23dBi
2462MHz: Directional gain = 0.11dBi + 10log(4) = 6.13dBi
5210MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5260MHz: Directional gain = 0.91dBi + 10log(4) = 6.93dBi
5270MHz: Directional gain = 1.01dBi + 10log(4) = 7.03dBi
5290MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5300MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5310MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5320MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5500MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi
5510MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5530MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5550MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5580MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi
5610MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi
5670MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5700MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi

*802.11ac (VHT80+VHT80):

5210MHz: Directional gain = 0.81dBi + 10log(4/2) = 3.82dBi
5290MHz: Directional gain = 1.11dBi + 10log(4/2) = 4.12dBi
5530MHz: Directional gain = 1.61dBi + 10log(4/2) = 4.62dBi
5610MHz: Directional gain = 1.51dBi + 10log(4/2) = 4.52dBi
5690MHz: Directional gain = 1.51dBi + 10log(4/2) = 4.52dBi
5575MHz: Directional gain = 1.51dBi + 10log(4/2) = 4.52dBi

Band	Modulation type	Frequency Channel (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
Beamforming_NSS1 Mode							
2.4GHz	802.11n (HT20)	2412	27.29	6.23	29	0.213	1
		2437	29.56	6.43	29	0.376	1
		2462	28.42	6.13	29	0.270	1
	802.11n (HT40)	2422	23.85	6.43	29	0.101	1
		2437	26.72	6.43	29	0.195	1
		2452	24.36	6.23	29	0.108	1
5GHz (U-NII-2A)	802.11n (HT20)	5260	23.07	6.93	29	0.095	1
		5300	22.87	7.13	29	0.095	1
		5320	22.87	7.13	29	0.095	1
	802.11n (HT40)	5270	22.66	7.03	29	0.088	1
		5310	22.85	7.13	29	0.094	1
	802.11ac (VHT80)	5290	20.46	7.13	29	0.054	1
5GHz (U-NII-2C)	802.11n (HT20)	5500	22.47	7.53	29	0.095	1
		5580	22.47	7.53	29	0.095	1
		5700	22.47	7.53	29	0.095	1
	802.11n (HT40)	5510	22.34	7.63	29	0.094	1
		5550	22.31	7.53	29	0.091	1
		5670	22.34	7.63	29	0.094	1
	802.11ac (VHT80)	5530	22.31	7.63	29	0.093	1
		5610	22.22	7.53	29	0.089	1

Band	Modulation type	Frequency Channel (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Total Power Density (mW/cm ²)	Limit (mW/cm ²)
5GHz (U-NII-1 & U-NII-2A)	802.11ac (VHT80+VHT80)	5210	22.82	3.82	29	0.044	0.091	1
		5290	22.81	4.12		0.047		
5GHz (U-NII-2A & U-NII-2C)	802.11ac (VHT80+VHT80)	5530	19.24	4.62	29	0.023	0.045	1
		5610	19.23	4.52	29	0.022		
5690		17.64	4.52	29	0.016	0.016	1	
5690		4.73	4.52		0.001	0.029		
5775		20.23	4.52		0.028			

Note:

2412MHz: Directional gain = 0.21dBi + 10log(4) = 6.23dBi
2422MHz: Directional gain = 0.41dBi + 10log(4) = 6.43dBi
2437MHz: Directional gain = 0.41dBi + 10log(4) = 6.43dBi
2452MHz: Directional gain = 0.21dBi + 10log(4) = 6.23dBi
2462MHz: Directional gain = 0.11dBi + 10log(4) = 6.13dBi
5260MHz: Directional gain = 0.91dBi + 10log(4) = 6.93dBi
5270MHz: Directional gain = 1.01dBi + 10log(4) = 7.03dBi
5290MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5300MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5310MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5320MHz: Directional gain = 1.11dBi + 10log(4) = 7.13dBi
5500MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi
5510MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5530MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5550MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5580MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi
5610MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi
5670MHz: Directional gain = 1.61dBi + 10log(4) = 7.63dBi
5700MHz: Directional gain = 1.51dBi + 10log(4) = 7.53dBi

*802.11ac (VHT80+VHT80):

5210MHz: Directional gain = 0.81dBi + 10log(4/2) = 3.82dBi
5290MHz: Directional gain = 1.11dBi + 10log(4/2) = 4.12dBi
5530MHz: Directional gain = 1.61dBi + 10log(4/2) = 4.62dBi
5610MHz: Directional gain = 1.51dBi + 10log(4/2) = 4.52dBi
5690MHz: Directional gain = 1.51dBi + 10log(4/2) = 4.52dBi
5575MHz: Directional gain = 1.51dBi + 10log(4/2) = 4.52dBi

Band	Modulation type	Frequency Channel (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
Beamforming_NSS2 Mode							
2.4GHz	802.11n (HT20)	2412	27.35	3.22	29	0.108	1
		2437	29.59	3.42	29	0.189	1
		2462	28.44	3.12	29	0.136	1
	802.11n (HT40)	2422	23.66	3.42	29	0.048	1
		2437	26.75	3.42	29	0.098	1
		2452	24.36	3.22	29	0.054	1
5GHz (U-NII-2A)	802.11n (HT20)	5260	22.67	3.92	29	0.043	1
		5300	22.70	4.12	29	0.045	1
		5320	22.73	4.12	29	0.046	1
	802.11n (HT40)	5270	23.66	4.02	29	0.055	1
		5310	23.84	4.12	29	0.059	1
	802.11ac (VHT80)	5290	20.45	4.12	29	0.027	1
5GHz (U-NII-2C)	802.11n (HT20)	5500	22.85	4.52	29	0.052	1
		5580	22.67	4.52	29	0.050	1
		5700	22.85	4.52	29	0.052	1
	802.11n (HT40)	5510	23.87	4.62	29	0.067	1
		5550	23.78	4.62	29	0.065	1
		5670	23.81	4.62	29	0.066	1
	802.11ac (VHT80)	5530	22.38	4.62	29	0.047	1
		5610	23.69	4.52	29	0.063	1

Note:

2412MHz: Directional gain = $0.21\text{dBi} + 10\log(4/2) = 3.22\text{dBi}$
 2422MHz: Directional gain = $0.41\text{dBi} + 10\log(4/2) = 3.42\text{dBi}$
 2437MHz: Directional gain = $0.41\text{dBi} + 10\log(4/2) = 3.42\text{dBi}$
 2452MHz: Directional gain = $0.21\text{dBi} + 10\log(4/2) = 3.22\text{dBi}$
 2462MHz: Directional gain = $0.11\text{dBi} + 10\log(4/2) = 3.12\text{dBi}$
 5260MHz: Directional gain = $0.91\text{dBi} + 10\log(4/2) = 3.92\text{dBi}$
 5270MHz: Directional gain = $1.01\text{dBi} + 10\log(4/2) = 4.02\text{dBi}$
 5290MHz: Directional gain = $1.11\text{dBi} + 10\log(4/2) = 4.12\text{dBi}$
 5300MHz: Directional gain = $1.11\text{dBi} + 10\log(4/2) = 4.12\text{dBi}$
 5310MHz: Directional gain = $1.11\text{dBi} + 10\log(4/2) = 4.12\text{dBi}$
 5320MHz: Directional gain = $1.11\text{dBi} + 10\log(4/2) = 4.12\text{dBi}$
 5500MHz: Directional gain = $1.51\text{dBi} + 10\log(4/2) = 4.52\text{dBi}$
 5510MHz: Directional gain = $1.61\text{dBi} + 10\log(4/2) = 4.62\text{dBi}$
 5550MHz: Directional gain = $1.61\text{dBi} + 10\log(4/2) = 4.62\text{dBi}$
 5530MHz: Directional gain = $1.61\text{dBi} + 10\log(4/2) = 4.62\text{dBi}$
 5580MHz: Directional gain = $1.51\text{dBi} + 10\log(4/2) = 4.52\text{dBi}$
 5610MHz: Directional gain = $1.51\text{dBi} + 10\log(4/2) = 4.52\text{dBi}$
 5670MHz: Directional gain = $1.61\text{dBi} + 10\log(4/2) = 4.62\text{dBi}$
 5700MHz: Directional gain = $1.51\text{dBi} + 10\log(4/2) = 4.52\text{dBi}$

CONCLUSION:

Both of the WLAN 2.4G & WLAN 5G can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WLAN\ 2.4G + WLAN\ 5.0G = 0.401 + 0.133 = 0.534$

Therefore, the maximum calculation of this situation is 0.534, which is less than the "1" limit.

---END---