

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EX0376-4 Issue 2



CFR Title 47 FCC Part 2.1093

Report Exhibit

Prepared for Controlid Industria e Comercio de Hardware e Servicos De
Tecnologia Ltda

This report presents the environmental impact of human exposure to radiofrequency radiation for
IDFACEFPM

Prepared by

Ryan Brown

Sr. EMC/Wireless Engineer

Approved by

Yunus Faziloglu

Wireless Manager

Issue date: Jan 2, 2024



Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EX0376-4 Issue 2

This test result relates only to the described test object.
 This document shall not be reproduced, except in full, without the written approval of Bureau Veritas Test Lab.
 Customer must not use this test report as the product certification of each accreditation body or each national organization.
 The test is traceable to national standard or related international standard

Contents

- 1 Device Under Test Information3
- 2 Test Laboratory Information4
- 3 RF Exposure – Determination of Exemption.....5
- 3.1 SAR-based Exemption per 447498 D01 General RF Exposure Guidance v06.....5

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EX0376-4 Issue 2

1 Device Under Test Information

1.1 Product Information

Project Number:	X0376
Applicant Information:	Controlid Industria e Comercio de Hardware e Servicos De Tecnologia Ltda Rua Hungria, 888, 8th Floor Sao Paulo SP, 01455000 - Brazil
Test Item Description:	IDFACEFPM
Model Number:	IDFACEFPM
Separation Distance:	0mm
Exposure Category of DUT:	Portable
Multiple Simultaneous RF Sources:	No
Type of Evaluation:	Extremity SAR Exemption Calculation
Evaluation Method:	447498 D01 General RF Exposure Guidance v06
Deviations from Standard:	None

Technical Information

FCC ID:	2AKJ4-IDFACEFPM
Transmit Frequency:	13.56MHz
Exposure Category of Transmitter:	Portable
Maximum field strength (dBuV/m @ 3m):	59.9dBuV/m at 3m
Maximum EIRP (mW):	0.0003mW (converted from maximum field strength)
Maximum Tune-up Tolerance (dB):	N/A

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EX0376-4 Issue 2

2 Test Laboratory Information

Location of Test Lab:	One Distribution Center Circle #1 Littleton, MA 01460 (978) 486-8880
Key Contact:	Yunus Faziloglu Yunus.faziloglu@bureauveritas.com
Laboratory Accreditations:	BUREAU VERITAS CONSUMER PRODUCTS SERVICES, INC is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.
ISO/IEC 17025:2017:	1627-01
FCC Test Site Number:	US1028

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EX0376-4 Issue 2

3 RF Exposure – Determination of Exemption

3.1 SAR-based Exemption per 447498 D01 General RF Exposure Guidance v06

3.1.1 13.56MHz RFID

SAR exemption calculation for 13.56MHz at 0mm is based on
 Per 447498 D01 General RF Exposure Guidance v06 Section 4.3.1 a), b)1) using 50mm separation and
 0.1GHz and applying it to 13.56MHz using c)2) as follows,

a) $(7.5/\sqrt{0.1\text{GHz}}) * 50\text{mm} = 1185.9\text{mW}$

b)1) $1185.9 + ((50-50) * (100/150)) = 1185.9\text{mW}$

c)2) $1185.9 * (1 + \log(100/13.56)) * \frac{1}{2} = 1107.4\text{mW}$

EIRP for 13.56MHz RFID is 0.0003mW and therefore exempt from stand-alone SAR testing.

3.1.2 Conclusion

Device meets the SAR test exemption criteria based on the calculations shown above.

Document Revisions

Issue No.	Summary of Changes	Date Issued	Prepared by	Approved by
1	Original Release	Oct 6, 2023	RMB	YF
2	Corrected a typographical error in Section 3.1.1 header	Jan 2, 2024	RMB	YF

End of Report