



Date: 10.JAN.2019 17:03:43

CH7, 802.11he40, HE0, SISO A, Range 30MHz to 9GHz - Delta Marker Measurement




Date: 10.JAN.2019 17:04:13

CH7, 802.11he40, HE0, SISO A, Range 9GHz to 18GHz - Delta Marker Measurement




Date: 10.JAN.2019 17:04:43

CH7, 802.11he40, HE0, SISO A, Range 18GHz to 26.5GHz - Delta Marker Measurement




Date: 8.JAN.2019 15:26:09

CH7, 802.11he40, HE0, SISO B, Range 30MHz to 9GHz - Delta Marker Measurement




Date: 8.JAN.2019 15:26:36

CH7, 802.11he40, HE0, SISO B, Range 9GHz to 18GHz - Delta Marker Measurement




Date: 8.JAN.2019 15:26:07


CH7, 802.11he40, HE0, SISO B, Range 18GHz to 26.5GHz - Delta Marker Measurement




CH7, 802.11he40, HE0, MIMO A, Range 30MHz to 9GHz - Delta Marker Measurement




CH7, 802.11he40, HE0, MIMO A, Range 9GHz to 18GHz - Delta Marker Measurement




CH7, 802.11he40, HE0, MIMO A, Range 18GHz to 26.5GHz - Delta Marker Measurement



CH7, 802.11he40, HE0, MIMO B, Range 30MHz to 9GHz - Delta Marker Measurement



CH7, 802.11he40, HE0, MIMO B, Range 9GHz to 18GHz - Delta Marker Measurement



CH7, 802.11he40, HE0, MIMO B, Range 18GHz to 26.5GHz - Delta Marker Measurement

B.4 Test Results BLE

B.4.1 6dB & 99% Bandwidth

Test limits

FCC part	RSS part	Limits
15.247 (a) (2)	RSS-247 Clause 5.2 (a)	Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


Test procedure

The conducted setup shown in section *Test & System Description* was used to measure the 6dB & 99% Bandwidth. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Results tables

Mode	Channel	Frequency [MHz]	6dB BW [MHz]	99% BW [MHz]
BLE	37	2402	0.667	1.16
	17	2440	0.675	1.16
	39	2480	0.681	1.15


Results screenshot




CH 37, 6dB



CH 37, 99%



CH 17, 6dB



CH 17, 99%



CH 39, 6dB



CH 39, 99%

B.4.2 Maximum Output Power and antenna gain

Test limits

	Limits
FCC Part 15.247 (b) (3)	<p>(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:</p> <p>(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level.</p> <p>(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.</p>
RSS-247 Clause 5.4 (d)	<p>For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).</p> <p>As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode</p>

Test procedure:

The Maximum peak conducted output power was measured using the *RBW ≥ DTS bandwidth* method defined in paragraph 9.1.1 of FCC KDB 558074 D01 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

The Maximum conducted average output power was measured using the channel integration method according to Method AVGSA-2, defined in paragraph 9.2.2.4 of FCC KDB 558074 D01 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power. The declared maximum antenna gain is +3.24dBi.

The conducted setup shown in section *Test & System Description* was used to measure the maximum conducted output power. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Results tables

				Peak Power [dBm]		
Mode	Meas. Duty Cycle [%]	CH	Frequency [MHz]	Measured Conducted Output Power	EIRP	Peak Output Power [mW]
BLE	60	37	2402	8.79	12.03	7.57
		17	2440	8.87	12.11	7.71
		39	2480	8.98	12.22	7.91


Max Value

Min Value


				Average Output Power* [dBm]			
Mode	Meas. Duty Cycle [%]	CH	Frequency [MHz]	Maximum Conducted Output Power	Maximum Conducted Output Power Duty cycle Compensated	EIRP	Average Output Power [mW]
BLE	60	37	2402	7.89	10.14	13.38	10.32
		19	2440	7.97	10.22	13.46	10.52
		39	2480	8.10	10.35	13.59	10.84

* Output Power RMS values are shown for indicative purpose only


Results screenshot




CH 37, Max Power RMS




CH 37, Max Power Peak




CH 17, Max Power RMS



CH 17, Max Power Peak



CH 39, Max Power RMS



CH 39, Max Power Peak

B.4.3 Power Spectral Density

Test limits

FCC part	RSS part	Limits
15.247 (e)	RSS-247 Clause 5.2 (b)	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test procedure

The maximum peak power spectral density level of the fundamental emission was measured using the method PKPSD, defined in paragraph 10.2 of FCC KDB 558074 D01 - Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

The conducted setup shown in section *Test & System Description* was used to measure the power spectral density. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.


The declared maximum antenna gain is +3.24dBi.

Results tables


Mode	CH	Frequency [MHz]	PSD Peak [dBm/3kHz]	PSD Peak* [dBm/100kHz]
BLE	37	2402	-7.55	8.66
	17	2440	-7.60	8.71
	39	2480	-7.17	8.90

*Note: these PSD_{Peak} values are shown just as a reference for the compliance of the Out-of-band Measurements. Thus the RBW used for these measurements was 100kHz.


Results screenshot



CH 37, PSD Peak



CH 17, PSD Peak



CH 39, PSD Peak

B.4.4 Out-of-band emission (Conducted)

Test Limits

FCC part	RSS part	Limits																				
15.247 (d)	RSS-247 Clause 5.5	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.																				
15.209	RSS-Gen Clause 8.9	<p>Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):</p> <table><tr><th>Freq Range (MHz)</th><th>Field Streghth (μV/m)</th><th>Field Streghth (dBμV/m)</th><th>Meas. Distance (m)</th></tr><tr><td>30-88</td><td>100</td><td>40</td><td>3</td></tr><tr><td>88-216</td><td>150</td><td>43.5</td><td>3</td></tr><tr><td>216-960</td><td>200</td><td>46</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>54</td><td>3</td></tr></table> <p>The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.</p>	Freq Range (MHz)	Field Streghth (μV/m)	Field Streghth (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Streghth (μV/m)	Field Streghth (dBμV/m)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			

Test procedure

In case of Band Edge measurements falling in restricted bands, the declared Antenna Gain is also compensated in the graph. The declared maximum antenna gain is +3.24dBi.


For Band Edge measurements falling in restricted bands, the following limits in dBm were applied for the average detector after the conversion from the limits detailed above in dBμV/m, according to FCC 47 CFR part 15 - Subpart C – §15.209(a). The limits in dBm for peak detector are 20dB above the indicated values in the table.

§15.209(a)			Converted values	
Freq Range (MHz)	Distance (m)	Field strength (microvolts/meter)	Field strength (dB microvolts/meter)	Power (dBm)
Above 960	3	500	54.0	-41.2


The conducted setup shown in section *Test & System Description* was used to measure the out-of-band emissions. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

Note: For the compliance of the Out-of-band Measurements, PSD_{Peak} were measured with 100kHz RBW and values are shown just as a reference in section B.4.3.


BE Results screenshot



CH 37, BE Low





CH 37, BE Low Non Restricted




CH 39, BE High Restricted


Spurious Results screenshot




CH 37, Conducted Spurious Range 30MHz to 9GHz




CH 37, Conducted Spurious Range 9GHz to 18GHz



CH 37, Conducted Spurious Range 18GHz to 2GHz




CH 17, Conducted Spurious Range 30MHz to 9GHz




CH 17, Conducted Spurious Range 9GHz to 18GHz


CH 17, Conducted Spurious Range 18GHz to 2GHz



CH 39, Conducted Spurious Range 30MHz to 9GHz



CH 39, Conducted Spurious Range 9GHz to 18GHz



CH 39, Conducted Spurious Range 18GHz to 2GHz

B.4.5 Radiated spurious emission

Standards references

FCC part	RSS part	Limits																				
15.247 (d) 15.209	RSS-247 Clause 5.5 RSS-Gen Clause 8.9	Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):																				
		<table><tr><th>Freq Range (MHz)</th><th>Field Strength (μV/m)</th><th>Field Strength (dBμV/m)</th><th>Meas. Distance (m)</th></tr><tr><td>30-88</td><td>100</td><td>40</td><td>3</td></tr><tr><td>88-216</td><td>150</td><td>43.5</td><td>3</td></tr><tr><td>216-960</td><td>200</td><td>46</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>54</td><td>3</td></tr></table>	Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
		Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																	
		30-88	100	40	3																	
		88-216	150	43.5	3																	
		216-960	200	46	3																	
Above 960	500	54	3																			
The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																						
For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.																						

Test procedure

The radiated setups shown in section *Test & System Description* were used to measure the radiated spurious emissions. were used to measure the radiated spurious emissions.

Depending of the frequency range and bands being tested, different antennas and filters were used.

The final measurement is done by varying the antenna height, the EUT azimuth over 360° and for both Vertical and Horizontal polarizations.

The radiated spurious emissions were measured on the lowest, middle and highest channels.

Test Results

30 MHz – 26.5 GHz, BLE

Radiated Spurious – CH37

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBµV/m	dBµV/m	dBµV/m	dB
187.5	28.0	---	43.6	15.6
624.0	34.5	---	46.0	11.5
672.0	33.4	---	46.0	12.6
6325.5	---	45.0	54.0	9.0
6326.0	57.1	---	74.0	16.9
17137.7	50.8	---	74.0	23.2
17145.0	---	39.8	54.0	14.2
20719.6	47.4	---	74.0	26.6
20719.6	---	39.2	54.0	14.8

Radiated Spurious – CH17

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBµV/m	dBµV/m	dBµV/m	dB
80.4	29.3	---	40.0	10.7
187.5	29.5	---	43.6	14.0
624.0	34.2	---	46.0	11.8
6315.5	---	45.0	54.0	9.0
6316.0	57.3	---	74.0	16.7
17133.9	---	39.9	54.0	14.1
17168.2	51.0	---	74.0	23.0
20720.0	47.8	---	74.0	26.2
20720.0	---	39.8	54.0	14.2

Radiated Spurious – CH39

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBµV/m	dBµV/m	dBµV/m	dB
216.0	28.8	---	43.6	14.8
624.0	34.6	---	46.0	11.4
672.0	34.3	---	46.0	11.7
6320.5	57.3	---	74.0	16.7
6322.0	---	45.0	54.0	9.0
17134.4	---	39.7	54.0	14.3
17167.2	51.1	---	74.0	22.9
20719.6	47.3	---	74.0	26.7
20720.0	---	40.1	54.0	13.9