

Page : 1 of 12 Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

# **Maximum Permissible Exposure Report**

**Product**: IEEE 802.11ax/ac/a/b/g/n 2x2 WiFi with Bluetooth5.0 Combo

Module

**Model Name**: WNFB-266AXI(BT)

Series Model : AP12275\_M2

FCC ID : RYK-WNFB266AXIBT

**Test Regulation**: 47 CFR FCC Part 2.1091

**Received Date** : Jul. 22, 2020

**Issued Date** : Mar. 18, 2021

**Applicant**: SparkLAN Communications, Inc.

8F., No.257, Sec. 2, Tiding Blvd., Neihu District, Taipei City

11493, Taiwan (R.O.C.)

**Issued By** : Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,

Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 3.0



Page : 2 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

# **REVISION HISTORY**

Original Test Report No.: 4789558396-US-R5-V0

Rev.	Test report No.	Date	Page revised	Contents
Original	Test report No. 4789558396-US-R5-V0	Mar. 18, 2021	-	Initial issue
U		,		
			1	ı

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 3.0



Page : 3 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

## **Table of Contents**

1.	Attestation of Test Results	4
2.	Test Methodology and Reference Procedures	5
3.	Facilities and Accreditation	5
4.	Equipment Under Test	6
4	4.1. Description of EUT	6
4	4.2. Description of Available Antennas	9
5.	Requirement	10
6.	Radio Frequency Radiation Exposure Evaluation	11



Page : 4 of 12 Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### 1. Attestation of Test Results

APPLICANT: SparkLAN Communications, Inc.

8F., No.257, Sec. 2, Tiding Blvd., Neihu District, Taipei City 11493,

Taiwan (R.O.C.)

**MANUFACTURER** SparkLAN Communications, Inc.

8F., No.257, Sec. 2, Tiding Blvd., Neihu District, Taipei City 11493,

Taiwan (R.O.C.)

**EUT DESCRIPTION:** IEEE 802.11ax/ac/a/b/g/n 2x2 WiFi with Bluetooth5.0 Combo Module

**MODEL:** WNFB-266AXI(BT)

**SERIES MODEL:** AP12275\_M2

**SAMPLE STAGE:** Identical Prototype

#### APPLICABLE STANDARDS

**STANDARD** 

**Test Results** 

47 CFR FCC PART 2.1091

**PASS** 

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Approved and Authorized By:

Sally Lu

Project Handler

Date: Mar. 18, 2021

Waternil Guan Date: Mar. 18, 2021

Engineer

#### **Underwriters Laboratories Taiwan Co., Ltd.**

Sally lu

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

:+886-2-7737-3000 Telephone Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 3.0



Page : 5 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### 2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

### 3. Facilities and Accreditation

Test Location Underwriters Laboratories Taiwan Co., Ltd.					
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan				
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398. The full scope of accreditation can be viewed at <a href="http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398">http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398</a>				



Page : 6 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### 4. Equipment Under Test

### 4.1. Description of EUT

Product	IEEE 802.11ax/ac/a/b/g/n 2x2 WiFi with Bluetooth5.0 Combo Module				
Model Name	WNFB-266AXI(BT)				
Series Model	AP12275_M2				
	Bluetooth EDR	2402MHz ~ 2480MHz			
	Bluetooth LE	2402MHz ~ 2480MHz			
		2.4GHz:			
Operating Frequency	WLAN	2412MHz ~ 2462MHz			
		5GHz:			
		5180 ~ 5240 MHz, 5260 ~ 5320 MHz			
		5500 ~ 5720 MHz, 5745 ~ 5825 MHz			
	Bluetooth EDR	GFSK, π/4-DQPSK, 8DPSK			
	Bluetooth LE	GFSK			
Modulation		CCK, DQPSK, DBPSK for DSSS			
	WLAN	64QAM, 16QAM, QPSK, BPSK for OFDM			
	WLAN	1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA			
N. I. COL.	Bluetooth EDR	79			
Number of Channel	Bluetooth LE	40			



Page : 7 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

	2.4G WLAN 2412 ~ 2462 MHz	11 for 802.11b, 802.11g, 802.11n (HT20)	
		4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20)	
	5G WLAN 5180 ~ 5240 MHz	2 for 802.11n (HT40), 802.11 ac (VHT40), 802.11ax (HE40)	
		1 for 802.11ac (VHT80), 802.11ax (HE80)	
		4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20)	
	5G WLAN 5260 ~ 5320 MHz	2 for 802.11n (HT40), 802.11 ac (VHT40),	
Number of Channel		802.11ax (HE40)	
1 (4111001 01 01 014111101		1 for 802.11ac (VHT80), 802.11ax (HE80)	
	5G WLAN 5500 ~ 5720 MHz	12 for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20)	
		6 for 802.11n (HT40), 802.11 ac (VHT40), 802.11ax (HE40)	
		3 for 802.11ac (VHT80), 802.11ax (HE80),	
		5 for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20)	
	5G WLAN	2 for 802.11n (HT40), 802.11 ac (VHT40),	
	5745 ~ 5825 MHz	802.11ax (HE40)	
		1 for 802.11ac (VHT80), 802.11ax (HE80)	
Normal Voltage	3.3 Vdc		
S/N	3200753		
Software Version	N/A		

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan



Page : 8 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

#### Note:

1. The models difference table as below:

Brand Model		Difference
SparkLAN	WNFB-266AXI(BT)	-
Ampak	AP12275_M2	Same as WNFB-266AXI(BT), marketing purpose only.

<sup>\*</sup>Except above change, there are no change to technical construction that is included circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction.

2. The EUT provides two completed transmitters and two receivers.

<b>Modulation Mode</b>	Tx,Rx Function
802.11a	2TX,2RX
802.11b	1TX,1RX
802.11g	2TX,2RX
802.11n (HT20)	2TX,2RX
802.11n (HT40)	2TX,2RX
802.11ac (VHT20)	2TX,2RX
802.11ac (VHT40)	2TX,2RX
802.11ac (VHT80)	2TX,2RX
802.11ax (HE20)	2TX,2RX
802.11ax (HE40)	2TX,2RX
802.11ax (HE80)	2TX,2RX

3. The EUT contains following accessory.

Product	Brand	Model	Description
			2.4GHz: 2.02dBi
Dipole Antenna 1	SparkLAN	AD-103AG	5GHz: 2.03dBi
			RP-SMA
			2.4GHz: 3.14dBi
Dipole Antenna 2	SparkLAN	AD-302N	5GHz: 2.73dBi
			RP-SMA
			2.4GHz: 3.14dBi
Dipole Antenna 3	SparkLAN	AD-303N	5GHz: 3.24dBi
			RP-SMA

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 3.0



Page : 9 of 12

Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### 4.2. Description of Available Antennas

Ant. No.	Transmitter Circuit	Brand Name	Model Name	Ant. Type	Maximum Gain (dBi)	Remark
1	Chain (0)+(1)	SparkLAN	AD-103AG	Dipole	2.4GHz: 2.02 5GHz: 2.03	Length of Antenna cable:150mm
2	Chain (0)+(1)	SparkLAN	AD-302N	Dipole	2.4GHz: 3.14 5GHz: 2.73	Connector type of Antenna cable: I-
3	Chain (0)+(1)	SparkLAN	AD-303N	Dipole	2.4GHz: 3.14 5GHz: 3.24	PEX/MHF4 to RP- SMA(F)

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.



Page : 10 of 12 Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### 5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure								
Frequency Range (MHz)	Averaging Time  E 2,  H 2 or S (minutes)							
0.3-1.34	614	1.63	*100	30				
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

Note 1: f = frequency in MHz, \* means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

 $S=(P*G)/4\pi R^2$ 

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator <math>R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Page : 11 of 12 Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### 6. Radio Frequency Radiation Exposure Evaluation

### **Non-Beamforming mode**

### **Bluetooth EDR**

Evaluation Frequency	Max. Average power	Antenna Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2402 ~ 2480	6.40	3.14	9.54	8.995	0.0018	1

### **Bluetooth LE**

Evaluation Frequency	Max. Average power	Antenna Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2402 ~ 2480	6.63	3.14	9.77	9.484	0.0019	1

### WLAN 2.4GHz

Evaluation	Max. Average	Directional	Max.	Max.	Power density @	Limit
Frequency	power	Gain	EIRP	EIRP	20 cm	Dillit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2412 ~ 2462	20.74	6.15	26.89	488.652	0.097	1

### **WLAN 5GHz**

Evaluation Frequency	Max. Average power	Directional Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
5180 ~ 5240	18.49	6.25	24.74	297.852	0.059	1
5260 ~ 5320	18.38	6.25	24.63	290.402	0.058	1
5500 ~ 5720	18.40	6.25	24.65	291.743	0.058	1
5745 ~ 5825	18.45	6.25	24.70	295.121	0.059	1

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 3.0



Page : 12 of 12 Issued date : Mar. 18, 2021

FCC ID : RYK-WNFB266AXIBT

### **Beamforming mode**

### WLAN 2.4GHz

Evaluation Frequency	Max. Average power	Directional Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2412 ~ 2462	20.63	6.15	26.78	476.431	0.095	1

### **WLAN 5GHz**

Evaluation Frequency	Max. Average power	Directional Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
5180 ~ 5240	17.85	6.25	24.10	257.040	0.051	1
5260 ~ 5320	17.90	6.25	24.15	260.016	0.052	1
5500 ~ 5720	17.91	6.25	24.16	260.615	0.052	1
5745 ~ 5825	17.86	6.25	24.11	257.632	0.051	1

#### Note:

- 1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
- 2. Max. EIRP (mW) =  $10^{(\text{Max. EIRP (dBm)}/10)}$
- 3. Power density (mW/cm<sup>2</sup>) = Max. EIRP (mW) / [  $4 \times \pi \times (\text{calculated distance})^2$  ], the calculated distance is 20 cm.

### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

### **END OF REPORT**