

Radio Frequency Exposure Evaluation Report

For: Rivian Automotive

Brand: Rivian Automotive

Marketing Name: Autonomy Experience Module 2.0/ AXM 2.0

Model Name: AXM 2.0

Product Description: Autonomy Experience Module

FCC ID: 2AW3A-2NAT23AXM IC: 26958-2NAT23AXM

Applied Rules and Standards: CFR Part Part1 (1.1307 &1.1310), Part 2 (2.1091), FCC KDB 447498 D01 General RF Exposure Guidance v06 ISED RSS-102 Issue 6

Report number: EMC_RIVIA_058_23001_RF_Exposure_Rev2

DATE: 2024-04-16



CETECOM Inc.

411 Dixon Landing Road ◆ Milpitas, CA 95035 ◆ U.S.A. Phone: + 1 (408) 586 6200 ◆ Fax: + 1 (408) 586 6299 ◆ E-mail: info@cetecom.com ◆ <u>http://www.cetecom.com</u> *CETECOM* Inc. is a Delaware Corporation with Corporation number: 2905571

© Copyright by CETECOM

TABLE OF CONTENTS

1	Assessment	
2	2 Administrative Data	4
	2.1 Identification of the Testing Laboratory Issuing the EMC Test Report	
	2.2 Identification of the Client	
	2.3 Identification of the Manufacturer	4
3	B Equipment under Assessment	5
	3.1 EUT Specifications	5
4	RF Exposure Limits and FCC and ISED Basic Rules	6
	FCC	6
	ISED RSS 102	6
5	5 Evaluations	7
5.	5.1 Analysis of RF Exposure	7
5.	5.2 FCC RF Exposure (Standalone)	7
5.	5.3 ISED RF Exposure (Standalone)	8
5.	5.4 RF Exposure Test Exemptions for Simultaneous Transmission Sources	9
6	8 Revision History	10



Test Report #:	EMC_RIVIA_058_23001_RF_Exposure_	_Rev2	FCC ID: 2AW3A-2NAT23AXM
Date of Report	2024-04-16	Page 3 of 10	IC: 26958-2NAT23AXM

1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 &1.1310), Part 2 (2.1091) and ISED standard RSS-102 issue 6 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant).

In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and ISED rule parts based on available specifications for worst-case conditions at 20 cm distance to the body.

Company	Description	Host Model #	Module Model #
Rivian Automotive	Autonomy Experience Module	AXM 2.0	-

Responsible for the Report:

npliance (Senior E	EMC Engineer)	
ection	Name	Signature
1	npliance (Senior E ection	npliance (Senior EMC Engineer) ection Name

The test results of this test report relate exclusively to the test item specified in Section3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.



2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Issa Ghama
Responsible Project Leader:	Rami Saman

2.2 Identification of the Client

Client Firm/Name:	Rivian Automotive, LLC
Street Address:	607 Hansen Way
City/Zip Code	Palo Alto, CA 94304
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	
Manufacturers Address:	Same as Client
City/Zip Code	
Country	



3 Equipment under Assessment

3.1 EUT Specifications

Product Description:	Autonomy Experience Module						
Model Name :	AXM 2.0						
HW Version :	D						
SW Version :	42						
FCC-ID :	2AW3A-2NAT23AXM						
IC:	26958-2NAT23AXM						
Contains FCC ID :	N/A						
Contains IC:	N/A						
Bands/Modes Supported	Cell QIPALAS5-AM: GSM: 850MHz, 1900MHz UMTS: II, IV, V LTE 2, 4, 5, 7, 12, 13, 66 Wi-Fi & Bluetooth Modules VPYLB2AJ internal: Wi-Fi 2.4GHz, 5GHz - UNII-1 and UNII- 3, EDR/BDR, BLE. 2VPYLB1TA External: Wi-Fi 2.4GHz, 5GHz - UNII-1/2A,C /3 GPS Modules Model Name : u-blox M8 concurrent GNSS module Model Number : NEO-M8						
Other Radios included in the device	N/A						
Power Supply/ Rated Operating Voltage Range	9 VDC – 16 VDC						
Operating Temperature Range	-30° to 45° C						
Sample Revision	☑Production □ Pre-Production						
EUT Dimensions	280mm x 230mm x 150mm						
Weight	5400 grams						
EUT Diameter	■ < 60 cm						
Note: The information of the EUT specifications in the table above is provided by the client.							



4 RF Exposure Limits and FCC and ISED Basic Rules

FCC

4.1.1 § 2.1093(c)(1)

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than ERP20cm in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

$$P_{th}(\text{mW}) = ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$$

4.1.2 § 2.1093(c)(2)

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

4.1.3 § 1.1307(b)(3)(ii)(B)

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

ISED RSS 102

4.1.4 Clause 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

• below 20 MHz and the source-based, time-averaged maximum EIRP. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

• at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 4.49/f0.5 W (adjusted for tune-up tolerance), where f is in MHz;

• at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

• at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10-2 f 0.6834$ W (adjusted for tune-up tolerance), where *f* is in MHz;

• at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived



5 Evaluations

5.1 Analysis of RF Exposure

Duty Cycle

The table below illustrates the highest possible duty cycle for each type of radio during operation.

Mode	Duty Cycle	Duty Cycle Correction [dBm]
LTE	1:1	0
WCDMA	1:1	0
GSM	1:2	-3
WLAN	1:1	0

5.2 FCC RF Exposure (Standalone)

Radio	Tech-Band	Freq-Low _[GHz]	Pwr _[dBm]	Pwr _[dBm] corrected by Duty Cycle	Cable Loss (dBm)	Ant-G _[dBi]	EIRP _[W]	ERP _[W]	FCC 2.1093(c)(1) Pth _{[mW] =} ERP _{20cm}	P/P _{th} ratio
	LTE 5	0.8290	23.19	23.19	2.30	2.52	0.219	0.134	1691.16	0.0790
	GSM850	0.8242	32.38	29.37	2.30	2.52	0.910	0.555	1681.37	0.3298
	UMTS V	0.8264	24.41	24.41	2.30	2.52	0.290	0.177	1685.86	0.1050
	LTE 2	1.8550	23.22	23.22	3.56	3.59	0.211	0.129	3060.00	0.0421
	GSM1900	1.8502	29.64	26.63	3.56	3.59	0.463	0.282	3060.00	0.0923
Cellurlar	UMTS II	1.8524	24.45	24.45	3.56	3.59	0.281	0.171	3060.00	0.0559
	LTE 4	1.7150	23.07	23.07	3.47	3.33	0.196	0.120	3060.00	0.0391
	UMTS IV	1.7124	24.35	24.35	3.47	3.33	0.264	0.161	3060.00	0.0525
	LTE 7	2.5050	23.29	23.29	4.34	4.63	0.228	0.139	3060.00	0.0454
	LTE 12	0.7040	23.41	23.41	2.13	1.54	0.191	0.117	1436.16	0.0935
	LTE 13	0.7820	23.18	23.18	2.30	1.37	0.168	0.102	1595.28	0.0768
	LTE 66	1.7150	23.16	23.16	3.47	3.33	0.200	0.122	3060.00	0.0399
Radio	Tech-Band	Freq-Low _[GHz]	Pwr _[dBm]	Pwr _[dBm] corrected by Duty Cycle	Cable Loss (dBm)	Ant-G _[dBi]	EIRP _[W]	ERP _[W]	FCC 2.1093(c)(1) Pth _{[mW] =} ERP _{20cm}	P/P _{th} ratio
BL	EDR	2.4020	-1.14	-1.14	3.80	2.19	0.0005	0.0003	3060.00	0.0001
ы	LE	2.4020	-1.13	-1.13	3.80	2.19	0.0005	0.0003	3060.00	0.0001
WI AN	802.11n HT20	2.4120	21.87	21.87	3.80	5.20	0.2123	0.1294	3060.00	0.0423
(Internal)	802.11ax HE80	5.1800	15.99	15.99	6.20	6.77	0.0453	0.0276	3060.00	0.0090
(internal)	802.11ax HE20	5.7450	15.98	15.98	6.60	4.85	0.0265	0.0161	3060.00	0.0053

Radio	Tech-Band	Freq-Low _[GHz]	Pwr _[dBm]	Pwr _[dBm] corrected by Duty Cycle	Cable Loss (dBm)	Ant-G _[dBi]	EIRP _[W]	ERP _[W]	FCC 2.1093(c)(1) Pth _{[mW] =} ERP _{20cm}	P/P _{th} ratio
	802.11b	2.4020	18.93	18.93	3.50	5.17	0.1148	0.0700	3060.00	0.0229
	802.11ax HE20	5.1800	18.86	18.86	5.49	7.58	0.1245	0.0759	3060.00	0.0248
(Extornal)	802.11ax HE20	5.2600	18.99	18.99	5.40	7.58	0.1309	0.0798	3060.00	0.0261
(External)	802.11ax HE20	5.5000	18.99	18.99	5.90	8.75	0.1528	0.0931	3060.00	0.0304
	802.11ax HE20	5.7450	18.99	18.99	5.75	8.43	0.1469	0.0895	3060.00	0.0293

Conclusion:

• The maximum RF emissions from this equipment fulfills the RF exclusion threshold limits for separation distance between the antenna and the human body greater than 20 cm. No RF Exposure evaluation is required.



ISED RF Exposure (Standalone) 5.3

								RF Exposure				
		-						RSS-102 2.5.2 D>20 cm (300 ≤ Freq < 6000 M				
Radio	Tech-Band	Freq-Low [MHZ]	Pwr _[dBm]	Pwr _[dBm] corrected by Duty Cycle	Cable Loss (dBm)	Ant-G [dBi]	EIRP _[W]	Exemption limit for Routine Evaluation	Exemption (Y/N)			
	LTE 5	829.00	23.19	23.19	2.30	2.52	0.22	1.29	Yes			
	GSM850	824.20	32.38	29.37	2.30	2.52	0.91	1.29	Yes			
	UMTS V	826.40	24.41	24.41	2.30	2.52	0.29	1.29	Yes			
	LTE 2	1855.00	23.22	23.22	3.56	3.59	0.21	2.24	Yes			
	GSM1900	1850.20	29.64	26.63	3.56	3.59	0.46	2.24	Yes			
Collular	UMTS II	1852.40	24.45	24.45	3.56	3.59	0.28	2.24	Yes			
Cellulai	LTE 4	1715.00	23.07	23.07	3.47	3.33	0.20	2.13	Yes			
	UMTS IV	1712.40	24.35	24.35	3.47	3.33	0.26	2.12	Yes			
	LTE 7	2505.00	23.29	23.29	4.34	4.63	0.23	2.75	Yes			
	LTE 12	704.00	23.41	23.41	2.13	1.54	0.19	1.16	Yes			
	LTE 13	782.00	23.18	23.18	2.30	1.37	0.17	1.24	Yes			
	LTE 66	1715.00	23.16	23.16	3.47	3.33	0.20	2.13	Yes			
Radio	Tech-Band	Freq-Low [MHZ]	Pwr _[dBm]	Pwr _[dBm] corrected by Duty Cycle	Cable Loss (dBm)	Ant-G [dBi]	EIRP _[W]	Exemption limit for Routine Evaluation	Exemption (Y/N)			
рт	EDR	2402.00	-1.14	-1.14	3.80	2.19	0.001	2.68	Yes			
ы	LE	2402.00	-1.13	-1.13	3.80	2.19	0.001	2.68	Yes			
	802.11n HT20	2412.00	21.87	21.87	3.80	5.20	0.212	2.68	Yes			
WLAN	802.11ax HE80	5180.00	10.50	10.50	6.20	6.77	0.013	4.53	Yes			
	802.11ax HE20	5745.00	15.98	15.98	6.60	4.85	0.026	4.86	Yes			
Radio	Tech-Band	Freq-Low [MHZ]	Pwr _[dBm]	Pwr _[dBm] corrected by Duty Cycle	Cable Loss (dBm)	Ant-G [dBi]	EIRP _[W]	Exemption limit for Routine Evaluation	Exemption (Y/N)			
	802.11b	2402.00	18.93	18.93	3.50	5.17	0.115	2.68	Yes			
	802.11ax HE20	5180.00	11.70	11.70	5.49	7.58	0.024	4.53	Yes			
WLAN	802.11ax HE20	5260.00	11.50	11.50	5.40	7.58	0.023	4.57	Yes			
	802.11ax HE20	5500.00	18.99	18.99	5.90	8.75	0.153	4.71	Yes			
	802.11ax HE20	5745.00	18.99	18.99	5.75	8.43	0.147	4.86	Yes			

Conclusion:

The maximum RF emissions from this equipment fulfills the RF exclusion threshold limits for separation • distance between the antenna and the human body greater than 20 cm. No RF Exposure evaluation is required.



IC: 26958-2NAT23AXM

5.4 <u>RF Exposure Test Exemptions for Simultaneous Transmission Sources</u>

- Theoretically, the worst case of simultaneous transmission operating at the highest output power mode, within the nearest frequency bands.
- The worst case of simultaneous transmission calculation : GSM850 + (Internal) WLAN 802.11ax HE20 (2.45 GHz) + (External) WLAN 802.11ax HE20 (5GHz) + Bluetooth LE: (0.511/1681.37) + (0.0641/3060) + (0.0204/3060) + (0.000321/3060) = 0.403

Applicable Simultaneous Transmission Sources	Sum of the ratios of the applicable terms	Limit	RF Exclusion No evaluation required
GSM850 + (Internal) Wi-Fi 2.4GHz + (External) Wi-Fi 5GHz+ BLE	0.330 + 0.0423 + 0.0304 + 0.0001 = 0.403	≤ 1	Yes

Conclusion:

The sum of the fractional contributions to the applicable thresholds is less than or equal to 1, hence the multiple RF sources are exempt



Test Report #:	EMC_RIVIA_058_23001_RF_Exposure	_Rev2	FCC ID: 2AW3A-2NAT23AXM
Date of Report	2024-04-16	Page 10 of 10	IC: 26958-2NAT23AXM

6 Revision History

Date	Report Name	Changes to report	Report prepared by
2024-02-23	EMC_RIVIA_058_23001_RF_Exposure	Initial Version	Art Thammanavarat
2024-04-01	EMC_RIVIA_058_23001_RF_Exposure_Rev1	 <u>Report Revised base on TCB's review.</u> Sections 1: Corrected typo. Title Page, Secs 1 & 3.1: Updated Product Description. Section 5.2, 5.3& 5.4: Updated table. 	Art Thammanavarat
2024-04-16	EMC_RIVIA_058_23001_RF_Exposure_Rev2	 <u>Report Revised base on TCB's review.</u> 1. Sections 5.1, 5.2 & 5.3: Updated table. 2. Section 5.4: Updated Worst case. 	Art Thammanavarat

<<< The End >>>

