

## Appendix F): Antenna Requirement

### 15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### EUT Antenna:

The antenna is Internal Antenna and no consideration of replacement. The best case gain of the antenna is 2dBi.



## Appendix G): AC Power Line Conducted Emission

Test Procedure:	<p>Test frequency range :150KHz-30MHz</p> <ol style="list-style-type: none"> <li>1)The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3)The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.</li> </ol>															
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dB<math>\mu</math>V)</th></tr> <tr> <th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table> <p>* The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. NOTE : The lower limit is applicable at the transition frequency</p>		Frequency range (MHz)	Limit (dB $\mu$ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dB $\mu$ V)															
	Quasi-peak	Average														
0.15-0.5	66 to 56*	56 to 46*														
0.5-5	56	46														
5-30	60	50														

### Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


**Product** : WIFI Module

**Model/Type reference** : W2MM2510

**Temperature** : 24°C

**Humidity** : 52%


Live line:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1770	30.52	10.00	40.52	64.63	-24.11	QP	
2		0.1770	12.48	10.00	22.48	54.63	-32.15	AVG	
3		0.4785	6.06	10.00	16.06	46.37	-30.31	AVG	
4		0.4786	21.00	10.00	31.00	56.36	-25.36	QP	
5		2.4810	-2.02	9.83	7.81	46.00	-38.19	AVG	
6		2.6385	14.29	9.83	24.12	56.00	-31.88	QP	
7		3.4125	17.13	9.83	26.96	56.00	-29.04	QP	
8		3.6690	4.13	9.83	13.96	46.00	-32.04	AVG	
9		6.3150	16.71	9.84	26.55	60.00	-33.45	QP	
10		6.3195	2.29	9.84	12.13	50.00	-37.87	AVG	
11		8.4120	14.94	9.90	24.84	60.00	-35.16	QP	
12		8.4120	1.83	9.90	11.73	50.00	-38.27	AVG	



Neutral line:



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1770	15.60	10.00	25.60	54.63	-29.03	AVG	
2	0.1815	29.43	10.00	39.43	64.42	-24.99	QP	
3	0.3030	23.59	10.10	33.69	60.16	-26.47	QP	
4	0.3075	13.18	10.09	23.27	50.04	-26.77	AVG	
5	0.6134	15.04	10.05	25.09	56.00	-30.91	QP	
6 *	0.6134	12.13	10.05	22.18	46.00	-23.82	AVG	
7	1.8015	12.87	9.85	22.72	56.00	-33.28	QP	
8	1.8375	7.87	9.84	17.71	46.00	-28.29	AVG	
9	3.6600	20.10	9.83	29.93	56.00	-26.07	QP	
10	3.7770	7.62	9.83	17.45	46.00	-28.55	AVG	
11	6.2565	16.99	9.84	26.83	60.00	-33.17	QP	
12	6.3239	2.52	9.84	12.36	50.00	-37.64	AVG	

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

## Appendix H): Restricted bands around fundamental frequency (Radiated)


Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:	<p><b>Below 1GHz test procedure as below:</b></p> <ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> </ol> <p><b>Above 1GHz test procedure as below:</b></p> <ol style="list-style-type: none"> <li>Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).</li> <li>Test the EUT in the lowest channel , the Highest channel</li> <li>The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</li> <li>Repeat above procedures until all frequencies measured was complete.</li> </ol>				
Limit:	Frequency	Limit (dBμV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	

**Test plot as follows:**

**Ant 1:**

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	PK		


**Test Graph**



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	50.28	52.78	74.00	21.22	Pass	Horizontal
2	2411.9024	32.28	13.35	-43.12	104.68	107.19	74.00	-33.19	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	PK		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	49.71	52.21	74.00	21.79	Pass	Vertical
2	2411.9024	32.28	13.35	-43.12	102.09	104.60	74.00	-30.60	Pass	Vertical



Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	39.66	42.16	54.00	11.84	Pass	Horizontal
2	2412.3342	32.28	13.36	-43.12	90.40	92.92	54.00	-38.92	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	39.32	41.82	54.00	12.18	Pass	Vertical
2	2411.0388	32.28	13.35	-43.12	88.46	90.97	54.00	-36.97	Pass	Vertical

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2461.8723	32.35	13.48	-43.12	105.00	107.71	74.00	-33.71	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	50.31	52.96	74.00	21.04	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2461.7998	32.35	13.48	-43.12	102.45	105.16	74.00	-31.16	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	49.92	52.57	74.00	21.43	Pass	Vertical



Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2462.3805	32.35	13.47	-43.11	90.28	92.99	54.00	-38.99	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	41.27	43.92	54.00	10.08	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2461.2190	32.35	13.48	-43.11	88.34	91.06	54.00	-37.06	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	41.00	43.65	54.00	10.35	Pass	Vertical

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	60.20	62.70	74.00	11.30	Pass	Horizontal
2	2413.6295	32.28	13.36	-43.12	103.92	106.44	74.00	-32.44	Pass	Horizontal

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	PK		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	58.59	61.09	74.00	12.91	Pass	Vertical
2	2413.4856	32.28	13.36	-43.12	101.24	103.76	74.00	-29.76	Pass	Vertical



Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	41.64	44.14	54.00	9.86	Pass	Horizontal
2	2412.9099	32.28	13.36	-43.12	68.28	70.80	54.00	-16.80	Pass	Horizontal

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	41.01	43.51	54.00	10.49	Pass	Vertical
2	2410.6070	32.27	13.35	-43.11	67.16	69.67	54.00	-15.67	Pass	Vertical

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2463.4693	32.35	13.47	-43.11	104.49	107.20	74.00	-33.20	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	58.72	61.37	74.00	12.63	Pass	Horizontal
3	2483.7947	32.38	13.37	-43.10	63.04	65.69	74.00	8.31	Pass	Horizontal

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	PK		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2459.6220	32.34	13.49	-43.11	102.02	104.74	74.00	-30.74	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	57.79	60.44	74.00	13.56	Pass	Vertical
3	2488.2228	32.38	13.35	-43.09	62.00	64.64	74.00	9.36	Pass	Vertical



Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2463.3242	32.35	13.47	-43.11	69.66	72.37	54.00	-18.37	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	42.83	45.48	54.00	8.52	Pass	Horizontal

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2460.7835	32.35	13.48	-43.11	68.48	71.20	54.00	-17.20	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	42.34	44.99	54.00	9.01	Pass	Vertical

Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2412
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	54.72	57.22	74.00	16.78	Pass	Horizontal
2	2411.0388	32.28	13.35	-43.12	101.76	104.27	74.00	-30.27	Pass	Horizontal

Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2412
Remark:	PK		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	52.48	54.98	74.00	19.02	Pass	Vertical
2	2413.0538	32.28	13.36	-43.12	98.94	101.46	74.00	-27.46	Pass	Vertical



Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	40.46	42.96	54.00	11.04	Pass	Horizontal
2	2410.4631	32.27	13.35	-43.12	66.27	68.77	54.00	-14.77	Pass	Horizontal

Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	40.01	42.51	54.00	11.49	Pass	Vertical
2	2410.4631	32.27	13.35	-43.12	65.19	67.69	54.00	-13.69	Pass	Vertical

Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2463.1790	32.35	13.47	-43.11	102.10	104.81	74.00	-30.81	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	52.07	54.72	74.00	19.28	Pass	Horizontal

Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2463.1064	32.35	13.47	-43.11	99.35	102.06	74.00	-28.06	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	51.14	53.79	74.00	20.21	Pass	Vertical

Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2462
Remark:	AV		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2460.7109	32.34	13.48	-43.10	67.59	70.31	54.00	-16.31	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	41.81	44.46	54.00	9.54	Pass	Horizontal



Mode:	802.11 n(HT20) (6.5Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2460.6383	32.34	13.48	-43.10	66.44	69.16	54.00	-15.16	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	41.51	44.16	54.00	9.84	Pass	Vertical

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2422
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	55.97	58.47	74.00	15.53	Pass	Horizontal
2	2424.4180	32.29	13.41	-43.11	98.98	101.57	74.00	-27.57	Pass	Horizontal

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2422
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	53.75	56.25	74.00	17.75	Pass	Vertical
2	2424.5932	32.29	13.41	-43.11	95.97	98.56	74.00	-24.56	Pass	Vertical

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2422
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	41.50	44.00	54.00	10.00	Pass	Horizontal
2	2418.8110	32.29	13.39	-43.12	58.87	61.43	54.00	-7.43	Pass	Horizontal

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2422
Remark:	AV		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	40.98	43.48	54.00	10.52	Pass	Vertical
2	2418.8110	32.29	13.39	-43.12	57.59	60.15	54.00	-6.15	Pass	Vertical



Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2452
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2454.4681	32.34	13.51	-43.11	98.90	101.64	74.00	-27.64	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	55.34	57.99	74.00	16.01	Pass	Horizontal

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2452
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2449.5745	32.33	13.53	-43.11	96.66	99.41	74.00	-25.41	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	53.78	56.43	74.00	17.57	Pass	Vertical

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2452
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2449.1489	32.33	13.53	-43.12	58.89	61.63	54.00	-7.63	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	40.77	43.42	54.00	10.58	Pass	Horizontal

Mode:	802.11 n(HT40) (13.5Mbps) Transmitting	Channel:	2452
Remark:	AV		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2449.0426	32.33	13.53	-43.12	57.90	60.64	54.00	-6.64	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	40.79	43.44	54.00	10.56	Pass	Vertical

**Ant 2:**

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	PK		

**Test Graph**




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	50.80	53.30	74.00	20.70	Pass	Horizontal
2	2411.9024	32.28	13.35	-43.12	105.32	107.83	74.00	-33.83	Pass	Horizontal



Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	50.85	53.35	74.00	20.65	Pass	Vertical
2	2411.9024	32.28	13.35	-43.12	101.45	103.96	74.00	-29.96	Pass	Vertical

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	40.84	43.34	54.00	10.66	Pass	Horizontal
2	2412.1902	32.28	13.36	-43.12	90.43	92.95	54.00	-38.95	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2412
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	39.70	42.20	54.00	11.80	Pass	Vertical
2	2412.1902	32.28	13.36	-43.12	87.63	90.15	54.00	-36.15	Pass	Vertical

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2461.8723	32.35	13.48	-43.12	106.29	109.00	74.00	-35.00	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	50.37	53.02	74.00	20.98	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	PK		

### Test Graph




NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2461.8723	32.35	13.48	-43.12	101.98	104.69	74.00	-30.69	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	50.50	53.15	74.00	20.85	Pass	Vertical



Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2461.2916	32.35	13.48	-43.11	91.34	94.06	54.00	-40.06	Pass	Horizontal
2	2483.5000	32.38	13.38	-43.11	41.64	44.29	54.00	9.71	Pass	Horizontal

Mode:	802.11 b(11Mbps) Transmitting	Channel:	2462
Remark:	AV		


### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2462.4531	32.35	13.47	-43.11	88.02	90.73	54.00	-36.73	Pass	Vertical
2	2483.5000	32.38	13.38	-43.11	41.00	43.65	54.00	10.35	Pass	Vertical

Mode:	802.11 g(6Mbps) Transmitting	Channel:	2412
Remark:	PK		

### Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-43.12	61.06	63.56	74.00	10.44	Pass	Horizontal
2	2413.3417	32.28	13.36	-43.12	104.75	107.27	74.00	-33.27	Pass	Horizontal