KB-333 说明书 尺寸: 85*105MM 70G铜版纸+双面印刷

透明蓝牙键盘使用说明书



 产品参数
 工作电流1mA

 产品条件:簡単証子提出
 工作电流1mA

 磁子技术3.0
 特別中記25万25万25万

 工作物面2.04GHz 2-40GHz
 电池产业3.79㎡

 概念是6.0FS
 电池容量500mAh/排产工作电距3.14.2y

 新音系统Windows/IDS/
 工作电路1.3.14.2y

键盘指示灯

- 報告指示力

 《日本の土」

 《日本の土」

 「日本の土」

 「日本の土

连接操作步骤

1.确保课量上的电源开关表动到 "ON"位置,状态指示灯将亮起3秒, 然后熄灭。 æ **e**

3.打开爿解锁iPad,点击"设置"图标



5.发现就牙键查说备"Bluetooth Keyboard"并身面它,低牙键盘会自 动连接



2.按下配对键"FN+C",亚牙指示灯 将会闪烁

...

4.在设置菜单中,点击"篮牙"菜单,并 打开罐牙开关,IPad会自动搜索器牙 建盘设备



等光 养育技术。如使2.64 14.356.17年代,用用 等于他均均有地质色"包括"度为效果让它" 24.356.17年代,用用 等于电路控制设施。"包括"度用的现象规定" 24.356.20年代,自分电路控制设施。"包括"原用的现象规定" 24.356.20年代,自然中的值用 "设置的显而" 20.64可用处理。 25.00年代有工程的显示。

多媒体功能键 ☆ 返回主页 144 上一曲 ※+ 英度+

Q	接索	►II	指法/暂停	8	WIFF
D)	全流	>>	下一曲	Ø,	触摸板开/关
Ð	复制	4-	市里-	233	屏幕设盘
묩	粘贴	4+	容量+	0	语言切换
У.	剪切	*-	亮度-	Fn	FN复合功能

PIH-C 都开展労働連点記述成式 PIH-C 一次の系統;
PIH-Command+ グラ 景風/密用敏度功能 PIH-Commond+ グラ 景風/密用敏度功能 PIH-C 一分の系統;
PIH-C 一分の系統;
PIH-文称・音 名言切換 注:切換成が編子盤対接/円二次

李**幼模式**. 第1档,荷竹背光英度,灯泡腿 **管** 按住,再接一下上腿 【】=英度加; 灯泡器 ^{**} 按住再按一下下键 【】=英度减;

通道切换 PN-11/I/可任电切除三个苗牙透接通道,Power直打常第三砂城功。即可同时记忆 珠族三个苗牙设备;

完电 当电池电量低的,他电量指示打会不新闪烁,这时是始刻也充电 1.将VSRA版作战场推接到现在上的农电阻口。 4.可以SRAK机能在现象中最近起来的电路以SRAT(电等波影響不包括)。 3.眼意先电过程中,光电能示灯会长光,先周和自动地灭。

节能模式

→ 沸动手指	移动光标	· 學指較市	鼠标左键
・ 単指決建双 击不松拖动	左键流中 目标拖动	00 选中双指联击	鼠标右键
-₩- 双指垂直/ 水平移动	液轮霉直/ 水平液动	0000 四指数击	截图
三指同时	最近任务 窗口切英	質問 三指同时 向下移动	显示应用结构图
三指同时 左/右滑动	切袋应用		

iOS 16系统触摸板手势

iOS 16 量标功能开启:"设置"---"辅助功能"----"触控"---"辅助触控"---"打

Transparent wireless keyboard instruction manual



Product parameter
Product parameter
Product have Transport without sproof
Newson works 130
Service from 500 fro

Keyboard indicator

Queen construct to

Construct to the construct to target construct to

construct the construction to target construct to

construct the construction to the dataset between construction to

construct the construction to the construction and account of the

construction construction to the construction of the

construction construction construction construction

construction construction construction

construction construction

construction construction

construction construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

construction

constructi

Ensure that the power writch CNI the leykcard 2, Pross the pairing key FN+C, and the sides so the Chi position. The status indicator will be on for 3 seconds and then ell. Histoch indicator will blok.



Connection procedure



...





Multimedia function key

⇧	Return to main page	144	Previous song	*+	Brightness +
Q	search	►II	Play/pause	8	Lock screen
	select all	PPI	Next song	65°	Touch pad on/off
0	сору	4-	Volume-	520	On-screen keyboard
뎰	paste	4	Volume +	0	Language switching
χ,	shear	*-	Brightness -	Fn	FN composite function

⇧	Return to main page	144	Previous song	*+	Brightness +
Q	search	►II	Play/pause	ð	Lockscreen
	select all	PPI	Next song	650	Touch pad on/off
0	сору	4-	Volume-	E20	On-screen keyboard
뎰	paste	4	Volume +		Language switching
χ,	shear	*-	Brightness •	Fn	RN composite

PN-CF: Excepted Myritech consisting or gaining more PN-CF Concerneds (67 The cost function is disabled or enabled PN-CF Cost (67 The cost function is disabled or enabled PN-PN-CF Cost (67 The Cost function is disabled PN-PN-CF Cost (67 The Cost funct

Igna key 3 backlight, and press are again to menually switch the backlight color of managed and are Bedight exacts (budget less)

Lipinals bits not find-bedge and priors

again to minusky within the bodget and prior

Annotalising recolously priors (without that it is a bodget and in the bodget and prior

Annotalising recolously priors) of bodget and or bodget bedget and recolously it is externed a window.

Anto id a priors of priors priors and order in the bodget is not priors.

Anto id a priors of priors and priors and order in the bodget is not cross for butter against a well-in the bodget is not cross for butter against a well-in the bodget is not cross for butter against a well-in the bodget is not cross for the bodget is not cross

Manual modes that is, 1 give, adjust the highly treas of the level spit, both key to be supply the spit of the public than the spit to be spit

Channel switching
The 100 can enhance which these blessoch connection channels. If the Power blue light is steady
on for 3 seconds, it can connect three Bluetosth-devices sins binecostly.

When the Sating power is jow, the joy power indicate will see glathing, then you need to charge the solicitiest.

Connected to cassing is served of the USB casely to the charges port on the Hepbasch.

Connected to the USB casely to provide or to be connected to the connected power celeptors are cell-solicities.

Country to example precess of the suplement. The chargest prefetcher will be on fit or large three and will be assembled by engineered after 1 cell.

Energy-saving mode

If there is respectful to the lagrant of the 10 modes, it will admissionly when the sleep mode and if the Limit is better of CP the representation in the lagrant of the Limit is secured. When the lagrant is used by so ofly need to press any key and used for stand of a secured. Then the implement will be verbinn up and extremitionly commissed to the Ellustration of the Konney Annual CP.

Pay attention

1. When not is use fire a largitime, we recommend surring of the keyboard to effect the battery file
2. In cases to close a larger training file, it is recommended to charge the subcase only when the
power larger lattering, it is better to despite the legisland for the set has that it have con-

Touch Pad	Gestures on	105 16	
Side Singer	Move cursor	C Single Separapping	Left mouse bellen
Sánglo Éngor quách double Click relifaces chag	Modes Target trap	OO Select double finger tup	Right mouse button
Double finger sertical / Horizontal movement	The roller is vertical / Hartcontal roll	COCC Transfer topping	screenshot
Trace-larger simultaneity Upward monoment	Recent mission Window switching	Three-finger sinsultaneity Hose stone	Display application thumbroal
Three-lings simulated by	Switching application		

iOS 16 mouse function open: "Settings" - "assist" - "touch" - "auxiliary touch" - "open"

FCC Caution:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception,

which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different

from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.