

Applicant:	Logitech Far East Ltd.
FCC ID:	JNZF00007
RF Exposure Requirements ( FCC KDB 680106 D01 v03)	
Requirements	Statements
Power transfer frequency is less than 1 MHz	Yes. Operating frequency is 127.795 kHz for the charging pad and charging stand. Operating frequency is 326.5 kHz for Apple watch charging module.
(b) Output power from each primary coil is less than or equal to 15 watts.	There are three coils that can operate simultaneously. <ul style="list-style-type: none"> <li>Phone Charging Coils: The maximum power per coil is 10W for two of the coils</li> <li>Apple Watch Charging coil: The Maximum Power is 5W.</li> </ul> The total maximum power is 25 watts across all three coils.
(c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	The three coils can be active simultaneously but each coil is charging a separate device. Each coil is only capable of charging a single device so for each coil there is only one primary and one secondary coil.
(d) Client device is placed directly in contact with the transmitter.	Yes. The client device is placed directly in contact with the transmitter. The device is a charging pad which the client device is placed (close coupling).
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes.
(f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes. Please refer to RF Exposure report.