

RF Exposure Evaluation Report

APPLICANT	: Shenzhen Tinno Mobile Technology Corp.
EQUIPMENT	: HONOR CHOICE TNHCHOP Pencil
BRAND NAME	: TNHCHOP
MODEL NAME	: MAL-HP00
FCC ID	: XD6MAL-HP00
STANDARD	: 47 CFR PART 2.1093
	FCC KDB 447498 D01 v06

The product evaluation date was started from Jan. 09, 2024 and completed on Jan. 09, 2024. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Si Zhang



Approved by: Si Zhang

Sporton International Inc. (Shenzhen) 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China



Table of Contents

1.	ADMINISTRATION DATA	4
	1.1. Testing Laboratory	4
2.	DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3.	MAXIMUM RF TUNE UP POWER AMONG PRODUCTION UNITS	6
4.	RF EXPOSURE EVALUATION	6



Report No. : FA3D0505

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA3D0505	Rev. 01	Initial issue of report	Feb. 04, 2024



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory					
Test Firm	Sporton International Inc. (Shenzhen)				
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595				
Toot Site No	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.		
Test Site No.	SAR01-SZ	CN1256	421272		

Applicant			
Company Name Shenzhen Tinno Mobile Technology Corp.			
Address	27-001,South Side of Tianlong Mobile Headquarters Building,Tongfa South Road,Xili Community, Xili Street,Nanshan District, Shenzhen City,Guangdong Province,PRC.		

Manufacturer			
Company Name	Shenzhen Tinno Mobile Technology Corp.		
Address	27-001,South Side of Tianlong Mobile Headquarters Building,Tongfa South Road,Xili Community, Xili Street,Nanshan District, Shenzhen City,Guangdong Province,PRC.		



SPORTON LAB. RF Exposure Evaluation Report

2. Description of Equipment Under Test (EUT)

Product Feature & Specification			
EUT Type	HONOR CHOICE TNHCHOP Pencil		
Brand Name	ТИНСНОР		
Model Name	MAL-HP00		
FCC ID	XD6MAL-HP00		
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz		
Mode	Bluetooth LE		
Antenna Type	Bluetooth : FPC Antenna		
Antenna Gain	Bluetooth: gain 0.8 dBi		
EUT Stage	Production Unit		
Demosily			

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

 The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF Tune Up power among production units

<Bluetooth>

Mode	Maximum Average Power (dBm)
Bluetooth LE	4.8

4. RF Exposure Evaluation

Mode	Maximum Average Power (dBm)
Bluetooth LE	4.8

Note:

- Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:
 - [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f}(GHz)] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - \cdot f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
4.8	< 5	2.48	1.0

Conclusion:

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.0 which is \leq 7.5 for 10-g extremity SAR, extremity SAR testing is not required, and complied with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (4.0 W/kg for extremity SAR) specified in FCC 47 CFR part 2 (2.1093).

