

Product Descriptions(Application/Features/Specification)

The EUT is a RF Keyboard. A major technical descriptions of EUT is described as following:

A .Operation Frequency	CH1:26.995 and CH2:27.195MHz
B. Modulation Type	FSK
C. Antenna Designation	Integral
D. Number Of Channel	2
E. Channel Spacing	100 KHz
F. Output Power	-41.91dBm
G.Operation Methodology	<p>The EUT encoder generates a pulse code serially transmit (typical designation) into the modulator(or called as mixer) stage in circuit. This pulse signal mixed with the carrier at modulator(mixer) stage by way of FSK mode frequency modulation. The modulation depth is designed such as $\pm 5\text{KHz}$ in this application, that means the pulse(may be at high level state or low level state) will trigger the oscillator to generate a frequency at a specified fundamental frequency $+5\text{KHz}$ or -5KHz, depended on the designation. For example, if the carrier frequency defined as fundamental frequency $+5\text{KHz}$ at high level state, then the alternative carrier frequency will be fundamental frequency -5KHz at low level state.</p> <p>Then the modulator(mixer) will output a modulated signal into RF amplifier stage and finally to the transmit antenna.</p>

Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual (Attachment - **E.**)