

FCC 47 CFR MPE REPORT

Shenzhen Proscenic Technology Co., Ltd

Robot Vacuum Cleaner

Model Number: LDS M6 PRO

FCC ID: 2ARZX-LDS-M6PRO

Prepared for:	Shenzhen Proscenic Technology Co., Ltd
	8F, Building 5A, Tusincere Park Longgang District, Shenzhen,
	Guangdong Province, shenzhen China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2010165
Date of Test:	Oct. 10~23, 2020
Date of Report:	Oct. 26, 2020

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	19.82	95.94	19±1	1	1.259
	2437	19.93	98.40	19±1	1	1.259
	2462	20.72	118.03	20±1	1	1.259
IEEE 802.11g	2412	18.73	74.65	18±1	1	1.259
	2437	18.94	78.34	18±1	1	1.259
	2462	19.76	94.62	19±1	1	1.259
IEEE 802.11n HT20	2412	18.82	76.21	18±1	1	1.259
	2437	19.00	79.43	19±1	1	1.259
	2462	19.68	92.90	19±1	1	1.259
IEEE 802.11n HT40	2422	18.97	78.89	18±1	1	1.259
	2437	18.63	72.95	18±1	1	1.259
	2425	19.05	80.35	19±1	1	1.259

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
		(dBi)	(Linear)			
2.4G Band						
2.4G Wi-Fi	21	1	1.259	0.0315	1	Compiles

End of Test Report

