

# TEST REPORT

**Applicant:** Guilin Zhishen Information Technology Co., Ltd.  
**Address:** 09 Huangtong Road, Tieshan Industrial Zone,  
Qixing District, Guilin, Guangxi, China.  
**Equipment Type:** SMOOTH-Q4  
**Model Name:** SM117  
**Brand Name:** ZHIYUN  
**FCC ID:** 2AIHFZYSM117  
**Test Standard:** 47 CFR Part 2.1093  
KDB 447498 D04  
**Test Date:** Apr. 14, 2022 ~ Apr. 27, 2022  
**Date of Issue:** May 23, 2022

## ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie zhu

**Checked by:** Zong Liyao

**Approved by:** Wei Yanquan  
(Chief Engineer)

*Julie zhu*

*Liyao. Zong*

*Wei Yanquan*

**Revision History**

| <u>Version</u> | <u>Issue Date</u>   | <u>Revisions Content</u> |
|----------------|---------------------|--------------------------|
| <u>Rev. 01</u> | <u>May 23, 2022</u> | <u>Initial Issue</u>     |

**TABLE OF CONTENTS**

|     |                                                          |   |
|-----|----------------------------------------------------------|---|
| 1   | GENERAL INFORMATION .....                                | 3 |
| 1.1 | Identification of the Testing Laboratory .....           | 3 |
| 1.2 | Identification of the Responsible Testing Location ..... | 3 |
| 2   | PRODUCT INFORMATION .....                                | 4 |
| 2.1 | Applicant Information.....                               | 4 |
| 2.2 | Manufacturer Information .....                           | 4 |
| 2.3 | Factory Information .....                                | 4 |
| 2.4 | General Description for Equipment under Test (EUT) ..... | 4 |
| 2.5 | Ancillary Equipment.....                                 | 4 |
| 2.6 | Technical Information .....                              | 5 |
| 3   | SUMMARY OF TEST RESULT .....                             | 6 |
| 3.1 | Test Standards .....                                     | 6 |
| 4   | DEVICE CATEGORY AND LEVELS LIMITS .....                  | 7 |
| 5   | ASSESSMENT RESULT .....                                  | 9 |
| 5.1 | Output Power .....                                       | 9 |
| 5.2 | Conclusion.....                                          | 9 |

# 1 GENERAL INFORMATION

## 1.1 Identification of the Testing Laboratory

|              |                                                                                                                          |
|--------------|--------------------------------------------------------------------------------------------------------------------------|
| Company Name | Shenzhen BALUN Technology Co., Ltd.                                                                                      |
| Address      | Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China |
| Phone Number | +86 755 6685 0100                                                                                                        |

## 1.2 Identification of the Responsible Testing Location

|                           |                                                                                                                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Location             | Shenzhen BALUN Technology Co., Ltd.                                                                                                                                                                     |
| Address                   | Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China                                                                                |
| Accreditation Certificate | The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.                                                                        |
| Description               | All measurement facilities used to collect the measurement data are located at Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China |

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

|           |                                                                                      |
|-----------|--------------------------------------------------------------------------------------|
| Applicant | Guilin Zhishen Information Technology Co., Ltd.                                      |
| Address   | 09 Huangtong Road, Tieshan Industrial Zone, Qixing District, Guilin, Guangxi, China. |

### 2.2 Manufacturer Information

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Manufacturer | Guilin Zhishen Information Technology Co., Ltd.                                      |
| Address      | 09 Huangtong Road, Tieshan Industrial Zone, Qixing District, Guilin, Guangxi, China. |

### 2.3 Factory Information

|         |                                                                                      |
|---------|--------------------------------------------------------------------------------------|
| Factory | Guilin Zhishen Information Technology Co., Ltd.                                      |
| Address | 09 Huangtong Road, Tieshan Industrial Zone, Qixing District, Guilin, Guangxi, China. |

### 2.4 General Description for Equipment under Test (EUT)

|                                           |           |
|-------------------------------------------|-----------|
| EUT Name                                  | SMOOTH-Q4 |
| Model Name Under Test                     | SM117     |
| Series Model Name                         | N/A       |
| Description of Model name differentiation | N/A       |
| Hardware Version                          | V1.0      |
| Software Version                          | N/A       |
| Dimensions (Approx.)                      | N/A       |
| Weight (Approx.)                          | N/A       |

### 2.5 Ancillary Equipment

|                       |                      |                |
|-----------------------|----------------------|----------------|
| Ancillary Equipment 1 | Battery              |                |
|                       | Brand Name           | N/A            |
|                       | Model No.            | 112637-1200mAh |
|                       | Serial No.           | N/A            |
|                       | Capacity             | 1200 mAh       |
|                       | Rated Voltage        | 7.7 V          |
|                       | Limit Charge Voltage | 8.8 V          |

## 2.6 Technical Information

|                                   |                 |
|-----------------------------------|-----------------|
| Network and Wireless connectivity | Bluetooth (BLE) |
|-----------------------------------|-----------------|

The requirement for the following technical information of the EUT was tested in this report:

|                   |                                          |                   |
|-------------------|------------------------------------------|-------------------|
| Operating Mode    | Bluetooth                                |                   |
| Frequency Range   | Bluetooth                                | 2400 ~ 2483.5 MHz |
| Antenna Type      | Bluetooth                                | Ceramic Antenna   |
| Exposure Category | General Population/Uncontrolled Exposure |                   |
| EUT Stage         | Portable Device                          |                   |

### 3 SUMMARY OF TEST RESULT

#### 3.1 Test Standards

| No. | Identity              | Document Title                                                 |
|-----|-----------------------|----------------------------------------------------------------|
| 1   | 47 CFR Part<br>2.1093 | Radiofrequency radiation exposure evaluation: portable devices |
| 2   | KDB 447498<br>D04     | KDB 447498 D04 Interim General RF Exposure Guidance v01        |

## 4 DEVICE CATEGORY AND LEVELS LIMITS

### Portable Derives:

CFR Title 47 §2.1093(b)

(b) For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

### FCC KDB 447498 Derives:

According with FCC KDB 447498 D04, Appendix B, The SAR-based exemption formula applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). The following table shows the power threshold from 5mm to 50mm.

| Power Thresholds (mW) |                                       |                                 |                                 |                                 |                                 |
|-----------------------|---------------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| Frequency (MHz)       | At separation distance of $\leq 5$ mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| 300                   | 39 mW                                 | 65 mW                           | 88 mW                           | 110 mW                          | 129 mW                          |
| 450                   | 22 mW                                 | 44 mW                           | 67 mW                           | 89 mW                           | 112 mW                          |
| 835                   | 9 mW                                  | 25 mW                           | 44 mW                           | 66 mW                           | 90 mW                           |
| 1900                  | 3 mW                                  | 12 mW                           | 26 mW                           | 44 mW                           | 66 mW                           |
| 2450                  | 3 mW                                  | 10 mW                           | 22 mW                           | 38 mW                           | 59 mW                           |
| 3600                  | 2 mW                                  | 8 mW                            | 18 mW                           | 32 mW                           | 49 mW                           |
| 5800                  | 1 mW                                  | 6 mW                            | 14 mW                           | 25 mW                           | 40 mW                           |
| Frequency (MHz)       | At separation distance of 30 mm       | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of 50 mm |
| 300                   | 148 mW                                | 166 mW                          | 184 mW                          | 201 mW                          | 217 mW                          |
| 450                   | 135 mW                                | 158 mW                          | 180 mW                          | 203 mW                          | 226 mW                          |
| 835                   | 116 mW                                | 145 mW                          | 175 mW                          | 207 mW                          | 240 mW                          |
| 1900                  | 92 mW                                 | 122 mW                          | 157 mW                          | 195 mW                          | 236 mW                          |
| 2450                  | 83 mW                                 | 111 mW                          | 143 mW                          | 179 mW                          | 219 mW                          |
| 3600                  | 71 mW                                 | 96 mW                           | 125 mW                          | 158 mW                          | 195 mW                          |
| 5800                  | 58 mW                                 | 80 mW                           | 106 mW                          | 136 mW                          | 169 mW                          |

Note:

1. Maximum power is the source-based time-average power and represents the maximum RF output power including tune-up tolerance among production units
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
4. Per KDB 447498 D04, for separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive), the threshold Pth (mW) is given by Following:

$$P_{th}(mW) = \begin{cases} ERP_{20cm}(d/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20cm}\sqrt{f}} \right)$$

- a. f(GHz) is the RF channel transmit frequency in GHz
- b. d is the separation distance (cm), The result is rounded to one decimal place for comparison
- c.  $ERP_{20cm}$  are determined by:

$$ERP_{20cm}(mW) = f(x) = \begin{cases} 2040f & 0.3GHz \leq f < 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases}$$

## 5 ASSESSMENT RESULT

### 5.1 Output Power

| Bluetooth                                                                                             |             |                |              |
|-------------------------------------------------------------------------------------------------------|-------------|----------------|--------------|
| Mode                                                                                                  | GFSK (BLE)  |                |              |
|                                                                                                       | Low Channel | Middle Channel | High Channel |
| Peak Power (dBm)                                                                                      | -2.89       | -1.07          | -5.62        |
| Antenna Gain (dBi)                                                                                    | 2.0         |                |              |
| EIRP                                                                                                  | -0.89       | 0.93           | -3.62        |
| Note: This report listed the worst case power value, please refer to RF test report for more details. |             |                |              |

### 5.2 Turn-up power

| Mode                    | EIRP Power Range (dBm) | ERP Range (dBm) |
|-------------------------|------------------------|-----------------|
| Bluetooth               | -4.0-1.0               | (-6.15)-(-1.15) |
| Note: ERP= EIRP -2.15dB |                        |                 |

### 5.3 RF Exposure Evaluation Result

| Mode      | Distance (mm) | Calculation Frequency (MHz) | Tune-up limit power (dBm) | Tune-up limit power (mW) | Threshold Value(mW) | Verdict    |
|-----------|---------------|-----------------------------|---------------------------|--------------------------|---------------------|------------|
| Bluetooth | 5             | 2440                        | 1.00                      | 1.26                     | 2.75                | Compliance |

### 5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--