



RF Exposure Evaluation Declaration

FCC ID: HD5-HONST60Q

APPLICANT: Honeywell International Inc
Honeywell Safety and Productivity Solutions

Application Type: Class II Permissive Change

Product: Wi-Fi module

Model No.: HON-ST60Q

Brand Name: Honeywell

FCC Rule Part(s): FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1-1992

Reviewed By:

Jame Yuan

(Jame Yuan)

Approved By:

Robin Wu

(Robin Wu)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1905RSU028-U8	Rev. 01	Initial Report	08-12-2019	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	Wi-Fi module
Model No.	HON-ST60Q
Brand Name	Honeywell
Wi-Fi Specification	802.11a/b/g/n/ac
Antenna Type:	Dipole Antenna
Antenna Gain:	2.44dBi for 2.4GHz and 5GHz
Frequency Range	<u>2.4GHz:</u> For 802.11b/g/n-HT20: 2412 ~ 2462 MHz For 802.11n-HT40: 2422 ~ 2452 MHz <u>5GHz:</u> For 802.11a/n-HT20/ac-VHT20: 5180~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40: 5190~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80: 5210MHz, 5290MHz, 5530MHz, 5610MHz, 5690MHz, 5775MHz
Type of Modulation	802.11b: DSSS 802.11g/a/n/ac: OFDM
Maximum Average Output Power	<u>For 2.4GHz Band:</u> 802.11b: 13.88dBm 802.11g: 13.75dBm 802.11n-HT20: 13.90dBm 802.11n-HT40: 13.78dBm <u>For 5GHz Band:</u> 802.11a: 15.82dBm 802.11n-HT20: 15.92dBm 802.11n-HT40: 14.14dBm 802.11ac-VHT20: 16.16dBm 802.11ac-VHT40: 14.33dBm 802.11ac-VHT80: 10.04dBm

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Wi-Fi module
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	E.I.R.P (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11b/g/n	2412 ~ 2462	13.90	16.34	0.0086	1
802.11a/n/ac	5180 ~ 5825	16.16	18.60	0.0144	1
Host Information (Product name: Printer, M/N: PX940)					
Bluetooth-LE	2402 ~ 2480	0.69	1.99	0.0003	1

CONCLUSION:

Both of the WLAN 2.4GHz or WLAN 5GHz Band and BLE can transmit simultaneously.

The Max Power Density at R (20 cm) = $0.0144\text{mW/cm}^2 + 0.0003\text{mW/cm}^2 = 0.0147\text{mW/cm}^2 < 1\text{mW/cm}^2$.

So the EUT complies with the requirement.

_____ The End _____