



FCC / IC Test Report

FOR:
Juniper Systems, Inc.

Model Name:
MS3

Product Description:
Ultra-rugged handheld computer with Windows 10, providing long battery life, 7-inch touchscreen display, programmable keys, 802.11ac, Bluetooth, camera

FCC ID: VSFMS3
IC ID: 7980A-MS3

Applied Rules and Standards:
47 CFR Part 15.247 (DTS)
RSS-247 Issue 2 (DTS) & RSS-Gen Issue 5

REPORT #: EMC_JUNIP-026-19001_15.247_BT_DTS

DATE: 2019-03-15



A2LA Accredited

IC recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

TABLE OF CONTENTS

1	ASSESSMENT	3
2	ADMINISTRATIVE DATA.....	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER	4
3	EQUIPMENT UNDER TEST (EUT).....	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS.....	6
3.3	ACCESSORY EQUIPMENT (AE) DETAILS.....	6
3.4	TEST SAMPLE CONFIGURATION	6
3.5	JUSTIFICATION FOR WORST CASE MODE OF OPERATION	7
4	SUBJECT OF INVESTIGATION	8
5	MEASUREMENT RESULTS SUMMARY	8
6	MEASUREMENT UNCERTAINTY	9
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING:	9
6.2	DATES OF TESTING:.....	9
7	MEASUREMENT PROCEDURES.....	10
7.1	RADIATED MEASUREMENT	10
7.2	RF CONDUCTED MEASUREMENT PROCEDURE	12
8	TEST RESULT DATA	13
8.1	MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	13
8.2	POWER SPECTRAL DENSITY.....	17
8.3	DUTY CYCLE.....	21
8.4	BAND EDGE COMPLIANCE	22
8.5	EMISSION BANDWIDTH 6 dB AND 99% OCCUPIED BANDWIDTH	27
8.6	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS	34
8.7	AC POWER LINE CONDUCTED EMISSIONS	48
9	TEST SETUP PHOTOS.....	50
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	50
11	REVISION HISTORY	51

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
Juniper Systems, Inc.	Ultra-rugged handheld computer with Windows 10, providing long battery life, 7-inch touchscreen display, programable keys, 802.11ac, Bluetooth, camera	MS3

Responsible for Testing Laboratory:

2019-03-15	Compliance	Cindy Li (EMC Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2019-03-15	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.
CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Cindy Li
Responsible Project Leader:	Sangeetha Sivaraman

2.2 Identification of the Client

Applicant's Name:	Juniper Systems, Inc.
Street Address:	1132 W 1700 N
City/Zip Code:	Logan, UT 84321
Country:	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	The same as client
Manufacturers Address:	N/A
City/Zip Code	N/A
Country	N/A

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	MS3
HW Version :	MS3_00
SW Version :	MS3_SW_00
FCC-ID:	VSFMS3
IC-ID:	7980A-MS3
HVIN:	MS3
PMN:	Mesa 3
Product Description:	Ultra-rugged handheld computer with Windows 10, providing long battery life, 7-inch touchscreen display, programable keys, 802.11ac, Bluetooth, camera
Frequency Range / number of channels:	Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
Type(s) of Modulation:	Bluetooth version 4.2, Low Energy, using Dynamic Sequence Spread Spectrum with GFSK modulation.
Modes of Operation:	Bluetooth LE in both advertising and connected mode of operation
Antenna Information as declared:	PCB Trace, 2.4dBi/Low channel, -0.1dBi/Mid channel, 1.1dBi/high channel
Max. Peak Output Power:	Conducted Power 1.82 dBm
Power Supply/ Rated Operating Voltage Range:	Battery: Vmin: 6 VDC/ Vnom: 7.3 VDC / Vmax: 7.3 VDC Charger: Vmin: 9.9 VDC/ Vnom: 12 VDC / Vmax: 15.6 VDC
Operating Temperature Range:	-20 °C to +50 °C
Other Radios included in the device:	Bluetooth BR / EDR; WIFI 802.11a/b/g/n/ac; WCDMA; LTE; GPS; RFID
Sample Revision:	☐ Prototype Unit; ☒ Production Unit; ☐ Pre-Production

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	MS3W-C01	MS3_00	MS3_SW_00	Conducted RF
2	MS3W-C03	MS3_00	MS3_SW_00	Radiated Emissions

3.3 Accessory Equipment (AE) details

AE #	Type	Model	Manufacturer	Serial Number
1	Switching power supply	PSAA30R-120	Phihong Technology	P74900943A1

3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1 + AE#1	The radio of the EUT was configured to a fixed channel transmission with highest possible duty cycle using software provided by client that is not available to the end user. The measurement equipment was connected to the 50 ohm RF port of the EUT.
2	EUT#2 + AE#1	The radio of the EUT was configured to a fixed channel with highest possible duty cycle using software provided by client that is not available to the end user.

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels with the highest possible duty cycle. For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

The output power of each mode was set to fixed level from configuration file provided by customer

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

Testing procedures are based on 558074 D01 DTS Meas Guidance v04 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(1)	Emission Bandwidth	Nominal	BTLE	■	□	□	Complies
§15.247(e) RSS-247 5.2(2)	Power Spectral Density	Nominal	BTLE	■	□	□	Complies
§15.247(b)(1) RSS-247 5.4(4)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	■	□	□	Complies
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BTLE	■	□	□	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	BTLE	■	□	□	Complies

Note1: NA= Not Applicable; NP= Not Performed.

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

9 kHz to 30 MHz	±2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	±2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	±2.3 dB (Horn Antenna)

Conducted measurement

150 kHz to 30 MHz	±0.7 dB (LISN)
-------------------	----------------

RF conducted measurement	±0.5 dB
--------------------------	---------

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

6.1 Environmental Conditions during Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 Dates of Testing:


03/11/2019 - 03/15/2019

7 Measurement Procedures

7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:


$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} - \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7.2 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 DTS Meas Guidance v04 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.
- Calculate the conducted power by taking into account attenuation of the cable and the attenuator

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8 Test Result Data

8.1 Maximum Peak Conducted Output Power

8.1.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- $RBW \geq$ DTS bandwidth
- $VBW \geq 3 \times RBW$
- $Span \geq 3 \times RBW$
- Sweep = Auto couple
- Detector function = Peak
- Trace = Max hold
- Use peak marker function to determine the peak amplitude level

8.1.2 Limits:

Maximum Peak Output Power:

- FCC §15.247 (b)(1): 1 W
- IC RSS-247: 1 W

8.1.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	GFSK Continuous fixed channel	120 VAC/Battery	Section 3.1

8.1.4 Measurement result:


Attenuation of cable and attenuator (already taken into account): 12.8 dB

Plot #	Frequency (MHz)	Actual reading (dBm)	Maximum Peak Conducted Output Power (consider path loss) (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	2402	0.22	1.34	3.74	30 (Pk) / 36 (EIRP)	Pass
2	2442	0.75	1.82	1.72	30 (Pk) / 36 (EIRP)	Pass
3	2480	0.52	1.51	2.91	30 (Pk) / 36 (EIRP)	Pass

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15


FCC ID: VSFMS3
IC ID: 7980A-MS3

8.1.5 Measurement Plots:




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8.2 Power Spectral Density

8.2.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

8.2.2 Limits:

FCC§15.247(e) & RSS-247 5.2(2)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.2.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
23° C	1	GFSK continuous fixed channel	120 VAC/Battery	Section 3.1

8.2.4 Measurement result:


Attenuation of cable and attenuator (already taken into account): 12.8 dB

Plot #	Frequency (MHz)	Actual reading (dBm/3kHz)	Maximum Power Spectral Density Power (consider path loss) (dBm/3 kHz)	PSD Adjusted for Antenna Gain (dBm/3 kHz)	Limit (dBm/3 kHz)	Result
4	2402	-14.34	-13.27	-10.87	8	Pass
5	2442	-13.9	-12.78	-12.88	8	Pass
6	2480	-14.11	-13.12	-11.72	8	Pass

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15


FCC ID: VSFMS3
IC ID: 7980A-MS3

8.2.5 Measurement Plots:



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

Plot #6

High channel

Modulation/Packet Type: BTLE




*RBW 3 kHz
*VBW 10 kHz
SWT 225 ms
Marker 1 [T1]
-14.11 dBm
2.479974359 GHz

Ref 5 dBm

*Att 5 dB

1 PK
MAXH



Date: 12.MAR.2019 17:22:16

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3


8.3 Duty cycle

8.3.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- Set the center frequency and of the instrument to the center frequency of the transmission
- Zero span
- Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value
- Detector = Peak or average

8.3.2 Measurement result



Duty cycle =66.6%

Duty cycle correction factor = $10 \cdot \log(0.668) = 1.75$ dB

8.4 Band Edge Compliance

8.4.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW $\geq 3 \times$ RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

8.4.2 Limits non restricted band:

FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5/5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=1 MHz

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8.4.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10

- *PEAK LIMIT= 74 dB μ V/m @3m =-21.23 dBm
 - *AVG LIMIT= 54 dB μ V/m @3m =-41.23 dBm
 - Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
 - Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.
- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

(b)

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

8.4.4 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	GFSK continuous fixed channel	120 VAC/Battery	Section 3.1

8.4.5 Measurement result:


Plot #	EUT operating mode	Band Edge	Band Edge Delta (dBc)	Limit (dBc)	Result
7	GFSK continuous fixed channel	Lower, Non-restricted	-54.25	20	Pass

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3


Plot #	EUT operating mode	Band Edge	Measured Value (dBm)	Corrected by duty cycle	Corrected by Antenna Gain and path loss (dBm)	Limit (dBm)	Result
8	GFSK continuous fixed channel	Upper Restricted peak	-40.53	NA	-38.14	-21.23 Peak	Pass
9	GFSK continuous fixed channel	Upper Restricted Average	-59.47	-57.66	-55.28	-41.23 AVG	Pass

8.4.6 Measurement Plots:




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8.5 Emission Bandwidth 6 dB and 99% Occupied Bandwidth

8.5.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.5.2 Limits:

FCC §15.247(a)(1) and RSS-247 5.2(1)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.5.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22° C	1	GFSK continuous fixed channel	120VAC/Battery

8.5.4 Measurement result:


Plot #	Frequency (MHz)	6 dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
10	2402	0.721	> 0.5	Pass
11	2442	0.721	> 0.5	Pass
12	2480	0.721	> 0.5	Pass

Plot #	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
13	2402	1.089	> 0.5	Pass
14	2442	1.097	> 0.5	Pass
15	2480	1.089	> 0.5	Pass

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15


FCC ID: VSFMS3
IC ID: 7980A-MS3

8.5.5 Measurement Plots:




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



8.6 Radiated Transmitter Spurious Emissions and Restricted Bands

8.6.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) = $40 \log (D/d) = 40 \log (300\text{m} / 3\text{m}) = 80\text{dB}$

8.6.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (μV/m)	Measurement Distance (m)	Field strength @ 3m (dBμV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBμV/m
88–216	150	3	43.5 dBμV/m
216–960	200	3	46 dBμV/m
Above 960	500	3	54 dBμV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74 dBμV/m

*AVG. LIMIT= 54 dBμV/m

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8.6.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
23° C	2	GFSK continuous fixed channel	120VAC


8.6.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
16-18	Low	30 MHz – 18 GHz	See section 8.5.2	Pass
19-23	Mid	9 kHz – 26 GHz	See section 8.5.2	Pass
24-26	High	30 MHz – 18 GHz	See section 8.5.2	Pass

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15


FCC ID: VSFMS3
IC ID: 7980A-MS3

8.6.5 Measurement Plots:




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3




Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report: 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3



Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8.7 AC Power Line Conducted Emissions

8.7.1 Measurement according to ANSI C63.10 (2013)

Analyzer Settings:

- RBW = 9 KHz (CISPR Bandwidth)
- Detector: Peak / Average for Pre-scan
- Quasi-Peak/Average for Final Measurements

8.7.2 Limits: §15.207 & RSS-Gen 8.8

FCC §15.207(a) & RSS-Gen 8.8

- Except as shown in paragraphs (b) and (c) of this section of the CFR, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table (1), as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

8.7.3 Test conditions and setup:

Ambient Temperature ©	EUT Set-Up #	EUT operating mode	Power line (L1, L2, L3, N)	Power Input
22	2	GFSK continuous fixed channel	Line & Neutral	110V / 60Hz

8.7.4 Measurement Result:

Plot #	Port	EUT Set-Up #:	EUT operating mode	Scan Frequency	Limit	Result
27	AC Mains	2	GFSK continuous fixed channel	150 kHz – 30 MHz	See section 8.6.2	Pass

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

8.7.5 Measurement Plots:


Plot #27

Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)
0.158000	39.15	---	65.57	26.42	500.0	9.000	L1	GND	10.7
0.170000	43.58	---	64.96	21.38	500.0	9.000	L1	GND	10.9
0.182000	43.33	---	64.39	21.06	500.0	9.000	L1	GND	10.6
0.194000	---	19.54	53.86	34.32	500.0	9.000	N	GND	10.5
0.258000	---	20.73	51.50	30.77	500.0	9.000	N	GND	10.5
0.338000	---	24.27	49.25	24.98	500.0	9.000	N	GND	10.3

(continuation of the "Final_Result" table from column 15 ...)

Frequency (MHz)	Comment
0.158000	1:14:05 PM - 3/14/2019
0.170000	1:14:09 PM - 3/14/2019
0.182000	1:14:13 PM - 3/14/2019
0.194000	1:14:52 PM - 3/14/2019
0.258000	1:14:56 PM - 3/14/2019
0.338000	1:15:00 PM - 3/14/2019



Preview Result 2-AVG
 Critical_Freqs AVG
 EN 55032 Voltage on Mains QP
 Final_Result QPK
 Preview Result 1-PK+
 Critical_Freqs PK+
 EN 55032 Voltage on Mains AV
 Final_Result CAV

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

9 Test setup photos

Setup photos are included in supporting file name: "EMC_JUNIP-026-19001 _15.247_Setup_Photos.pdf"

10 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Biconlog Antenna	EMCO	3142E	166067	3 years	6/28/2017
Loop Antenna	ETS Lindgren	6507	161344	3 years	10/26/2017
Horn Antenna	EMCO	3115	35114	3 years	07/31/2017
Horn Antenna	ETS Lindgren	3117 PA	169547	3 years	10/31/2017
Compact Digital Barometer	Control Company	35519-055	91119547	2 Years	6/20/2017
Spectrum Analyzer	R&S	FSU26	200065	3 years	7/3/2017
Spectrum Analyzer	R&S	FSV40	101022	3 years	7/5/2017
LISN Line Impedance Stabilization Network	FCC	FCC-LISN-50-25-2-08	8014	3 Year	11/10/2016
Thermometer Humidity	Dickson	TM320	5280063	3 Year	11/2/2017

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

Test Report #: EMC_JUNIP-026-19001_15.247_BT_DTS
Date of Report 2019-03-15

FCC ID: VSFMS3
IC ID: 7980A-MS3

11 Revision History

Date	Report Name	Changes to report	Report prepared by
2019/03/15	EMC_JUNIP-026-19001_15.247_BT_DTS	Initial version	Yuchan Lu