

# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



# **HEARING AID COMPATIBILITY**

**Applicant Name:** 

LG Electronics MobileComm U.S.A. Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 **United States** 

**Date of Testing:** 05/30/2018 - 06/07/2018 Test Site/Location: PCTEST Lab, Columbia, MD, USA **Test Report Serial No.:** 1M1805210108-11-R1.ZNF

FCC ID: ZNFQ610TA

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A. INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification FCC Rule Part(s): CFR §20.19(b) **HAC Standard:** ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

**DUT Type:** Portable Handset Model: LM-Q610TA

Additional Model(s): LMQ610TA, Q610TA, LM-Q610MA, LMQ610MA, Q610MA

**Test Device Serial No.:** Pre-Production Sample [S/N: 05443]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 1M1805210108-11-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez President





FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Dogo 1 of 79	
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Page 1 of 78	

# TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	21
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	24
8.	FCC 3G MEASUREMENTS	27
9.	T-COIL TEST SUMMARY	28
10.	MEASUREMENT UNCERTAINTY	39
11.	EQUIPMENT LIST	40
12.	TEST DATA	41
13.	CALIBRATION CERTIFICATES	66
14.	CONCLUSION	73
15.	REFERENCES	74
16.	TEST SETUP PHOTOGRAPHS	76

FCC ID: ZNFQ610TA	PCTEST*	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 2 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 2 01 70

### 1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

#### **Compatibility Tests Involved:**

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

<sup>1</sup> FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 3 01 76

#### **DUT DESCRIPTION** 2.



FCC ID: ZNFQ610TA

Applicant: LG Electronics MobileComm U.S.A. Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

**United States** 

Model: LM-Q610TA

Additional Model(s): LMQ610TA, Q610TA, LM-Q610MA, LMQ610MA, Q610MA

Serial Number: 05443 HW Version: Rev.1.0 SW Version: Q610TA09a Antenna: Internal Antenna DUT Type: Portable Handset

#### I. LTE Band Selection

This device supports the following pair of LTE bands with similar frequencies: LTE B4 & B66. This pair of LTE bands has the same target power and shares the same transmission path. Since the supported frequency span for the smaller LTE band is completely covered by the larger LTE band, only the larger LTE band (LTE B66) was evaluated for hearing-aid compliance.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 4 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye + 01 70

### Table 2-1 **ZNFQ610TA HAC Air Interfaces**

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service
	850	VO	Yes	Yes: WIFI or BT	CMRS Voice*
GSM	1900	VO	163	res. Wiri Oi Bi	CIVINS VOICE
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo**
	850				
UMTS	1700	VD	Yes	Yes: WIFI or BT	CMRS Voice*
UIVITS	1900				
	HSPA	VD	Yes	Yes: WIFI or BT	Google Duo**
	680 (B71)		Yes <sup>1</sup>		
	700 (B12)	VD	Yes	Yes: WIFI or BT	VoLTE*, Google Duo**
	780 (B13)				
LTE (FDD)	850 (B5)				
	1700 (B4)				
	1700 (B66)				
	1900 (B2)				
LTE (TDD)	2600 (B41)	VD	Yes	Yes: WIFI or BT	VoLTE*, Google Duo**
	2450				
	5200 (U-NII 1)				
WIFI	5300 (U-NII 2A)	VD	Yes	Yes: GSM, UMTS, or LTE	VoWIFI**, Google Duo**
	5500 (U-NII 2C)				
	5800 (U-NII 3)				
ВТ	2450	DT	No	Yes: GSM, UMTS, or LTE	N/A
Type Transport  VO = Voice Only  * Reference level in accordance with 7.4.2.1 of ANSI C63.19-2011 and July 2012 C63 Vol.  DT = Digital Data. Not intended for CMPS Society.			11 and July 2012 C63 VoLTE		

DT = Digital Data - Not intended for CMRS Service

VD = CMRS and IP Voice over Data Transport

Interpretation.

\*\* Reference level is -20dBm0 in accordance with FCC KDB 285076 D02

1. LTE B71, while outside the scope of ANSI C63.19 and FCC HAC regulations, was tested according to the existing HAC procedures.

FCC ID: ZNFQ610TA	PETEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 5 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 3 01 70

# 3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

#### I. MAGNETIC COUPLING

#### **Axial and Radial Field Intensity**

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be  $\geq$  -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

#### **Frequency Response**

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 6 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		rage 6 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

### **Signal Quality**

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Category	Telephone RF Parameters		
Calegory	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]		
T1	0 to 10 dB		
T2	10 to 20 dB		
Т3	20 to 30 dB		
T4	> 30 dB		
Table 3-1  Magnetic Coupling Parameters			

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 7 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage / Ul /o

# 4. METHOD OF MEASUREMENT

# I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:





Figure 4-1
Validation Setup with Helmholtz Coil



FCC ID: ZNFQ610TA

HAC (T-COIL) TEST REPORT

Quality Manager

Filename:

1M1805210108-11-R1.ZNF

05/30/2018 - 06/07/2018

Page 8 of 78

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

# II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size: 0.1 mm

Maximum speed 6.1 cm/sec
Line Voltage: 115 VAC
Line Frequency: 60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

## III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T

Active Frequency Range: 100 Hz – 8 kHz

Stimulus Type: Male and Female, no spaces

Single Sample 20.96 seconds

Duration: 20.90 sec

Activity Level: 100%




Figure 4-4
Spectral Characteristic of full P.50





Figure 4-5
Temporal Characteristic of full P.50

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 9 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 3 01 70



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

#### IV. Test Procedure

- 1. Ambient Noise Check per C63.19 §7.3.1
  - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
  - b. "A-weighting" and Half-Band Integration was applied to the measurements.
  - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
  - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
  - b. ABM1 Validation

The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where  $H_c$  = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of  $-10 \, dB(A/m)$  in the center of the Helmholtz coil which was used to validate the probe measurement at  $-10 \, dB(A/m)$ . This was verified to be within  $\pm 0.5 \, dB$  of the  $-10 \, dB(A/m)$  value (see Page 37).

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Page 10 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

Frequency Response Validation
 The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:



Figure 4-7 Frequency Response Validation

#### d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 11 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Page 110176







Figure 4-8
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2
ABM2 Power Sum Validation

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFQ610TA	PETEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 12 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Page 12 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M




Figure 4-10
ABM2 Power Sum Validation

#### 3. Measurement Test Setup

- a. Fine scan above the WD (TEM)
  - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):




Figure 4-11
Measurement Distance




Figure 4-12 Measurement Grid

- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
  - i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN <sup>TM</sup>	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 13 of 78
1M1805210108-11-R1 7NF	05/30/2018 - 06/07/2018	Portable Handset		Fage 13 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.

#### c. Real-Time Analyzer (RTA)

i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.

#### d. WD Radio Configuration Selection

i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 8 for more information regarding worst-case configurations for UMTS. LTE configuration information can be found in Section 5. WIFI configuration information can be found in Section 6 and 7):




Figure 4-13 Vocoder Analysis for ABM Noise for GSM

#### 4. Signal Quality Data Analysis

- a. Narrow-band Magnetic Intensity
  - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.

#### b. Frequency Response

- i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
- ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
- iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 14 01 76

# c. Signal Quality Index

- i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
- ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
- This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

# V. Test Setup




Figure 4-14
Audio Magnetic Field Test Setup

#### VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessible RF ports.

### VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 15 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 13 01 76

# VIII. Wireless Device Channels and Frequencies

#### 1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes since circuit-switched voice modes were worst-case.

> Table 4-3 Center Channels and Frequencies

Test frequencies & associated channels				
Channel	Frequency (MHz)			
Cellular 850				
190 (GSM) 836.60				
4183 (UMTS)	836.60			
AWS 1750				
1412 (UMTS)	1730.40			
PCS 1900				
661 (GSM)	1880			
9400 (UMTS)	1880			

#### 2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for LTE TDD. The middle channel and supported bandwidths from the worst-case band according to Table 7-5 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-4 to 9-10 and Tables 9-17 to 9-18 for LTE bandwidths and channels.

#### 3. WIFI

The middle channel for each 802.11 standard was tested for each probe orientation. The 2.4GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-11 to 9-14 and Tables 9-19 to 9-22 for WIFI standards and channels.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		rage 10 01 76

### IX. Test Flow

The flow diagram below was followed (From C63.19):




Figure 4-15 C63.19 T-Coil Signal Test Process

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 17 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 17 0176

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

# 5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

# I. Test System Setup for VoLTE over IMS T-coil Testing

# 1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

#### 2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level\*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

\* http://c63.org/documents/misc/posting/new\_interpretations.htm

FCC ID: ZNFQ610TA	PCTEST'	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 18 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		rage 10 01 70

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

# II. DUT Configuration for VoLTE over IMS T-coil Testing

### 1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

Table 5-1
VoLTE over IMS SNNR by Radio Configuration

	VOLTE OVER INIS SINING BY RADIO CONTIGURATION											
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]				
1880.0	18900	20	QPSK	1	0	6.17	-34.06	40.23				
1880.0	18900	20	QPSK	1	50	6.21	-34.03	40.24				
1880.0	18900	20	QPSK	1	99	6.30	-33.69	39.99				
1880.0	18900	20	QPSK	50	0	5.95	-34.66	40.61				
1880.0	18900	20	QPSK	50	25	6.03	-34.53	40.56				
1880.0	18900	20	QPSK	50	50	6.25	-34.16	40.41				
1880.0	18900	20	QPSK	100	0	5.88	-34.07	39.95				
1880.0	18900	20	16QAM	1	0	5.75	-32.40	38.15				
1880.0	18900	20	16QAM	1	50	6.15	-32.71	38.86				
1880.0	18900	20	16QAM	1	99	6.18	-32.17	38.35				
1880.0	18900	20	16QAM	50	0	5.98	-34.78	40.76				
1880.0	18900	20	16QAM	50	25	6.24	-34.61	40.85				
1880.0	18900	20	16QAM	50	50	5.94	-34.57	40.51				
1880.0	18900	20	16QAM	100	0	6.15	-34.52	40.67				
1880.0	18900	20	64QAM	1	0	6.26	-33.06	39.32				
1880.0	18900	20	64QAM	1	50	5.97	-33.08	39.05				
1880.0	18900	20	64QAM	1	99	6.23	-32.42	38.65				
1880.0	18900	20	64QAM	50	0	5.89	-34.09	39.98				
1880.0	18900	20	64QAM	50	25	5.87	-36.03	41.90				
1880.0	18900	20	64QAM	50	50	5.85	-36.07	41.92				
1880.0	18900	20	64QAM	100	0	5.83	-36.68	42.51				

#### 2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between codecs and codec data rates:

Table 5-2
AMR Codec Investigation – VoLTE over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	8.18	6.03	9.44	9.64		Band 2 20MHz	18900
ABM2 (dBA/m)	-33.31	-32.89	-32.94	-32.71	Axial		
Frequency Response	Pass	Pass	Pass	Pass	Axidi		
S+N/N (dB)	41.49	38.92	42.38	42.35			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"




Figure 5-2
Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFQ610TA	HAC (T-COIL) TEST REPORT		① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 19 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 19 01 76

#### 3. LTE TDD Uplink-Downlink Configuration Investigation for VoLTE over IMS

An investigation was performed to determine the worst-case Uplink-Downlink configuration for VoLTE over IMS T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length  $T_f$  = 307200 ·  $T_s$ = 10 ms, where T<sub>s</sub> is a number of time units equal to 1/(15000 x 2048) seconds. Additionally, each radio frame consists of 10 subframes, each of length 30720 · T<sub>s</sub> = 1 ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is 2192 · Ts which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

> Table 5-3 **Uplink-Downlink Configurations for Type 2 Frame Structures**

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									Calculated Transmission	
comiguration	Switch-point periodicity	0	1	2	3	4	5	6	7	8	9	Duty Cycle (%)
0	5 ms	D	S	U	U	U	D	S	J	5	U	61.4%
1	5 ms	D	S	U	U	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	U	D	D	21.4%
3	10 ms	D	S	U	U	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	U	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

#### a. Power Class 3 Uplink-Downlink Configuration Investigation

Power class 3 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 0RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 1 was used as the worst-case configuration for Power Class 3 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-4 Power Class 3 Vol TE over IMS SNNR by III -DL Configuration

	rower class 3 volite over INIS SINING by OL-DE Configuration												
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]				
2593.0	40620	20	16QAM	1	0	0	6.01	-20.35	26.36				
2593.0	40620	20	16QAM	1	0	1	6.10	-19.90	26.00				
2593.0	40620	20	16QAM	1	0	2	6.06	-20.04	26.10				
2593.0	40620	20	16QAM	1	0	3	6.16	-22.89	29.05				
2593.0	40620	20	16QAM	1	0	4	6.09	-22.76	28.85				
2593.0	40620	20	16QAM	1	0	5	6.08	-22.77	28.85				
2593.0	40620	20	16QAM	1	0	6	5.81	-20.30	26.11				

#### b. Conclusion

Per the investigations above, UL-DL Configuration 1 was used to evaluate Power Class 3 VoLTE over IMS.

FCC ID: ZNFQ610TA	HAC (T-COIL) TEST REPORT		① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 20 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 20 01 76

#### **VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION** 6.

#### I. Test System Setup for VoWIFI over IMS T-coil Testing

#### **Equipment Setup**

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1 Test Setup for VoWIFI over IMS T-Coil Measurements

#### 2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level2. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

<sup>2</sup> FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 21 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 21 01 70

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

#### **DUT Configuration for VoWIFI over IMS T-coil Testing** II.

### 1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each 802.11 standard:

> Table 6-1 802.11b SNNR by Radio Configuration

COZ. TID CIVILLE BY INCOIN GUILLOIN											
Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]					
802.11b	6	DSSS	1	0.67	-30.68	31.35					
802.11b	6	DSSS	2	0.33	-30.81	31.14					
802.11b	6	CCK	5.5	-0.82	-30.78	29.96					
802.11b	6	CCK	11	-0.29	-32.31	32.02					

Table 6-2 802.11g/a SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11g	6	BPSK	6	-0.64	-35.44	34.80
802.11g	6	BPSK	9	0.15	-36.08	36.23
802.11g	6	QPSK	12	-0.59	-38.04	37.45
802.11g	6	QPSK	18	-1.02	-36.77	35.75
802.11g	6	16-QAM	24	-0.90	-36.88	35.98
802.11g	6	16-QAM	36	-0.16	-38.53	38.37
802.11g	6	64-QAM	48	-0.91	-36.04	35.13
802.11g	6	64-QAM	54	-0.98	-37.24	36.26

Table 6-3 802 11n/ac 20MHz RW SNNR by Radio Configuration

802.1111/ac 20MHZ BW SNNR by Radio Configuration										
Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]			
802.11n	20	40	BPSK	6.5	-0.24	-35.68	35.44			
802.11n	20	40	QPSK	13	-0.82	-37.72	36.90			
802.11n	20	40	QPSK	19.5	-0.12	-37.68	37.56			
802.11n	20	40	16-QAM	26	0.05	-36.55	36.60			
802.11n	20	40	16-QAM	39	-0.63	-37.11	36.48			
802.11n	20	40	64-QAM	52	0.01	-37.55	37.56			
802.11n	20	40	64-QAM	58.5	-0.06	-37.45	37.39			
802.11n	20	40	64-QAM	65	-0.41	-36.63	36.22			
802.11ac	20	40	256-QAM	78	-0.10	-37.00	36.90			

FCC ID: ZNFQ610TA	PETEST*	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 22 01 76

Table 6-4 802.11n/ac 40MHz BW SNNR by Radio Configuration

602.1 Illiac 40MHz BW SINIX by Radio Configuration											
Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]				
802.11n	40	38	BPSK	13.5	-0.43	-36.23	35.80				
802.11n	40	38	QPSK	27	0.38	-35.63	36.01				
802.11n	40	38	QPSK	40.5	-0.08	-36.11	36.03				
802.11n	40	38	16-QAM	54	0.14	-36.96	37.10				
802.11n	40	38	16-QAM	81	0.40	-36.41	36.81				
802.11n	40	38	64-QAM	108	-0.76	-36.02	35.26				
802.11n	40	38	64-QAM	121.5	0.07	-36.12	36.19				
802.11n	40	38	64-QAM	135	-0.61	-34.84	34.23				
802.11ac	40	38	256-QAM	162	-0.13	-36.81	36.68				
802.11ac	40	38	256-QAM	180	0.79	-36.08	36.87				

#### 2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The NB AMR 12.2kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 6-5 AMR Codec Investigation - VoWIFI over IMS

AMIN Codec Investigation - vovin rover into										
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel		
ABM1 (dBA/m)	4.04	2.76	0.79	0.71						
ABM2 (dBA/m)	-31.06	-31.48	-31.67	-32.17	Axial	2.4GHz	IEEE 802.11b	6		
Frequency Response	Pass	Pass	Pass	Pass	Axiai	2.40112	ILLE 002.110	Ü		
S+N/N (dB)	35.10	34.24	32.46	32.88						

Mute on; Backlight off; Max Volume; Max Contrast




Figure 6-2 **Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 23 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 23 01 76

#### 7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

#### I. Test System Setup for OTT VolP T-Coil Testing

#### 1. OTT VolP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 64kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

#### 2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

### **Audio Level Settings**

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation3. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

#### II. **DUT Configuration for OTT VolP T-Coil Testing**

#### 1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

> Table 7-1 Codec Investigation - OTT VolP (EDGE)

Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	14.92	14.79		
ABM2 (dBA/m)	-16.86	-16.76	Avial	661
Frequency Response	Pass	Pass	Axial	
S+N/N (dB)	31.78	31.55		

<sup>3</sup> FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03" September 13, 2017.

T CC Office of Engineer	T CC Office of Engineering and Technology KDB, 2000/0 D02 T-Coll Testing for CMK3 IF V03, September 13, 2017								
FCC ID: ZNFQ610TA	ENCINETAL LADRETORS, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager					
Filename:	Test Dates:	DUT Type:		Page 24 of 78					
1M1805210108-11-R1 7NF	05/30/2018 - 06/07/2018	Portable Handset		-					

Table 7-2
Codec Investigation – OTT VoIP (HSPA)

Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	15.06	15.13		
ABM2 (dBA/m)	-33.32	-29.99	Axial	9400
Frequency Response	Pass	Pass	Axiai	
S+N/N (dB)	48.38	45.12		


Table 7-3
Codec Investigation – OTT VoIP (LTE)

Todos invocinguion OTT von (212)										
Codec Setting:	64kbps	6kbps	Orientation	Band / BW	Channel					
ABM1 (dBA/m)	15.52	15.03								
ABM2 (dBA/m)	-31.34	-31.05	Axial	Band 2	18900					
Frequency Response	Pass	Pass	AAIAI	20MHz						
S+N/N (dB)	46.86	46.08								

Table 7-4
Codec Investigation – OTT VoIP (WIFI)

Codec Setting:	64kbps	6kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	15.62	15.49				6
ABM2 (dBA/m)	-24.76	-23.93	Axial	2 4CH <del>2</del>	2.4GHz IEEE 802.11b	
Frequency Response	Pass	Pass	Axiai	2.4GHz		
S+N/N (dB)	40.38	39.42				

- Mute on; Backlight off; Max Volume; Max Contrast
- · Radio Configurations can be found in Section 9.II.G



**Audio Band Magnetic Curve Measurement Block Diagram** 

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 25 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 23 01 76

# 2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE band to be used for OTT VoIP testing. LTE Band 71 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE bands:

Table 7-5
OTT VoIP (LTE) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2	1880.0	18900	20	16QAM	1	0	14.98	-30.58	45.56
5	836.5	20525	10	16QAM	1	0	14.84	-31.02	45.86
12	707.5	23095	10	16QAM	1	0	15.21	-28.28	43.49
13	782.0	23230	10	16QAM	1	0	14.77	-29.04	43.81
66	1745.0	132322	20	16QAM	1	0	14.83	-29.27	44.10
71	680.5	133297	20	16QAM	1	0	15.16	-27.90	43.06

FCC ID: ZNFQ610TA	PETEST*	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 26 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 20 01 76

# 8. FCC 3G MEASUREMENTS

# I. UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:





Figure 8-1
UMTS Audio Band Magnetic Noise

Table 8-1 Codec Investigation - UMTS

- Coulo III Coul									
Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel				
ABM1 (dBA/m)	-3.25	-2.38	-1.91		9400				
ABM2 (dBA/m)	-38.59	-40.10	-39.97	Axial					
Frequency Response	Pass	Pass	Pass	Axiai	3400				
S+N/N (dB)	35.34	37.72	38.06						

- Mute on; Backlight off; Max Volume; Max Contrast
- · TPC="All 1s"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 27 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 21 01 16

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

# 9. T-COIL TEST SUMMARY

Table 9-1
Consolidated Tabled Results

			701130110	aated 1	abica it	Courto			
			esponse rgin	_	netic / Verdict		SNNR dict	Margin from FCC Limit	C63.19-2011
000.40	Section	8.3	3.2	8.	3.1	8.	3.4	(dB)	Rating
C63.19	9 Section	Axial	Radial	Axial	Radial	Axial	Radial		
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-1.94	Т3
	PCS	PASS	NA	PASS	PASS	PASS	PASS	-1.34	13
EDGE	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-6.09	Т3
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-0.03	13
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-8.34	Т3
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
1105.	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
HSPA (OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-26.27	T4
,	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	B71	PASS	NA	PASS	PASS	PASS	PASS		
	B12	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD	B13	PASS	NA	PASS	PASS	PASS	PASS	-13.44	Т4
LILIUU	B5	PASS	NA	PASS	PASS	PASS	PASS	-13.44	14
	B66	PASS	NA	PASS	PASS	PASS	PASS	SS SS	
	B2	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD (OTT VoIP)	B71	PASS	NA	PASS	PASS	PASS	PASS	-21.95	T4
LTE TDD	B41	PASS	NA	PASS	PASS	PASS	PASS	-5.45	Т3
LTE TDD (OTT VoIP)	B41	PASS	NA	PASS	PASS	PASS	PASS	-13.74	Т4
	802.11b	PASS	NA	PASS	PASS	PASS	PASS		
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-5.46	Т3
WLAIN	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-5.40	13
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS		
	802.11b	PASS	NA	PASS	PASS	PASS	PASS		
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-16.86	T4
(OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-10.00	14
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS		
	802.11a	PASS	NA	PASS	PASS	PASS	PASS		
U-NII	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-11.02	T4
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS		
	802.11a	PASS	NA	PASS	PASS	PASS	PASS		
U-NII (OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-14.81	T4
(011 4011)	802.11ac	PASS	NA	PASS	PASS	PASS	PASS		

FCC ID: ZNFQ610TA	PETEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 28 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 20 01 / 0

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

# I. Raw Handset Data

Table 9-2
Raw Data Results for GSM

					- utu - 1001						
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		128	14.06	-7.88		1.53	21.94	20.00	-1.94	Т3	
	Axial	190	14.10	-9.05	-63.60	1.51	23.15	20.00	-3.15	Т3	2.0, 3.2
GSM850		251	14.51	-9.66		1.51	24.17	20.00	-4.17	Т3	
GSIVIOSU		128	6.04	-21.22			27.26	20.00	-7.26	Т3	
	Radial	190	6.26	-22.67	-64.53	N/A	28.93	20.00	-8.93	Т3	2.0, 4.0
		251	6.40	-23.36			29.76	20.00	-9.76	Т3	
		512	14.53	-12.90		1.47	27.43	20.00	-7.43	Т3	
	Axial	661	14.27	-13.58	-63.60	1.47	27.85	20.00	-7.85	Т3	2.0, 3.2
CSM1000		810	14.05	-13.83		1.49	27.88	20.00	-7.88	Т3	
GSM1900		512	5.90	-26.27			32.17	20.00	-12.17	T4	
	Radial	661	6.34	-27.19		N/A	33.53	20.00	-13.53	T4	2.0, 4.0
		810	6.08	-27.12			33.20	20.00	-13.20	T4	

Table 9-3
Raw Data Results for UMTS

				11411 5	utu i toou	ונס וטו טו	<u> </u>				
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		4132	-2.77	-39.23		1.20	36.46	20.00	-16.46	T4	
	Axial	4183	-2.81	-39.01	-63.60	1.33	36.20	20.00	-16.20	T4	2.0, 3.2
UMTS V		4233	-3.62	-38.88		1.35	35.26	20.00	-15.26	T4	
UNITSV		4132	-13.33	-41.67			28.34	20.00	-8.34	Т3	
	Radial	4183	-12.52	-42.57	-64.53	N/A	30.05	20.00	-10.05	T4	2.0, 4.0
		4233	-12.76	-42.43			29.67	20.00	-9.67	T3	
		1312	-2.37	-38.81	-63.60	1.33	36.44	20.00	-16.44	T4	
	Axial	1412	-3.26	-39.12		1.32	35.86	20.00	-15.86	T4	2.0, 3.2
UMTS IV		1513	-2.46	-39.22		1.34	36.76	20.00	-16.76	T4	
OWITO IV		1312	-11.84	-42.26			30.42	20.00	-10.42	T4	
	Radial	1412	-10.64	-42.39	-64.53	N/A	31.75	20.00	-11.75	T4	2.0, 4.0
		1513	-11.42	-42.55			31.13	20.00	-11.13	T4	
		9262	-2.79	-39.99		1.34	37.20	20.00	-17.20	T4	
	Axial	9400	-3.03	-39.32	-63.60	1.34	36.29	20.00	-16.29	T4	2.0, 3.2
UMTS II		9538	-4.02	-39.40		1.34	35.38	20.00	-15.38	T4	
Om 13 II		9262	-10.61	-43.27			32.66	20.00	-12.66	T4	
	Radial	9400	-11.64	-42.84	-64.53	N/A	31.20	20.00	-11.20	T4	2.0, 4.0
		9538	-11.86	-42.95			31.09	20.00	-11.09	T4	

# Table 9-4 Raw Data Results for LTE B71

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	133297	6.14	-28.50		2.00	34.64	20.00	-14.64	T4	
	Axial	15MHz	133297	5.99	-28.46	-64.18	2.00	34.45	20.00	-14.45	T4	2.0. 3.2
	Axiai	10MHz	133297	5.89	-28.00	-04.10	2.00	33.89	20.00	-13.89	T4	2.0, 3.2
LTE Band		5MHz	133297	5.90	-30.20		2.00	36.10	20.00	-16.10	T4	
71		20MHz	133297	-0.69	-37.11			36.42	20.00	-16.42	T4	
	Radial	15MHz	133297	-0.69	-36.48	64.25	N/A	35.79	20.00	-15.79	T4	2.0. 4.0
	Raulai	10MHz	133297	-0.70	-37.01	-64.25	IN/A	36.31	20.00	-16.31	T4	2.0, 4.0
		5MHz	133297	-0.59	-38.34			37.75	20.00	-17.75	T4	

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 29 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 29 01 76

# Table 9-5 Raw Data Results for LTE B12

						<del>ocaito io</del>																
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates										
		10MHz	23095	6.23	-28.31		2.00	34.54	20.00	-14.54	T4											
		5MHz	23095	6.22	-27.88		2.00	34.10	20.00	-14.10	T4											
	Axial	3MHz	23165	6.24	-30.68	-64.18	2.00	36.92	20.00	-16.92	T4	2.0, 3.2										
	Axiai	3MHz	23095	6.22	-27.42	-04.18	2.00	33.64	20.00	-13.64	T4	2.0, 3.2										
		3MHz	23025	6.13	-27.31		2.00	33.44	20.00	-13.44	T4											
LTE Band		1.4MHz	23095	6.05	-28.00		2.00	34.05	20.00	-14.05	T4											
12		10MHz	23095	-0.64	-37.62			36.98	20.00	-16.98	T4											
		5MHz	23095	-0.64	-36.59			35.95	20.00	-15.95	T4											
	Radial	3MHz	23165	-0.81	-38.32	64.25	N/A	37.51	20.00	-17.51	T4	2.0, 4.0										
	Naulai	3MHz	23095	-0.64	-36.22	-64.25	-64.25	-64.25	-64.25	IN/A	35.58	20.00	-15.58	T4	2.0, 4.0							
		3MHz	23025	-0.73	-38.99					<u> </u>			7	7	7				_			38.26
		1.4MHz	23095	-0.66	-36.49			35.83	20.00	-15.83	T4	1										

# Table 9-6 Raw Data Results for LTE B13

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
Ī		Avial	10MHz	23230	5.95	-30.49	-64.18	2.00	36.44	20.00	-16.44	T4	2.0, 3.2
	LTE Band Axial	5MHz	23230	6.23	-29.55	-04.10	2.00	35.78	20.00	-15.78	T4	2.0, 3.2	
	13	Radial	10MHz	23230	-0.63	-37.54	-64.25	N/A	36.91	20.00	-16.91	T4	2.0. 4.0
		Raulai	5MHz	23230	-0.73	-37.65	-04.25	N/A	36.92	20.00	-16.92	T4	2.0, 4.0

# Table 9-7 Raw Data Results for LTE B5

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	20525	6.19	-32.17		2.00	38.36	20.00	-18.36	T4	
	Avial	5MHz	20525	6.31	-32.24	-64.18	2.00	38.55	20.00	-18.55	T4	2.0, 3.2
	Axial	3MHz	20525	6.20	-31.24	-04.10	2.00	37.44	20.00	-17.44	T4	2.0, 3.2
I TE Band 6		1.4MHz	20525	6.19	-31.07		2.00	37.26	20.00	-17.26	T4	
LIE Ballu 5	_TE Band 5	10MHz	20525	-0.68	-42.16			41.48	20.00	-21.48	T4	
	Radial	5MHz	20525	-0.82	-41.22	64.25	-64.25 N/A	40.40	20.00	-20.40	T4	2.0, 4.0
	Naulai	3MHz	20525	-0.87	-40.74	-64.25	IN/A	39.87	20.00	-19.87	T4	2.0, 4.0
		1.4MHz	20525	-0.61	-39.64			39.03	20.00	-19.03	T4	

# Table 9-8 Raw Data Results for LTE B66

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	132322	6.14	-30.71		2.00	36.85	20.00	-16.85	T4	
		15MHz	132322	6.32	-29.98		2.00	36.30	20.00	-16.30	T4	
	Avial	10MHz	132322	5.98	-31.12	-64.18	2.00	37.10	20.00	-17.10	T4	2.0, 3.2
	Axial	5MHz	132322	6.03	-31.28	-04.10	2.00	37.31	20.00	-17.31	T4	2.0, 3.2
		3MHz	132322	6.16	-31.06		2.00	37.22	20.00	-17.22	T4	
LTE Band		1.4MHz	132322	5.95	-31.50		2.00	37.45	20.00	-17.45	T4	
66		20MHz	132322	-0.76	-39.22			38.46	20.00	-18.46	T4	
		15MHz	132322	-0.57	-39.70			39.13	20.00	-19.13	T4	
	Radial	10MHz	132322	-0.63	-40.18	-64.25	N/A	39.55	20.00	-19.55	T4	2.0, 4.0
	Naulai	5MHz	132322	-0.69	-40.09	-04.25	IN/A	39.40	20.00	-19.40	T4	2.0, 4.0
		3MHz	132322	-0.61	-38.95	1		38.34	20.00	-18.34	T4	
		1.4MHz	132322	-0.56	-40.84			40.28	20.00	-20.28	T4	

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 30 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 30 01 76

# Table 9-9 Raw Data Results for LTE B2

				- 1011		Courto ic														
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates								
		20MHz	18900	6.29	-32.52		2.00	38.81	20.00	-18.81	T4									
		15MHz	18900	6.24	-31.53		2.00	37.77	20.00	-17.77	T4									
	Axial –	10MHz	18900	5.91	-32.03	-64.18	2.00	37.94	20.00	-17.94	T4	2.0, 3.2								
		5MHz	18900	6.21	-32.70	-04.10	2.00	38.91	20.00	-18.91	T4	2.0, 3.2								
		3MHz	18900	6.41	-31.90		2.00	38.31	20.00	-18.31	T4									
LTE Bond 2		1.4MHz	18900	6.16	-31.71		2.00	37.87	20.00	-17.87	T4									
LIE Ballu 2		20MHz	18900	-0.54	-41.10			40.56	20.00	-20.56	T4									
		15MHz	18900	-0.62	-40.12			39.50	20.00	-19.50	T4									
	Radial	10MHz	18900	-0.67	-41.26	64.25	N/A	40.59	20.00	-20.59	T4	2.0, 4.0								
	Raulai	5MHz	18900	-0.74	-41.13	-64.25	-64.25	-64.25 N	-64.25	-64.25	-64.25	-64.25	-64.25	-64.25	IN/A	40.39	20.00	-20.39	T4	2.0, 4.0
		3MHz	18900	-0.62	-41.23					40.61	20.00	-20.61	T4							
		1.4MHz	18900	-0.81	-39.52			38.71	20.00	-18.71	T4									

# Table 9-10 Raw Data Results for LTE B41 Power Class 3

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	40620	6.20	-20.30		2.00	26.50	20.00	-6.50	T3	
		15MHz	40620	6.00	-20.00		2.00	26.00	20.00	-6.00	T3	
		10MHz	41490	6.20	-19.77		2.00	25.97	20.00	-5.97	T3	
	Axial	10MHz	41055	6.05	-19.54	-64.18	2.00	25.59	20.00	-5.59	Т3	2.0, 3.2
	Axiai	10MHz	40620	6.18	-19.53	-04.10	2.00	25.71	20.00	-5.71	T3	2.0, 3.2
		10MHz	40185	6.20	-19.55	[	2.00	25.75	20.00	-5.75	T3	
		10MHz	39750	6.02	-19.43		2.00	25.45	20.00	-5.45	T3	
LTE Band		5MHz	40620	6.30	-19.53		2.00	25.83	20.00	-5.83	T3	
41		20MHz	40620	-0.71	-31.18			30.47	20.00	-10.47	T4	
		15MHz	40620	-0.73	-30.95			30.22	20.00	-10.22	T4	
		10MHz	41490	-0.70	-30.89			30.19	20.00	-10.19	T4	
	Radial	10MHz	41055	-0.83	-30.84	-64.25	N/A	30.01	20.00	-10.01	T4	2.0, 4.0
	Naulai	10MHz	40620	-0.76	-30.90	-04.25	IWA	30.14	20.00	-10.14	T4	2.0, 4.0
		10MHz	40185	-0.73	-30.34			29.61	20.00	-9.61	T3	
		10MHz	39750	-0.72	-30.52			29.80	20.00	-9.80	T3	
		5MHz	40620	-0.73	-30.99			30.26	20.00	-10.26	T4	

# Table 9-11 Raw Data Results for 2.4GHz WIFI

				arr Bata	Nesulis	101 2.701	<u></u>				
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	-1.04	-31.59		2.00	30.55	20.00	-10.55	T4	
	Axial	6	-0.55	-29.17	-64.18	2.00	28.62	20.00	-8.62	Т3	2.0, 3.2
WLAN		11	-0.39	-31.95		2.00	31.56	20.00	-11.56	T4	
802.11b		1	-8.02	-34.09			26.07	20.00	-6.07	Т3	
	Radial	6	-7.62	-33.08	-64.25	N/A	25.46	20.00	-5.46	Т3	2.0, 4.0
		11	-8.60	-35.22			26.62	20.00	-6.62	Т3	1
WLAN	Axial	6	-0.95	-35.90	-64.18	2.00	34.95	20.00	-14.95	T4	2.0, 3.2
802.11g	Radial	6	-7.36	-40.49	-64.25	N/A	33.13	20.00	-13.13	T4	2.0, 4.0
WLAN	Axial	6	0.05	-35.42	-64.18	2.00	35.47	20.00	-15.47	T4	2.0, 3.2
802.11n	Radial	6	-8.49	-38.53	-64.25	N/A	30.04	20.00	-10.04	T4	2.0, 4.0

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 31 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 31 01 76

#### **Table 9-12** Raw Data Results for 5GHz WIFI 802.11a

				- 14111 -	Julu IXC								
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	1	40	-0.08	-34.60		2.00	34.52	20.00	-14.52	T4	
		20MHz	2A	56	-0.62	-35.03		2.00	34.41	20.00	-14.41	T4	
	Axial	20MHz	2C	120	-0.06	-32.13	-64.18	2.00	32.07	20.00	-12.07	T4	2.0, 3.2
	Axiai	20MHz	3	149	-0.35	-33.03	-04.10	2.00	32.68	20.00	-12.68	T4	2.0, 3.2
		20MHz	3	157	-0.68	-31.96		2.00	31.28	20.00	-11.28	T4	
		20MHz	3	165	-0.15	-32.11		2.00	31.96	20.00	-11.96	T4	
802.11a													
		20MHz	1	36	-8.52	-41.13			32.61	20.00	-12.61	T4	
		20MHz	1	40	-7.84	-40.83			32.99	20.00	-12.99	T4	
	Radial	20MHz	1	48	-8.11	-39.13	-64.25	N/A	31.02	20.00	-11.02	T4	2.0, 4.0
	Raulai	20MHz	2A	56	-8.06	-41.91	-04.25	IN/A	33.85	20.00	-13.85	T4	2.0, 4.0
		20MHz	2C	120	-8.34	-41.53			33.19	20.00	-13.19	T4	
		20MHz	3	157	-7.85	-41.44			33.59	20.00	-13.59	T4	

#### **Table 9-13** Raw Data Results for 5GHz WIFI 802.11n

Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	40MHz	1	38	0.49	-36.15	-64.18	2.00	36.64	20.00	-16.64	T4	2.0, 3.8
	Axiai	20MHz	1	40	-0.20	-35.38	-04.10	2.00	35.18	20.00	-15.18	T4	2.0, 3.6
802.11n													
	Radial	40MHz	1	38	-8.95	-42.51	-64.25	N/A	33.56	20.00	-13.56	T4	2.0, 4.0
	Raulai	20MHz	1	40	-8.34	-45.49	-04.25	IVA	37.15	20.00	-17.15	T4	2.0, 4.0

#### **Table 9-14** Raw Data Results for 5GHz WIFI 802.11ac

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
ſ		Axial	40MHz	1	38	-0.87	-37.41	-64.18	2.00	36.54	20.00	-16.54	T4	2.0. 3.2
		Axiai	20MHz	1	40	-0.78	-36.12	-04.16	2.00	35.34	20.00	-15.34	T4	2.0, 3.2
	802.11ac													
		Radial	40MHz	1	38	-7.56	-43.61	-64.25	N/A	36.05	20.00	-16.05	T4	2.0, 4.0
		Nadiai	20MHz	1	40	-8.08	-41.12	-04.25	IWA	33.04	20.00	-13.04	T4	2.0, 4.0

## **Table 9-15** Raw Data Results for EDGE (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
EDGE850	Axial	190	14.51	-11.58	-64.18	2.00	26.09	20.00	-6.09	Т3	2.0, 3.2
EDGE050	Radial	190	7.64	-25.05	-64.25	N/A	32.69	20.00	-12.69	T4	2.0, 4.0
EDGE1900	Axial	661	14.68	-16.65	-64.18	2.00	31.33	20.00	-11.33	T4	2.0, 3.2
EDGE 1900	Radial	661	8.19	-30.46	-64.25	N/A	38.65	20.00	-18.65	T4	2.0, 4.0

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 32 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 32 01 76

### **Table 9-16** Raw Data Results for HSPA (OTT VoIP)

					counto ioi		011 4011	,			
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
HSPA V	Axial	4183	14.84	-32.17	-64.18	1.83	47.01	20.00	-27.01	T4	2.0, 3.2
HOPA V	Radial	4183	7.41	-46.99	-64.25	N/A	54.40	20.00	-34.40	T4	2.0, 4.0
HSPA IV	Axial	1412	14.53	-33.09	-64.18	1.83	47.62	20.00	-27.62	T4	2.0, 3.2
HOPAIV	Radial	1412	7.79	-46.20	-64.25	N/A	53.99	20.00	-33.99	T4	2.0, 4.0
HSPA II	Axial	9400	14.76	-31.51	-64.18	1.91	46.27	20.00	-26.27	T4	2.0, 3.2
HOPAII	Radial	9400	7.81	-47.33	-64.25	N/A	55.14	20.00	-35.14	T4	2.0, 4.0

### **Table 9-17** Raw Data Results for LTE FDD B71 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	133297	15.00	-27.59		1.84	42.59	20.00	-22.59	T4	
		15MHz	133397	14.94	-31.38		1.74	46.32	20.00	-26.32	T4	
	Axial	15MHz	133297	14.95	-27.00	-64.18	2.00	41.95	20.00	-21.95	T4	2.0. 3.2
	Axiai	15MHz	133197	14.70	-29.04	-04.16	1.97	43.74	20.00	-23.74	T4	2.0, 3.2
		10MHz	133297	14.75	-28.00		1.90	42.75	20.00	-22.75	T4	
LTE Band		5MHz	133297	14.51	-29.09		1.85	43.60	20.00	-23.60	T4	
71		20MHz	133297	7.84	-38.40			46.24	20.00	-26.24	T4	
		15MHz	133397	7.76	-42.18			49.94	20.00	-29.94	T4	
	Radial	15MHz	133297	7.71	-37.52	-64.25	N/A	45.23	20.00	-25.23	T4	2.0, 4.0
	Naulai	15MHz	133197	7.58	-38.68	-04.25	IN/A	46.26	20.00	-26.26	T4	2.0, 4.0
		10MHz	133297	7.63	-37.63			45.26	20.00	-25.26	T4	
		5MHz	133297	7.33	-39.91			47.24	20.00	-27.24	T4	

### **Table 9-18** Raw Data Results for LTE TDD B41 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	40620	15.01	-19.81		1.92	34.82	20.00	-14.82	T4	
		15MHz	41490	14.59	-19.78	1	2.00	34.37	20.00	-14.37	T4	
		15MHz	41055	14.81	-20.12		1.90	34.93	20.00	-14.93	T4	
	Axial	15MHz	40620	14.49	-19.90	-64.18	2.00	34.39	20.00	-14.39	T4	2.0, 3.2
	Axiai	15MHz	40185	14.42	-19.32	-04.16	1.72	33.74	20.00	-13.74	T4	2.0, 3.2
		15MHz	39750	15.08	-19.52		2.00	34.60	20.00	-14.60	T4	
		10MHz	40620	14.70	-19.71		2.00	34.41	20.00	-14.41	T4	
LTE Band		5MHz	40620	16.06	-18.83		2.00	34.89	20.00	-14.89	T4	
41		20MHz	40620	8.04	-31.15			39.19	20.00	-19.19	T4	
		15MHz	41490	8.02	-30.06			38.08	20.00	-18.08	T4	
		15MHz	41055	8.26	-30.62			38.88	20.00	-18.88	T4	
	Dodial	15MHz	40620	8.30	-29.86	64.05	NI/A	38.16	20.00	-18.16	T4	20.40
	Radial	15MHz	40185	8.06	-30.33	-64.25	N/A	38.39	20.00	-18.39	T4	2.0, 4.0
		15MHz	39750	8.03	-29.72			37.75	20.00	-17.75	T4	
		10MHz	40620	8.22	-30.57			38.79	20.00	-18.79	T4	
		5MHz	40620	8.19	-30.70			38.89	20.00	-18.89	T4	

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 33 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 33 01 76

## **Table 9-19** Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Naw Data Results for 2.40112 Will for 1 Voll j											
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	15.24	-24.99		2.00	40.23	20.00	-20.23	T4	
	Axial	6	15.64	-24.05	-64.18	1.86	39.69	20.00	-19.69	T4	2.0, 3.2
WLAN		11	15.27	-26.04		1.92	41.31	20.00	-21.31	T4	
802.11b		1	7.80	-30.42			38.22	20.00	-18.22	T4	
	Radial	6	7.35	-30.62	-64.25	N/A	37.97	20.00	-17.97	T4	2.0, 4.0
		11	7.74	-29.12			36.86	20.00	-16.86	T4	
WLAN	Axial	6	15.51	-24.47	-64.18	1.88	39.98	20.00	-19.98	T4	2.0, 3.2
802.11g	Radial	6	7.61	-34.87	-64.25	N/A	42.48	20.00	-22.48	T4	2.0, 4.0
WLAN	Axial	6	15.44	-25.17	-64.18	1.88	40.61	20.00	-20.61	T4	2.0, 3.2
802.11n	Radial	6	7.80	-33.47	-64.25	N/A	41.27	20.00	-21.27	T4	2.0, 4.0

#### **Table 9-20** Raw Data Results for 5GHz WIFI 802.11a (OTT VoIP)

									(0:::0:::)				
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	1	40	15.14	-26.63		1.90	41.77	20.00	-21.77	T4	
		20MHz	2A	56	15.10	-28.49		2.00	43.59	20.00	-23.59	T4	2.0, 3.2
	Axial	20MHz	2C	120	15.53	-28.24	-64.18	2.00	43.77	20.00	-23.77	T4	
	Axiai	20MHz	3	149	15.62	-25.40	-04.10	1.81	41.02	20.00	-21.02	T4	
		20MHz	3	157	15.34	-24.72		1.97	40.06	20.00	-20.06	T4	
		20MHz	3	165	15.13	-29.54		1.79	44.67	20.00	-24.67	T4	
802.11a													
		20MHz	1	40	7.83	-28.08			35.91	20.00	-15.91	T4	
		20MHz	2A	56	7.76	-29.29			37.05	20.00	-17.05	T4	
	Radial	20MHz	2C	120	7.27	-31.68	-64.25	N/A	38.95	20.00	-18.95	T4	2.0, 4.0
	Raulai	20MHz	3	149	8.46	-28.34	-04.25	IN/A	36.80	20.00	-16.80	T4	2.0, 4.0
		20MHz	3	157	7.34	-27.47			34.81	20.00	-14.81	T4	
		20MHz	3	165	7.47	-27.40			34.87	20.00	-14.87	T4	

## **Table 9-21** Raw Data Results for 5GHz WIFI 802.11n (OTT VoIP)

				-				-	-	<b>,</b> -	• ,			
	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		Axial	40MHz	1	38	15.60	-29.40	-64.18	2.00	45.00	20.00	-25.00	T4	2.0, 3.2
			20MHz	1	40	15.26	-27.35		2.00	42.61	20.00	-22.61	T4	
	802.11n													
		Radial	40MHz	1	38	7.65	-34.10	-64.25	-64.25 N/A	41.75	20.00	-21.75	T4	2.0, 4.0
		Radiai	20MHz	1	40	7.76	-28.95			36.71	20.00	-16.71	T4	2.0, 4.0

#### **Table 9-22** Raw Data Results for 5GHz WIFI 802.11ac (OTT VoIP)

				Data i ii	Journey 1	0. 00		<b>02</b> 0	(0	~ <i>,</i>			
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	40MHz	1	38	15.71	-28.57	-64.18	1.76	44.28	20.00	-24.28	T4	2.0, 3.2
		20MHz	1	40	15.59	-27.51		1.88	43.10	20.00	-23.10	T4	
802.11ac													
	Radial	40MHz	1	38	7.89	-31.61	-64.25	.25 N/A	39.50	20.00	-19.50	T4	2.0, 4.0
		20MHz	1	40	7.27	-30.41			37.68	20.00	-17.68	T4	2.0, 4.0

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 34 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 34 01 76

#### II. Test Notes

#### A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- 3. Hearing Aid Mode (Phone→Call Settings→Additional Settings→Hearing aids) as well as Noise Suppression Mode (Phone→Call Settings→Additional Settings→Noise suppression) were set to ON for Frequency Response compliance
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled while testing 2G/3G/4G modes.
- 6. Licensed data modes and Bluetooth were disabled while testing WIFI modes.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

#### B. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

#### C. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

#### D. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Vocoder Configuration: WB AMR 6.60kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 12 at 3MHz is the worst-case for both the Axial and Radial probe orientations.

#### E. LTE TDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Power Class 3 Uplink-Downlink configuration: 1
- 4. Vocoder Configuration: WB AMR 6.60kbps
- 5. The worst-case bandwidth for each probe orientation is additionally tested on the low, low-mid, mid-high and high channels for those bandwidths. LTE Band 41 at 10MHz is the worst-case for both the Axial and Radial probe orientations.

#### F. WIFI


- 1. Radio Configuration
  - a. 802.11b: CCK, 5.5Mbps
  - b. 802.11g/a: BPSK, 6Mbps
  - c. 802.11n/ac 20MHz: BPSK, 6.5Mbps
  - d. 802.11n/ac 40MHz: 64-QAM, 135Mbps
- 2. Vocoder Configuration: NB AMR 12.2kbps
- 3. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both the Axial and Radial probe orientations.
- 4. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 3) is the worst-case for the Axial probe orientation. 802.11a (U-NII 1) is the worst-case for the Radial probe orientation.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 35 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 33 01 76

#### G. OTT VoIP

- 1. Vocoder Configuration: 6kbps
- 2. EDGE Configuration
  - a. MCS Index: 7
  - b. Number of TX slots: 2
- 3. HSPA Configuration:
  - a. Release: 6
  - b. 3GPP 34.121 Subtest 1
- 4. LTE FDD Configuration:
  - a. Power Configuration: TPC = "Max Power"
  - b. Radio Configuration: 16QAM, 1RB, 0RB offset
  - c. LTE Band 71 was the worst-case band from Table 7-5 and was used to test both Axial and Radial probe orientations.
  - d. The worst-case bandwidth for each probe orientation is additionally tested on the low and high channels for those bandwidths. LTE Band 71 at 15MHz is the worst-case for both the Axial and Radial probe orientations.
- 5. LTE TDD Configuration:
  - a. Power Configuration: TPC = "Max Power"
  - b. Radio Configuration: 16QAM, 1RB, 0RB offset
  - c. Power Class 3 Uplink-Downlink configuration: 1
  - d. The worst-case bandwidth for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those bandwidths. LTE Band 41 (Power Class 3) at 15MHz is the worst-case for both the Axial and Radial probe orientations.
- 6. WIFI Configuration:
  - a. Radio Configuration
    - i. 802.11b: CCK, 5.5Mbps
    - ii. 802.11g/a: BPSK, 6Mbps
    - iii. 802.11n/ac 20MHz: BPSK, 6.5Mbps
    - iv. 802.11n/ac 40MHz: 64-QAM, 135Mbps
  - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both the Axial and Radial probe orientations.
  - c. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 3) is the worst-case for both the Axial and Radial probe orientations.

# III. 1 kHz Vocoder Application Check




This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 36 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 30 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

# IV. T-Coil Validation Test Results

Table 9-23
Helmholtz Coil Validation Table of Results, 5/30/2018

Tienmore con validation rable of recoales, 0/00/2010						
Item	Target Result		Verdict			
Axial						
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.171	PASS			
Environmental Noise	< -58 dBA/m	-63.60	PASS			
Frequency Response, from limits	> 0 dB	0.70	PASS			
Radial						
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.275	PASS			
Environmental Noise	< -58 dBA/m	-64.53	PASS			
Frequency Response, from limits	> 0 dB	0.70	PASS			

Table 9-24 Helmholtz Coil Validation Table of Results, 6/2/2018

Item	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.170	PASS
Environmental Noise	< -58 dBA/m	-64.18	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS
Radial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.289	PASS
Environmental Noise	< -58 dBA/m	-64.25	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 37 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

# V. ABM1 Magnetic Field Distribution Scan Overlays




Figure 9-1
T-Coil Scan Overlay Magnetic Field Distributions

## Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 38 of 78
1M1805210108-11-R1 7NF	05/30/2018 - 06/07/2018	Portable Handset		raye 30 Ul 70

 $\hbox{@}$  2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

# 10. MEASUREMENT UNCERTAINTY

Table 10-1
Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty	Combined standard uncertainty, uc (k=1)						0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

#### Notes:

- 1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 39 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 39 01 76

# 11. EQUIPMENT LIST

Table 11-1 Equipment List

	Edulphioni Liot						
Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number	
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/11/2017	Biennial	4/11/2019	7BFNM32	
Listen	SoundConnect	Microphone Power Supply	N/A		N/A	0899-PS150	
Listen	SoundConnect	Microphone Power Supply	12/2/2016	Biennial	12/2/2018	PS2612	
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/11/2017	Biennial	4/11/2019	23528889	
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	162125	
Seekonk	NC-100	Torque Wrench (8" lb)	9/1/2016	Biennial	9/1/2018	21053	
TEM	C63.19	Helmholtz Coil	12/7/2016	Biennial	12/7/2018	925	
TEM	Radial T-Coil Probe	Radial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1130	
TEM	Axial T-Coil Probe	Axial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1124	
TEM		HAC System Controller with Software	N/A		N/A	N/A	
TEM		HAC Positioner	N/A		N/A	N/A	

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 40 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 40 01 76

# 12. TEST DATA

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 410176




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

#### Noise Spectrum



#### Frequency Response



#### Results

Verification 1kHz Intensity	-10.171 dB	<b>✓</b>	Max/Min	-9.5/-10.5
Verification ABM2	-63.6 dB	V	Maximum	-58.0
Frequency Response Margin	700m dB	<b>✓</b>	Tolerance curves	Aligned Data

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 42 01 70




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

#### Noise Spectrum



## Frequency Response



#### Results

Verification 1kHz Intensity	-10.17 dB	~	Max/Min	-9.5/-10.5	
Verification ABM2	-64.18 dB	~	Maximum	-58.0	
Frequency Response Margin	800m dB	•	Tolerance curves	Aligned Data	

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 43 01 76




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

#### Noise Spectrum



#### Frequency Response



## Results

Verification 1kHz Intensity	-10.275 dB	•	Max/Min	-9.5/-10.5
Verification ABM2	-64.53 dB	•	Maximum	-58.0
Frequency Response Margin	700m dB	$\checkmark$	Tolerance curves	Aligned Data

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 44 01 76




Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


#### Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

#### Noise Spectrum



## Frequency Response



## Results

Verification 1kHz Intensity	-10.289 dB	$\checkmark$	Max/Min	-9.5/-10.5
Verification ABM2	-64.25 dB	$\checkmark$	Maximum	-58.0
Frequency Response Margin	800m dB	$\checkmark$	Tolerance curves	Aligned Data

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 45 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 43 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM 850Channel: 128

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 46 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 40 01 70



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011


#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM 1900Channel: 512

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 47 01 70



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016


#### **Test Configuration:**

Mode: UMTS Band V

Aligned Response - P.50

Channel: 4233

• Speech Signal: ITU-T P.50 Artificial Voice



### PCTEST 2018

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 48 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 40 01 70

1.35 dB

Aligned Data

Tolerance curves



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS Band IV

Channel: 1412

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 49 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 43 01 70



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS Band II

Channel: 9538

Speech Signal: ITU-T P.50 Artificial Voice



### PCTEST 2018

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 50 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 30 01 76

Tolerance curves



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: LTE FDD Band 12Bandwidth: 3MHz

Channel: 23025

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 51 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 31 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: LTE TDD Band 41Bandwidth: 10MHz

Channel: 39750

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	⊕ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 52 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 32 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

Channel: 6

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 53 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 33 01 76



Type: Portable Handset Serial: 05443


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

- Mode: 5GHz WIFI
- Standard: IEEE 802.11a (U-NII 3)
- Channel: 157
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 34 01 76



Type: Portable Handset Serial: 05443


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

#### **Test Configuration:**

- VolP Application: Google Duo
- Mode: EDGE 850
- Channel: 190
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 55 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 55 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

### **Test Configuration:**

Mode: GSM 850Channel: 128



FCC ID: ZNFQ610TA	PETEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Page 50 01 76



Type: Portable Handset Serial: 05443


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: GSM 1900Channel: 512



FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 57 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 37 01 76



Type: Portable Handset Serial: 05443


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS Band VChannel: 4132



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 58 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 30 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS Band IVChannel: 1312



FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 39 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: UMTS Band IIChannel: 9538



FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 00 01 76



Type: Portable Handset Serial: 05443


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

## **Test Configuration:**

Mode: LTE FDD Band 12
Bandwidth: 3MHz
Channel: 23095



# Results

ABM1	-640m	dB	lacksquare	Minimum	-18.0
ABM2	-36.22	dB	<b>✓</b>	Maximum	0.0
SNNR	35.58	dB	$\checkmark$	Minimum	20.0

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 010176



Type: Portable Handset Serial: 05443


Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

## **Test Configuration:**

Mode: LTE TDD Band 41Bandwidth: 10MHzChannel: 40185



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 02 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

Channel: 6

#### Noise Spectrum -20.0 -25.0 -30.0 -35.0 -40.0 --45.0-E -55.0-E -55.0--60.0--65.0 -70.0 --75.0--80.0 -85.0 -90.0 [Hz] Results Minimum -18.0 ABM1 -7.62 dB ABM2 -33.08 dB 0.0

25.46 dB

Minimum

20.0

#### PCTEST 2018

FCC ID: ZNFQ610TA	PETEST VALUE CALLED TO THE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 63 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 03 01 76

SNNR



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

## **Test Configuration:**

Mode: 5GHz WIFI

• Standard: IEEE 802.11a (U-NII 1)

Channel: 48

#### Noise Spectrum -10.0 -15.0 -20.0 -25.0 --30.0 --35.0 --40.0 --45.0-E -50.0-E -55.0--60.0--65.0 --70.0 --75.0 -80.0 -85.0 -90.0 -100 [Hz] Results -18.0 ABM1 -8.11 dB Minimum 0.0 ABM2 -39.13 dB Maximum SNNR 31.02 dB Minimum 20.0

FCC ID: ZNFQ610TA	PETEST	HAC (T-COIL) TEST REPORT	<b>⊕</b> LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 04 01 76



Type: Portable Handset Serial: 05443

Measurement Standard: ANSI C63.19-2011

#### Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

#### **Test Configuration:**

VoIP Application: Google Duo

Mode: EDGE 850Channel: 190

#### Noise Spectrum -20.0 -25.0 -30.0 -35.0 -40.0 -45.0-E -55.0-E -55.0--60.0--65.0 -70.0 -75.0 -80.0 -85.0 -90.0 -100 [Hz] Results -18.0 ABM1 7.64 dB Minimum ABM2 -25.05 dB 0.0

32.69 dB

Minimum

20.0


#### PCTEST 2018

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Faye 03 01 76

SNNR

# 13. CALIBRATION CERTIFICATES

FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 00 01 76



FCC ID: ZNFQ610TA	PCTEST*	HAC (T-COIL) TEST REPORT	( LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 67 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		rage or or ro

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

## HCATEMC TEM 1124 Dec-07-2016



ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01

# REPORT OF CALIBRATION

**TEM Consulting LP Axial T Coil Probe** Model No.: Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab. I. D. No: 80578

Probe Sensitivity measured with	h Heimheit	z Call			
Helmholtz Coil;			Bafora & afte	r data sam s	: <b>X</b>
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	Α	Ambient Temperature:	20.2	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambient Pressure:	99.1	кP«
			Calibration Date:	7-D••-16	
Probe Sensitivity at	1000	Hz.			
WSB	-60.23	a BV/A/m	Report Number:	27068	-3
	0.974	m V/A/ m	Control Number:	27068	
Probe resistance	904	Oh m •			

Graph represents Probes Frequency Response

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

**Axial Probe Response**  Measured Probe Resp. 20 15 10 Magnitude (dB) 5 0 -5 -10 -15 -20 10000 Freq. (Hz)

The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Felix Christopher Calibrated on WCCL system type 9700

Rev. 7.0 Jan. 24, 2014 Dec. # 1038 HCATEMC

#### Page 1 of 2

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 68 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 00 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

# HCATEMC\_TEM 1124\_Dec-07-2016

## West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

# Calibration Data Record

Model No.: Axial T Coil Probe TEM Consulting LP Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab.

Test	Function	Tolerance		Measured values		
				Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.23		
2.0	Probe Level Linearity	Rof. (0 a B)	a B 6 0 -6 -12	6.03 0.00 -6.03 -12.05		
3.0	Probe Frequency Response	Ref. (0 a B)	H <sub>2</sub> 100 126 158 200 251 316 398 501 631 794 1000 1259 1585 1995 2512 3162 3981 5012 6310 7943 10000	-19.8 -18.0 -16.0 -13.9 -12.0 -9.9 -8.0 -6.0 -4.0 -2.0 0.0 2.0 4.0 6.0 7.9 9.9 11.9 13.9 15.9 18.0 20.2		

Instruments used for celibre	tion:		Date or Cal.	Traceability No.	Dua Dato
HP	34401A	S/N 36064102	1-Oct-2016	,287708	1-Oct-2017
HP	34401 A	S/N 36102471	1-Oet-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oct-2016	683/284413-14	1-Oct-2017

Cal. Date: 7-Dec-2016


Tested by: Felix Christopher

Calibrated on WCCL system type 9700

Rev. 7.0 Jan. 24, 2014 Dec. # 1038 HCATEMC

## Page 2 of 2

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 69 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 09 01 70



FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 70 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 10 01 10

#### HCRTEMC TEM-1130 Dec-07-2016



ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01

# REPORT OF CALIBRATION


TEM Consulting LP Radial T Coil Probe Model No.: Radial T Coil Probe Serial No.: TEM-1130

I. D. No: 80579 Company: PCTEST Engineering Lab.

Probe Sensitivity measured with	h Helmholt	z Coll			
Helmholtz Coil;			Botoro & atte	r data same	: <b>X</b>
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	Α	Ambient Temperature:	20.2	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambient Pressure:	99.1	кP«
			Calibration Date:	7-D••-16	
Probe Sensitivity at	1000	Hz.			
Was	-60.27	aBV/A/™	Report Number:	27068	-2
	0.969	m V/A/m	Control Number:	27068	
Proberesistance	902	Oh m •			
he above listed instrument meets or e	xceeds th	ne tested manufact	urer's specifications.		
is Calibration is traceable through NIST test numbers	:	683/284413-14	•		

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016

Felix Christopher Calibrated on WCCL system type 9700 Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

## Page 1 of 2

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 71 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage / 1 01 / 6

© 2018 PCTEST Engineering Laboratory, Inc.

**REV 3.2.M** 

# HCRTEMC\_TEM-1130\_Dec-07-2016

## West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

# Calibration Data Record

TEM Consulting LP Radial T Coil Probe Model No.: Radial T Coil Probe Serial No.: TEM-1130

Company: PCTEST Engineering Lab.

Test	Function	Tolera	Tolerance		Measured values		
				Before	Out	Remarks	
1.0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.27			
2.0	Probe Level Linearity	Røf. (0 dB)	a B 6 0 -6 -12	6.03 0.00 -6.03 -12.06			
3.0	Probe Frequency Response	Ror. (0 d B)	H <sub>2</sub> 100 126 158 200 251 316 398 501 631 794 1000 1259 1585 1995 2512 3162 3981 5012 6310 7943 10000	-19.9 -18.0 -16.0 -13.9 -12.0 -10.0 -8.0 -6.0 -4.0 -2.0 0.0 2.0 4.0 6.0 7.9 9.9 11.9 13.9 15.9 18.0 20.2			

Instruments used for celibration	ın:		Date or Cal.	Tracesbility No.	Dua Data
HP	34401A	S/N 36064102	1-Oct-2016	,287708	1-Oct-2017
HP	34401A	S/N 36102471	1-Oet-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oct-2016	683/284413-14	1-Oat-2017

Call Date: 7-Dac-2016 Test

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Laber Inc.

Tested by: Fellx Christopher

Ray. 7.0 Jan. 24, 2014 Day. # 1038 HCRTEMC

## Page 2 of 2

FCC ID: ZNFQ610TA	PETEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 72 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 72 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

# 14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 73 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		rage 73 01 76

# 15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
- Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- 8. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, " IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, " U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
- 13. EHIMA GSM Project, Development phase, Project Report (1<sup>st</sup> part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- 14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- 15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.

FCC ID: ZNFQ610TA	PETEST	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 74 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 74 01 76

- Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- 19. Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.
- Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7<sup>th</sup> International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- 28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFQ610TA	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 75 of 78
1M1805210108-11-R1.ZNF	05/30/2018 - 06/07/2018	Portable Handset		Fage 13 01 16