

TEST REPORT

Reference No..... : WTN22X12256062W002
FCC ID : 2BBU5-ZG-JJM1215A
Applicant : Guangdong Zhangong Electric Technology Co., Ltd.
Address..... : 7th Floor,Building29,Zhifugarden,ShundeDistrict, FoshanCity,
GuangdongProvince, China
Manufacturer : The same as Applicant
Address..... : The same as Applicant
Product Name : Furniture socket
Model No..... : ZG-JJM/12/15A
Standards : KDB 680106 D01 V03
Date of Receipt sample : 2022-12-20
Date of Test..... : 2022-12-20 to 2023-05-23
Date of Issue : 2023-05-23
Test Report Form No. : WTX_KDB 680106_D01_V03W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:


Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:



Mike Shi



Silin Chen

TABLE OF CONTENTS

1. GENERAL INFORMATION..... 4

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

1.2 AUXILIARY EQUIPMENT LIST AND DETAILS 5

1.3 TEST EQUIPMENT LIST AND DETAILS 6

2. RF EXPOSURE TEST REPORT..... 7

2.1 STANDARD APPLICABLE..... 7

2.2 TEST CONDITIONS..... 7

2.3 TEST PROCEDURE 8

2.4 TEST RESULT..... 9

2.5 MEASUREMENT UNCERTAINTY 11

2.6 TEST PHOTOS..... 12

APPENDIX PHOTOGRAPHS 13

Report version

Version No.	Date of issue	Description
Rev.00	2023-05-23	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Furniture socket
Trade Name:	/
Model No.:	ZG-JJM/12/15A
Adding Model:	ZG-PDU00/10A/15A, ZG-PDUG1/10A/15A, ZG-PDUG1/10A/15A, ZG-PDUC3/10A/15A, ZG-PDUC9/10A/15A, ZG-PDUA/10A/15A, ZG-PDUY/10A/15A, ZG-PDUM/12A/15A, ZG-JJ/12A/15A, ZG-HG/12A/15A, ZG-ZJ/12A/15A, ZG-SJ/12A/15A, ZG-DQ/12A/15A, ZG-PC/12A/15A, ZG-PDU JO0/12A/15A
Battery Capacity	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model ZG-JJM/12/15A, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	112-205kHz
Modulation Type:	ASK
Antenna Type:	Coil Antenna
Wireless output:	15W(MAX)

1.2 Auxiliary Equipment List and Details

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
AC CABLE	1.9	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Wireless charging tester	/	YBZ	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200AC	180ZX10226	2021-05-20	2024-05-19
Note: The deviation response is 0.8dB.					

2. RF Exposure Test Report

2.1 Standard Applicable

According to §1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)



Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

2.2 Test Conditions

Test Mode	Description	Remark	Power Supply Mode
TM1	Wireless charging	Wireless output(5W)	/
TM2	Wireless charging	Wireless output(7.5W)	/
TM3	Wireless charging	Wireless output(15W)	/
Note: The EUT was tested with empty load, half load, and full load, and recorded the worst mode (full load) data in the report.			
Measurement Distance:	15 cm and 20 cm		

2.3 Test Procedure



- The measurement probe was placed at test distance (15 cm for A, B, C, D, F and 20 cm for E) which is between the edge of the charger and the geometric center of probe.
- The highest emission level was recorded at the measurement points (A, B, C, D, E, F).
- The EUT was measured according to the distance of KDB 680106 D01 v03r01.

2.4 Test Result

The EUT complies with item 5.2 of KDB 680106 D01V03

1. Power transfer frequency is less than 1 MHz
Yes, the device operates in the frequency range from 112kHz to 205kHz.
2. Output power from each primary coil is less than or equal to 15 watts
Yes, the maximum output power of the primary coil is equal to 15W.
3. The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils
Yes, the client device includes only single primary coils.
4. Client device is inserted in or placed directly in contact with the transmitter
Yes, Client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
Yes, it is mobile exposure conditions only.
6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
Yes, The EUT field strength levels are less than 50% of the MPE limit, refer to test TM1list, and the coils can't be transmitted simultaneously.

Test Mode: TM1 (worst case)

Electric Field Emissions			
Test Position	Measure Value (V/m)	Limit(V/m)	50% Limit (V/m)
Point E	6.85	614	307
Point F	2.96	614	307
Point A	4.12	614	307
Point B	2.82	614	307
Point C	3.18	614	307
Point D	2.89	614	307
Magnetic Field Emissions			
Test Position	Measure Value (A/m)	Limit(A/m)	50% Limit (A/m)
Point E	0.51	1.63	0.815
Point F	0.23	1.63	0.815
Point A	0.38	1.63	0.815
Point B	0.24	1.63	0.815
Point C	0.20	1.63	0.815
Point D	0.21	1.63	0.815

2.5 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Electric Field Emissions	Radiated	±1.56 (V/m)
Magnetic Field Emissions	Radiated	±0.08(A/m)

2.6 Test Photos



APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****