

APPENDIX F: LTE AND NR LOWER BANDWIDTH RF CONDUCTED POWERS

All conducted power measurements for 4G/5G Sub6 WWAN technologies and bands in this section were performed by setting *Reserve_power_margin* (Qualcomm® Smart Transmit EFS entry) to 0 dB, so that the EUT transmits continuously at minimum (Plimit, maximum tune up output power Pmax).

F.1 LTE Lower Bandwidth RF Conducted Powers

F.1.1 LTE Band 71

Table F-1
LTE Band 71 Measured P_{Max} for all DSI - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.57	0	0
	1	36	24.49		0
	1	74	24.24		0
	36	0	23.70	0-1	1
	36	18	23.64		1
	36	37	23.47		1
	75	0	23.53		1
16QAM	1	0	24.05	0-1	1
	1	36	23.97		1
	1	74	23.77		1
	36	0	22.66	0-2	2
	36	18	22.66		2
	36	37	22.51		2
	75	0	22.58		2
64QAM	1	0	22.80	0-2	2
	1	36	22.86		2
	1	74	22.50		2
	36	0	21.81	0-3	3
	36	18	21.71		3
	36	37	21.55		3
	75	0	21.58		3

Note: LTE Band 71 at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 1 of 55

Table F-2
LTE Band 71 Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.85	24.66	24.48	0	0
	1	25	24.65	24.66	24.41		0
	1	49	24.62	24.45	24.26		0
	25	0	23.94	23.76	23.56	0-1	1
	25	12	23.88	23.72	23.52		1
	25	25	23.79	23.63	23.45		1
	50	0	23.84	23.66	23.43	0-1	1
1	0	24.30	24.10	23.84	1		
1	25	24.03	23.92	23.71	1		
16QAM	1	49	24.00	23.89	23.69	0-1	1
	25	0	22.99	22.80	22.62		2
	25	12	22.93	22.79	22.62		2
	25	25	22.85	22.68	22.50	0-2	2
	50	0	22.88	22.69	22.50		2
	1	0	23.17	22.93	22.68		0-2
	1	25	23.03	22.89	22.70	2	
1	49	22.91	22.75	22.60	2		
64QAM	25	0	21.95	21.84	21.60	0-3	3
	25	12	21.90	21.77	21.59		3
	25	25	21.84	21.71	21.48		3
	50	0	21.87	21.73	21.45		3

Table F-3
LTE Band 71 Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.80	24.59	24.35	0	0
	1	12	24.78	24.60	24.40		0
	1	24	24.84	24.55	24.36		0
	12	0	23.99	23.74	23.46	0-1	1
	12	6	23.96	23.80	23.54		1
	12	13	23.92	23.76	23.52		1
16QAM	25	0	23.97	23.76	23.50	0-1	1
	1	0	24.27	23.89	23.68		1
	1	12	24.09	23.95	23.70		1
	1	24	24.15	23.93	23.70	0-2	1
	12	0	23.05	22.77	22.48		2
	12	6	23.03	22.77	22.56		2
64QAM	12	13	22.97	22.76	22.53	0-2	2
	25	0	22.99	22.78	22.51		2
	1	0	23.10	22.76	22.64	0-2	2
	1	12	22.96	22.85	22.61		2
	1	24	23.01	22.73	22.63	0-3	2
	12	0	22.10	21.82	21.53		3
12	6	22.08	21.86	21.57	3		
12	13	22.01	21.84	21.57	3		
	25	0	21.97	21.80	21.52		3

FCC ID A3LSMA426U



SAR EVALUATION REPORT



Approved by:
Quality Manager

Test Dates:
01/12/21 – 02/19/21

DUT Type:
Portable Handset

APPENDIX F:
Page 2 of 55

F.1.2 LTE Band 12

Table F-4
LTE Band 12 Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.77	22.60	22.52	0	0
	1	12	22.76	22.56	22.48		0
	1	24	22.60	22.44	22.35		0
	12	0	21.83	21.69	21.57	0-1	1
	12	6	21.73	21.62	21.58		1
	12	13	21.67	21.56	21.49		1
16QAM	25	0	21.76	21.57	21.61	0-1	1
	1	0	22.15	21.88	21.93		1
	1	12	22.02	21.93	21.84		1
	1	24	21.97	21.83	21.65	0-2	1
	12	0	20.90	20.72	20.64		2
	12	6	20.82	20.67	20.63		2
64QAM	12	13	20.74	20.58	20.60	0-2	2
	25	0	20.71	20.65	20.48		2
	1	0	21.05	21.00	20.77		0-2
	1	12	21.08	20.84	20.70	2	
	1	24	20.93	20.72	20.62	2	
	64QAM	12	0	19.84	19.71	19.58	0-3
12		6	19.82	19.66	19.59	3	
12		13	19.75	19.59	19.51	3	
25		0	19.69	19.68	19.52		3

Table F-5
LTE Band 12 Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.78	22.63	22.51	0	0
	1	7	22.67	22.52	22.44		0
	1	14	22.61	22.47	22.36		0
	8	0	21.78	21.69	21.53	0-1	1
	8	4	21.71	21.62	21.56		1
	8	7	21.72	21.61	21.45		1
	15	0	21.76	21.60	21.54		1
16QAM	1	0	22.13	21.94	21.92	0-1	1
	1	7	22.07	21.81	21.73		1
	1	14	22.02	21.82	21.61		1
	8	0	20.93	20.71	20.65	0-2	2
	8	4	20.83	20.66	20.59		2
	8	7	20.79	20.64	20.55		2
	15	0	20.78	20.58	20.51		2
64QAM	1	0	21.03	20.88	20.73	0-2	2
	1	7	21.08	20.86	20.69		2
	1	14	20.89	20.70	20.63		2
	8	0	19.87	19.67	19.61	0-3	3
	8	4	19.82	19.61	19.52		3
	8	7	19.70	19.58	19.58		3
	15	0	19.81	19.68	19.58		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 3 of 55

Table F-6
LTE Band 12 Measured P_{Max} for all DSI - 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.66	22.47	22.44	0	0
	1	2	22.68	22.49	22.32		0
	1	5	22.56	22.44	22.33		0
	3	0	22.61	22.42	22.25		0
	3	2	22.62	22.39	22.32		0
	3	3	22.59	22.31	22.26		0
	6	0	21.72	21.46	21.42	0-1	1
16QAM	1	0	21.95	21.69	21.61	0-1	1
	1	2	22.09	21.91	21.81		1
	1	5	22.01	21.71	21.62		1
	3	0	21.85	21.74	21.63		1
	3	2	21.92	21.62	21.60		1
	3	3	21.93	21.65	21.58		1
	6	0	20.72	20.62	20.43	0-2	2
64QAM	1	0	20.86	20.79	20.53	0-2	2
	1	2	20.97	20.78	20.71		2
	1	5	20.83	20.64	20.57		2
	3	0	20.84	20.62	20.56		2
	3	2	20.86	20.57	20.55		2
	3	3	20.82	20.59	20.48		2
	6	0	19.76	19.51	19.39	0-3	3

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 4 of 55

F.1.3 LTE Band 13

Table F-7
LTE Band 13 Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.05	0	0
	1	12	23.05		0
	1	24	23.17		0
	12	0	22.03	0-1	1
	12	6	22.05		1
	12	13	22.12		1
	25	0	22.04		1
16QAM	1	0	22.26	0-1	1
	1	12	22.37		1
	1	24	22.45		1
	12	0	21.08	0-2	2
	12	6	21.16		2
	12	13	21.20		2
	25	0	21.11		2
64QAM	1	0	21.17	0-2	2
	1	12	21.10		2
	1	24	21.25		2
	12	0	20.09	0-3	3
	12	6	20.11		3
	12	13	20.18		3
	25	0	20.05		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 5 of 55

F.1.4 LTE Band 14

Table F-8
LTE Band 14 Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.18	0	0
	1	12	24.22		0
	1	24	24.11		0
	12	0	23.23	0-1	1
	12	6	23.32		1
	12	13	23.23		1
	25	0	23.24		1
16QAM	1	0	23.52	0-1	1
	1	12	23.51		1
	1	24	23.49		1
	12	0	22.33	0-2	2
	12	6	22.35		2
	12	13	22.30		2
	25	0	22.28		2
64QAM	1	0	22.48	0-2	2
	1	12	22.63		2
	1	24	22.45		2
	12	0	21.37	0-3	3
	12	6	21.43		3
	12	13	21.27		3
	25	0	21.33		3

Note: LTE Band 14 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of the element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 6 of 55

F.1.5 LTE Band 26

Table F-9
LTE Band 26 (Cell) Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.97	23.90	24.01	0	0
	1	25	23.81	23.97	23.93		0
	1	49	23.80	24.02	23.99		0
	25	0	22.83	22.95	22.93	0-1	1
	25	12	22.94	23.07	23.02		1
	25	25	22.88	23.08	22.95		1
	50	0	22.87	22.99	22.88		1
16QAM	1	0	23.43	23.39	23.60	0-1	1
	1	25	23.23	23.38	23.52		1
	1	49	23.30	23.34	23.47		1
	25	0	21.86	21.96	21.98	0-2	2
	25	12	22.05	22.13	22.02		2
	25	25	21.96	22.12	22.05		2
	50	0	21.92	22.04	21.93		2
64QAM	1	0	22.38	22.28	22.37	0-2	2
	1	25	22.20	22.35	22.21		2
	1	49	22.35	22.33	22.18		2
	25	0	20.90	21.02	21.01	0-3	3
	25	12	21.03	21.09	21.06		3
	25	25	20.94	21.10	21.08		3
	50	0	20.94	21.00	20.92		3

Table F-10
LTE Band 26 (Cell) Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.82	23.91	23.97	0	0
	1	12	23.90	23.75	23.95		0
	1	24	23.83	23.85	23.92		0
	12	0	22.94	22.97	23.03	0-1	1
	12	6	23.07	22.96	23.03		1
	12	13	22.96	23.00	23.03		1
	25	0	22.94	22.92	23.00		1
16QAM	1	0	23.08	23.15	23.17	0-1	1
	1	12	23.34	23.07	23.11		1
	1	24	23.15	23.15	23.12		1
	12	0	22.02	21.98	22.06	0-2	2
	12	6	22.03	22.04	22.13		2
	12	13	22.03	22.11	22.04		2
	25	0	21.94	21.94	22.07		2
64QAM	1	0	22.33	22.25	22.24	0-2	2
	1	12	22.24	22.08	22.22		2
	1	24	22.04	22.22	22.31		2
	12	0	21.00	20.97	21.04	0-3	3
	12	6	21.04	21.01	21.11		3
	12	13	21.02	21.05	21.05		3
	25	0	20.93	20.95	21.07		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 7 of 55

Table F-11
LTE Band 26 (Cell) Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.93	23.72	23.97	0	0
	1	7	23.86	23.89	23.96		0
	1	14	23.80	23.99	24.01		0
	8	0	22.91	22.91	22.98	0-1	1
	8	4	22.94	22.99	23.04		1
	8	7	22.90	22.98	23.00		1
	15	0	22.97	22.92	23.01		1
16QAM	1	0	23.00	23.12	23.21	0-1	1
	1	7	23.05	23.29	23.03		1
	1	14	23.09	23.27	23.13		1
	8	0	22.04	21.99	22.08	0-2	2
	8	4	22.07	22.09	22.13		2
	8	7	22.01	22.06	22.09		2
	15	0	21.99	21.93	22.04		2
64QAM	1	0	22.25	22.12	22.22	0-2	2
	1	7	22.07	22.10	22.25		2
	1	14	22.13	22.21	22.22		2
	8	0	20.94	20.97	21.02	0-3	3
	8	4	20.99	21.09	21.06		3
	8	7	20.95	21.02	21.01		3
	15	0	21.01	20.96	21.10		3

Table F-12
LTE Band 26 (Cell) Measured P_{Max} for all DSI - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.75	23.75	23.78	0	0
	1	2	23.78	23.86	23.79		0
	1	5	23.77	23.73	23.77		0
	3	0	23.72	23.73	23.78		0
	3	2	23.77	23.78	23.86		0
	3	3	23.71	23.74	23.75		0
	6	0	22.89	22.93	22.92	0-1	1
16QAM	1	0	23.22	23.18	23.16	0-1	1
	1	2	23.15	23.20	23.54		1
	1	5	23.15	23.27	23.26		1
	3	0	23.13	23.00	23.01		1
	3	2	23.16	23.09	23.15		1
	3	3	23.01	23.13	23.17		1
	6	0	21.99	22.01	21.94	0-2	2
64QAM	1	0	22.04	21.99	22.09	0-2	2
	1	2	22.08	22.15	22.05		2
	1	5	21.94	22.09	22.01		2
	3	0	22.00	21.93	22.01		2
	3	2	22.06	22.04	22.05		2
	3	3	21.90	21.98	22.02		2
	6	0	20.98	20.97	21.03	0-3	3

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 8 of 55

F.1.6 LTE Band 5

Table F-13
LTE Band 5 (Cell) Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.81	22.74	22.69	0	0
	1	12	22.65	22.87	22.74		0
	1	24	22.65	22.81	22.72		0
	12	0	21.90	21.86	21.77	0-1	1
	12	6	21.94	21.95	21.87		1
	12	13	21.92	21.94	21.85		1
	25	0	21.93	21.92	21.82		1
16QAM	1	0	22.02	22.14	22.01	0-1	1
	1	12	22.01	22.19	21.97		1
	1	24	21.97	22.19	22.07		1
	12	0	20.92	20.91	20.87	0-2	2
	12	6	21.02	21.03	20.95		2
	12	13	21.07	21.00	20.89		2
	25	0	20.97	20.94	20.84		2
64QAM	1	0	21.04	21.21	21.07	0-2	2
	1	12	21.14	21.15	20.92		2
	1	24	20.98	21.13	21.12		2
	12	0	19.97	19.92	19.87	0-3	3
	12	6	20.01	19.95	19.96		3
	12	13	19.96	19.98	19.84		3
	25	0	19.94	19.91	19.89		3

Table F-14
LTE Band 5 (Cell) Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.67	22.83	22.78	0	0
	1	7	22.90	22.89	22.64		0
	1	14	22.77	22.81	22.67		0
	8	0	21.89	21.87	21.76	0-1	1
	8	4	21.92	21.89	21.79		1
	8	7	21.94	21.98	21.89		1
	15	0	22.01	21.87	21.79		1
16QAM	1	0	22.08	22.18	22.00	0-1	1
	1	7	22.00	22.20	21.99		1
	1	14	22.03	22.27	22.03		1
	8	0	20.97	20.95	20.82	0-2	2
	8	4	21.05	20.97	20.91		2
	8	7	20.99	21.04	20.90		2
	15	0	20.97	20.90	20.78		2
64QAM	1	0	21.05	21.05	20.91	0-2	2
	1	7	21.13	21.12	21.03		2
	1	14	21.06	21.07	21.06		2
	8	0	19.97	19.94	19.79	0-3	3
	8	4	20.02	19.97	19.83		3
	8	7	19.99	19.99	19.87		3
	15	0	20.04	19.94	19.82		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 9 of 55

Table F-15
LTE Band 5 (Cell) Measured P_{Max} for all DSI - 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.62	22.72	22.57	0	0
	1	2	22.72	22.93	22.65		0
	1	5	22.62	22.78	22.61		0
	3	0	22.75	22.72	22.58		0
	3	2	22.70	22.81	22.69		0
	3	3	22.77	22.77	22.61		0
	6	0	21.90	21.79	21.77		1
16QAM	1	0	22.02	22.17	21.95	0-1	1
	1	2	22.24	22.22	22.11		1
	1	5	22.11	22.13	21.91		1
	3	0	22.00	21.93	21.89		1
	3	2	22.13	22.02	21.80		1
	3	3	21.98	21.83	21.89		1
	6	0	21.04	20.77	20.79		2
64QAM	1	0	21.03	21.23	20.84	0-2	2
	1	2	21.10	21.10	20.93		2
	1	5	21.01	21.03	20.86		2
	3	0	20.97	20.93	20.82		2
	3	2	21.03	21.00	20.89		2
	3	3	20.94	20.92	20.82		2
	6	0	19.91	19.90	19.81		0-3

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 10 of 55		

F.1.7 LTE Band 66

Table F-16

LTE Band 66 (AWS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.98	22.71	22.94	0	0
	1	36	23.10	22.71	22.95		0
	1	74	22.99	22.70	23.14		0
	36	0	22.24	21.89	22.14	0-1	1
	36	18	22.18	21.86	22.11		1
	36	37	22.05	21.76	22.19		1
	75	0	22.17	21.79	22.17		1
16QAM	1	0	22.31	21.86	22.45	0-1	1
	1	36	22.37	22.07	22.45		1
	1	74	22.26	22.08	22.58		1
	36	0	21.24	20.87	21.12	0-2	2
	36	18	21.24	20.89	21.15		2
	36	37	21.05	20.75	21.20		2
	75	0	21.11	20.84	21.18		2
64QAM	1	0	21.52	20.81	21.25	0-2	2
	1	36	21.04	20.86	21.35		2
	1	74	21.15	21.03	21.36		2
	36	0	20.24	19.88	20.13	0-3	3
	36	18	20.23	19.85	20.18		3
	36	37	20.00	19.80	20.17		3
	75	0	20.17	19.80	20.17		3

Table F-17

LTE Band 66 (AWS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.01	22.76	22.96	0	0
	1	12	23.03	22.75	23.00		0
	1	24	22.91	22.72	23.02		0
	12	0	22.18	21.93	22.11	0-1	1
	12	6	22.18	21.91	22.18		1
	12	13	22.04	21.83	22.12		1
	25	0	22.18	21.81	22.15		1
16QAM	1	0	22.33	22.10	22.29	0-1	1
	1	12	22.32	22.07	22.34		1
	1	24	22.24	22.07	22.29		1
	12	0	21.19	20.90	21.12	0-2	2
	12	6	21.20	20.91	21.20		2
	12	13	21.05	20.87	21.11		2
	25	0	21.13	20.88	21.10		2
64QAM	1	0	21.23	21.04	21.22	0-2	2
	1	12	21.30	21.01	21.27		2
	1	24	21.16	20.98	21.27		2
	12	0	20.20	19.95	20.09	0-3	3
	12	6	20.16	19.93	20.20		3
	12	13	20.03	19.86	20.14		3
	25	0	20.16	19.88	20.16		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 11 of 55

Table F-18

LTE Band 66 (AWS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.06	22.77	23.05	0	0
	1	7	22.97	22.77	23.06		0
	1	14	23.10	22.73	23.02		0
	8	0	22.26	21.86	22.13	0-1	1
	8	4	22.22	21.87	22.14		1
	8	7	22.15	21.85	22.10		1
16QAM	15	0	22.20	21.85	22.07	1	
	1	0	22.61	22.15	22.33	0-1	1
	1	7	22.44	22.05	22.35		1
	1	14	22.35	22.09	22.29		0-2
	8	0	21.36	20.96	21.18	2	
	8	4	21.26	20.93	21.22	2	
64QAM	8	7	21.20	20.87	21.15	0-2	2
	15	0	21.25	20.90	21.12		2
	1	0	21.37	21.05	21.28	0-2	2
	1	7	21.29	21.03	21.30		2
	1	14	21.19	20.98	21.30		2
	64QAM	8	0	20.35	19.95	20.17	0-3
8		4	20.26	19.93	20.22	3	
8		7	20.20	19.87	20.16	3	
15		0	20.23	19.90	20.12	3	

Table F-19

LTE Band 66 (AWS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.99	22.72	22.93	0	0
	1	2	23.11	22.77	23.03		0
	1	5	23.05	22.68	22.93		0
	3	0	23.03	22.66	22.91		0
	3	2	23.04	22.68	22.97		0
	3	3	23.02	22.65	22.93		0
	6	0	22.15	21.78	22.06		0-1
16QAM	1	0	22.46	22.02	22.25	0-1	1
	1	2	22.48	22.13	22.37		1
	1	5	22.42	22.01	22.35		1
	3	0	22.16	21.80	22.06		1
	3	2	22.18	21.86	22.14		1
	3	3	22.21	21.75	22.04		1
	6	0	21.25	20.87	21.17		0-2
64QAM	1	0	21.30	20.96	21.19	0-2	2
	1	2	21.40	21.02	21.27		2
	1	5	21.29	20.93	21.18		2
	3	0	21.28	20.94	21.11		2
	3	2	21.36	21.01	21.24		2
	3	3	21.24	20.90	21.21		2
	6	0	20.18	19.79	20.09		0-3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 12 of 55

Table F-20

LTE Band 66 (AWS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.93	20.59	20.85	0	0
	1	36	20.95	20.66	20.92		0
	1	74	20.87	20.62	20.98		0
	36	0	21.10	20.79	20.95	0-1	0
	36	18	21.13	20.77	21.02		0
	36	37	20.98	20.76	21.00		0
16QAM	75	0	21.07	20.97	21.01	0	
	1	0	21.28	20.88	21.22	0-1	0
	1	36	21.33	20.94	21.23		0
	1	74	21.15	20.93	21.27		0
	36	0	21.11	20.81	20.90	0-2	0
	36	18	21.13	20.85	20.98		0
36	37	21.00	20.80	21.01	0		
64QAM	75	0	21.12	20.82	21.00	0	
	1	0	21.22	20.86	21.14	0-2	0
	1	36	21.29	20.90	21.20		0
	1	74	21.06	20.81	21.25		0
	36	0	20.20	19.80	20.01	0-3	0.5
	36	18	20.15	19.86	20.03		0.5
36	37	20.00	19.75	20.02	0.5		
	75	0	20.09	19.79	20.02	0.5	

Table F-21

LTE Band 66 (AWS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.05	20.82	20.99	0	0
	1	12	21.17	20.80	21.09		0
	1	24	21.03	20.74	21.02		0
	12	0	21.33	20.96	21.18	0-1	0
	12	6	21.29	20.94	21.17		0
	12	13	21.17	20.86	21.14		0
16QAM	25	0	21.28	20.88	21.16	0	
	1	0	21.45	21.15	21.30	0-1	0
	1	12	21.42	21.13	21.43		0
	1	24	21.39	21.09	21.37		0
	12	0	21.37	20.97	21.15	0-2	0
	12	6	21.31	20.95	21.23		0
12	13	21.20	20.88	21.15	0		
64QAM	25	0	21.29	20.93	21.18	0	
	1	0	21.38	21.08	21.21	0-2	0
	1	12	21.33	21.08	21.33		0
	1	24	21.21	21.02	21.24		0
	12	0	20.40	20.02	20.15	0-3	0.5
	12	6	20.37	19.98	20.21		0.5
12	13	20.22	19.93	20.17	0.5		
	25	0	20.29	19.94	20.16		

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 13 of 55

Table F-22

LTE Band 66 (AWS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.05	20.85	21.06	0	0
	1	7	21.11	20.83	21.04		0
	1	14	21.07	20.75	21.03		0
	8	0	21.30	20.90	21.18	0-1	0
	8	4	21.23	20.94	21.21		0
	8	7	21.17	20.87	21.15		0
16QAM	15	0	21.27	20.93	21.12	0-1	0
	1	0	21.45	21.17	21.40		0
	1	7	21.43	21.08	21.45		0
	1	14	21.34	21.09	21.34	0-2	0
	8	0	21.39	20.97	21.19		0
	8	4	21.26	20.94	21.22		0
64QAM	8	7	21.21	20.94	21.19	0-2	0
	15	0	21.26	20.90	21.12		0
	1	0	21.38	21.08	21.29	0-2	0
	1	7	21.33	21.01	21.32		0
	1	14	21.32	21.01	21.31	0-3	0
	8	0	20.41	19.99	20.19		0.5
	8	4	20.30	19.98	20.28		0.5
	8	7	20.23	19.92	20.22		0.5
	15	0	20.23	19.93	20.13		0.5

Table F-23

LTE Band 66 (AWS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.06	20.75	20.94	0	0
	1	2	21.17	20.80	21.11		0
	1	5	21.05	20.66	21.00		0
	3	0	21.10	20.70	20.95		0
	3	2	21.12	20.75	21.06		0
	3	3	21.06	20.68	20.96		0
	6	0	21.20	20.82	21.13		0
16QAM	1	0	21.43	21.09	21.27	0-1	0
	1	2	21.48	21.12	21.40		0
	1	5	21.41	21.06	21.30		0
	3	0	21.25	20.84	21.05		0
	3	2	21.23	20.84	21.20		0
	3	3	21.13	20.79	21.10		0
	6	0	21.29	20.86	21.18		0
64QAM	1	0	21.35	21.01	21.21	0-2	0
	1	2	21.40	21.04	21.31		0
	1	5	21.29	20.95	21.24		0
	3	0	21.38	20.98	21.22		0
	3	2	21.42	21.01	21.33		0
	3	3	21.36	20.93	21.21		0
	6	0	20.22	19.86	20.12		0-3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 14 of 55

F.1.8 LTE Band 25

Table F-24

LTE Band 25 (PCS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.22	23.50	23.01	0	0
	1	36	23.36	23.51	22.99		0
	1	74	23.24	23.52	22.98		0
	36	0	22.48	22.50	22.14	0-1	1
	36	18	22.56	22.30	22.10		1
	36	37	22.43	22.29	22.06		1
	75	0	22.45	22.92	22.07		1
16QAM	1	0	22.78	22.93	22.55	0-1	1
	1	36	23.16	22.95	22.50		1
	1	74	22.93	23.05	22.67		1
	36	0	21.46	21.30	21.09	0-2	2
	36	18	21.56	21.33	21.15		2
	36	37	21.47	21.30	21.07		2
	75	0	21.40	21.26	21.09		2
64QAM	1	0	21.44	21.58	21.36	0-2	2
	1	36	21.67	21.57	21.30		2
	1	74	21.55	21.47	21.24		2
	36	0	20.46	20.33	20.07	0-3	3
	36	18	20.60	20.36	20.18		3
	36	37	20.45	20.35	20.13		3
	75	0	20.43	20.28	20.12		3

Table F-25

LTE Band 25 (PCS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.23	23.33	23.01	0	0
	1	25	23.40	23.54	22.94		0
	1	49	23.22	23.35	23.05		0
	25	0	22.54	22.35	22.08	0-1	1
	25	12	22.66	22.43	22.18		1
	25	25	22.58	22.36	22.10		1
	50	0	22.60	22.38	22.10		1
16QAM	1	0	22.70	22.56	22.55	0-1	1
	1	25	22.95	22.86	22.54		1
	1	49	22.76	22.50	22.59		1
	25	0	21.60	21.46	21.13	0-2	2
	25	12	21.70	21.48	21.26		2
	25	25	21.65	21.41	21.21		2
	50	0	21.60	21.36	21.18		2
64QAM	1	0	21.57	21.41	21.34	0-2	2
	1	25	21.80	21.60	21.45		2
	1	49	21.60	21.39	21.45		2
	25	0	20.57	20.45	20.18	0-3	3
	25	12	20.70	20.46	20.29		3
	25	25	20.64	20.42	20.21		3
	50	0	20.65	20.36	20.15		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 15 of 55		

Table F-26
LTE Band 25 (PCS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.41	23.40	23.00	0	0
	1	12	23.45	23.36	23.08		0
	1	24	23.50	23.30	23.02		0
	12	0	22.60	22.45	22.17	0-1	1
	12	6	22.64	22.48	22.25		1
	12	13	22.60	22.46	22.22		1
	25	0	22.64	22.42	22.20		1
16QAM	1	0	22.77	22.63	22.50	0-1	1
	1	12	22.68	22.50	22.33		1
	1	24	22.80	22.57	22.50		1
	12	0	21.67	21.54	21.21	0-2	2
	12	6	21.75	21.53	21.25		2
	12	13	21.75	21.52	21.31		2
	25	0	21.69	21.50	21.29		2
64QAM	1	0	21.80	21.58	21.34	0-2	2
	1	12	21.70	21.65	21.30		2
	1	24	21.86	21.65	21.35		2
	12	0	20.69	20.51	20.25	0-3	3
	12	6	20.75	20.48	20.27		3
	12	13	20.68	20.50	20.30		3
	25	0	20.68	20.45	20.27		3

Table F-27
LTE Band 25 (PCS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.50	23.31	23.01	0	0
	1	7	23.48	23.43	23.00		0
	1	14	23.50	23.30	23.07		0
	8	0	22.62	22.45	22.11	0-1	1
	8	4	22.63	22.47	22.17		1
	8	7	22.63	22.43	22.14		1
	15	0	22.66	22.45	22.17		1
16QAM	1	0	22.77	22.61	22.45	0-1	1
	1	7	22.75	22.60	22.45		1
	1	14	22.78	22.49	22.46		1
	8	0	21.70	21.50	21.18	0-2	2
	8	4	21.73	21.56	21.25		2
	8	7	21.75	21.50	21.22		2
	15	0	21.70	21.45	21.24		2
64QAM	1	0	21.71	21.68	21.40	0-2	2
	1	7	21.77	21.50	21.33		2
	1	14	21.88	21.54	21.40		2
	8	0	20.63	20.46	20.18	0-3	3
	8	4	20.70	20.50	20.23		3
	8	7	20.61	20.45	20.27		3
	15	0	20.67	20.45	20.28		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 16 of 55

Table F-28
LTE Band 25 (PCS) Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.36	23.50	23.15	0	0
	1	2	23.44	23.50	23.00		0
	1	5	23.33	23.24	22.94		0
	3	0	23.36	23.15	22.95		0
	3	2	23.40	23.24	22.98		0
	3	3	23.35	23.20	22.92		0
	6	0	22.49	22.36	22.08	0-1	1
16QAM	1	0	22.72	22.68	22.45	0-1	1
	1	2	22.84	22.70	22.49		1
	1	5	22.74	22.68	22.42		1
	3	0	22.69	22.48	22.30		1
	3	2	22.70	22.53	22.32		1
	3	3	22.67	22.52	22.27		1
	6	0	21.60	21.42	21.09	0-2	2
64QAM	1	0	21.57	21.44	21.19	0-2	2
	1	2	21.68	21.53	21.24		2
	1	5	21.70	21.54	21.24		2
	3	0	21.58	21.45	21.17		2
	3	2	21.67	21.50	21.22		2
	3	3	21.61	21.45	21.19		2
	6	0	20.59	20.47	20.11	0-3	3

Table F-29
LTE Band 25 (PCS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.05	19.28	19.01	0	0
	1	36	19.35	19.30	19.07		0
	1	74	19.28	19.18	19.03		0
	36	0	19.18	19.23	18.98	0-1	0
	36	18	19.36	19.28	19.06		0
	36	37	19.35	19.25	18.91		0
16QAM	75	0	19.38	19.20	18.93	0	
	1	0	19.36	19.54	19.26	0-1	0
	1	36	19.46	19.52	19.18		0
	1	74	19.37	19.45	19.20		0
	36	0	19.21	19.26	19.05	0-2	0
	36	18	19.41	19.33	19.01		0
36	37	19.42	19.30	18.91	0		
64QAM	75	0	19.34	19.36	19.00	0	
	1	0	19.32	19.42	19.23	0-2	0
	1	36	19.54	19.48	19.19		0
	1	74	19.48	19.45	19.07		0
	36	0	19.28	19.27	19.06	0-3	0
	36	18	19.44	19.40	19.06		0
	36	37	19.41	19.38	18.96		0
75	0	19.41	19.21	19.01	0		

FCC ID A3LSMA426U	 PCTEST Proud to be part of the element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 17 of 55

Table F-30
LTE Band 25 (PCS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.18	19.15	19.01	0	0
	1	25	19.39	19.33	19.00		0
	1	49	19.29	19.17	19.04		0
	25	0	19.37	19.30	18.97	0-1	0
	25	12	19.48	19.36	19.07		0
	25	25	19.42	19.38	18.98		0
	50	0	19.44	19.32	19.01		0
16QAM	1	0	19.47	19.53	19.30	0-1	0
	1	25	19.70	19.65	19.25		0
	1	49	19.51	19.46	19.30		0
	25	0	19.35	19.25	19.04	0-2	0
	25	12	19.48	19.40	19.03		0
	25	25	19.44	19.33	18.94		0
	50	0	19.40	19.38	19.10		0
64QAM	1	0	19.37	19.35	19.28	0-2	0
	1	25	19.52	19.56	19.17		0
	1	49	19.41	19.34	19.10		0
	25	0	19.39	19.35	19.06	0-3	0
	25	12	19.46	19.41	19.10		0
	25	25	19.44	19.39	19.02		0
	50	0	19.45	19.36	19.03		0

Table F-31
LTE Band 25 (PCS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.37	19.26	18.96	0	0
	1	12	19.41	19.37	19.00		0
	1	24	19.42	19.30	18.95		0
	12	0	19.43	19.39	19.02	0-1	0
	12	6	19.50	19.45	19.10		0
	12	13	19.48	19.42	19.07		0
	25	0	19.49	19.42	19.06		0
16QAM	1	0	19.65	19.86	19.54	0-1	0
	1	12	19.79	19.86	19.52		0
	1	24	19.86	19.73	19.48		0
	12	0	19.49	19.45	19.07	0-2	0
	12	6	19.49	19.46	19.14		0
	12	13	19.53	19.48	19.12		0
	25	0	19.45	19.44	19.03		0
64QAM	1	0	19.53	19.49	19.26	0-2	0
	1	12	19.56	19.59	19.22		0
	1	24	19.64	19.53	19.19		0
	12	0	19.46	19.40	19.07	0-3	0
	12	6	19.52	19.44	19.17		0
	12	13	19.54	19.44	19.11		0
	25	0	19.49	19.41	19.07		0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 18 of 55

Table F-32

LTE Band 25 (PCS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.35	19.29	18.95	0	0
	1	7	19.32	19.31	18.94		0
	1	14	19.34	19.34	18.98		0
	8	0	19.43	19.38	19.00	0-1	0
	8	4	19.49	19.44	19.04		0
	8	7	19.45	19.43	19.09		0
	15	0	19.47	19.43	19.04		0
16QAM	1	0	19.66	19.49	19.35	0-1	0
	1	7	19.80	19.69	19.38		0
	1	14	19.80	19.58	19.52		0
	8	0	19.62	19.37	19.18	0-2	0
	8	4	19.57	19.40	19.21		0
	8	7	19.62	19.40	19.18		0
	15	0	19.48	19.41	19.06		0
64QAM	1	0	19.54	19.52	19.26	0-2	0
	1	7	19.58	19.61	19.20		0
	1	14	19.64	19.58	19.21		0
	8	0	19.50	19.44	19.07	0-3	0
	8	4	19.46	19.43	19.09		0
	8	7	19.54	19.39	19.06		0
	15	0	19.54	19.50	19.14		0

Table F-33

LTE Band 25 (PCS) Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.24	19.25	18.96	0	0
	1	2	19.34	19.38	18.91		0
	1	5	19.29	19.27	18.93		0
	3	0	19.29	19.28	18.96		0
	3	2	19.33	19.36	19.03		0
	3	3	19.25	19.33	18.85		0
	6	0	19.39	19.42	18.94	0-1	0
16QAM	1	0	19.72	19.60	19.26	0-1	0
	1	2	19.89	19.72	19.23		0
	1	5	19.69	19.57	19.32		0
	3	0	19.51	19.38	19.04		0
	3	2	19.52	19.44	19.08		0
	3	3	19.50	19.40	19.04		0
	6	0	19.45	19.37	18.92	0-2	0
64QAM	1	0	19.52	19.42	19.23	0-2	0
	1	2	19.59	19.54	19.12		0
	1	5	19.57	19.44	19.15		0
	3	0	19.50	19.39	19.06		0
	3	2	19.60	19.48	19.10		0
	3	3	19.48	19.33	19.04		0
	6	0	19.40	19.26	18.99	0-3	0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 19 of 55		

F.1.9 LTE Band 30

Table F-34
LTE Band 30 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.44	0	0
	1	12	22.35		0
	1	24	22.34		0
	12	0	21.32	0-1	1
	12	6	21.25		1
	12	13	21.37		1
	25	0	21.23		1
16QAM	1	0	21.49	0-1	1
	1	12	21.57		1
	1	24	21.50		1
	12	0	20.35	0-2	2
	12	6	20.39		2
	12	13	20.42		2
	25	0	20.56		2
64QAM	1	0	20.54	0-2	2
	1	12	20.55		2
	1	24	20.59		2
	12	0	19.56	0-3	3
	12	6	19.63		3
	12	13	19.51		3
	25	0	19.53		3

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 20 of 55

Table F-35

LTE Band 30 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.09	0	0
	1	12	19.11		0
	1	24	19.00		0
	12	0	19.17	0-1	0
	12	6	19.13		0
	12	13	19.14		0
	25	0	19.05		0
16QAM	1	0	19.17	0-1	0
	1	12	19.16		0
	1	24	19.08		0
	12	0	19.10	0-2	0
	12	6	19.14		0
	12	13	19.01		0
	25	0	19.11		0
64QAM	1	0	19.10	0-2	0
	1	12	19.23		0
	1	24	19.15		0
	12	0	19.12	0-3	0
	12	6	19.16		0
	12	13	19.15		0
	25	0	19.13		0

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 21 of 55

F.1.10 LTE Band 7

Table F-36
LTE Band 7 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 15 MHz Bandwidth

LTE Band 7							
15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.49	23.14	22.82	0	0
	1	36	23.50	22.99	22.73		0
	1	74	23.37	22.95	22.68		0
	36	0	22.64	22.14	21.94	0-1	1
	36	18	22.65	22.10	21.90		1
	36	37	22.58	22.00	21.80		1
	75	0	22.51	22.10	21.83		1
16QAM	1	0	23.00	22.55	22.18	0-1	1
	1	36	22.95	22.45	22.15		1
	1	74	22.89	22.30	22.20		1
	36	0	21.76	21.20	20.94	0-2	2
	36	18	21.70	21.15	20.87		2
	36	37	21.59	21.05	20.78		2
	75	0	21.58	21.12	20.89		2
64QAM	1	0	21.94	21.37	21.08	0-2	2
	1	36	21.87	21.22	20.96		2
	1	74	21.70	21.05	20.92		2
	36	0	20.74	20.21	19.91	0-3	3
	36	18	20.76	20.19	19.92		3
	36	37	20.62	20.00	19.80		3
	75	0	20.60	20.13	19.88		3

Table F-37
LTE Band 7 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.66	23.20	22.88	0	0
	1	25	23.58	23.10	22.89		0
	1	49	23.62	23.03	22.92		0
	25	0	22.80	22.26	21.99	0-1	1
	25	12	22.72	22.26	21.97		1
	25	25	22.70	22.12	21.85		1
	50	0	22.66	22.21	21.89		1
16QAM	1	0	23.00	22.65	22.29	0-1	1
	1	25	22.98	22.67	22.34		1
	1	49	22.96	22.50	22.27		1
	25	0	21.86	21.30	21.04	0-2	2
	25	12	21.80	21.25	21.04		2
	25	25	21.74	21.13	21.00		2
	50	0	21.68	21.19	20.85		2
64QAM	1	0	21.99	21.49	21.15	0-2	2
	1	25	22.00	21.38	21.20		2
	1	49	21.92	21.30	21.17		2
	25	0	20.90	20.32	20.11	0-3	3
	25	12	20.76	20.30	19.98		3
	25	25	20.78	20.18	20.00		3
	50	0	20.73	20.19	20.00		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 22 of 55

Table F-38
LTE Band 7 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.67	23.20	22.88	0	0
	1	12	23.60	23.19	22.89		0
	1	24	23.73	23.14	22.86		0
	12	0	22.80	22.27	21.99	0-1	1
	12	6	22.86	22.33	21.99		1
	12	13	22.84	22.17	21.94		1
	25	0	22.78	22.26	21.98		1
16QAM	1	0	22.93	22.56	22.21	0-1	1
	1	12	22.98	22.51	22.19		1
	1	24	23.00	22.47	22.20		1
	12	0	21.88	21.33	21.00	0-2	2
	12	6	21.94	21.38	21.10		2
	12	13	21.89	21.22	21.01		2
	25	0	21.85	21.26	20.98		2
64QAM	1	0	21.92	21.51	21.20	0-2	2
	1	12	21.99	21.38	21.10		2
	1	24	21.88	21.37	21.17		2
	12	0	20.84	20.30	20.00	0-3	3
	12	6	20.92	20.33	20.06		3
	12	13	20.88	20.22	20.00		3
	25	0	20.84	20.24	19.98		3

Table F-39
LTE Band 7 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.45	18.70	19.00	0	0
	1	36	18.40	18.83	18.88		0
	1	74	18.50	18.92	18.97		0
	36	0	18.37	18.82	18.99	0-1	0
	36	18	18.52	18.78	18.96		0
	36	37	18.53	18.97	19.00		0
	75	0	18.50	18.92	18.87		0
16QAM	1	0	18.62	19.06	19.19	0-1	0
	1	36	18.73	18.94	19.15		0
	1	74	18.73	19.12	19.17		0
	36	0	18.40	18.83	18.93	0-2	0
	36	18	18.52	18.85	18.93		0
	36	37	18.53	18.94	18.94		0
	75	0	18.50	18.79	18.79		0
64QAM	1	0	18.44	19.04	19.07	0-2	0
	1	36	18.60	19.06	19.09		0
	1	74	18.62	19.00	19.10		0
	36	0	18.42	18.82	18.94	0-3	0
	36	18	18.52	18.85	18.97		0
	36	37	18.48	18.93	18.98		0
	75	0	18.42	18.80	18.86		0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 23 of 55

Table F-40
LTE Band 7 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.53	19.00	19.10	0	0
	1	25	18.57	19.03	19.10		0
	1	49	18.67	19.10	18.96		0
	25	0	18.53	18.96	19.02	0-1	0
	25	12	18.53	18.94	19.10		0
	25	25	18.61	19.01	19.07		0
	50	0	18.54	18.89	18.91		0
16QAM	1	0	18.72	19.25	19.32	0-1	0
	1	25	18.81	19.14	19.32		0
	1	49	18.86	19.33	19.32		0
	25	0	18.54	18.97	19.10	0-2	0
	25	12	18.63	19.02	19.09		0
	25	25	18.68	19.09	19.11		0
	50	0	18.56	18.88	18.98		0
64QAM	1	0	18.69	19.02	19.27	0-2	0
	1	25	18.74	19.12	19.30		0
	1	49	18.87	19.28	19.07		0
	25	0	18.57	18.97	19.07	0-3	0
	25	12	18.60	19.01	19.05		0
	25	25	18.62	19.09	19.15		0
	50	0	18.54	18.92	18.94		0

Table F-41
LTE Band 7 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.53	18.90	19.05	0	0
	1	12	18.60	19.01	19.09		0
	1	24	18.53	18.95	18.99		0
	12	0	18.56	18.93	19.11	0-1	0
	12	6	18.60	19.00	19.13		0
	12	13	18.60	19.05	19.07		0
	25	0	18.61	18.99	19.08	0	
16QAM	1	0	18.80	19.23	19.37	0-1	0
	1	12	18.90	19.27	19.40		0
	1	24	18.85	19.33	19.40		0
	12	0	18.54	18.98	19.09	0-2	0
	12	6	18.62	19.05	19.21		0
	12	13	18.57	19.06	19.06		0
	25	0	18.59	19.01	19.12	0	
64QAM	1	0	18.82	19.25	19.40	0-2	0
	1	12	18.86	19.31	19.26		0
	1	24	18.75	19.37	19.36		0
	12	0	18.61	19.01	19.14	0-3	0
	12	6	18.64	19.09	19.14		0
	12	13	18.65	19.09	19.14		0
	25	0	18.57	18.96	19.15	0	

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 24 of 55

F.1.11 LTE Band 48

Table F-42

LTE Band 48 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	22.10	21.20	21.02	21.82	0	0
	1	36	22.11	20.96	21.09	21.96		0
	1	74	21.94	20.91	21.32	22.09		0
	36	0	21.14	20.14	19.93	20.95	0-1	1
	36	18	21.09	20.12	20.07	21.04		1
	36	37	21.04	19.96	20.14	21.11		1
75	0	21.01	20.02	20.02	20.94	1		
16QAM	1	0	21.29	20.30	20.13	21.02	0-1	1
	1	36	21.25	20.24	20.22	21.18		1
	1	74	21.10	20.15	20.37	21.24		1
	36	0	20.13	19.28	18.91	19.98	0-2	2
	36	18	20.15	19.27	19.11	20.07		2
	36	37	20.04	19.11	19.13	20.12		2
75	0	20.02	19.10	18.91	19.98	2		
64QAM	1	0	20.34	19.55	19.11	20.02	0-2	2
	1	36	20.26	19.43	19.27	20.19		2
	1	74	19.99	19.09	19.18	20.03		2
	36	0	19.15	18.20	17.99	18.97	0-3	3
	36	18	19.17	18.17	18.06	19.02		3
	36	37	19.02	18.02	18.16	19.08		3
75	0	19.06	17.99	17.99	18.97	3		

Table F-43

LTE Band 48 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	22.34	21.36	21.29	22.19	0	0
	1	25	22.32	21.30	21.32	22.20		0
	1	49	22.33	21.26	21.41	22.28		0
	25	0	21.31	20.28	20.05	21.12	0-1	1
	25	12	21.33	20.40	20.32	21.30		1
	25	25	21.25	20.27	20.31	21.33		1
16QAM	50	0	21.25	20.33	20.24	21.19	0-1	1
	1	0	21.47	20.51	20.12	21.28		1
	1	25	21.43	20.48	20.17	21.37		1
	1	49	21.44	20.43	20.18	21.43	0-2	1
	25	0	20.30	19.32	19.11	20.10		2
	25	12	20.34	19.44	19.36	20.31		2
64QAM	25	25	20.33	19.28	19.30	20.33	0-2	2
	50	0	20.25	19.25	19.22	20.17		2
	1	0	20.32	19.36	19.00	20.11	0-2	2
	1	25	20.38	19.39	19.06	20.26		2
	1	49	20.14	19.20	19.18	20.29		0-3
	25	0	19.28	18.29	18.06	19.14	3	
25	12	19.37	18.42	18.29	19.28	3		
64QAM	25	25	19.27	18.28	18.24	19.34	0-3	3
	50	0	19.32	18.36	18.17	19.23		3

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 25 of 55		

Table F-44

LTE Band 48 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

LTE Band 48								
5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	22.23	21.22	21.04	22.12	0	0
	1	12	22.34	21.37	21.29	22.23		0
	1	24	22.37	21.23	21.26	22.28		0
	12	0	21.39	20.40	20.19	21.29	0-1	1
	12	6	21.45	20.48	20.30	21.40		1
	12	13	21.27	20.37	20.37	21.42		1
	25	0	21.44	20.42	20.28	21.32	1	
16QAM	1	0	21.52	20.47	20.27	21.39	0-1	1
	1	12	21.62	20.63	20.49	21.52		1
	1	24	21.59	20.49	20.49	21.52		1
	12	0	20.36	19.39	19.18	20.27	0-2	2
	12	6	20.46	19.44	19.29	20.36		2
	12	13	20.46	19.36	19.33	20.38		2
	25	0	20.47	19.48	19.27	20.41	2	
64QAM	1	0	20.20	19.25	19.02	20.07	0-2	2
	1	12	20.33	19.38	19.27	20.24		2
	1	24	20.05	19.15	19.24	20.24		2
	12	0	19.42	18.45	18.23	19.33	0-3	3
	12	6	19.51	18.53	18.34	19.47		3
	12	13	19.48	18.45	18.39	19.46		3
	25	0	19.34	18.42	18.24	19.31		3

Table F-45

LTE Band 48 Measured P_{Limit} for DSI = 2 (Hotspot Mode) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)			
			Conducted Power [dBm]						
QPSK	1	0	20.90	19.91	19.65	20.71	0	0	
	1	36	20.85	19.80	19.78	20.84		0	
	1	74	20.70	19.74	19.94	20.92		0	
	36	0	20.88	20.02	19.71	20.73	0-1	0	
	36	18	20.88	20.05	19.83	20.80		0	
	36	37	20.79	19.90	19.86	20.85		0	
16QAM	75	0	20.83	19.87	19.71	20.76	0-1	0	
	1	0	20.52	19.90	19.83	20.56		0	
	1	36	20.48	19.83	19.94	20.69		0	
	1	74	20.32	19.76	20.08	20.79	0-2	0	
	36	0	19.97	19.01	18.91	19.76		0.5	
	36	18	19.98	19.00	18.91	19.80		0.5	
64QAM	36	37	19.89	18.88	18.99	19.94	0-2	0.5	
	75	0	19.92	18.85	18.82	19.78		0.5	
	64QAM	1	0	20.15	19.04	18.95	19.69	0-2	0.5
		1	36	20.13	18.95	19.06	19.86		0.5
		1	74	20.01	18.81	19.24	19.96		0.5
		36	0	19.05	18.03	17.93	18.83	0-3	1.5
36		18	19.00	18.04	17.92	18.88	1.5		
36		37	18.95	17.88	18.00	18.93	1.5		
	75	0	18.93	17.92	17.90	18.82		1.5	

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 26 of 55

Table F-46
LTE Band 48 Measured P_{Limit} for DSI = 2 (Hotspot Mode)- 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	21.11	20.15	20.02	21.03	0	0
	1	25	21.09	20.11	20.03	21.07		0
	1	49	20.99	20.05	20.10	21.13		0
	25	0	21.04	20.03	19.79	20.87	0-1	0
	25	12	21.11	20.15	20.02	21.02		0
	25	25	21.04	19.97	20.00	21.04		0
	50	0	20.96	20.06	19.97	20.92		0
16QAM	1	0	21.19	20.21	19.81	21.04	0-1	0
	1	25	21.18	20.18	19.83	21.15		0
	1	49	21.16	20.14	19.89	21.23		0
	25	0	20.14	19.14	18.97	19.99	0-2	0.5
	25	12	20.19	19.24	19.14	20.13		0.5
	25	25	20.13	19.14	19.12	20.21		0.5
	50	0	20.07	19.20	19.02	20.07		0.5
64QAM	1	0	20.12	19.18	18.99	19.91	0-2	0.5
	1	25	20.18	19.12	19.05	20.06		0.5
	1	49	20.01	19.00	19.16	20.13		0.5
	25	0	19.12	18.07	17.96	18.92	0-3	1.5
	25	12	19.15	18.20	18.12	19.07		1.5
	25	25	19.10	18.03	18.09	19.14		1.5
	50	0	19.15	18.12	18.00	19.00		1.5

Table F-47
LTE Band 48 Measured P_{Limit} for DSI = 2 (Hotspot Mode) - 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	21.00	20.02	19.77	20.93	0	0
	1	12	21.08	20.10	20.00	21.02		0
	1	24	20.98	20.01	19.99	21.03		0
	12	0	21.11	20.09	19.92	21.07	0-1	0
	12	6	21.18	20.16	20.05	21.15		0
	12	13	21.12	20.09	20.08	21.16		0
	25	0	21.16	20.13	19.96	21.15		0
16QAM	1	0	21.22	20.03	20.06	20.97	0-1	0
	1	12	21.35	20.13	20.24	21.07		0
	1	24	21.21	20.04	20.29	21.10		0
	12	0	20.24	19.17	19.05	20.16	0-2	0.5
	12	6	20.31	19.30	19.12	20.22		0.5
	12	13	20.32	19.21	19.13	20.24		0.5
	25	0	20.26	19.23	19.02	20.18		0.5
64QAM	1	0	19.87	19.31	18.95	20.21	0-2	0.5
	1	12	20.06	19.42	18.98	20.35		0.5
	1	24	19.98	19.34	18.97	20.34		0.5
	12	0	19.26	18.23	17.94	19.33	0-3	1.5
	12	6	19.28	18.29	18.09	19.23		1.5
	12	13	19.36	18.24	18.13	19.28		1.5
	25	0	19.23	18.16	18.07	19.17		1.5

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 27 of 55

Table F-48
LTE Band 48 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	17.81	16.93	16.63	17.57	0	0
	1	36	17.79	16.82	16.71	17.68		0
	1	74	17.65	16.77	16.85	17.75		0
	36	0	17.80	16.93	16.57	17.58	0-1	0
	36	18	17.78	16.91	16.77	17.67		0
	36	37	17.70	16.77	16.84	17.74		0
	75	0	17.59	16.74	16.65	17.54		0
16QAM	1	0	17.94	16.80	16.78	17.46	0-1	0
	1	36	17.93	16.70	16.87	17.55		0
	1	74	17.82	16.57	16.99	17.64		0
	36	0	17.85	16.86	16.68	17.59	0-2	0
	36	18	17.82	16.89	16.77	17.68		0
	36	37	17.75	16.73	16.90	17.75		0
	75	0	17.65	16.71	16.66	17.60		0
64QAM	1	0	17.84	16.92	16.85	17.53	0-2	0
	1	36	17.85	16.82	16.92	17.74		0
	1	74	17.68	16.70	17.07	17.83		0
	36	0	17.87	16.94	16.71	17.63	0-3	0
	36	18	17.85	16.96	16.76	17.77		0
	36	37	17.75	16.74	16.88	17.82		0
	75	0	17.76	16.36	16.62	17.67		0

Table F-49
LTE Band 48 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	17.98	17.01	16.81	17.84	0	0
	1	25	17.97	16.96	16.83	17.88		0
	1	49	17.93	16.94	16.91	17.95		0
	25	0	17.92	16.90	16.70	17.73	0-1	0
	25	12	18.00	17.04	16.96	17.90		0
	25	25	17.95	16.93	16.93	17.97		0
	50	0	17.85	16.93	16.84	17.80		0
16QAM	1	0	18.00	17.16	16.94	17.92	0-1	0
	1	25	17.99	17.08	16.97	18.00		0
	1	49	17.98	17.06	17.08	17.99		0
	25	0	17.97	16.98	16.75	17.79	0-2	0
	25	12	18.00	17.09	17.02	17.94		0
	25	25	18.00	16.97	16.98	17.97		0
	50	0	17.90	16.95	16.87	17.74		0
64QAM	1	0	17.85	17.32	17.02	17.76	0-2	0
	1	25	17.84	17.30	17.19	17.84		0
	1	49	17.63	17.10	17.16	17.83		0
	25	0	17.95	17.01	16.77	17.83	0-3	0
	25	12	17.96	17.12	17.01	17.98		0
	25	25	17.97	16.99	17.00	17.95		0
	50	0	18.00	17.05	16.95	17.92		0

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 28 of 55

Table F-50
LTE Band 48 Measured P_{Limit} for DSI = 1 (Head)- 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	17.57	16.86	16.61	17.51	0	0
	1	12	17.70	16.92	16.83	17.68		0
	1	24	17.67	16.80	16.85	17.67		0
	12	0	17.75	17.00	16.84	17.70	0-1	0
	12	6	17.86	17.09	16.96	17.84		0
	12	13	17.88	17.00	17.04	17.83		0
	25	0	17.77	17.03	16.79	17.79		0
16QAM	1	0	17.88	17.11	16.88	17.82	0-1	0
	1	12	17.99	17.15	17.09	17.95		0
	1	24	17.96	17.04	17.10	17.96		0
	12	0	17.83	17.01	16.80	17.73	0-2	0
	12	6	17.89	17.08	16.96	17.82		0
	12	13	17.88	17.01	17.03	17.81		0
	25	0	17.57	17.05	16.92	17.79		0
64QAM	1	0	17.84	17.08	16.86	17.76	0-2	0
	1	12	17.85	17.19	17.07	17.71		0
	1	24	17.68	17.06	17.08	17.68		0
	12	0	17.90	17.07	16.92	17.95	0-3	0
	12	6	17.99	17.18	17.03	18.00		0
	12	13	18.00	17.15	17.11	17.99		0
	25	0	17.95	17.04	16.89	17.97		0

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 29 of 55		

F.1.12 LTE Band 41

Table F-51

LTE Band 41 PC3 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.57	23.37	23.63	23.30	22.96	0	0
	1	36	23.60	23.56	23.68	23.37	23.26		0
	1	74	23.61	23.42	23.75	23.14	23.29		0
	36	0	22.69	22.53	22.74	22.39	22.26	0-1	1
	36	18	22.73	22.67	22.86	22.42	22.38		1
	36	37	22.72	22.61	22.87	22.41	22.39		1
	75	0	22.67	22.59	22.81	22.40	22.36		1
16QAM	1	0	22.83	21.97	22.65	22.24	21.61	0-1	1
	1	36	22.84	22.16	22.94	22.41	21.89		1
	1	74	22.87	22.01	22.77	22.15	21.90		1
	36	0	21.66	21.52	21.75	21.39	21.33	0-2	2
	36	18	21.75	21.68	21.84	21.43	21.39		2
	36	37	21.74	21.61	21.87	21.36	21.41		2
	75	0	21.70	21.63	21.78	21.33	21.32		2
64QAM	1	0	21.69	21.68	21.58	21.24	21.31	0-2	2
	1	36	21.81	21.92	21.89	21.28	21.58		2
	1	74	21.83	21.79	21.72	21.01	21.61		2
	36	0	20.67	20.55	20.81	20.46	20.32	0-3	3
	36	18	20.78	20.69	20.92	20.50	20.39		3
	36	37	20.72	20.66	20.91	20.45	20.45		3
	75	0	20.72	20.64	20.82	20.39	20.40		3

Table F-52

LTE Band 41 PC3 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.72	23.58	23.65	23.34	23.21	0	0
	1	25	23.73	23.76	23.72	23.58	23.49		0
	1	49	23.75	23.68	23.65	23.26	23.30		0
	25	0	22.80	22.76	22.99	22.56	22.49	0-1	1
	25	12	22.90	22.91	23.12	22.64	22.56		1
	25	25	22.91	22.81	23.01	22.53	22.44		1
	50	0	22.83	22.83	23.04	22.54	22.46		1
16QAM	1	0	22.97	22.65	22.71	22.28	22.34	0-1	1
	1	25	22.91	22.94	23.09	22.55	22.55		1
	1	49	22.98	22.76	22.76	22.23	22.39		1
	25	0	21.81	21.80	22.07	21.59	21.51	0-2	2
	25	12	21.92	21.94	22.14	21.68	21.58		2
	25	25	21.90	21.88	22.03	21.58	21.52		2
	50	0	21.81	21.87	21.99	21.56	21.53		2
64QAM	1	0	21.91	21.63	21.75	21.27	21.33	0-2	2
	1	25	22.02	21.95	22.06	21.55	21.58		2
	1	49	22.01	21.66	21.76	21.27	21.37		2
	25	0	20.84	20.69	20.96	20.52	20.42	0-3	3
	25	12	20.93	20.88	21.09	20.67	20.52		3
	25	25	20.90	20.77	20.97	20.54	20.42		3
	50	0	20.91	20.83	20.98	20.52	20.45		3

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 30 of 55

Table F-53
LTE Band 41 PC3 Measured P_{Max} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.73	23.57	23.69	23.54	23.47	0	0
	1	12	23.75	23.61	23.74	23.51	23.45		0
	1	24	23.68	23.64	23.69	23.49	23.47		0
	12	0	23.10	22.86	23.13	22.60	22.53	0-1	1
	12	6	22.85	22.94	23.12	22.64	22.55		1
	12	13	22.91	22.90	23.12	22.64	22.51		1
16QAM	25	0	22.90	22.89	23.09	22.62	22.51	0-1	1
	1	0	23.12	22.64	23.29	22.79	22.38		1
	1	12	23.14	22.72	23.32	22.74	22.33		1
	1	24	23.14	22.74	23.27	22.75	22.38	0-2	1
	12	0	21.84	21.84	22.11	21.64	21.53		2
	12	6	21.92	21.93	22.14	21.65	21.56		2
64QAM	12	13	21.91	21.92	22.14	21.66	21.54	0-2	2
	25	0	21.93	21.87	22.01	21.59	21.51		2
	1	0	22.06	22.04	21.99	21.47	21.67	0-2	2
	1	12	22.10	22.09	22.01	21.50	21.72		2
	1	24	22.10	22.10	21.97	21.46	21.69	0-3	2
	12	0	20.90	20.90	21.04	20.59	20.52		3
12	6	20.94	20.90	21.06	20.61	20.54	3		
64QAM	12	13	20.97	20.88	21.05	20.58	20.57	0-3	3
	25	0	20.87	20.88	21.15	20.66	20.51		3

Table F-54
LTE Band 41 PC3 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

LTE Band 41										
15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	20.33	20.41	20.50	20.07	20.08	0	0	
	1	36	20.42	20.44	20.86	20.27	20.15		0-1	0
	1	74	20.48	20.56	20.63	20.00	20.16			0
	36	0	20.42	20.31	20.53	20.11	20.28	0		
	36	18	20.58	20.36	20.67	20.18	20.21	0		0
	36	37	20.52	20.49	20.70	20.06	20.19		0	
	75	0	20.53	20.41	20.58	20.10	20.16		0	
16QAM	1	0	20.56	20.40	20.58	20.11	20.06	0-1	0	
	1	36	20.62	20.49	20.55	20.24	20.21		0-2	0
	1	74	20.61	20.28	20.55	19.88	20.04			0
	36	0	20.46	20.31	20.56	20.18	20.26	0		
	36	18	20.59	20.47	20.72	20.27	20.33	0		0
	36	37	20.61	20.38	20.63	20.11	20.23		0	
	75	0	20.53	20.41	20.62	20.14	20.11		0	
64QAM	1	0	20.06	20.00	20.02	19.94	19.68	0-2	0	
	1	36	20.08	20.07	20.25	20.01	19.99		0-3	0
	1	74	20.14	20.02	20.04	19.88	19.66			0
	36	0	20.42	20.32	20.59	20.13	20.08	0		
	36	18	20.54	20.33	20.63	20.05	20.11	0		0
	36	37	20.56	20.44	20.63	20.08	20.21		0	
	75	0	20.52	20.21	20.62	20.09	20.10		0	

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 31 of 55		

Table F-55

LTE Band 41 PC3 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 10 MHz Bandwidth

LTE Band 41									
10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	20.36	20.25	20.55	20.00	20.02	0	0
	1	25	20.45	20.30	20.84	20.26	20.28		0
	1	49	20.41	20.29	20.79	19.92	20.04		0
	25	0	20.56	20.49	20.80	20.32	20.25	0-1	0
	25	12	20.71	20.65	20.84	20.33	20.36		0
	25	25	20.66	20.53	20.87	20.18	20.24		0
	50	0	20.60	20.58	20.81	20.27	20.25		0
16QAM	1	0	20.72	20.47	20.73	20.30	20.28	0-1	0
	1	25	20.73	20.67	20.65	20.34	20.38		0
	1	49	20.67	20.50	20.71	20.13	20.21		0
	25	0	20.43	20.50	20.69	20.16	20.23	0-2	0
	25	12	20.54	20.46	20.85	20.31	20.35		0
	25	25	20.51	20.46	20.82	20.21	20.24		0
	50	0	20.58	20.60	20.79	20.29	20.23		0
64QAM	1	0	20.28	20.01	20.26	19.74	19.90	0-2	0
	1	25	20.26	20.23	20.47	19.99	20.00		0
	1	49	20.38	20.04	20.23	19.66	19.80		0
	25	0	20.57	20.59	20.83	20.21	20.25	0-3	0
	25	12	20.63	20.77	20.76	20.34	20.33		0
	25	25	20.68	20.62	20.94	20.27	20.36		0
	50	0	20.64	20.64	20.83	20.33	20.24		0

Table F-56

LTE Band 41 PC3 Measured P_{Limit} for DSI = 1 (Head), DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	20.50	20.42	20.79	20.17	20.18	0	0
	1	12	20.56	20.48	20.86	20.24	20.15		0
	1	24	20.40	20.44	20.71	20.16	20.16		0
	12	0	20.58	20.59	20.84	20.33	20.35	0-1	0
	12	6	20.67	20.69	20.88	20.35	20.34		0
	12	13	20.66	20.60	20.85	20.41	20.33		0
	25	0	20.63	20.57	20.84	20.28	20.33		0
16QAM	1	0	20.65	20.64	20.88	20.40	20.39	0-1	0
	1	12	20.58	20.71	20.89	20.33	20.39		0
	1	24	20.60	20.67	20.83	20.39	20.32		0
	12	0	20.62	20.53	20.87	20.27	20.33	0-2	0
	12	6	20.66	20.71	20.94	20.26	20.37		0
	12	13	20.73	20.67	20.87	20.38	20.38		0
	25	0	20.63	20.57	20.80	20.28	20.21		0
64QAM	1	0	20.29	20.22	20.15	19.95	19.97	0-2	0
	1	12	20.27	20.24	20.18	20.16	19.95		0
	1	24	20.23	20.25	20.13	20.07	19.93		0
	12	0	20.61	20.64	20.54	20.31	20.38	0-3	0
	12	6	20.72	20.76	20.66	20.39	20.45		0
	12	13	20.71	20.70	20.67	20.41	20.35		0
	25	0	20.70	20.65	20.70	20.37	20.41		0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 32 of 55

F.2 NR Lower Bandwidth RF Conducted Powers

F.2.1 NR Band n71

Table F-57
NR Band n71 Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.30	0	0.0
	1	40	23.22		0.0
	1	77	23.10		0.0
	36	0	22.75	0-0.5	0.5
	36	22	23.20	0	0.0
	36	43	22.65	0-0.5	0.5
	75	0	22.74		0.5
DFT-s-OFDM QPSK	1	1	23.27	0	0.0
	1	40	23.30		0.0
	1	77	23.16		0.0
	36	0	22.25	0-1	1.0
	36	22	23.20	0	0.0
	36	43	22.08	0-1	1.0
	75	0	22.24		1.0
DFT-s-OFDM 16QAM	1	1	21.86	0-1	1.0
CP-OFDM QPSK	1	1	21.79	0-1.5	1.5

Note: NR Band n71 at 15 MHz bandwidth does not support non-overlapping channels. Per FCC Guidance, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 33 of 55

Table F-58
NR Band n71 Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.40	23.40	23.14	0	0.0
	1	26	23.25	23.40	23.12		0.0
	1	50	23.20	23.36	23.11		0.0
	25	0	22.90	22.85	22.61	0-0.5	0.5
	25	14	23.32	23.33	23.14	0	0.0
	25	27	22.83	22.79	22.68	0-0.5	0.5
	50	0	22.88	22.89	22.64		0.5
DFT-s-OFDM QPSK	1	1	23.53	23.38	23.15	0	0.0
	1	26	23.55	23.53	23.15		0.0
	1	50	23.43	23.30	23.18		0.0
	25	0	22.36	22.36	22.15	0-1	1.0
	25	14	23.35	23.35	23.10	0	0.0
	25	27	22.30	22.26	22.07	0-1	1.0
	50	0	22.38	22.37	22.15		1.0
DFT-s-OFDM 16QAM	1	1	22.25	22.08	21.89	0-1	1.0
CP-OFDM QPSK	1	1	22.05	21.81	21.50	0-1.5	1.5

Table F-59
NR Band n71 Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.50	23.52	23.12	0	0.0
	1	13	23.41	23.57	23.22		0.0
	1	23	23.30	23.45	23.20		0.0
	12	0	22.88	22.95	22.68	0-0.5	0.5
	12	7	23.45	23.45	23.27	0	0.0
	12	13	22.90	22.93	22.70	0-0.5	0.5
	25	0	22.87	22.96	22.70		0.5
DFT-s-OFDM QPSK	1	1	23.60	23.70	23.41	0	0.0
	1	13	23.47	23.80	23.55		0.0
	1	23	23.51	23.70	23.45		0.0
	12	0	22.50	22.53	22.25	0-1	1.0
	12	7	23.45	23.60	23.31	0	0.0
	12	13	22.45	22.51	22.15	0-1	1.0
	25	0	22.42	22.48	22.27		1.0
DFT-s-OFDM 16QAM	1	1	22.20	22.57	22.30	0-1	1.0
CP-OFDM QPSK	1	1	22.00	22.10	21.65	0-1.5	1.5

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 34 of 55

F.2.2 NR Band n5

Table F-60
NR Band n5 Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.73	0	0.0
	1	40	23.71		0.0
	1	77	23.60		0.0
	36	0	23.25	0-0.5	0.5
	36	22	23.72	0	0.0
	36	43	23.14	0-0.5	0.5
	75	0	23.23		0.5
DFT-s-OFDM QPSK	1	1	23.98	0	0.0
	1	40	23.91		0.0
	1	77	23.80		0.0
	36	0	22.74	0-1	1.0
	36	22	23.78	0	0.0
	36	43	22.72	0-1	1.0
	75	0	22.73		1.0
DFT-s-OFDM 16QAM	1	1	22.71	0-1	1.0
CP-OFDM QPSK	1	1	22.17	0-1.5	1.5

Note: NR Band n5 at 15 MHz bandwidth does not support non-overlapping channels. Per FCC Guidance, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 35 of 55

Table F-61
NR Band n5 Measured P_{Max} for all DSI - 10 MHz Bandwidth
NR Band n5
10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.80	0	0.0
	1	26	23.81		0.0
	1	50	23.65		0.0
	25	0	23.40	0-0.5	0.5
	25	14	23.85	0	0.0
	25	27	23.34	0-0.5	0.5
	50	0	23.39		0.5
DFT-s-OFDM QPSK	1	1	24.01	0	0.0
	1	26	24.11		0.0
	1	50	23.87		0.0
	25	0	22.85	0-1	1.0
	25	14	23.92	0	0.0
	25	27	22.73	0-1	1.0
	50	0	22.92		1.0
DFT-s-OFDM 16QAM	1	1	22.68	0-1	1.0
CP-OFDM QPSK	1	1	22.27	0-1.5	1.5

Note: NR Band n5 at 10 MHz bandwidth does not support non-overlapping channels. Per FCC Guidance, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 36 of 55

Table F-62
NR Band n5 Measured P_{Max} for all DSI - 5 MHz Bandwidth
NR Band n5
5 MHz Bandwidth

			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.72	23.83	23.52	0	0.0
	1	13	23.87	23.76	23.60		0.0
	1	23	23.91	23.77	23.66		0.0
	12	0	23.40	23.29	23.08	0-0.5	0.5
	12	7	23.87	23.76	23.45	0	0.0
	12	13	23.29	23.25	23.03	0-0.5	0.5
	25	0	23.24	23.21	22.95		0.5
DFT-s-OFDM QPSK	1	1	24.00	23.92	23.59	0	0.0
	1	13	23.94	23.97	23.52		0.0
	1	23	23.87	23.88	23.53		0.0
	12	0	22.94	22.86	22.48	0-1	1.0
	12	7	23.77	23.80	23.49	0	0.0
	12	13	22.72	22.71	22.40	0-1	1.0
	25	0	22.80	22.69	22.45		1.0
DFT-s-OFDM 16QAM	1	1	23.16	22.65	22.42	0-1	1.0
CP-OFDM QPSK	1	1	22.37	22.21	21.91	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of  element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 37 of 55

F.2.3 NR Band n66

Table F-63
NR Band n66 Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.80	24.05	24.20	0	0.0
	1	40	23.91	24.03	24.31		0.0
	1	77	24.20	24.12	24.36		0.0
	36	0	23.36	23.51	23.71	0-0.5	0.5
	36	22	23.86	23.99	24.20	0	0.0
	36	43	23.57	23.52	23.74	0-0.5	0.5
	75	0	23.40	23.53	23.74		0.5
DFT-s-OFDM QPSK	1	1	24.41	24.53	24.57	0	0.0
	1	40	24.30	24.42	24.59		0.0
	1	77	24.53	24.50	24.68		0.0
	36	0	23.02	23.11	23.29	0-1	1.0
	36	22	23.95	24.05	24.21	0	0.0
	36	43	23.15	23.05	23.25	0-1	1.0
	75	0	23.03	23.15	23.33		1.0
DFT-s-OFDM 16QAM	1	1	23.47	23.61	23.55	0-1	1.0
CP-OFDM QPSK	1	1	22.55	22.75	22.81	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of the Samsung ecosystem	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 38 of 55		

Table F-64
NR Band n66 Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	24.21	24.20	24.35	0	0.0
	1	26	24.37	24.50	24.40		0.0
	1	50	24.40	24.38	24.45		0.0
	25	0	23.33	23.34	23.85	0-0.5	0.5
	25	14	24.30	24.32	24.40	0	0.0
	25	27	23.33	23.36	23.89	0-0.5	0.5
	50	0	23.40	23.32	23.91		0.5
DFT-s-OFDM QPSK	1	1	24.25	24.16	24.42	0	0.0
	1	26	24.10	24.43	24.50		0.0
	1	50	24.45	24.39	24.46		0.0
	25	0	23.35	23.38	23.80	0-1	1.0
	25	14	24.27	24.43	24.41	0	0.0
	25	27	23.40	23.34	23.83	0-1	1.0
	50	0	23.35	23.42	23.72		1.0
DFT-s-OFDM 16QAM	1	1	23.80	23.70	23.73	0-1	1.0
CP-OFDM QPSK	1	1	23.02	22.88	23.03	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of Samsung	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 39 of 55		

Table F-65
NR Band n66 Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	23.91	24.14	24.22	0	0.0
	1	13	24.15	24.30	24.31		0.0
	1	23	24.06	24.34	24.42		0.0
	12	0	23.45	23.83	23.88	0-0.5	0.5
	12	7	24.16	24.37	24.47	0	0.0
	12	13	23.72	23.80	23.90	0-0.5	0.5
	25	0	23.60	23.80	23.91		0.5
DFT-s-OFDM QPSK	1	1	24.23	24.39	24.56	0	0.0
	1	13	24.30	24.44	24.45		0.0
	1	23	24.30	24.44	24.61		0.0
	12	0	23.25	23.40	23.50	0-1	1.0
	12	7	24.12	24.41	24.48	0	0.0
	12	13	23.20	23.40	23.58	0-1	1.0
	25	0	23.20	23.35	23.42		1.0
DFT-s-OFDM 16QAM	1	1	23.60	23.75	23.70	0-1	1.0
CP-OFDM QPSK	1	1	22.82	22.96	23.09	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 40 of 55		

Table F-66

NR Band n66 Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	21.22	21.40	21.23	0	0.0
	1	40	21.28	21.44	21.21		0.0
	1	77	21.43	21.49	21.31		0.0
	36	0	21.25	21.41	21.17	0-0.5	0.0
	36	22	21.23	21.34	21.18	0	0.0
	36	43	21.38	21.43	21.26	0-0.5	0.0
	75	0	21.37	21.39	21.25		0.0
DFT-s-OFDM QPSK	1	1	21.38	21.35	21.34	0	0.0
	1	40	21.32	21.60	21.23		0.0
	1	77	21.52	21.54	21.37		0.0
	36	0	21.30	21.43	21.28	0-1	0.0
	36	22	21.29	21.39	21.16	0	0.0
	36	43	21.35	21.47	21.23	0-1	0.0
	75	0	21.34	21.49	21.31		0.0
DFT-s-OFDM 16QAM	1	1	21.39	21.53	21.44	0-1	0.0
CP-OFDM QPSK	1	1	21.45	21.61	21.42	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 41 of 55		

Table F-67

NR Band n66 Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	21.41	21.60	21.36	0	0.0
	1	26	21.63	21.67	21.46		0.0
	1	50	21.48	21.67	21.41		0.0
	25	0	21.46	21.56	21.38	0-0.5	0.0
	25	14	21.42	21.61	21.42	0	0.0
	25	27	21.40	21.62	21.40	0-0.5	0.0
	50	0	21.48	21.67	21.41		0.0
DFT-s-OFDM QPSK	1	1	21.60	21.65	21.38	0	0.0
	1	26	21.54	21.83	21.56		0.0
	1	50	21.59	21.77	21.45		0.0
	25	0	21.49	21.62	21.40	0-1	0.0
	25	14	21.53	21.68	21.46	0	0.0
	25	27	21.38	21.65	21.41	0-1	0.0
	50	0	21.45	21.68	21.47		0.0
DFT-s-OFDM 16QAM	1	1	21.60	21.71	21.67	0-1	0.0
CP-OFDM QPSK	1	1	21.58	21.77	21.63	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 42 of 55		

Table F-68

NR Band n66 Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	21.51	21.67	21.41	0	0.0
	1	13	21.47	21.81	21.47		0.0
	1	23	21.32	21.69	21.44		0.0
	12	0	21.38	21.60	21.39	0-0.5	0.0
	12	7	21.40	21.62	21.40	0	0.0
	12	13	21.43	21.67	21.33	0-0.5	0.0
	25	0	21.38	21.53	21.34		0.0
DFT-s-OFDM QPSK	1	1	21.58	21.74	21.57	0	0.0
	1	13	21.62	21.75	21.53		0.0
	1	23	21.55	21.80	21.54		0.0
	12	0	21.49	21.63	21.40	0-1	0.0
	12	7	21.58	21.75	21.43	0	0.0
	12	13	21.57	21.74	21.43	0-1	0.0
	25	0	21.42	21.52	21.32		0.0
DFT-s-OFDM 16QAM	1	1	21.30	21.57	21.22	0-1	0.0
CP-OFDM QPSK	1	1	21.42	21.73	21.57	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 43 of 55

F.2.4 NR Band n25

Table F-69
NR Band n25 Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	24.17	24.30	24.14	0	0.0
	1	40	24.29	24.26	24.07		0.0
	1	77	24.48	24.37	24.10		0.0
	36	0	23.82	23.80	23.71	0-0.5	0.5
	36	22	24.27	24.24	24.12	0	0.0
	36	43	23.85	23.80	23.59	0-0.5	0.5
	75	0	23.83	23.76	23.70		0.5
DFT-s-OFDM QPSK	1	1	24.25	24.47	24.36	0	0.0
	1	40	24.42	24.40	24.28		0.0
	1	77	24.51	24.51	24.21		0.0
	36	0	23.30	23.30	23.32	0-1	1.0
	36	22	24.31	24.26	24.25	0	0.0
	36	43	23.37	23.32	23.13	0-1	1.0
	75	0	23.42	23.28	23.25		1.0
DFT-s-OFDM 16QAM	1	1	23.34	23.47	23.45	0-1	1.0
CP-OFDM QPSK	1	1	22.30	22.65	22.60	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of Samsung	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 44 of 55		

Table F-70
NR Band n25 Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	24.25	24.31	24.28	0	0.0
	1	26	24.51	24.33	24.23		0.0
	1	50	24.46	24.31	24.21		0.0
	25	0	23.85	23.99	23.82	0-0.5	0.5
	25	14	24.36	24.46	24.29	0	0.0
	25	27	23.90	24.04	23.70	0-0.5	0.5
	50	0	23.88	24.04	23.87		0.5
DFT-s-OFDM QPSK	1	1	24.66	24.61	24.70	0	0.0
	1	26	24.64	24.60	24.53		0.0
	1	50	24.82	24.71	24.43		0.0
	25	0	23.42	23.50	23.39	0-1	1.0
	25	14	24.47	24.52	24.42	0	0.0
	25	27	23.41	23.53	23.33	0-1	1.0
	50	0	23.45	23.55	23.38		1.0
DFT-s-OFDM 16QAM	1	1	23.25	23.51	23.40	0-1	1.0
CP-OFDM QPSK	1	1	22.76	22.86	22.53	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of Samsung	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 45 of 55		

Table F-71
NR Band n25 Measured P_{Max} for DSI = 1 (Head) or DSI = 0 (Body-worn, or Phablet with grip sensor inactive) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	24.43	24.42	24.13	0	0.0
	1	13	24.46	24.50	24.19		0.0
	1	23	24.51	24.47	24.24		0.0
	12	0	23.91	23.84	23.75	0-0.5	0.5
	12	7	24.49	24.45	24.30	0	0.0
	12	13	23.89	23.88	23.82	0-0.5	0.5
	25	0	23.90	23.82	23.68		0.5
DFT-s-OFDM QPSK	1	1	24.37	24.50	24.44	0	0.0
	1	13	24.52	24.40	24.21		0.0
	1	23	24.46	24.47	24.24		0.0
	12	0	23.51	23.52	23.35	0-1	1.0
	12	7	24.57	24.46	24.32	0	0.0
	12	13	23.45	23.62	23.41	0-1	1.0
	25	0	23.40	23.34	23.24		1.0
DFT-s-OFDM 16QAM	1	1	23.23	23.31	23.41	0-1	1.0
CP-OFDM QPSK	1	1	22.55	22.82	22.51	0-1.5	1.5

FCC ID A3LSMA426U	 PCTEST Proud to be part of Samsung	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 46 of 55		

Table F-72

NR Band n25 Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	20.98	20.97	20.79	0	0.0
	1	40	20.91	21.00	20.82		0.0
	1	77	21.02	21.01	20.69		0.0
	36	0	20.87	20.87	20.79	0-0.5	0.0
	36	22	20.90	20.93	20.72	0	0.0
	36	43	20.94	20.97	20.67	0-0.5	0.0
	75	0	20.89	20.98	20.79		0.0
DFT-s-OFDM QPSK	1	1	21.17	21.11	20.91	0	0.0
	1	40	21.15	21.09	21.08		0.0
	1	77	21.14	21.11	20.92		0.0
	36	0	20.86	20.87	20.77	0-1	0.0
	36	22	20.88	20.85	20.74	0	0.0
	36	43	20.91	20.87	20.68	0-1	0.0
	75	0	20.89	20.88	20.82		0.0
DFT-s-OFDM 16QAM	1	1	21.09	21.08	20.97	0-1	0.0
CP-OFDM QPSK	1	1	20.76	20.83	20.60	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 47 of 55

Table F-73

NR Band n25 Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	21.09	20.82	20.80	0	0.0
	1	26	20.98	20.84	20.83		0.0
	1	50	21.11	20.80	20.81		0.0
	25	0	20.98	20.83	20.80	0-0.5	0.0
	25	14	21.02	20.85	20.79	0	0.0
	25	27	21.01	20.88	20.83	0-0.5	0.0
	50	0	21.08	20.86	20.84		0.0
DFT-s-OFDM QPSK	1	1	21.12	20.82	20.78	0	0.0
	1	26	21.00	20.86	20.75		0.0
	1	50	20.99	20.84	20.83		0.0
	25	0	20.97	20.82	20.81	0-1	0.0
	25	14	21.03	20.87	20.81	0	0.0
	25	27	21.04	20.92	20.83	0-1	0.0
	50	0	21.04	20.93	20.87		0.0
DFT-s-OFDM 16QAM	1	1	21.38	21.21	21.11	0-1	0.0
CP-OFDM QPSK	1	1	20.92	20.78	20.75	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 48 of 55

Table F-74

NR Band n25 Measured P_{Limit} for DSI = 2 (Hotspot Mode), DSI = 4, 5, or 6 (Phablet with Grip Sensor Active) and/or DSI = 3 (Earjack Active) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	21.20	20.99	20.62	0	0.0
	1	13	21.24	20.73	20.70		0.0
	1	23	21.02	20.95	20.63		0.0
	12	0	21.21	20.98	20.66	0-0.5	0.0
	12	7	21.27	20.95	20.73	0	0.0
	12	13	21.28	21.11	20.63	0-0.5	0.0
	25	0	21.18	20.97	20.62		0.0
DFT-s-OFDM QPSK	1	1	21.48	21.04	21.03	0	0.0
	1	13	21.56	20.93	21.12		0.0
	1	23	21.30	20.91	21.01		0.0
	12	0	21.20	20.96	20.72	0-1	0.0
	12	7	21.22	20.97	20.74	0	0.0
	12	13	21.07	21.01	20.75	0-1	0.0
	25	0	21.11	21.04	20.69		0.0
DFT-s-OFDM 16QAM	1	1	21.12	21.18	20.45	0-1	0.0
CP-OFDM QPSK	1	1	21.15	20.96	20.60	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 49 of 55

F.2.5 NR Band n41

Table F-75

NR Band n41 Measured P_{limit} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), or DSI = 2 (Hotspot mode active), or DSI = 4, 5, or 6 (Phablet with grip sensor active) and/or DSI = 3 (Earjack Active) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM $\pi/2$ BPSK	1	1	17.61	17.51	0	0.0
	1	109	18.27	17.80		0.0
	1	215	18.18	18.16		0.0
	108	0	17.97	17.63	0-0.5	0.0
	108	55	18.31	17.79	0	0.0
	108	109	18.36	18.06	0-0.5	0.0
	216	0	18.30	17.90		0.0
DFT-s-OFDM QPSK	1	1	17.85	17.70	0	0.0
	1	109	18.46	17.87		0.0
	1	215	18.33	18.24		0.0
	108	0	18.25	17.65	0-1	0.0
	108	55	18.48	17.85	0	0.0
	108	109	18.49	18.12	0-1	0.0
	216	0	18.35	17.92		0.0
DFT-s-OFDM 16QAM	1	1	18.14	17.90	0-1	0.0
CP-OFDM QPSK	1	1	17.95	17.70	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 50 of 55

Table F-76

NR Band n41 Measured P_{limit} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), or DSI = 2 (Hotspot mode active), or DSI = 4, 5, or 6 (Phablet with grip sensor active) and/or DSI = 3 (Earjack Active) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	17.74	18.12	17.57	0	0.0
	1	81	18.29	18.12	18.02		0.0
	1	160	18.43	18.02	18.41		0.0
	81	0	18.10	18.18	17.83	0-0.5	0.0
	81	41	18.40	18.15	18.05	0	0.0
	81	81	18.45	18.13	18.26	0-0.5	0.0
	162	0	18.39	18.15	18.07		0.0
DFT-s-OFDM QPSK	1	1	17.99	18.32	17.81	0	0.0
	1	81	18.43	18.18	18.16		0.0
	1	160	18.49	18.18	18.41		0.0
	81	0	18.26	18.24	17.82	0-1	0.0
	81	41	18.45	18.17	18.01	0	0.0
	81	81	18.45	18.12	18.25	0-1	0.0
	162	0	18.45	18.15	18.08		0.0
DFT-s-OFDM 16QAM	1	1	18.25	18.19	17.73	0-1	0.0
CP-OFDM QPSK	1	1	18.00	18.25	17.68	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 51 of 55

Table F-77

NR Band n41 Measured P_{limit} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), or DSI = 2 (Hotspot mode active), or DSI = 4, 5, or 6 (Phablet with grip sensor active) and/or DSI = 3 (Earjack Active) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
			503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM $\pi/2$ BPSK	1	1	17.91	18.08	17.77	17.67	0	0.0
	1	53	18.10	18.18	17.63	17.90		0.0
	1	104	18.35	18.16	17.77	18.19		0.0
	50	0	18.10	18.25	17.89	17.87	0-0.5	0.0
	50	28	18.15	18.22	17.77	17.98	0	0.0
	50	56	18.32	18.21	17.90	18.16	0-0.5	0.0
	100	0	18.13	18.23	17.91	18.01		0.0
DFT-s-OFDM QPSK	1	1	18.01	18.32	17.98	17.84	0	0.0
	1	53	18.17	18.22	17.86	18.06		0.0
	1	104	18.47	18.24	17.93	18.29		0.0
	50	0	18.14	18.28	17.91	17.93	0-1	0.0
	50	28	18.18	18.24	17.84	18.04	0	0.0
	50	56	18.25	18.22	17.90	18.17	0-1	0.0
	100	0	18.18	18.27	17.89	18.10		0.0
DFT-s-OFDM 16QAM	1	1	17.90	18.22	17.85	17.81	0-1	0.0
CP-OFDM QPSK	1	1	17.89	18.31	17.85	17.81	0-1.5	0.0

Table F-78

NR Band n41 Measured P_{limit} for DSI = 0 (Body-worn, or Phablet with grip sensor inactive), or DSI = 2 (Hotspot mode active), or DSI = 4, 5, or 6 (Phablet with grip sensor active) and/or DSI = 3 (Earjack Active) - 20 MHz Bandwidth

NR Band n41									
20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM $\pi/2$ BPSK	1	1	17.89	18.00	17.88	17.62	17.76	0	0.0
	1	26	18.02	18.04	17.75	17.81	17.88		0.0
	1	49	18.15	18.06	17.81	17.89	17.98		0.0
	25	0	18.00	18.09	17.92	17.82	17.94	0-0.5	0.0
	25	13	18.19	18.07	17.89	17.82	18.00	0	0.0
	25	26	18.25	18.12	17.81	17.85	18.06	0-0.5	0.0
50	0	18.22	18.10	17.89	17.82	18.02	0.0		
DFT-s-OFDM QPSK	1	1	18.02	18.19	17.91	17.92	18.00	0	0.0
	1	26	17.99	18.17	17.77	17.77	17.99		0.0
	1	49	18.22	18.19	17.89	17.87	18.10		0.0
	25	0	18.00	18.15	17.88	17.85	17.99	0-1	0.0
	25	13	18.20	18.10	17.90	17.84	18.13	0	0.0
	25	26	18.19	18.16	17.85	17.92	18.15	0-1	0.0
50	0	18.24	18.15	17.89	17.87	18.10	0.0		
DFT-s-OFDM 16QAM	1	1	17.66	18.08	17.74	17.55	17.78	0-1	0.0
CP-OFDM QPSK	1	1	18.00	18.19	17.98	17.80	18.16	0-1.5	0.0

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 52 of 55

Table F-79
NR Band n41 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM $\pi/2$ BPSK	1	1	13.85	13.75	0	0.0
	1	109	14.49	13.94		0.0
	1	215	14.40	14.18		0.0
	108	0	14.28	13.79	0-0.5	0.0
	108	55	14.45	13.95	0	0.0
	108	109	14.50	14.20	0-0.5	0.0
	216	0	14.36	14.01		0.0
DFT-s-OFDM QPSK	1	1	13.88	13.72	0	0.0
	1	109	14.50	13.95		0.0
	1	215	14.40	14.27		0.0
	108	0	14.23	13.85	0-1	0.0
	108	55	14.55	13.95	0	0.0
	108	109	14.58	14.22	0-1	0.0
	216	0	14.40	14.05		0.0
DFT-s-OFDM 16QAM	1	1	14.12	13.95	0-1	0.0
CP-OFDM QPSK	1	1	13.94	13.83	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of  element	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset			APPENDIX F: Page 53 of 55

Table F-80
NR Band n41 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM $\pi/2$ BPSK	1	1	14.17	14.24	13.80	0	0.0
	1	81	14.70	14.06	14.03		0.0
	1	160	14.77	14.08	14.45		0.0
	81	0	14.46	14.30	13.91	0-0.5	0.0
	81	41	14.75	14.22	14.07	0	0.0
	81	81	14.74	14.15	14.28	0-0.5	0.0
	162	0	14.67	14.19	14.14		0.0
DFT-s-OFDM QPSK	1	1	14.12	14.29	13.79	0	0.0
	1	81	14.71	14.15	14.01		0.0
	1	160	14.71	14.08	14.47		0.0
	81	0	14.45	14.31	13.94	0-1	0.0
	81	41	14.69	14.21	14.11	0	0.0
	81	81	14.68	14.18	14.32	0-1	0.0
	162	0	14.66	14.24	14.16		0.0
DFT-s-OFDM 16QAM	1	1	14.55	14.62	14.11	0-1	0.0
CP-OFDM QPSK	1	1	14.01	14.21	13.80	0-1.5	0.0

FCC ID A3LSMA426U	 PCTEST Proud to be part of Samsung	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 54 of 55		

Table F-81
NR Band n41 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM $\pi/2$ BPSK	1	1	14.34	14.59	14.54	14.23	0	0.0
	1	53	14.47	14.60	14.43	14.36		0.0
	1	104	14.74	14.61	14.50	14.45		0.0
	50	0	14.51	14.74	14.51	14.28	0-0.5	0.0
	50	28	14.53	14.69	14.49	14.40	0	0.0
	50	56	14.75	14.69	14.50	14.54	0-0.5	0.0
	100	0	14.55	14.69	14.58	14.39		0.0
DFT-s-OFDM QPSK	1	1	14.33	14.61	14.60	14.15	0	0.0
	1	53	14.57	14.60	14.45	14.40		0.0
	1	104	14.75	14.57	14.51	14.61		0.0
	50	0	14.51	14.74	14.57	14.33	0-1	0.0
	50	28	14.60	14.73	14.51	14.42	0	0.0
	50	56	14.75	14.67	14.59	14.61	0-1	0.0
	100	0	14.55	14.72	14.58	14.40		0.0
DFT-s-OFDM 16QAM	1	1	14.58	14.62	14.57	14.20	0-1	0.0
CP-OFDM QPSK	1	1	14.38	14.52	14.48	14.15	0-1.5	0.0

Table F-82
NR Band n41 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41									
20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
			501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM $\pi/2$ BPSK	1	1	14.00	14.49	14.20	14.05	14.15	0	0.0
	1	26	14.18	14.39	14.10	14.03	14.18		0.0
	1	49	14.30	14.52	14.14	14.11	14.25		0.0
	25	0	14.15	14.48	14.20	14.05	14.25	0-0.5	0.0
	25	13	14.27	14.45	14.13	14.07	14.25	0	0.0
	25	26	14.32	14.57	14.08	14.11	14.33	0-0.5	0.0
	50	0	14.25	14.46	14.14	14.11	14.28		0.0
DFT-s-OFDM QPSK	1	1	14.16	14.57	14.23	14.10	14.20	0	0.0
	1	26	14.25	14.54	14.21	14.05	14.37		0.0
	1	49	14.33	14.60	14.20	14.17	14.41		0.0
	25	0	14.12	14.50	14.21	14.12	14.22	0-1	0.0
	25	13	14.34	14.46	14.20	14.11	14.36	0	0.0
	25	26	14.24	14.57	14.16	14.10	14.40	0-1	0.0
	50	0	14.32	14.51	14.20	14.12	14.35		0.0
DFT-s-OFDM 16QAM	1	1	14.38	14.61	14.50	14.45	14.26	0-1	0.0
CP-OFDM QPSK	1	1	14.11	14.54	14.11	14.04	14.20	0-1.5	0.0

FCC ID A3LSMA426U		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 01/12/21 – 02/19/21	DUT Type: Portable Handset	APPENDIX F: Page 55 of 55		