

RF Exposure Evaluation Report

APPLICANT : Smawave Technology Co. ,Ltd
EQUIPMENT : 5G ODU_NA
BRAND NAME : smawave
MODEL NAME : SRE620-b
FCC ID : 2AU8HSRE620-BH
STANDARD : 47 CFR Part 2.1091

The product evaluation date was started from Jul. 11, 2023 and completed on Jul. 11, 2023. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA342001-01	Rev. 01	Initial issue of report.	Jul. 17, 2023



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Smawave Technology Co. ,Ltd
Address	3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

Manufacturer	
Company Name	Smawave Technology Co. ,Ltd
Address	3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	5G ODU_NA
Brand Name	smawave
Model Name	SRE620-b
FCC ID	2AU8HSRE620-BH
Wireless Technology and Frequency Range	LTE Band 48: 3550 MHz ~ 3700 MHz 5G NR n48 : 3550 MHz ~ 3700 MHz
Mode	LTE: QPSK, 16QAM, 64QAM, 256QAM 5G NR : CP-OFDM / DFT-s-OFDM, PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM
Antenna Gain	<Ant. 0> LTE Band 48 : 16.32 dBi 5G NR n48 : 16.32 dBi <Ant.3>: 5G NR n48 : 15.92 dBi
Antenna Type	WWAN : Fixed External Antenna
HW Version	V1.0
SW Version	Codium_FW_5G_1.0.8

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This device supports intra-band ULCA, due to intra-band ULCA and non-CA power is same, so non-CA MPE analysis can represent ULCA MPE analysis.
3. 5G NR n48 support SA mode only.
4. WWAN 5G NR n48 support SISO/MIMO mode, so only chose MIMO tune up power to perform MPE calculation conservatively for MIMO power is higher.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

**3. Maximum RF average output tune up power among production units****<LTE>**

Mode		Maximum Average power(dBm)
LTE	Band 48	23.00

<5GNR>

Mode		Maximum Average power(dBm)
5GNR	n48	21.00

<MIMO>

Mode		Maximum Average power(dBm)
5GNR	n48 Ant0+3	21.00



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 27 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 27cm (mW/cm ²)	Limit (mW/cm ²)
LTE Band 48	3550.0	16.32	23.00	39.320	8550.667	0.934	1.000
5G NR n48	3550.0	16.32	21.00	37.320	5395.106	0.589	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. Chose the maximum RF output tune up power of all antennas among same frequency WWAN bands and the maximum antenna gain to perform MPE calculation conservatively.
4. The MIMO mode is completely uncorrelated, so selected the higher SISO gain among all antennas as MIMO gain to perform MPE calculation.

Conclusion:

According to 47 CFR §2.1091, the MPE was calculated at 27 cm to show compliance with the power density limit, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----