

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

**FCC PART 15 SUBPART C TEST REPORT****FCC PART 15.247****Report Reference No.....: GTS20200303006-1-21****FCC ID.....: 2AQAA-EZPADPRO8**

Compiled by

( position+printed name+signature)...: File administrators Tracy Hu

Supervised by

( position+printed name+signature)...: Test Engineer Moon Tan

Approved by

( position+printed name+signature)...: Manager Simon Hu

Date of issue.....: Apr. 14, 2020

**Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.**

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

**Applicant's name.....: SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Address .....: 101, 102, 201, 301 No.13-2 Pingxi South Rd., Pingxi Community, Pingdi Street, Longgang District, Shenzhen, Guangdong

**Test specification .....**Standard .....: **FCC Part 15.247**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

**Shenzhen Global Test Service Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description .....: Portable computer**


Trade Mark .....: N/A

Manufacturer .....: **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Model/Type reference.....: EZpad Pro8

Listed Models .....: EZpad Pro 8S,EZpad Pro 8D,EZpad Pro 9,EZpad Pro 9S, EZpad Pro 9D

Operation Frequency.....: From 2412MHz to 2462MHz

Rating .....: DC 7.6V by battery  
Recharged by DC 12V/3AResult.....: **PASS**

**TEST REPORT**

|                                                     |                                |
|-----------------------------------------------------|--------------------------------|
| <b>Test Report No. :</b> <b>GTS20200303006-1-21</b> | Apr. 14, 2020<br>Date of issue |
|-----------------------------------------------------|--------------------------------|

Equipment under Test        :     Portable computer

Model /Type                    :     EZpad Pro8

Listed model                   :     EZpad Pro 8S,EZpad Pro 8D,EZpad Pro 9,EZpad Pro 9S,  
EZpad Pro 9D

**Applicant**                    :     **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Address                        :     101, 102, 201, 301 No.13-2 Pingxi South Rd., Pingxi Community,  
Pingdi Street, Longgang District, Shenzhen, Guangdong

**Manufacturer**               :     **SHENZHEN JUMPER TECHNOLOGY CO.,LTD**

Address                        :     101, 102, 201, 301 No.13-2 Pingxi South Rd., Pingxi Community,  
Pingdi Street, Longgang District, Shenzhen, Guangdong

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|                                                                |           |
|----------------------------------------------------------------|-----------|
| <b>1. TEST STANDARDS .....</b>                                 | <b>4</b>  |
| <b>2. SUMMARY .....</b>                                        | <b>5</b>  |
| 2.1. General Remarks .....                                     | 5         |
| 2.2. Product Description .....                                 | 5         |
| 2.3. Equipment Under Test .....                                | 6         |
| 2.4. Short description of the Equipment under Test (EUT) ..... | 6         |
| 2.5. EUT operation mode .....                                  | 6         |
| 2.6. Block Diagram of Test Setup .....                         | 6         |
| 2.7. Related Submittal(s) / Grant (s) .....                    | 6         |
| 2.8. Special Accessories .....                                 | 6         |
| 2.9. Modifications .....                                       | 6         |
| <b>3. TEST ENVIRONMENT .....</b>                               | <b>7</b>  |
| 3.1. Address of the test laboratory .....                      | 7         |
| 3.2. Test Facility .....                                       | 7         |
| 3.3. Environmental conditions .....                            | 7         |
| 3.4. Test Description .....                                    | 8         |
| 3.5. Statement of the measurement uncertainty .....            | 9         |
| 3.6. Equipments Used during the Test.....                      | 10        |
| <b>4. TEST CONDITIONS AND RESULTS .....</b>                    | <b>11</b> |
| 4.1. AC Power Conducted Emission .....                         | 11        |
| 4.2. Radiated Emission .....                                   | 13        |
| 4.3. Maximum Peak Output Power .....                           | 19        |
| 4.4. Power Spectral Density .....                              | 20        |
| 4.5. 6dB Bandwidth .....                                       | 25        |
| 4.6. Band Edge Compliance of RF Emission .....                 | 30        |
| 4.7. Antenna Requirement .....                                 | 37        |
| <b>5. TEST SETUP PHOTOS OF THE EUT .....</b>                   | <b>38</b> |
| <b>6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>        | <b>38</b> |

## **1. TEST STANDARDS**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 DTS Meas Guidance v05r02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

## 2. SUMMARY

### 2.1. General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Apr. 3, 2020  |
|                                | : |               |
| Testing commenced on           | : | Apr. 4, 2020  |
|                                | : |               |
| Testing concluded on           | : | Apr. 14, 2020 |

### 2.2. Product Description

|                       |                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:         | Portable computer                                                                                                                                                                                                                                                                                                                                                                                 |
| Trade Mark:           | N/A                                                                                                                                                                                                                                                                                                                                                                                               |
| Model/Type reference: | EZpad Pro8                                                                                                                                                                                                                                                                                                                                                                                        |
| List Model:           | EZpad Pro 8S,EZpad Pro 8D,EZpad Pro 9,EZpad Pro 9S, EZpad Pro 9D                                                                                                                                                                                                                                                                                                                                  |
| Power supply:         | DC 7.6V form battery                                                                                                                                                                                                                                                                                                                                                                              |
| <b>WIFI</b>           |                                                                                                                                                                                                                                                                                                                                                                                                   |
| WLAN                  | Supported 802.11 a/b/g/n/ac                                                                                                                                                                                                                                                                                                                                                                       |
| Modulation Type       | IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)<br>IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)<br>IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)<br>IEEE 802.11ac20/40/80: OFDM(256QAM,64QAM, 16QAM, QPSK, BPSK)                                                                                     |
| Operation frequency   | IEEE 802.11a:5180-5240MHz 5745-5825MHz<br>IEEE 802.11b:2412-2462MHz<br>IEEE 802.11g:2412-2462MHz<br>IEEE 802.11n HT20:2412-2462MHz, 5180-5240MHz 5745-5825MHz<br>IEEE 802.11n HT40:2422-2452MHz, 5190-5230MHz 5755-5795MHz<br>IEEE 802.11ac20:5180-5240MHz 5745-5825MHz<br>IEEE 802.11ac40:5190-5230MHz 5755-5795MHz<br>IEEE 802.11ac80:5210MHz 5775MHz                                           |
| Channel number        | 11 Channels for WIFI 20MHz Bandwidth(802.11b/g/n-HT20)<br>7 Channels for WIFI 40MHz Bandwidth(802.11n-HT40)<br>4 channels for 20MHz bandwidth(5180-5240MHz)<br>2 channels for 40MHz bandwidth(5190~5230MHz)<br>1 channels for 80MHz bandwidth(5210MHz)<br>5 channels for 20MHz bandwidth(5745-5825MHz)<br>2 channels for 40MHz bandwidth(5755~5795MHz)<br>1 channels for 80MHz bandwidth(5775MHz) |
| <b>BT</b>             |                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operation frequency   | 2402-2480MHz                                                                                                                                                                                                                                                                                                                                                                                      |
| Channel Number        | 79 channels for Bluetooth (DSS)<br>40 channels for Bluetooth (DTS)                                                                                                                                                                                                                                                                                                                                |
| Channel Spacing       | 1MHz for Bluetooth (DSS)<br>2MHz for Bluetooth (DTS)                                                                                                                                                                                                                                                                                                                                              |
| Modulation Type       | GFSK, $\pi/4$ DQPSK, 8DPSK for Bluetooth (DSS)<br>GFSK for Bluetooth (DTS)                                                                                                                                                                                                                                                                                                                        |
| Antenna Description   | Two same FPC Antenna, but not support MIMO technology<br>ANT0 used for Bluetooth & WIFI TX/RX, 1.87dBi(Max.) for 2.4G Band and 1.85dBi(Max.) for 5G Band<br>ANT1 used for WIFI TX/RX, 1.87dBi(Max.) for 2.4G Band and 1.85dBi(Max.) for 5G Band                                                                                                                                                   |

### 2.3. Equipment Under Test

#### Power supply system utilised

|                      |   |                                                                   |                                   |
|----------------------|---|-------------------------------------------------------------------|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz                                | <input type="radio"/> 120V / 60Hz |
|                      |   | <input type="radio"/> 12 V DC                                     | <input type="radio"/> 24 V DC     |
|                      |   | <input checked="" type="radio"/> Other (specified in blank below) |                                   |

DC 7.6V form battery

### 2.4. Short description of the Equipment under Test (EUT)

This is a Portable computer.

For more details, refer to the user's manual of the EUT.

### 2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.


#### NOTE:

**Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used.**

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| 1       | 2412           | 8       | 2447           |
| 2       | 2417           | 9       | 2452           |
| 3       | 2422           | 10      | 2457           |
| 4       | 2427           | 11      | 2462           |
| 5       | 2432           |         |                |
| 6       | 2437           |         |                |
| 7       | 2442           |         |                |

### 2.6. Block Diagram of Test Setup



### 2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID:2AQAA-EZPADPRO8** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

### 2.8. Special Accessories

| Manufacturer                     | Description | Model                 | Serial Number | Certificate |
|----------------------------------|-------------|-----------------------|---------------|-------------|
| Shenzhen Jihongda Power Co.,Ltd. | Adapter     | JHD-AP036U-120300AA-A | --            | SDOC        |

### 2.9. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

#### **3.3. Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 15-35 ° C    |
|                       |              |
| Humidity:             | 30-60 %      |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

### 3.4. Test Description

| Test Specification clause | Test case                               | Test Mode                                          | Test Channel                                                                                                                            | Recorded In Report                                 |                                                                                                                                         | Pass                                                                                                              | Fail                     | NA                                  | NP                       | Remark   |
|---------------------------|-----------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------|--------------------------|----------|
| §15.247(b)(4)             | Antenna gain                            | 802.11b                                            | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b                                            | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(e)                | Power spectral density                  | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(a)(2)             | Spectrum bandwidth – 6 dB bandwidth     | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/>                                        | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(b)(1)             | Maximum output power                    | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/><br><input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(d)                | Band edge compliance conducted          | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/>                                        | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.205                   | Band edge compliance radiated           | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(d)                | TX spurious emissions conducted         | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/>                                        | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(d)                | TX spurious emissions radiated          | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.109                   | RX spurious emissions radiated          | -/-                                                | -/-                                                                                                                                     | -/-                                                | -/-                                                                                                                                     | <input type="checkbox"/>                                                                                          | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | complies |
| §15.209(a)                | TX spurious Emissions radiated < 30 MHz | 802.11b                                            | -/-                                                                                                                                     | 802.11b                                            | -/-                                                                                                                                     | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.107(a)<br>§15.207     | Conducted Emissions < 30 MHz            | 802.11b                                            | -/-                                                                                                                                     | 802.11b                                            | -/-                                                                                                                                     | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                                                                                                                                                                                           | Mode            | Data Rate | Channel |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------|---------|
| Maximum Peak Conducted Output Power<br>Power Spectral Density<br>6dB Bandwidth<br>Spurious RF conducted emission<br>Radiated Emission 9kHz~1GHz&<br>Radiated Emission 1GHz~10 <sup>th</sup> Harmonic | 11b/DSSS        | 1 Mbps    | 1/6/11  |
|                                                                                                                                                                                                      | 11g/OFDM        | 6 Mbps    | 1/6/11  |
|                                                                                                                                                                                                      | 11n(20MHz)/OFDM | 6.5Mbps   | 1/6/11  |
|                                                                                                                                                                                                      | 11n(40MHz)/OFDM | 13.5Mbps  | 3/6/9   |
| Band Edge                                                                                                                                                                                            | 11b/DSSS        | 1 Mbps    | 1/11    |
|                                                                                                                                                                                                      | 11g/OFDM        | 6 Mbps    | 1/11    |
|                                                                                                                                                                                                      | 11n(20MHz)/OFDM | 6.5Mbps   | 1/11    |
|                                                                                                                                                                                                      | 11n(40MHz)/OFDM | 13.5Mbps  | 3/9     |

### 3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test                  | Range      | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission     | 30~1000MHz | 4.10 dB                 | (1)   |
| Radiated Emission     | 1~18GHz    | 4.32 dB                 | (1)   |
| Radiated Emission     | 18-40GHz   | 5.54 dB                 | (1)   |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB                 | (1)   |

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.6. Equipments Used during the Test


| Test Equipment             | Manufacturer                      | Model No.             | Serial No.      | Calibration Date | Calibration Due Date |
|----------------------------|-----------------------------------|-----------------------|-----------------|------------------|----------------------|
| LISN                       | R&S                               | ENV216                | 3560.6550.08    | 2019/09/20       | 2020/09/19           |
| LISN                       | R&S                               | ESH2-Z5               | 893606/008      | 2019/09/20       | 2020/09/19           |
| EMI Test Receiver          | R&S                               | ESPI3                 | 101841-cd       | 2019/09/20       | 2020/09/19           |
| EMI Test Receiver          | R&S                               | ESCI7                 | 101102          | 2019/09/20       | 2020/09/19           |
| Spectrum Analyzer          | Agilent                           | N9020A                | MY48010425      | 2019/09/20       | 2020/09/19           |
| Spectrum Analyzer          | R&S                               | FSV40                 | 100019          | 2019/09/20       | 2020/09/19           |
| Vector Signal generator    | Agilent                           | N5181A                | MY49060502      | 2019/09/20       | 2020/09/19           |
| Signal generator           | Agilent                           | E4421B                | 3610AO1069      | 2019/09/20       | 2020/09/19           |
| Climate Chamber            | ESPEC                             | EL-10KA               | A20120523       | 2019/09/20       | 2020/09/19           |
| Controller                 | EM Electronics                    | Controller EM 1000    | N/A             | N/A              | N/A                  |
| Horn Antenna               | Schwarzbeck                       | BBHA 9120D            | 01622           | 2019/09/23       | 2020/09/22           |
| Active Loop Antenna        | Beijing Da Ze Technology Co.,Ltd. | ZN30900C              | 15006           | 2019/10/12       | 2020/10/11           |
| Bilog Antenna              | Schwarzbeck                       | VULB9163              | 000976          | 2019/05/26       | 2020/05/25           |
| Broadband Horn Antenna     | SCHWARZBECK                       | BBHA 9170             | 791             | 2019/09/20       | 2020/09/19           |
| Amplifier                  | Schwarzbeck                       | BBV 9743              | #202            | 2019/09/20       | 2020/09/19           |
| Amplifier                  | Schwarzbeck                       | BBV9179               | 9719-025        | 2019/09/20       | 2020/09/19           |
| Amplifier                  | EMCI                              | EMC051845B            | 980355          | 2019/09/20       | 2020/09/19           |
| Temperature/Humidity Meter | Gangxing                          | CTH-608               | 02              | 2019/09/20       | 2020/09/19           |
| High-Pass Filter           | K&L                               | 9SH10-2700/X12750-O/O | KL142031        | 2019/09/20       | 2020/09/19           |
| High-Pass Filter           | K&L                               | 41H10-1375/U12750-O/O | KL142032        | 2019/09/20       | 2020/09/19           |
| RF Cable(below 1GHz)       | HUBER+SUHNER                      | RG214                 | RE01            | 2019/09/20       | 2020/09/19           |
| RF Cable(above 1GHz)       | HUBER+SUHNER                      | RG214                 | RE02            | 2019/09/20       | 2020/09/19           |
| Data acquisition card      | Agilent                           | U2531A                | TW53323507      | 2019/09/20       | 2020/09/19           |
| Power Sensor               | Agilent                           | U2021XA               | MY5365004       | 2019/09/20       | 2020/09/19           |
| Test Control Unit          | Tonscend                          | JS0806-1              | 178060067       | 2019/06/20       | 2020/06/19           |
| Automated filter bank      | Tonscend                          | JS0806-F              | 19F8060177      | 2019/06/20       | 2020/06/19           |
| EMI Test Software          | Tonscend                          | JS1120-1              | Ver 2.6.8.0518  | /                | /                    |
| EMI Test Software          | Tonscend                          | JS1120-3              | Ver 2.5.77.0418 | /                | /                    |
| EMI Test Software          | Tonscend                          | JS32-CE               | Ver 2.5         | /                | /                    |
| EMI Test Software          | Tonscend                          | JS32-RE               | Ver 2.5.1.8     | /                | /                    |

Note: The Cal.Interval was one year.

## 4. TEST CONDITIONS AND RESULTS

### 4.1. AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark: We measured Conducted Emission at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode in AC 120V/60Hz , the worst case was recorded .


Power supply:

AC 120V/60Hz

Polarization

L

Test Graph



Final Data List

| NO. | Frequency<br>[MHz] | QP<br>Reading<br>[dBμV] | AVG.<br>Reading<br>[dBμV] | Factor<br>[dB] | QP<br>Result<br>[dBμV] | AVG.<br>Result<br>[dBμV] | QP<br>Limit<br>[dBμV] | AVG.<br>Limit<br>[dBμV] | QP<br>Margin<br>[dB] | AVG.<br>Margin<br>[dB] | Line | Remark |
|-----|--------------------|-------------------------|---------------------------|----------------|------------------------|--------------------------|-----------------------|-------------------------|----------------------|------------------------|------|--------|
| 1   | 0.1559             | 48.29                   | 36.65                     | 10.32          | 58.61                  | 46.97                    | 65.68                 | 55.68                   | 7.07                 | 8.71                   | L1   | PASS   |
| 2   | 0.1906             | 45.28                   | 33.46                     | 10.16          | 55.44                  | 43.62                    | 64.01                 | 54.01                   | 8.57                 | 10.39                  | L1   | PASS   |
| 3   | 0.2264             | 38.80                   | 28.63                     | 10.14          | 48.94                  | 38.77                    | 62.58                 | 52.58                   | 13.64                | 13.81                  | L1   | PASS   |
| 4   | 0.4843             | 34.79                   | 28.60                     | 10.25          | 45.04                  | 38.85                    | 56.27                 | 46.27                   | 11.23                | 7.42                   | L1   | PASS   |
| 5   | 0.8174             | 32.77                   | 26.78                     | 10.24          | 43.01                  | 37.02                    | 56.00                 | 46.00                   | 12.99                | 8.98                   | L1   | PASS   |
| 6   | 1.1099             | 31.55                   | 25.59                     | 10.21          | 41.76                  | 35.80                    | 56.00                 | 46.00                   | 14.24                | 10.20                  | L1   | PASS   |


Power supply:

AC 120V/60Hz

Polarization

N

Test Graph




Final Data List

| NO. | Frequency<br>[MHz] | QP<br>Reading<br>[dBμV] | AVG.<br>Reading<br>[dBμV] | Factor<br>[dB] | QP<br>Result<br>[dBμV] | AVG.<br>Result<br>[dBμV] | QP<br>Limit<br>[dBμV] | AVG.<br>Limit<br>[dBμV] | QP<br>Margin<br>[dB] | AVG.<br>Margin<br>[dB] | Line | Remark |
|-----|--------------------|-------------------------|---------------------------|----------------|------------------------|--------------------------|-----------------------|-------------------------|----------------------|------------------------|------|--------|
| 1   | 0.1551             | 47.30                   | 34.94                     | 10.33          | 57.63                  | 45.27                    | 65.72                 | 55.72                   | 8.09                 | 10.45                  | N    | PASS   |
| 2   | 0.1595             | 46.40                   | 34.43                     | 10.31          | 56.71                  | 44.74                    | 65.49                 | 55.49                   | 8.78                 | 10.75                  | N    | PASS   |
| 3   | 0.2033             | 41.56                   | 29.58                     | 10.15          | 51.71                  | 39.73                    | 63.47                 | 53.47                   | 11.76                | 13.74                  | N    | PASS   |
| 4   | 0.5595             | 38.36                   | 30.60                     | 10.21          | 48.57                  | 40.81                    | 56.00                 | 46.00                   | 7.43                 | 5.19                   | N    | PASS   |
| 5   | 0.8169             | 37.93                   | 31.95                     | 10.24          | 48.17                  | 42.19                    | 56.00                 | 46.00                   | 7.83                 | 3.81                   | N    | PASS   |
| 6   | 1.8569             | 37.38                   | 30.94                     | 10.26          | 47.64                  | 41.20                    | 56.00                 | 46.00                   | 8.36                 | 4.80                   | N    | PASS   |


## 4.2. Radiated Emission

### TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 30MHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 30MHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type          | Test Distance |
|----------------------|----------------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna        | 3             |
| 30MHz-1GHz           | Ultra-Broadband Antenna    | 3             |
| 1GHz-18GHz           | Double Ridged Horn Antenna | 3             |
| 18GHz-25GHz          | Horn Antenna               | 1             |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

|                           |                                            |
|---------------------------|--------------------------------------------|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude    | AG = Amplifier Gain                        |
| AF = Antenna Factor       |                                            |

$$Transd=AF +CL-AG$$

**RADIATION LIMIT**


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


| Frequency (MHz) | Distance (Meters) | Radiated (dBµV/m)                    | Radiated (µV/m) |
|-----------------|-------------------|--------------------------------------|-----------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(KHz))+40\log(300/3)$  | $2400/F(KHz)$   |
| 0.49-1.705      | 3                 | $20\log(24000/F(KHz))+ 40\log(30/3)$ | $24000/F(KHz)$  |
| 1.705-30        | 3                 | $20\log(30)+ 40\log(30/3)$           | 30              |
| 30-88           | 3                 | 40.0                                 | 100             |
| 88-216          | 3                 | 43.5                                 | 150             |
| 216-960         | 3                 | 46.0                                 | 200             |
| Above 960       | 3                 | 54.0                                 | 500             |

**TEST RESULTS**

Remark: We measured Radiated Emission at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode from 30 MHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

**For 30MHz-1GHz****Horizontal****Test Graph****Suspected List**

| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity   | Remark |
|-----|-----------------|------------------|-------------|-----------------|----------------|-------------|-------------|-----------|----------|------------|--------|
| 1   | 118.7550        | 40.02            | -10.11      | 29.91           | 43.50          | 13.59       | 100         | 46        | PK       | Horizontal | PASS   |
| 2   | 195.3850        | 40.53            | -9.45       | 31.08           | 43.50          | 12.42       | 100         | 35        | PK       | Horizontal | PASS   |
| 3   | 256.4950        | 43.06            | -8.12       | 34.94           | 46.00          | 11.06       | 100         | 2         | PK       | Horizontal | PASS   |
| 4   | 593.5700        | 41.97            | -1.87       | 40.10           | 46.00          | 5.90        | 100         | 46        | PK       | Horizontal | PASS   |
| 5   | 741.9800        | 39.53            | 0.15        | 39.68           | 46.00          | 6.32        | 100         | 291       | PK       | Horizontal | PASS   |
| 6   | 890.3900        | 37.69            | 2.60        | 40.29           | 46.00          | 5.71        | 100         | 44        | PK       | Horizontal | PASS   |

**Vertical****Test Graph****Suspected List**

| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity | Remark |
|-----|-----------------|------------------|-------------|-----------------|----------------|-------------|-------------|-----------|----------|----------|--------|
| 1   | 38.2450         | 42.70            | -7.85       | 34.85           | 40.00          | 5.15        | 100         | 181       | PK       | Vertical | PASS   |
| 2   | 110.9950        | 44.14            | -8.73       | 35.41           | 43.50          | 8.09        | 100         | 275       | PK       | Vertical | PASS   |
| 3   | 185.6850        | 39.76            | -10.77      | 28.99           | 43.50          | 14.51       | 100         | 134       | PK       | Vertical | PASS   |
| 4   | 420.4250        | 42.14            | -4.75       | 37.39           | 46.00          | 8.61        | 100         | 165       | PK       | Vertical | PASS   |
| 5   | 741.9800        | 41.38            | 0.15        | 41.53           | 46.00          | 4.47        | 100         | 347       | PK       | Vertical | PASS   |
| 6   | 890.3900        | 39.28            | 2.60        | 41.88           | 46.00          | 4.12        | 100         | 20        | PK       | Vertical | PASS   |

**NOTE:the worst case was ant 0.  
For 1GHz to 25GHz**

IEEE 802.11b

Channel 1 / 2412 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4824.00   | 51.30        | 32.44          | 30.25        | 7.95         | 61.44           | 74.00        | -12.56    | Peak    | Horizontal |
| 4824.00   | 34.90        | 32.44          | 30.25        | 7.95         | 45.04           | 54.00        | -8.96     | Average | Horizontal |
| 4824.00   | 54.03        | 32.44          | 30.25        | 7.95         | 64.17           | 74.00        | -9.83     | Peak    | Vertical   |
| 4824.00   | 35.56        | 32.44          | 30.25        | 7.95         | 45.70           | 54.00        | -8.30     | Average | Vertical   |

Channel 6 / 2437 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.97        | 32.52          | 30.31        | 8.12         | 60.30           | 74.00        | -13.70    | Peak    | Horizontal |
| 4874.00   | 35.56        | 32.52          | 30.31        | 8.12         | 45.89           | 54.00        | -8.11     | Average | Horizontal |
| 4874.00   | 51.01        | 32.52          | 30.31        | 8.12         | 61.34           | 74.00        | -12.66    | Peak    | Vertical   |
| 4874.00   | 36.05        | 32.52          | 30.31        | 8.12         | 46.38           | 54.00        | -7.62     | Average | Vertical   |

Channel 11 / 2462 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4924.00   | 50.19        | 32.68          | 30.27        | 7.88         | 60.48           | 74.00        | -13.52    | Peak    | Horizontal |
| 4924.00   | 35.92        | 32.68          | 30.27        | 7.88         | 46.21           | 54.00        | -7.79     | Average | Horizontal |
| 4924.00   | 49.56        | 32.68          | 30.27        | 7.88         | 59.85           | 74.00        | -14.15    | Peak    | Vertical   |
| 4924.00   | 35.67        | 32.68          | 30.27        | 7.88         | 45.96           | 54.00        | -8.04     | Average | Vertical   |

IEEE 802.11g

Channel 1 / 2412 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4824.00   | 49.68        | 32.44          | 30.25        | 7.95         | 59.82           | 74.00        | -14.18    | Peak    | Horizontal |
| 4824.00   | 36.35        | 32.44          | 30.25        | 7.95         | 46.49           | 54.00        | -7.51     | Average | Horizontal |
| 4824.00   | 53.59        | 32.44          | 30.25        | 7.95         | 63.73           | 74.00        | -10.27    | Peak    | Vertical   |
| 4824.00   | 35.58        | 32.44          | 30.25        | 7.95         | 45.72           | 54.00        | -8.28     | Average | Vertical   |

Channel 6 / 2437 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.60        | 32.52          | 30.31        | 8.12         | 59.93           | 74.00        | -14.07    | Peak    | Horizontal |
| 4874.00   | 35.23        | 32.52          | 30.31        | 8.12         | 45.56           | 54.00        | -8.44     | Average | Horizontal |
| 4874.00   | 50.99        | 32.52          | 30.31        | 8.12         | 61.32           | 74.00        | -12.68    | Peak    | Vertical   |
| 4874.00   | 36.39        | 32.52          | 30.31        | 8.12         | 46.72           | 54.00        | -7.28     | Average | Vertical   |

## Channel 11 / 2462 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4924.00   | 50.89        | 32.68          | 30.27        | 7.88         | 61.18           | 74.00        | -12.82    | Peak    | Horizontal |
| 4924.00   | 35.55        | 32.68          | 30.27        | 7.88         | 45.84           | 54.00        | -8.16     | Average | Horizontal |
| 4924.00   | 49.59        | 32.68          | 30.27        | 7.88         | 59.88           | 74.00        | -14.12    | Peak    | Vertical   |
| 4924.00   | 35.63        | 32.68          | 30.27        | 7.88         | 45.92           | 54.00        | -8.08     | Average | Vertical   |

## IEEE802.11 n HT20

## Channel 1 / 2412 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4824.00   | 50.24        | 32.44          | 30.25        | 7.95         | 60.38           | 74.00        | -13.62    | Peak    | Horizontal |
| 4824.00   | 35.47        | 32.44          | 30.25        | 7.95         | 45.61           | 54.00        | -8.39     | Average | Horizontal |
| 4824.00   | 54.24        | 32.44          | 30.25        | 7.95         | 64.38           | 74.00        | -9.62     | Peak    | Vertical   |
| 4824.00   | 36.11        | 32.44          | 30.25        | 7.95         | 46.25           | 54.00        | -7.75     | Average | Vertical   |

## Channel 6 / 2437 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.74        | 32.52          | 30.31        | 8.12         | 60.07           | 74.00        | -13.93    | Peak    | Horizontal |
| 4874.00   | 35.22        | 32.52          | 30.31        | 8.12         | 45.55           | 54.00        | -8.45     | Average | Horizontal |
| 4874.00   | 51.73        | 32.52          | 30.31        | 8.12         | 62.06           | 74.00        | -11.94    | Peak    | Vertical   |
| 4874.00   | 35.54        | 32.52          | 30.31        | 8.12         | 45.87           | 54.00        | -8.13     | Average | Vertical   |

## Channel 11 / 2462 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4924.00   | 50.86        | 32.68          | 30.27        | 7.88         | 61.15           | 74.00        | -12.85    | Peak    | Horizontal |
| 4924.00   | 35.69        | 32.68          | 30.27        | 7.88         | 45.98           | 54.00        | -8.02     | Average | Horizontal |
| 4924.00   | 49.31        | 32.68          | 30.27        | 7.88         | 59.60           | 74.00        | -14.40    | Peak    | Vertical   |
| 4924.00   | 35.04        | 32.68          | 30.27        | 7.88         | 45.33           | 54.00        | -8.67     | Average | Vertical   |

## IEEE802.11 n HT40

## Channel 3 / 2422 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4844.00   | 51.02        | 32.44          | 30.25        | 7.95         | 61.16           | 74.00        | -12.84    | Peak    | Horizontal |
| 4844.00   | 34.95        | 32.44          | 30.25        | 7.95         | 45.09           | 54.00        | -8.91     | Average | Horizontal |
| 4844.00   | 54.69        | 32.44          | 30.25        | 7.95         | 64.83           | 74.00        | -9.17     | Peak    | Vertical   |
| 4844.00   | 36.08        | 32.44          | 30.25        | 7.95         | 46.22           | 54.00        | -7.78     | Average | Vertical   |

## Channel 6 / 2437 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.39        | 32.52          | 30.31        | 8.12         | 59.72           | 74.00        | -14.28    | Peak    | Horizontal |
| 4874.00   | 36.92        | 32.52          | 30.31        | 8.12         | 47.25           | 54.00        | -6.75     | Average | Horizontal |
| 4874.00   | 51.12        | 32.52          | 30.31        | 8.12         | 61.45           | 74.00        | -12.55    | Peak    | Vertical   |
| 4874.00   | 35.53        | 32.52          | 30.31        | 8.12         | 45.86           | 54.00        | -8.14     | Average | Vertical   |

## Channel 9 / 2452 MHz


| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4904.00   | 50.94        | 32.68          | 30.27        | 7.88         | 61.23           | 74.00        | -12.77    | Peak    | Horizontal |
| 4904.00   | 35.40        | 32.68          | 30.27        | 7.88         | 45.69           | 54.00        | -8.31     | Average | Horizontal |
| 4904.00   | 49.37        | 32.68          | 30.27        | 7.88         | 59.66           | 74.00        | -14.34    | Peak    | Vertical   |
| 4904.00   | 35.45        | 32.68          | 30.27        | 7.88         | 45.74           | 54.00        | -8.26     | Average | Vertical   |

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

### 4.3. Maximum Peak Output Power

#### TEST CONFIGURATION



#### TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2. and Average conducted output power, 9.2.3.1.

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The maximum Average conducted output power may be measured using a wideband RF power meter with a thermocouple detector or equivalent. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

#### TEST RESULTS

##### Antenna 0:

| Type          | Channel | Output power PK (dBm) | Output power AV (dBm) | Limit (dBm) | Result |
|---------------|---------|-----------------------|-----------------------|-------------|--------|
| 802.11b       | 01      | 16.21                 | 14.23                 | 30.00       | Pass   |
|               | 06      | 16.22                 | 14.27                 |             |        |
|               | 11      | 17.17                 | 14.44                 |             |        |
| 802.11g       | 01      | 16.42                 | 13.54                 | 30.00       | Pass   |
|               | 06      | 16.49                 | 13.59                 |             |        |
|               | 11      | 17.14                 | 13.63                 |             |        |
| 802.11n(HT20) | 01      | 16.28                 | 13.76                 | 30.00       | Pass   |
|               | 06      | 16.41                 | 13.75                 |             |        |
|               | 11      | 17.22                 | 13.97                 |             |        |
| 802.11n(HT40) | 03      | 16.80                 | 14.40                 | 30.00       | Pass   |
|               | 06      | 17.40                 | 14.65                 |             |        |
|               | 09      | 17.01                 | 14.58                 |             |        |

##### Antenna 1:


| Type          | Channel | Output power PK (dBm) | Output power AV (dBm) | Limit (dBm) | Result |
|---------------|---------|-----------------------|-----------------------|-------------|--------|
| 802.11b       | 01      | 15.99                 | 14.31                 | 30.00       | Pass   |
|               | 06      | 16.70                 | 14.25                 |             |        |
|               | 11      | 17.06                 | 14.44                 |             |        |
| 802.11g       | 01      | 16.59                 | 13.65                 | 30.00       | Pass   |
|               | 06      | 16.64                 | 13.62                 |             |        |
|               | 11      | 16.90                 | 13.72                 |             |        |
| 802.11n(HT20) | 01      | 16.31                 | 13.81                 | 30.00       | Pass   |
|               | 06      | 16.92                 | 13.91                 |             |        |
|               | 11      | 17.27                 | 14.06                 |             |        |
| 802.11n(HT40) | 03      | 17.41                 | 14.62                 | 30.00       | Pass   |
|               | 06      | 17.40                 | 14.57                 |             |        |
|               | 09      | 17.13                 | 14.44                 |             |        |

Note: 1. The test results including the cable loss.

Duty cycle used in all test items: 100%.

#### 4.4. Power Spectral Density

##### TEST CONFIGURATION



##### TEST PROCEDURE

According to KDB 558074 D01 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

##### LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

##### TEST RESULTS


###### Antenna 0:







| Type          | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|---------------|---------|-----------------------------------|------------------|--------|
| 802.11b       | 01      | -11.20                            | 8.00             | Pass   |
|               | 06      | -10.71                            |                  |        |
|               | 11      | -10.26                            |                  |        |
| 802.11g       | 01      | -15.78                            | 8.00             | Pass   |
|               | 06      | -15.16                            |                  |        |
|               | 11      | -14.47                            |                  |        |
| 802.11n(HT20) | 01      | -13.16                            | 8.00             | Pass   |
|               | 06      | -14.18                            |                  |        |
|               | 11      | -12.75                            |                  |        |
| 802.11n(HT40) | 03      | -17.09                            | 8.00             | Pass   |
|               | 06      | -16.61                            |                  |        |
|               | 09      | -16.22                            |                  |        |

###### Antenna 1:

| Type          | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|---------------|---------|-----------------------------------|------------------|--------|
| 802.11b       | 01      | -10.75                            | 8.00             | Pass   |
|               | 06      | -10.57                            |                  |        |
|               | 11      | -10.41                            |                  |        |
| 802.11g       | 01      | -15.42                            | 8.00             | Pass   |
|               | 06      | -14.56                            |                  |        |
|               | 11      | -15.14                            |                  |        |
| 802.11n(HT20) | 01      | -15.30                            | 8.00             | Pass   |
|               | 06      | -15.00                            |                  |        |
|               | 11      | -14.23                            |                  |        |
| 802.11n(HT40) | 03      | -16.60                            | 8.00             | Pass   |
|               | 06      | -16.58                            |                  |        |
|               | 09      | -17.38                            |                  |        |

## Antenna 0:












CH11

CH09

## Antenna 1:






CH11

CH09

## 4.5. 6dB Bandwidth

### TEST CONFIGURATION



### TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

### TEST RESULTS

#### Antenna 0:

| Type        | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|-------------|---------|---------------------|-------------|--------|
| 802.11b     | 01      | 9.64                | $\geq 500$  | Pass   |
|             | 06      | 9.20                |             |        |
|             | 11      | 10.08               |             |        |
| 802.11g     | 01      | 14.12               | $\geq 500$  | Pass   |
|             | 06      | 13.04               |             |        |
|             | 11      | 15.20               |             |        |
| 802.11nHT20 | 01      | 14.72               | $\geq 500$  | Pass   |
|             | 06      | 11.72               |             |        |
|             | 11      | 14.16               |             |        |
| 802.11nHT40 | 03      | 34.00               | $\geq 500$  | Pass   |
|             | 06      | 35.28               |             |        |
|             | 09      | 35.28               |             |        |

#### Antenna 1:

| Type        | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|-------------|---------|---------------------|-------------|--------|
| 802.11b     | 01      | 9.20                | $\geq 500$  | Pass   |
|             | 06      | 10.04               |             |        |
|             | 11      | 9.64                |             |        |
| 802.11g     | 01      | 15.40               | $\geq 500$  | Pass   |
|             | 06      | 14.04               |             |        |
|             | 11      | 13.84               |             |        |
| 802.11nHT20 | 01      | 14.72               | $\geq 500$  | Pass   |
|             | 06      | 13.96               |             |        |
|             | 11      | 15.12               |             |        |
| 802.11nHT40 | 03      | 35.20               | $\geq 500$  | Pass   |
|             | 06      | 35.28               |             |        |
|             | 09      | 35.20               |             |        |