

No. DAT-P-114/01-10

TEST REPORT No. <u>SAR2005001</u>

Test name	Electromagnetic Field (Specific Absorption Rate)		
Product	GSM Triple Frequency Mobile Station		
Model	T538		
Client	TCL Mobile Communication Co., Ltd.		
Type of test	Entrusted		

Telecommunication Metrology Center of Ministry of Information Industry

GENERAL TERMS

- 1. The test report is invalid if not marked with "exclusive stamp for the test report" or the stamp of the test center.
- 2. Any copy of the test report is invalid if not re-marked with the "exclusive stamp for the test report" or the stamp of the test center.
- 3. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
- 4. The test report is invalid if there is any evidence of erasure and/or falsification.
- 5. If there is any dissidence for the test report, please file objection to the test center within 15 days from the date of receiving the test report.
- 6. Normally, entrust test is only responsible for the samples that have undergone the test.
- 7. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permissions of the test center.

Address: No. 52, Huayuanbei Road, Beijing, P. R. China

Post code: 100083

Cable: 04282

Telephone: +86 10 62302041

Fax: +86 10 62304793

No. SAR2005001

Page 3 of 60

GSM Triple Frequency Mobile Product Model T538 Station TCL Mobile Communication Co., **TCL Mobile Communication** Manufacturer Client Ltd. Co., Ltd. **Arrival Date** Type of test Entrusted December 17, 2004 of sample Place of **Carrier of the** Luo Jian (Blank) sampling samples Quantity of the Date of One (Blank) samples product Base of the Items of test SAR (Blank) samples Series number 354883000008632 EN 50360-2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones. EN 50361-2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones. IEC 62209 Draft: Procedure to Determine the Specific Absorption Rate(SAR) for Hand-hold Mobile Phone (Part 2) ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Standard(s) Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits. IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques. Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the Conclusion relevant standards cited in Clause 5.1 of this test report. General Judgment: Pass (Stamp) Date of issue: January 10, 2005 TX Freq. Band: 1850-1910 MHz (PCS) 1 Watt (PCS) Max. Power: Comment Antenna Character: 21mm The test result only responds to the measured sample. Performed by Approved by **Revised** by (Lu Binasona) (Wang Hongbo) (Qi Dianyuan)

GENERAL SUMMARY

TABLE OF CONTENT

1 COMPETENCE AND WARRANTIES	5
2 GENERAL CONDITIONS	5
3 DESCRIPTION OF EUT	5
3.1 Addressing Information Related to EUT	5
3.2 Constituents of EUT	6
3.3 GENERAL DESCRIPTION	7
4 OPERATIONAL CONDITIONS DURING TEST	7
4.1 SCHEMATIC TEST CONFIGURATION	7
4.2 SAR MEASUREMENT SET-UP	7
4.3 DASY4 E-FIELD PROBE SYSTEM	8
4.4 E-field Probe Calibration	9
4.5 Other Test Equipment	10
4.5.1 Device Holder for Transmitters	10
4.5.2 Phantom	10
4.6 Equivalent Tissues	10
4.7 System Specifications	
4.7.1 ROBOTIC SYSTEM SPECIFICATIONS	11
5 CHARACTERISTICS OF THE TEST	11
5.1 APPLICABLE LIMIT REGULATIONS	11
5.2 Applicable Measurement Standards	12
5.3 Character of the Test	12
6 LABORATORY ENVIRONMENT	12
7 TEST RESULTS	12
7.1 Dielectric Performance	12
7.2 System Validation	13
7.3 SUMMARY OF MEASUREMENT RESULTS (HEAD, PCS 1900 MHz BAND)	13
7.4 SUMMARY OF MEASUREMENT RESULTS (BODY-WORN, PCS 1900 MHZ BAND)	14
7.5 Conclusion	15
8 MEASUREMENT UNCERTAINTY	15
9 MAIN TEST INSTRUMENTS	16
10 TEST PERIOD	17
11 TEST LOCATION	17
ANNEX A : MEASUREMENT PROCESS	
ANNEX B : TEST LAYOUT	
ANNEX C: GRAPH RESULTS	24
ANNEX D SYSTEM VALIDATION RESULTS	60

No. SAR2005001

1 COMPETENCE AND WARRANTIES

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory accredited by DAR (DATech) – Deutschen Akkreditierungs Rat (Deutsche Akkreditierungsstelle Technik) for the tests indicated in the Certificate No. **DAT-P-114/01-10**.

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory accredited by CNAL – China National Accreditation Committee for Laboratories, for the tests indicated in the Certificate No. **L0442**.

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory competent to carry out the tests described in this test report.

Telecommunication Metrology Center of Ministry of Information Industry guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at **Telecommunication Metrology Center of Ministry of Information Industry** at the time of execution of the test.

Telecommunication Metrology Center of Ministry of Information Industry is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test.

2 GENERAL CONDITIONS

- 2.1 This report only refers to the item that has undergone the test.
- 2.2 This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities.
- 2.3 This document is only valid if complete; no partial reproduction can be made without written approval of Telecommunication Metrology Center of Ministry of Information Industry.
- 2.4 This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Telecommunication Metrology Center of Ministry of Information Industry and the Accreditation Bodies, if it applies.

3 DESCRIPTION OF EUT

3.1 Addressing Information Related to EUT

Name or Company	TCL Mobile Communication Co., Ltd.		
Addross/Doct	No.23 Zone, Zhongkai High-technology Development Zone, Huizhou,		
Address/Fost	Guangdong		
City	Huizhou		
Postal Code	516006		
Country	China		
Telephone	+86 752 2636729		

Table 1: Applicant (The Client)

No. SAR2005001

Page 6 of 60

Fax +86 752 2636525

Table 2: Manufacturer

Name or Company	TCL Mobile Communication Co., Ltd.		
Address/Post	23 Zone, Zhongkai High-technology Development Zone, Huizhou, Guangdong		
City	Huizhou		
Postal Code	516006		
Country	China		
Telephone	+86 752 2636729		
Fax	+86 752 2636525		

3.2 Constituents of EUT

Table 3: Constituents of Samples

Description	Model	Serial Number	Manufacturer
Handset	T538	354883000008632	TCL Mobile Communication Co., Ltd.
Lithium Battery	GC06-1LB550	/	TCL Hyper-Power Batteries Inc.
AC/DC Adapter		1	Huizhou Weiyeshun Electronics Co.,
AC/DC Adapter	WT 3-030	1	Ltd.



Figure 1: Constituents of the sample (Lithium Battery is in the Handset)

No. SAR2005001

3.3 General Description

Equipment Under Test (EUT) is a model of GSM Phase II portable Mobile Station (MS) with non-integrated antenna. It consists of Handset and normal options: Lithium Battery and AC/DC Adapter as Table 3 and Fig.1.

The sample undergoing test was selected by the Client.

Components list please refer to documents of the manufacturer.

4 OPERATIONAL CONDITIONS DURING TEST

4.1 Schematic Test Configuration

During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established. Upon the client's request, only the band of PCS 1900 MHz will be tested and the result will be showed in this report. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 512, 661 and 810 respectively in the case of PCS 1900 MHz. The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 30 dB.

4.2 SAR Measurement Set-up

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9m) which positions the probes with a positional repeatability of better than \pm 0.02mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length =300mm) to the data acquisition unit.

A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the Micron Pentium III 800 MHz computer with Windows 2000 system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

No. SAR2005001

Page 8 of 60



Figure 2. SAR Lab Test Measurement Set-up

The DAE3 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

4.3 Dasy4 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ET3DV6 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the standard procedure with an accuracy of better than \pm 10%. The spherical isotropy was evaluated and found to be better than \pm 0.25dB.

ET3DV6 Probe Specification

Construction	Symmetrical design with triangular core		
	Built-in optical fiber for surface detection		
	System(ET3DV6 only)		
	Built-in shielding against static charges		
	PEEK enclosure material(resistant to		
	organic solvents, e.q., glycol)		
Calibration	In air from 10 MHz to 2.5 GHz		
	In brain and muscle simulating tissue at		
	frequencies of 450MHz, 900MHz and 1.8GHz		
	(accuracy±8%)		
	Calibration for other liquids and frequencies		
	upon request		
Frequency	I 0 MHz to > 6 GHz; Linearity: ±0.2 dB		



Figure 3. ET3DV6 E-field Probe

No. SAR2005001

Page 9 of 60

	(30 MHz to 3 GHz)	
Directivity	±0.2 dB in brain tissue (rotation around probe axis)	
	±0.4 dB in brain tissue (rotation normal probe axis)	
Dynamic Range	5u W/g to > 100mW/g; Linearity: ±0.2dB	
Surface Detection	±0.2 mm repeatability in air and clear liquids	
	over diffuse reflecting surface(ET3DV6 only)	
Dimensions	Overall length: 330mm	
	Tip length: 16mm	
	Body diameter: 12mm	
	Tip diarneter: 6.8mm	
	Distance from probe tip to dipole centers: 2.7mm	
Application	General dosimetry up to 3GHz	
	Compliance tests of mobile phones	
	Fast automatic scanning in arbitrary phantoms	



Figure 4. ET3DV6 E-field probe

4.4 E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than \pm 10%. The spherical isotropy was evaluated and found to be better than \pm 0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\mathbf{SAR} = \mathbf{C} \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),

- C = Heat capacity of tissue (brain or muscle),
- ΔT = Temperature increase due to RF exposure.

Or

$$\mathbf{SAR} = \frac{|\mathbf{E}|^{1} \sigma}{\rho}$$

No. SAR2005001

Page 10 of 60

Where:

 σ = Simulated tissue conductivity,

 ρ = Tissue density (kg/m3).

4.5 Other Test Equipment

4.5.1 Device Holder for Transmitters

In combination with the Generic Twin Phantom V3.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeat ably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



Figure 5. Device Holder

4.5.2 Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness	2±0. l mm
Filling Volume	Approx. 20 liters
Dimensions	810 x l000 x 500 mm (H x L x W)
Available	Special

4.6 Equivalent Tissues

The liquid used for the frequency range of 800-2000 MHz consisted of water, sugar, salt and Cellulose. The liquid has previously been proven to be suited for worst-case. The Table 4 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528.



Figure 6. Generic Twin Phantom

No. SAR2005001

 Table 4. Composition of the Head Tissue Equivalent Matter

MIXTURE %	FREQUENCY 1850-1910MHz		
Water	55.242		
Glycol monobutyl	44.452		
Salt	0.306		
Dielectric Parameters	f=1900MHz ε=40.0 σ=1.40		
Target Value			

Table 5. Composition of the Body Tissue Equivalent Matter

MIXTURE %	FREQUENCY 1900MHz		
Water	69.91		
Glycol monobutyl	29.96		
Salt	0.13		
Dielectric Parameters	f=1900MHz ε=53.3 σ=1.52		
Target Value			

4.7 System Specifications

4.7.1 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX90L Repeatability: ±0.02 mm No. of Axis: 6 Data Acquisition Electronic (DAE) System Cell Controller Processor: Pentium III Clock Speed: 800 MHz Operating System: Windows 2000 Data Converter Features:Signal Amplifier, multiplexer, A/D converter, and control logic Software: DASY4 software

Connecting Lines: Optical downlink for data and status info.

Optical uplink for commands and clock

5 CHARACTERISTICS OF THE TEST

5.1 Applicable Limit Regulations

EN 50360–2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

It specifies the maximum exposure limit of **2.0 W/kg** as averaged over any 10 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

No. SAR2005001

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

EN 50361–2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

IEC 62209 Draft : Procedure to Determine the Specific Absorption Rate(SAR) for Hand-hold Mobile Phone (Part 2)

OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

5.3 Character of the Test

Handsets that are held on the side of a person's head next to the ear have been tested using realistic-shaped head phantoms.

Since it may be used for body-worn situation, the mobile phone is test with the flat phantom to simulate this case.

6 LABORATORY ENVIRONMENT

Table 6: The Ambient Conditions during EMF Test

Temperature	Min. = 15 °C, Max. = 30 °C	
Relative humidity	Min. = 30%, Max. = 70%	
Ground system resistance $< 0.5 \Omega$		
Ambient noise is checked and found very low and in compliance with requirement of standards.		

Reflection of surrounding objects is minimized and in compliance with requirement of standards.

7 TEST RESULTS

7.1 Dielectric Performance

Table 7: Dielectric Performance of Head Tissue Simulating Liquid

Measurement is made at temperature 22.5 °C and relative humidity 49%.					
Liquid temperature during the test: 21.4°C					
/	Frequency Permittivity ε Conductivity σ (S/m)				
Target value	1900 MHz	40.0	1.40		
Measurement value	1900 MHz	40 1	1 41		
(Average of 10 tests)	1000 10112	-0.1	1.71		

No. SAR2005001

Page 13 of 60

Table 8: Dielectric Performance of Body Tissue Simulating Liquid

Measurement is made at temperature 22.6 °C and relative humidity 51%.								
Liquid temperature during the test: 22.0°C								
/ Frequency Permittivity ε Conductivity σ (S/m)								
Target value	1900 MHz	53.30	1.52					
Measurement value (Average of 10 tests)	1900 MHz	52.9	1.54					

7.2 System Validation

Table 9: System Validation

Measurement is made at temperature 23.3 °C, relative humidity 47%, input power 250 mW.								
Liquid temperature during the test: 22.6°C								
Liquid parameters Frequency Permittivity ε Conductivity σ (S/m)								
		1900 MHz	40.1	1	1.41			
Varification	Fraguanay	Target value (W/kg)		Measur	easurement value (W/kg)			
verification	Frequency	10 g Average	1 g Average	10 g Ave	rage	1 g Average		
results	1900 MHz	5.31	10.1	4.91		9.8		

7.3 Summary of Measurement Results (Head, PCS 1900 MHz Band)

Table 10: SAR Values (PCS 1900 MHz Band, head)

l l	, ,		
Temperature: 22 °C, humidity: 50%.			
Liquid temperature during the test: 22.2°C			
	10 g	1 g	
Limit of SAD (M//kg)	Average	Average	
Limit of SAR (W/kg)	2.0	1.6	Conducted Power before/after each
	Measurem	ent Result	test
Test Case	(W/	kg)	(dBm)
Test Case	10 g	1 g	
	Average	Average	
Left hand, Touch cheek, Top frequency	0.484	0.888	29.41/29.52
Left hand, Touch cheek, Mid frequency	0.473	0.867	29.88/29.79
Left hand, Touch cheek, Bottom frequency	0.497	0.900	29.68/29.72
Left hand, Tilt 15 Degree, Top frequency	0.526	0.958	29.42/29.38
Left hand, Tilt 15 Degree, Mid frequency	0.518	0.931	29.79/29.87

No. SAR2005001

Page 14 of 60

Left hand, Tilt 15 Degree, Bottom frequency	0.550	0.980	29.53/29.65
Right hand, Touch cheek, Top frequency	0.529	1.04	29.45/29.41
Right hand, Touch cheek, Mid frequency	0.481	0.933	29.66/29.52
Right hand, Touch cheek, Bottom frequency	0.490	0.941	29.87/29.68
Right hand, Tilt 15 Degree, Top frequency	0.626	1.25	29.54/29.46
Right hand, Tilt 15 Degree, Mid frequency	0.554	1.1	29.90/29.96
Right hand, Tilt 15 Degree, Bottom frequency	0.554	1.1	29.74/29.72

7.4 Summary of Measurement Results (Body-Worn, PCS 1900 MHz Band)

Temperature: 22 °C, humidity: 50%.							
Liquid temperature during the test: 22.2°C							
	10 g	1 g					
Limit of SAD (M/ka)	Average	Average					
Limit of SAR (W/Kg)	2.0 1.6		Conducted Power before/after each				
	Measurem	ent Result	test				
Test Occur	(W/	kg)	(dBm)				
lest Case	10 a	1 a					
	Average	Average					
	ge	ge					
Display of EUT towards the phantom, Top Frequency	0.177	0.283	29.31/29.55				
Display of EUT towards the phantom, Mid Frequency	0.190	0.301	29.89/29.88				
Display of EUT towards the phantom, Bottom Frequency	0.209	0.330	29.47/29.36				
Display of EUT towards the ground, Top frequency	0.247	0.392	29.71/29.42				
Display of EUT towards the ground, Mid frequency	0.262	0.417	29.86/29.84				

Table 11: SAR Values (PCS 1900 MHz Band, body-worn)

No. SAR2005001	Page 15 of 60		
Display of EUT towards the ground, Bottom	0.283	0.452	29.64/29.65

7.5 Conclusion

Localized Specific Absorption Rate (SAR) of this portable wireless device has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.

Uncertainty Standard Degree of Value Probability freedom Uncertainty No. Error source Туре k Ci (%) Distribution V_{eff} or v_i $(\%) u_i(\%)$ 1 System repetivity А 0.5 Ν 1 1 0.5 9 Measurement system 2 - probe calibration В 7 Ν 2 1 3.5 ∞ - axial isotropy of the $\sqrt{3}$ 3 В 4.7 R $\sqrt{0.5}$ probe 4.3 ∞ - hemisphere isotropy of $\sqrt{3}$ В 9.4 R 4 $\sqrt{0.5}$ the probe $\sqrt{3}$ 5 - spatial resolution В 0 R 1 0 ∞ $\sqrt{3}$ 6 - boundary effect В 11.0 R 1 6.4 ∞ 7 - probe linearity В 4.7 R $\sqrt{3}$ 2.7 1 ∞ $\sqrt{3}$ 8 - detection limit В 1.0 R 1 0.6 ∞ 9 - electronic readout В 1.0 Ν 1 1 1.0 ∞ $\sqrt{3}$ R 10 - RF interference В 3.0 1 1.73 ∞ probe mechanical -В 0.4 $\sqrt{3}$ 11 R 1 0.2 ∞ positioning constraint - matching between probe $\sqrt{3}$ 12 В 2.9 R 1 1.7 ∞ and phantom references - SAR interpolation and $\sqrt{3}$ 13 В 3.9 R 1 2.3 ∞ extrapolation Uncertainties of the DUT - position of the DUT 4.9 Ν 1 1 4.9 5 14 А

8 Measurement Uncertainty

No. SAR2005001

Page 16 of 60

15	- holder of the DUT	А	6.1	N	1	1	6.1	5
16	- drift of the output power	В	5.0	R	$\sqrt{3}$	1	2.9	8
	physical parameters							
17	- phantom shell	В	1.0	R	$\sqrt{3}$	1	0.6	8
18	- liquid conductivity (deviation from target)	В	5.0	R	$\sqrt{3}$	0.6	1.7	∞
19	- liquid conductivity(measurement error)	В	10.0	R	$\sqrt{3}$	0.6	3.4	×
20	- liquid permittivity(deviation from target)	В	5.0	R	$\sqrt{3}$	0.6	1.7	8
21	- liquid permittivity(measurement error)	В	5.0	R	$\sqrt{3}$	0.6	1.7	8
Combined standard uncertainty		<i>u</i> _c =	$\sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$				13.5	88.7
Expa (cont	inded uncertainty fidence interval of 95 %)	U	$u_e = 2u_c$	Ν	k	=2	27	

9 MAIN TEST INSTRUMENTS

Table 13: List of Main Instruments

No.	Name	Туре	Serial Number	Calibration Date	Valid Period
01	Network analyzer	HP 8753C	3146A01905	August 18,2003	One year
02	Dielectric Probe Kit	Agilent 85070C	US99360113	No Calibration Requested	
03	Power meter	HP 436A	2101A11858	August 19,2003	One year
04	Power sensor	HP 8481H	2349A07289		
05	Signal Generator	MG 3633A	M73386	No Calibration Requested	
06	Amplifier	AT 50S1G4A	26549	No Calibration Requested	
07	Validation Kit 835MHz	SPEAG D 835V2	443	September 3, 2003	Two years
08	Validation Kit 900MHz	SPEAG D 900V2	125	September 3, 2003	Two years
09	Validation Kit 1800MHz	SPEAG D 1800V2	2d010	September 3, 2003	Two years
10	Validation Kit 1900MHz	1900 V2	541	September 3, 2003	Two years
11	BTS	CMU 200	100680	September 13, 2003	One year
12	E-field Probe	SPEAG ET3DV6	1738	December 9, 2002	Two years
13	DAE	SPEAG DAE3	589	October 21 2003	Two years

No. SAR2005001

Page 17 of 60

10 TEST PERIOD

The test is performed from January 4, 2005 to January 5, 2005.

11 TEST LOCATION

The test is performed at Radio Communication & Electromagnetic Compatibility Laboratory of Telecommunication Metrology Center of Ministry of Information Industry of The People's Republic of China

END OF REPORT BODY

No. SAR2005001

ANNEX A: MEASUREMENT PROCESS

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point was measured and was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 20 mm x 20 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Around this point, a volume of 32 mm x 32 mm x 34 mm was assessed by measuring 7 x 7 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

b. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot"-condition (in $x \sim y$ and z-directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.

c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation is repeated.



Figure 2 SAR Measurement Points in Area Scan

Page 19 of 60

ANNEX B: TEST LAYOUT



Picture 1 Specific Absorption Rate Test Layout

No. SAR2005001

Page 20 of 60



Picture 2 Left Hand Touch Cheek Position



Picture 3 Left Hand Tilt 15° Position

No. SAR2005001

Page 21 of 60



Picture 4 Right Hand Touch Cheek Position



Picture 5 Right Hand Tilt 15° Position

Page 22 of 60



Picture 6 Flat Phantom -- Body-worn Position (toward phantom, the distance from handset to the bottom of the Phantom is 1.5cm)



Picture 7 Flat Phantom -- Body-worn Position (toward ground, the distance from handset to the bottom of the Phantom is 1.5cm)

No. SAR2005001

Page 23 of 60



Picture 8 Liquid depth in the Head Phantom (Head, 1900MHz)



Picture 9 Liquid depth in the Flat Phantom (Body 1900MHz)

ANNEX C: GRAPH RESULTS

1900 Left Cheek Low

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Cheek Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 25.7 V/m; Power Drift = -0.006 dB Maximum value of SAR (interpolated) = 0.996 mW/g

Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 25.7 V/m; Power Drift = -0.006 dB Maximum value of SAR (measured) = 0.934 mW/g Peak SAR (extrapolated) = 1.62 W/kg SAR(1 g) = 0.900 mW/g; SAR(10 g) = 0.497 mW/g



 $0 \ dB = 0.934 mW/g$



Page 25 of 60



Fig. 2 Z-Scan at power reference point (Left Hand Touch Cheek 1900MHz CH512)

No. SAR2005001

PCS 1900 Left Cheek Middle

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Cheek Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 24.9 V/m; Power Drift = 0.1 dB Maximum value of SAR (interpolated) = 0.975 mW/g

Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 24.9 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.902 mW/gPeak SAR (extrapolated) = 1.55 W/kgSAR(1 g) = 0.867 mW/g; SAR(10 g) = 0.473 mW/g



 $0 \ dB = 0.902 mW/g$

No. SAR2005001

Page 27 of 60



Fig. 4 Z-Scan at power reference point (Left Hand Touch Cheek 1900MHz CH661)

No. SAR2005001

PCS 1900 Left Cheek High

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04)

Cheek High/Area Scan (51x81x1): Measurement grid: dx=10mm, dy=10mmReference Value = 25.2 V/m; Power Drift = 0.2 dB Maximum value of SAR (interpolated) = 1.01 mW/g

Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 25.2 V/m; Power Drift = 0.2 dB

Maximum value of SAR (measured) = 0.921 mW/gPeak SAR (extrapolated) = 1.6 W/kgSAR(1 g) = 0.888 mW/g; SAR(10 g) = 0.484 mW/g



 $0 \ dB = 0.921 mW/g$

No. SAR2005001

Page 29 of 60



Fig. 6 Z-Scan at power reference point (Left Hand Touch Cheek 1900MHz CH810)

No. SAR2005001

Page 30 of 60

PCS 1900 Left Tilt Low

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Tilt Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 28 V/m; Power Drift = -0.008 dB Maximum value of SAR (interpolated) = 1.12 mW/g

Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 28 V/m; Power Drift = -0.008 dB Maximum value of SAR (measured) = 1.02 mW/g Peak SAR (extrapolated) = 1.7 W/kg SAR(1 g) = 0.980 mW/g; SAR(10 g) = 0.550 mW/g



 $0 \ dB = 1.02 mW/g$

No. SAR2005001

Page 31 of 60



Fig. 8 Z-Scan at power reference point (Left Hand Tilt 15° 1900MHz CH512)

No. SAR2005001

PCS 1900 Left Tilt Middle

Electronics: DAE3 Sn536

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Tilt Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 27.1 V/m; Power Drift = -0.1 dB

Maximum value of SAR (interpolated) = 1.08 mW/g

Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.1 V/m; Power Drift = -0.1 dBMaximum value of SAR (measured) = 0.941 mW/gPeak SAR (extrapolated) = 1.65 W/kgSAR(1 g) = 0.931 mW/g; SAR(10 g) = 0.518 mW/g



 $0 \ dB = 0.941 mW/g$

No. SAR2005001

Page 33 of 60



Fig. 10 Z-Scan at power reference point (Left Hand Tilt 15° 1900MHz CH661)

No. SAR2005001

Page 34 of 60

PCS 1900 Left Tilt High

Electronics: DAE3 Sn536

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Tilt High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Reference Value = 27.2 V/m; Power Drift = -0.0009 dB

Maximum value of SAR (interpolated) = 1.11 mW/g

Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.2 V/m; Power Drift = -0.0009 dBMaximum value of SAR (measured) = 0.993 mW/gPeak SAR (extrapolated) = 1.72 W/kgSAR(1 g) = 0.958 mW/g; SAR(10 g) = 0.526 mW/g



 $0 \ dB = 0.993 mW/g$

No. SAR2005001

Page 35 of 60



Fig. 12 Z-Scan at power reference point (left Hand Tilt 15° 1900MHz CH810)

No. SAR2005001

PCS 1900 Right Cheek Low

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Cheek Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Reference Value = 22 V/m; Power Drift = -0.004 dB

Maximum value of SAR (interpolated) = 1.06 mW/g

Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22 V/m; Power Drift = -0.004 dBMaximum value of SAR (measured) = 0.929 mW/gPeak SAR (extrapolated) = 1.78 W/kgSAR(1 g) = 0.941 mW/g; SAR(10 g) = 0.490 mW/g



 $0 \ dB = 0.929 mW/g$

No. SAR2005001

Page 37 of 60



Fig. 14 Z-Scan at power reference point (Right Hand Touch Cheek 1800MHz CH512)

No. SAR2005001

PCS 1900 Right Cheek Middle

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Cheek Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 21.4 V/m; Power Drift = -0.0 dB Maximum value of SAR (interpolated) = 1.04 mW/g

Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 21.4 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.906 mW/gPeak SAR (extrapolated) = 1.81 W/kgSAR(1 g) = 0.933 mW/g; SAR(10 g) = 0.481 mW/g



 $0 \ dB = 0.906 mW/g$

No. SAR2005001

Page 39 of 60



Fig. 16 Z-Scan at power reference point (Right Hand Touch Cheek 1900MHz CH661)

No. SAR2005001

PCS 1900 Right Cheek High

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Cheek High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 22.1 V/m; Power Drift = 0.006 dB Maximum value of SAR (interpolated) = 1.15 mW/g

Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 22.1 V/m; Power Drift = 0.006 dB Maximum value of SAR (measured) = 1 mW/g Peak SAR (extrapolated) = 2.04 W/kg

SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.529 mW/g



 $0 \ dB = 1 mW/g$

No. SAR2005001

Page 41 of 60



Fig. 18 Z-Scan at power reference point (Right Hand Touch Cheek 1900MHz CH810)

No. SAR2005001

Page 42 of 60

PCS 1900 Right Tilt Low

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Tilt Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 23.5 V/m; Power Drift = 0.0 dB Maximum value of SAR (interpolated) = 1.24 mW/g

Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 23.5 V/m; Power Drift = 0.0 dB Maximum value of SAR (measured) = 1.08 mW/g Peak SAR (extrapolated) = 2.14 W/kg SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.554 mW/g



 $0 \ dB = 1.08 mW/g$

No. SAR2005001

Page 43 of 60



Fig. 20 Z-Scan at power reference point (Right Hand Tilt 15° 1900MHz CH512)

No. SAR2005001

PCS 1900 Right Tilt Middle

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Tilt Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 23.2 V/m; Power Drift = -0.01 dB Maximum value of SAR (interpolated) = 1.22 mW/g

Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 23.2 V/m; Power Drift = -0.01 dB Maximum value of SAR (measured) = 1.1 mW/g Peak SAR (extrapolated) = 2.17 W/kg

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.554 mW/g



0 dB = 1.1 mW/g



No. SAR2005001

PCS 1900 Right Tilt High

Electronics: DAE3 Sn536

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Tilt High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 24.2 V/m; Power Drift = 0.0 dB

Maximum value of SAR (interpolated) = 1.38 mW/g

Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.2 V/m; Power Drift = 0.0 dB Maximum value of SAR (measured) = 1.26 mW/gPeak SAR (extrapolated) = 2.45 W/kgSAR(1 g) = 1.25 mW/g; SAR(10 g) = 0.626 mW/g



0 dB = 1.26 mW/g

No. SAR2005001

Page 47 of 60



Fig. 24 Z-Scan at power reference point (Right Hand Tilt 15° 1900MHz CH810)

No. SAR2005001

Page 48 of 60

PCS 1900 Body Toward Phantom Low

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04)

Toward Phantom Low/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 12.6 V/m; Power Drift = 0.003 dBMaximum value of SAR (interpolated) = 0.352 mW/g

Maximum value of SAR (interpolated) = 0.352 mW/g

Toward Phantom Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = 0.003 dBMaximum value of SAR (measured) = 0.339 mW/gPeak SAR (extrapolated) = 0.509 W/kgSAR(1 g) = 0.330 mW/g; SAR(10 g) = 0.209 mW/g



0 dB = 0.339 mW/g

No. SAR2005001

Page 49 of 60



Fig. 26 Z-Scan at power reference point (Flat Phantom 1900MHz CH512 with the display of the handset towards the phantom)

No. SAR2005001

PCS 1900 Body Toward Phantom Middle

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Toward Phantom Middle/Area Scan (51x91x1):** Measurement grid: dx=10mm,

Toward Phantom Middle/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 11.8 V/m; Power Drift = 0.006 dBMaximum value of SAR (interpolated) = 0.324 mW/g

Toward Phantom Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 11.8 V/m; Power Drift = 0.006 dBMaximum value of SAR (measured) = 0.319 mW/gPeak SAR (extrapolated) = 0.470 W/kgSAR(1 g) = 0.301 mW/g; SAR(10 g) = 0.190 mW/g



 $0 \ dB = 0.319 mW/g$

No. SAR2005001

Page 51 of 60



Fig. 28 Z-Scan at power reference point (Flat Phantom 1900MHz CH661 with the display of the handset towards the phantom)

No. SAR2005001

Page 52 of 60

PCS 1900 Body Toward Phantom High

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) Toward Phontom High/Arrow Scop (51v01v1): Measurement with the 10

Toward Phantom High/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 11.1 V/m; Power Drift = -0.1 dBMaximum value of SAR (interpolated) = 0.309 mW/g

Toward Phantom High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.1 V/m; Power Drift = -0.1 dB Maximum value of SAR (measured) = 0.304 mW/gPeak SAR (extrapolated) = 0.445 W/kgSAR(1 g) = 0.283 mW/g; SAR(10 g) = 0.177 mW/g



 $0 \ dB = 0.304 mW/g$

Fig. 29 Flat Phantom Body-worn Position 1900MHz CH810 with the display of the handset towards the phantom

No. SAR2005001

Page 53 of 60



Fig. 30 Z-Scan at power reference point (Flat Phantom 1900MHz CH810 with the display of the handset towards the phantom)

No. SAR2005001

PCS 1900 Body Toward Ground Low

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Toward Ground Low/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm Reference Value = 14.8 V/m; Power Drift = 0.004 dB Maximum value of SAR (interpolated) = 0.508 mW/g

Toward Ground Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 14.8 V/m; Power Drift = 0.004 dB Maximum value of SAR (measured) = 0.468 mW/g Peak SAR (extrapolated) = 0.712 W/kg SAR(1 g) = 0.452 mW/g; SAR(10 g) = 0.283 mW/g



 $0 \ dB = 0.468 mW/g$

Fig. 31 Flat Phantom Body-worn Position 1900MHz CH512 with the display of the handset towards the ground

No. SAR2005001

Page 55 of 60



No. SAR2005001

PCS 1900 Body Toward Ground Middle

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04) **Toward Ground Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm,

dy=10mm

Reference Value = 14.2 V/m; Power Drift = 0.0 dBMaximum value of SAR (interpolated) = 0.474 mW/g

Toward Ground Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 14.2 V/m; Power Drift = 0.0 dBMaximum value of SAR (measured) = 0.432 mW/gPeak SAR (extrapolated) = 0.648 W/kgSAR(1 g) = 0.417 mW/g; SAR(10 g) = 0.262 mW/g



 $0 \ dB = 0.432 mW/g$



Page 57 of 60



Fig. 34 Z-Scan at power reference point (Flat Phantom 1900MHz CH661 with the display of the handset towards the ground)

No. SAR2005001

PCS 1900 Body Toward Ground High

Electronics: DAE3 Sn536 Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8 Probe: ET3DV6 - SN1600 ConvF(5.04, 5.04, 5.04)

Toward Ground High/Area Scan (41x71x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 13.7 V/m; Power Drift = -0.1 dBMaximum value of SAR (interpolated) = 0.442 mW/g

Toward Ground High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.7 V/m; Power Drift = -0.1 dBMaximum value of SAR (measured) = 0.404 mW/gPeak SAR (extrapolated) = 0.615 W/kgSAR(1 g) = 0.392 mW/g; SAR(10 g) = 0.247 mW/g



 $0 \ dB = 0.404 mW/g$



Page 59 of 60



Fig. 36 Z-Scan at power reference point (Flat Phantom 1900MHz CH810 with the display of the handset towards the ground)

Page 60 of 60

ANNEX D SYSTEM VALIDATION RESULTS

Test Laboratory: TMC File Name: D1900_SystemCheck_040403.da4

DUT: Dipole 1900 MHz Type & Serial Number: D1900V2 - SN:541 Program: Unnamed Program; Dipole 1900MHz

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1 Medium: Head 1900 MHz ($\sigma = 1.46$ mho/m, $\epsilon = 39.66$, $\rho = 1000$ kg/m3) Phantom section: FlatSection

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm Reference Value = 90.9 V/m Peak SAR = 18.3 mW/g SAR(1 g) = 9.8 mW/g; SAR(10 g) = 4.91 mW/g Power Drift = 0.004 dB Area Scan (101x101x1): Measurement grid: dx=10mm, dy=10mm



Fig.37 System Performance Check 1900MHz 250mW