

PowerPro Portable Power Station

Model: PS09703

Battery capacity: 2560Wh, 51.2V $\approx$ 50Ah

Power input/output: 40-58.8V $\approx$ 50A charge, 70A discharge (max.)

Discharge temperature range: -20-45°C

Charge temperature range: 0-45°C

AC Input: 100-120V~, 60Hz, 15A max., 1800W max.

Solar/Car input x2: 13-45V $\approx$ 12A max., 800W max.

AC socket x3: 100-120V~, 60Hz, 20A max., 2400W max.

AC socket x1: 100-120V~, 60Hz, 25A max., 3000W max.

AC socket (Bypass Mode): 100-120V~, 60Hz, 15A max., 1800W max.

Car charger output/DC 5521 total: max.126W

Car charger output: 12.6V $\approx$ 10A max., 126W max.

DC 5521 Output x2: 12.6V $\approx$ 3A, 40.8W max.

Anderson terminal output: 12.6V $\approx$ 30A max., 378W max.

USB-C1/C2 output: 5/9/12/15V $\approx$ 3A, 20V $\approx$ 5A, 100W max.

USB-A1/A2 output: 5V $\approx$ 3A, 9V $\approx$ 2A, 12V $\approx$ 1.5A, 18W max.

USB-A3/A4 output: 5V $\approx$ 2.4A, 12W max.

Protection rating: IP20

Made in China

www.CODiWorldwide.com



FCC ID: 2A7KX-PS09703
IC: 31852-PS09703

155.1x36.6mm

