



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Specification

1.1 Electrical Properties

Characteristics	Specifications
Working Band	2.4G WiFi/5G WiFi
Antenna From	PIFA
Impedance	50 Ω
Polarization	Linear
Peak Effi	35%@2.4G; 34%@5G
Peak Gain	1.6dBi@2.4G; 2.8dBi@5G

1.2 Physical Properties

Characteristics	Specifications
Operating Temp	-10°C~+60°C
Storage Temp	-10°C~+70°C
Humidity	10~95%RH

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com




深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Test Data

S11 Parameter-VSWR



Frequency (MHZ)	2400	2500	5150	5850
VSWR	2.06	1.37	1.22	1.39
Return Loss (DB)	-9.17	-16.01	-19.98	-15.63

WiFi Active Test Data

802.11b	Frequency	TRP		TIS	
	2412	CH1 11Mbps	12.77	CH1 11Mbps	-83.61
	2437	CH6 11Mbps	12.21	CH6 11Mbps	-83.12
	2467	CH11 11Mbps	12.14	CH11 11Mbps	-82.03
802.11a		TRP		TIS	
	5180	CH36 6Mbps	11.17	CH36 54Mbps	-74.10
	5300	CH60 6Mbps	11.81	CH60 54Mbps	-72.89
	5805	CH161 6Mbps	12.28	CH161 54Mbps	-73.0

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Efficiency Table

Passive Test For 2.4G												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	irectivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	35.68	-4.48	1.18	-0.97	14.493	21.187	1.18	-15.86	5.66	0	52.44	52.61
2410	32.16	-4.93	0.92	-1.23	12.958	19.205	0.92	-16.65	5.85	0	52.37	52.53
2420	32.87	-4.83	1.29	-0.86	13.167	19.708	1.29	-17.47	6.13	0	52.38	52.56
2430	32.54	-4.88	1.41	-0.74	13.009	19.535	1.41	-18.64	6.29	0	52.56	52.67
2440	32.72	-4.85	1.64	-0.51	12.998	19.721	1.64	-18.61	6.49	0	52.86	53.02
2450	33.62	-4.73	1.65	-0.5	13.462	20.16	1.65	-18.66	6.39	15	52.73	52.84
2460	32.41	-4.89	1.47	-0.68	12.974	19.439	1.47	-21.12	6.36	15	52.67	52.76
2470	31.81	-4.97	1.21	-0.94	12.861	18.946	1.21	-23.42	6.19	15	52.57	52.66
2480	32.42	-4.89	1.38	-0.77	13.001	19.419	1.38	-27.14	6.28	75	52.78	52.88
2490	33.79	-4.71	1.48	-0.67	13.565	20.226	1.48	-20.15	6.19	75	53.06	53.25
2500	33.7	-4.72	1.55	-0.6	13.387	20.313	1.55	-19.25	6.27	75	52.92	53.06
Passive Test For 5G												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	irectivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
5150	34.61	-4.61	2.71	0.56	23.161	11.451	2.71	-25.76	7.31	60	62.66	62.14
5170	30.35	-5.18	2.53	0.38	20.277	10.078	2.53	-22.37	7.7	45	62.13	61.73
5190	27.97	-5.53	2.32	0.17	18.656	9.315	2.32	-21.57	7.86	30	61.9	61.56
5210	30.1	-5.21	2.8	0.65	19.881	10.22	2.8	-20.09	8.01	60	62.58	62.08
5230	29.46	-5.31	2.82	0.67	19.219	10.239	2.82	-20.3	8.13	60	62	61.81
5250	29.14	-5.36	2.8	0.65	18.865	10.273	2.8	-23.16	8.15	45	61.89	61.7
5270	26.54	-5.76	2.3	0.15	17.044	9.498	2.3	-23.02	8.07	60	61.76	61.41
5290	29.4	-5.32	2.41	0.26	18.673	10.727	2.41	-22.47	7.72	45	61.94	61.89
5310	25.59	-5.92	1.75	-0.4	16.272	9.314	1.75	-26.71	7.67	45	61.61	61.56
5330	25.66	-5.91	1.67	-0.48	16.215	9.444	1.67	-20.39	7.58	45	61.83	61.76
5350	27.17	-5.66	1.38	-0.77	17.203	9.968	1.38	-19.63	7.04	45	62.08	62.46
5370	28.03	-5.52	1.09	-1.06	17.659	10.371	1.09	-28.27	6.62	45	62.14	62.36
5390	25.08	-6.01	0.15	-2	15.698	9.381	0.15	-19.38	6.16	45	61.64	61.88
5410	28.76	-5.41	0.67	-1.48	17.928	10.831	0.67	-21.06	6.08	45	62.69	63.01
5430	26.85	-5.71	0.66	-1.49	16.603	10.247	0.66	-24.01	6.37	45	62.41	62.93
5450	25.87	-5.87	0.56	-1.59	15.774	10.095	0.56	-22.32	6.44	45	62.21	62.94
5470	23.92	-6.21	0.42	-1.73	14.623	9.297	0.42	-22.32	6.63	30	62.56	63.24
5490	22.57	-6.47	0.16	-1.99	13.584	8.982	0.16	-24.05	6.63	30	63.06	63.84
5510	22.85	-6.41	-0.01	-2.16	13.513	9.337	-0.01	-27.99	6.41	30	63.46	64.44
5530	23.95	-6.21	0.26	-1.89	14.284	9.661	0.26	-23.14	6.47	30	63.75	64.89
5550	26.37	-5.79	0.62	-1.53	15.652	10.716	0.62	-19.69	6.41	30	64.34	65.2
5570	26.42	-5.78	0.76	-1.39	15.456	10.962	0.76	-21.37	6.54	45	64.38	65.25
5590	25.69	-5.9	0.63	-1.52	15.023	10.663	0.63	-20.92	6.53	45	64.47	64.74
5610	26.84	-5.71	1.07	-1.08	15.724	11.117	1.07	-22.92	6.78	45	64.28	65.11
5630	27.69	-5.58	0.67	-1.48	15.998	11.692	0.67	-20.97	6.25	45	64.52	65.32
5650	27.87	-5.55	0.87	-1.28	16.006	11.863	0.87	-20.34	6.42	45	64.43	65.08
5670	26.08	-5.84	0.27	-1.88	14.867	11.214	0.27	-24.52	6.11	45	64.58	65.06
5690	27.38	-5.63	0.44	-1.71	15.644	11.732	0.44	-20.61	6.07	45	64.65	66
5710	25.84	-5.88	0.52	-1.63	14.683	11.153	0.52	-23.85	6.4	45	65.18	65.08
5730	28.59	-5.44	0.3	-1.85	16.234	12.356	0.3	-16.66	5.74	45	64.91	65.55
5750	25.26	-5.98	-0.23	-2.38	14.458	10.804	-0.23	-19.56	5.75	45	64.64	64.89
5770	25.38	-5.95	-0.29	-2.44	14.531	10.851	-0.29	-19.95	5.67	45	64.61	65.28
5790	24.02	-6.19	-0.39	-2.54	13.557	10.462	-0.39	-23.16	5.8	45	64.83	64.78
5810	25.76	-5.89	0.01	-2.14	14.385	11.374	0.01	-25.36	5.9	60	64.97	65.66
5830	25.28	-5.97	0.13	-2.02	13.966	11.315	0.13	-26.45	6.11	60	65.45	66.02
5850	26.11	-5.83	0.1	-2.05	14.236	11.873	0.1	-21.97	5.93	15	65.65	66.39

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address:1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen


Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com




深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Radiation Pattern (2.4G)



Radiation Pattern (5G)



BT Test

测试环境：开放空间（通道）

Testing environment: Open space (passageway)

测试工具：蓝牙音响

Testing tool: Bluetooth speaker

测试距离：10+m

Testing distance: More than 10 meters

结果：播放音乐流畅，无杂音

Result: The music plays smoothly without any noise

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Throughput Test(2.4G)

上行 Upload	369M	下行 Upstream	409M
图片 pic.		图片 pic.	

Throughput Test(5G)

上行 Upload	939M	下行 Upstream	880M
图片 pic.		图片 pic.	

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen


Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Antenna Assembly



地址: 深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stepdeng_Vis@126.com



Inspection Standard

Shenzhen Xingyuan Chuang Technology Co., Ltd.	Document Code	XYC-WI-PZ-02	Page
	Document Version	A0	1 of 1
Document Name	Sampling Plan		

Sampling Level Comparison Table

Special Inspection Level				General Inspection Level			Lot Size Range	Sample Code Letter	Sample Size	0.65		1.0		1.5		2.5		4.0		6.0	
S-1	S-2	S-3	S-4	I	II	III				AC	RE	AC	RE	AC	RE	AC	RE	AC	RE	AC	RE
A	A	A	A	A	A	B	2---8	A	2	0	1	0	1	0	1	0	1	0	1	0	1
A	A	A	A	A	B	C	9---15	B	3	0	1	0	1	0	1	0	1	0	1	0	1
A	A	B	B	B	C	D	16---25	C	5	0	1	0	1	0	1	0	1	0	1	1	2
A	B	B	C	C	D	E	26---50	D	8	0	1	0	1	0	1	0	1	1	2	1	2
B	B	C	C	C	E	F	51---90	E	13	0	1	0	1	0	1	1	2	1	2	2	3
B	B	C	D	D	F	G	91---150	F	20	0	1	0	1	1	2	1	2	2	3	3	4
B	C	D	E	E	G	H	151---280	G	32	0	1	1	2	1	2	2	3	3	4	5	6
B	C	D	E	F	H	J	281---500	H	50	1	2	1	2	2	3	3	4	5	6	7	8
C	C	E	F	G	J	K	501---1200	J	80	1	2	2	3	3	4	5	6	7	8	10	11
C	D	E	G	H	K	L	1201---3200	K	125	2	3	3	4	5	6	7	8	10	11	14	15
C	D	F	G	J	L	M	3201---10000	L	200	3	4	5	6	7	8	10	11	14	15	21	22
C	D	F	H	K	M	N	10001---35000	M	315	5	6	7	8	10	11	14	15	21	22	21	22
D	E	G	J	L	N	P	35001---150000	N	500	7	8	10	11	14	15	21	22	21	22	21	22
D	E	G	J	M	P	Q	150001---500000	P	800	10	11	14	15	21	22	21	22	21	22	21	22
D	E	H	K	N	Q	R	500001 and over	Q	1250	14	15	21	22	21	22	21	22	21	22	21	22
								R	2000	21	22	21	22	21	22	21	22	21	22	21	22

AC is the acceptable item

RE is the reject item

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com