



Shenzhen Jiexuntong Wireless Technology Co., LTD

Antenna specification

Customer name: Allianz

Project model: XLB547

Antenna specification: WIFI FPC antenna



Recognition Letter Change CV

editi on	date	Change description	remark
R/A	2024-11-6	First edition	

This specification belongs to Shenzhen Jixuntong Wireless Technology Co., Ltd. and relevant customer confidential archive, please keep properly, without the permission of our company and relevant customers, no one is allowed to leak.



catalogue

1、 COVER.....	PAGE 1
2、 CHANGE THE RESUME.....	PAGE 2
3、 CATALOGUE.....	PAGE 3
4、 ANTENNA PICTURES.....	PAGE 4
5、 ANTENNA MATCHING.....	PAGE 4
6、 PRODUCT SPECIFICATION	PAGE 5
7、 ELECTRICAL PERFORMANCE REPOR.....	PAGE 6-11
8、 ENGINEERING DRAWING.....	PAGE 12

**Address: 409, Building A, No.30, Sanwei Aviation Road, Sanwei Community, Hangcheng Street,
Bao'an District, Shenzhen City**

Contact number: 0755-23731203

website: <http://www.jxtant.com>





1. Antenna assembly picture



2. Test environment


2.1. Environmental treatment

no



3. antenna loading coil

3.1. The antenna



*: Our company has not changed the original antenna front end matching,

4. size of product


Passive Electrical Specifications	
Frequency Range (MHz)	2400-2500MHZ
Input Impendence (Ω)	50
n bobitu VSWR	≤3
Gain (dBi)	<3dBi
Polarization Type	Linear polarization

This specification belongs to Shenzhen Jixuntong Wireless Technology Co., Ltd. and relevant customer confidential archive, please keep properly, without the permission of our company and relevant customers, no one is allowed to leak.



5. Electrical performance report

- n bobitu VSWR



This specification belongs to Shenzhen Jixuntong Wireless Technology Co., Ltd. and relevant customer confidential archive, please keep properly, without the permission of our company and relevant customers, no one is allowed to leak.



6. Active test data

B die 2400-2500MHz			
Frequency band	1	6	11
TRP	13. 52	13. 72	13. 81
TIS	-84. 69	-84. 56	-85. 24







6. Gain efficiency

Freq (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
2400	3.136882973	-3.755243584	42.11876628
2410	2.951496527	-3.857602917	41.13767173
2420	2.822011113	-4.022675766	39.60339554
2430	2.922929373	-4.100878503	38.89664558
2440	2.743542686	-4.261232401	37.4866611
2450	2.683032124	-4.247368789	37.60651777
2460	2.690581895	-4.343741373	36.78119733
2470	2.966030906	-4.263268272	37.46909234
2480	3.006546037	-4.258341852	37.51161953
2490	2.715557257	-4.333577034	36.86738181
2500	2.600122764	-4.490339181	35.56035451



directional diagram



2400MHZ



This specification belongs to Shenzhen Jixuntong Wireless Technology Co., Ltd. and relevant customer confidential archive, please keep properly, without the permission of our company and relevant customers, no one is allowed to leak.







2450MHZ





2500MHZ




This specification belongs to Shenzhen Jixuntong Wireless Technology Co., Ltd. and relevant customer confidential archive, please keep properly, without the permission of our company and relevant customers, no one is allowed to leak.



7. Engineering drawings

Antenna 2D pattern



Unit:mm

