

## SAR Exclusion Evaluation Report

Applicant : LEXON  
Product Type : MINO L  
Trade Name : LEXON  
Model Number : LA121  
Received Date : Mar. 26, 2019  
Test Period : May 28, 2019  
Issue Date : May 31, 2019

### Issue by

Approved By : Edison Hu  
(Edison Hu)

Tested By : Kris Pan  
(Kris Pan)

A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,

Taoyuan City 33465, Taiwan (R.O.C.)

Tel : +886-3-2710188 / Fax : +886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

Test Firm MRA designation number: TW0010



**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.



### **Revision History**

| Rev. | Issue Date   | Revisions     | Revised By  |
|------|--------------|---------------|-------------|
| 00   | May 31, 2019 | Initial Issue | Shelly Chen |
|      |              |               |             |
|      |              |               |             |
|      |              |               |             |



## Contents

|     |                                                 |   |
|-----|-------------------------------------------------|---|
| 1.  | Description of Equipment under Test (EUT) ..... | 4 |
| 2.  | Reference Testing Standards .....               | 4 |
| 3.  | SAR Test Exclusion .....                        | 5 |
| 3.1 | Conducted Power .....                           | 5 |
| 3.2 | Antenna Location .....                          | 6 |
| 3.3 | Evaluation Results .....                        | 6 |



## 1. Description of Equipment under Test (EUT)

|                     |                                                                    |                       |
|---------------------|--------------------------------------------------------------------|-----------------------|
| Applicant           | LEXON<br>91 avenue Jean-Baptiste Clément - 92100 Boulogne - FRANCE |                       |
| Manufacturer        | LEXON<br>91 avenue Jean-Baptiste Clément - 92100 Boulogne - FRANCE |                       |
| Product Type        | MINO L                                                             |                       |
| Trade Name          | LEXON                                                              |                       |
| Model Number        | LA121                                                              |                       |
| FCC ID              | 2ARD3-LA121                                                        |                       |
| Frequency Range     | Operate Band                                                       | Frequency Range (MHz) |
|                     | Bluetooth BR/EDR                                                   | 2402 - 2480           |
|                     | Bluetooth LE                                                       | 2402 - 2480           |
| Antenna Information | Type                                                               | Max. Gain (dBi)       |
|                     | Inverted F Antenna                                                 | -0.58                 |

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1093. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

## 2. Reference Testing Standards

| Standard               | Description                                                                                                                                                                       | Version |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| ANSI/IEEE C95.1        | American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.                                  | 1992    |
| IEEE 1528              | IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head From Wireless Communications Devices: Measurement Techniques. | 2013    |
| FCC 47 CFR Part 2.1093 | Radiofrequency radiation exposure evaluation: portable devices.                                                                                                                   | ---     |
| FCC KDB 865664 D01     | SAR measurement 100 MHz to 6 GHz - describes SAR measurement procedures for devices operating between 100 MHz to 6 GHz                                                            | v01r04  |
| FCC KDB 865664 D02     | RF Exposure Reporting - provides general reporting requirements as well as certain specific information required to support MPE and SAR compliance.                               | v01r02  |
| FCC KDB 447498 D01     | General RF Exposure Guidance - provides guidance pertaining to RF exposure requirements for mobile and portable device equipment authorizations.                                  | v06     |

### 3. SAR Test Exclusion

As RF exposure evaluation of portable device, SAR test is not required when the evaluation results. According to KDB 447498 4.3.1, unless excluded by specific FCC test procedures, portable devices shall include SAR data for equipment approval. SAR test necessity will be based on the exclusion result.

The test exclusion refers KDB 447498 as below:

**≤50 mm:**

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

**>50 mm and <200 mm:**

- $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]$  mW, at 100 MHz to 1500 MHz
- $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10]$  mW at > 1500 MHz and  $\leq 6$  GHz

#### 3.1 Conducted Power

The conducted power turn-up tolerance, please reference manufacturer specification.

| Operate Band                    | Frequency (MHz) | Packet Type | Average Conducted power (dBm) |
|---------------------------------|-----------------|-------------|-------------------------------|
| Bluetooth BR<br>GFSK            | 2402.0          | DH1         | -1.87                         |
|                                 |                 | DH3         | -1.86                         |
|                                 |                 | DH5         | -1.84                         |
|                                 | 2441.0          | DH1         | -1.75                         |
|                                 |                 | DH3         | -1.72                         |
|                                 |                 | DH5         | <b>-1.69</b>                  |
|                                 | 2480.0          | DH1         | -1.97                         |
|                                 |                 | DH3         | -1.95                         |
|                                 |                 | DH5         | -1.93                         |
| Bluetooth EDR<br>$\pi/4$ -DQPSK | 2402.0          | DH1         | -3.09                         |
|                                 |                 | DH3         | -3.07                         |
|                                 |                 | DH5         | -3.04                         |
|                                 | 2441.0          | DH1         | -2.92                         |
|                                 |                 | DH3         | -2.90                         |
|                                 |                 | DH5         | <b>-2.88</b>                  |
|                                 | 2480.0          | DH1         | -3.17                         |
|                                 |                 | DH3         | -3.15                         |
|                                 |                 | DH5         | -3.12                         |
| Bluetooth LE                    | 2402.0          | ---         | -1.30                         |
|                                 | 2440.0          |             | <b>-1.15</b>                  |
|                                 | 2480.0          |             | -1.39                         |

### 3.2 Antenna Location

| Ant. Used         | Antenna to user distance<br>(mm) |      |
|-------------------|----------------------------------|------|
|                   | Front                            | Back |
| Bluetooth Antenna | 5                                | 5    |

Note : We use a minimum distance of 5 mm for bluetooth function.

### 3.3 Evaluation Results

The evaluation of SAR test reduction according to KDB447498

SAR test is not required when the results showed "EXEMPT".

| SAR test reduction |           |                    |            |       |                            |        |
|--------------------|-----------|--------------------|------------|-------|----------------------------|--------|
| Ant. Used          | Band      | Frequency<br>(GHz) | Tune-Power |       | Calculated threshold value |        |
|                    |           |                    | (dBm)      | (mW)  | Front                      | Back   |
| Bluetooth Antenna  | Bluetooth | 2.48               | 0          | 1.000 | 0.3                        | 0.3    |
|                    |           |                    |            |       | EXEMPT                     | EXEMPT |

#### Exclusion Considerations: SAR is not required

- Note:
1. Calculated Value include string "mW", that is mean through compare output power with threshold, if the output power more than threshold value the SAR test should be perform. Otherwise, the SAR test could be exempt. (> 50 mm)
  2. Calculated Value only include number format, that is mean through compare output power with threshold, if the Calculated value more than 3, the SAR test should be perform. Otherwise, the SAR test could be exempt. (<50 mm)
  3. When an antenna qualifies for the standalone SAR test exclusion of KDB 447498 section 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value must be estimated according to KDB 447498 section "4.3.2. Simultaneous transmission SAR test exclusion considerations b) ".
  4. We used highest frequency and power, that result should be evaluated the worst case.
  5. Power and distance are rounded to the nearest mW and mm before calculation.
  6. The result is rounded to one decimal place for comparison.
  7. We use a minimum distance of 5 mm for bluetooth function.