



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Linksys LLC
Applicant Address	131 Theory Drive, Irvine, CA 92617, USA
FCC ID	Q87-RE6500
Manufacturer's company	U-MEDIA Communications, Inc.
Manufacturer Address	9F, No. 1, Jin-Shan 7th St., Hsinchu 300, Taiwan

Product Name	Linksys AC1200 MAX Wi-Fi Range Extender
Brand Name	Linksys
Model No.	RE6500
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250MHz
Received Date	Feb. 18, 2014
Final Test Date	Jul. 08, 2014
Submission Type	Class II Change
Operating Mode	Master and Client (without radar detection function)

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart E, KDB789033 D02 v01, KDB662911 D01 v02r01, KDB644545 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	8
3.7. Table for Class II Change	8
3.8. Table for Supporting Units	9
3.9. Table for Parameters of Test Software Setting	10
3.10. EUT Operation during Test	11
3.11. Duty Cycle	12
3.12. Test Configurations	14
4. TEST RESULT	16
4.1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	16
4.2. Maximum Conducted Output Power Measurement.....	24
4.3. Power Spectral Density Measurement	27
4.4. Radiated Emissions Measurement	37
4.5. Band Edge Emissions Measurement	53
4.6. Frequency Stability Measurement	58
4.7. Antenna Requirements	60
5. LIST OF MEASURING EQUIPMENTS	61
6. MEASUREMENT UNCERTAINTY.....	63
APPENDIX A. TEST PHOTOS	A1 ~ A4
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B4
APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT	C1 ~ C3


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR421849-01AB	Rev. 01	Initial issue of report	Jul. 15, 2014

1. CERTIFICATE OF COMPLIANCE

Product Name : Linksys AC1200 MAX Wi-Fi Range Extender
Brand Name : Linksys
Model No. : RE6500
Applicant : Linksys LLC
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 18, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.2	15.407(a)	Maximum Conducted Output Power	Complies	0.31 dB
4.3	15.407(a)	Power Spectral Density	Complies	0.01 dB
4.4	15.407(b)	Radiated Emissions	Complies	3.09 dB
4.5	15.407(b)	Band Edge Emissions	Complies	1.00 dB
4.6	15.407(g)	Frequency Stability	Complies	-
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	5150 ~ 5250MHz
Channel Number	4 for 20MHz bandwidth ; 2 for 40MHz bandwidth 1 for 80MHz bandwidth
Channel Band Width (99%)	802.11ac MCS0/Nss1 (VHT20): 33.60 MHz ; 802.11ac MCS0/Nss1 (VHT40): 59.20 MHz ; 802.11ac MCS0/Nss1 (VHT80): 74.88 MHz
Maximum Conducted Output Power	For Master function: 802.11ac MCS0/Nss1 (VHT20): 24.06 dBm ; 802.11ac MCS0/Nss1 (VHT40): 23.50 dBm ; 802.11ac MCS0/Nss1 (VHT80): 17.98 dBm For Client without radar detection function: 802.11ac MCS0/Nss1 (VHT20): 23.69 dBm ; 802.11ac MCS0/Nss1 (VHT40): 23.50 dBm ; 802.11ac MCS0/Nss1 (VHT80): 17.98 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5150 ~ 5250MHz
Channel Number	4
Channel Band Width (99%)	31.52 MHz
Maximum Conducted Output Power	For Master function: 24.07 dBm For Client without radar detection function: 23.28 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Communication Mode	☒ IP Based (Load Based) ☐ Frame Based
Beamforming Function	☐ With beamforming ☒ Without beamforming

Antenna and Band width

Antenna	Two (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15
802.11ac (VHT20)	2	MCS 0-9/Nss1-2
802.11ac (VHT40)	2	MCS 0-9/Nss1-2
802.11ac (VHT80)	2	MCS 0-9/Nss1-2

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1 (Fixed plug)	Ktec	KSAS0121200100VU	INPUT: 100-240Vac, 50/60Hz, 0.4A OUTPUT: 12Vdc, 1.0A
Adapter 2 (Removable plug)	Ktec	KSAS0121200100D5	INPUT: 100-240Vac, 50/60Hz, 0.4A OUTPUT: 12Vdc, 1.0A
Others			
Plug*1 (Only for Adapter 2's use)			
RJ-45 cable*1: Non-shielded, 1.5m			

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)		Cable Loss (dB)		True Gain (dBi)	
					2.4GHz	5GHz	2.4GHz	5GHz	2.4GHz	5GHz
1	Joymax	TWX-1561RSXX-711	Dipole	Reversed-SMA	5.5	5.62	1.0	2.8	4.50	2.82
2	Joymax	TWX-1561RSXX-711	Dipole	Reversed-SMA	5.5	5.62	2.8	1.0	2.70	4.62
3	Cortec	AN2450-9220BRS	Dipole	SMA Male Reverse	5.03	5.01	1.0	2.8	4.03	2.21
4	Cortec	AN2450-9220BRS	Dipole	SMA Male Reverse	5.03	5.01	2.8	1.0	2.23	4.01

Note:

Ant. 1~4 are the same type antennas. Only the higher gain antennas "Ant. 1~2" were tested and recorded in the report.

For 2.4GHz function:


For IEEE 802.11b/g/n mode (2TX/2RX)

Chain 1 and Chain 2 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11a/n/ac mode (2TX/2RX):

Chain 1 and Chain 2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

For 80MHz bandwidth systems, use Channel 42.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Chain
AC Power Conducted Emission	Normal Link		-	-	-
Max. Conducted Output Power	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2
Power Spectral Density	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2
Radiated Emission Below 1GHz	Normal Link		-	-	-
Radiated Emission Above 1GHz	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2
Band Edge Emission	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2
Frequency Stability	Un-modulation		-	40	1+2

The following test modes were performed for all tests:

For Radiated Emissions below 1GHz test:

Mode 1. EUT laying + Adapter 1

Mode 2. EUT standing + Adapter 1

Mode 1 has been evaluated to be the worst case among Mode 1~2, thus measurement for Mode 3 will follow this same test mode.

Mode 3. EUT laying + Adapter 2

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emissions above 1GHz test:

The EUT for Radiated emission test was performed at laying and standing position and the worst case was found from laying. So the measurement will follow this same test configuration.

Mode 1. EUT laying

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Class II Change

This product is an extension of original one reported under Sporton project number: 421849

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Adding 4 higher gain antennas.	1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement 2. Maximum Conducted Output Power Measurement 3. Power Spectral Density Measurement 4. Radiated Emissions Measurement 5. Band Edge Emissions Measurement 6. Frequency Stability Measurement 7. Maximum Permissible Exposure 8. Radiated Emission Co-location

3.8. Table for Supporting Units

For Test Site No: 03CH01-CB

For Radiated Emissions below 1GHz test:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1340	E2K4965AGNM
Notebook	DELL	E6430	DoC
Notebook	DELL	D420	E2KWM3945ABG
AP Router	Planex	GW-AP54SGX	KA220030603014-1
Earphone	E-BOOKI	E-EPC040	N/A

For Radiated Emissions above 1GHz test:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2K4965AGNM

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For Master function:

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

Test Software Version	MT7662 QA V0.0.2.3		
Frequency	5180 MHz	5200 MHz	5240 MHz
MCS0/Nss1 VHT20	2D/2A	3E/3B	3E/3C

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

Test Software Version	MT7662 QA V0.0.2.3	
Frequency	5190 MHz	5230 MHz
MCS0/Nss1 VHT40	1F/20	32/30

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

Test Software Version	MT7662 QA V0.0.2.3
Frequency	5210 MHz
MCS0/Nss1 VHT80	1E/1B

Power Parameters of IEEE 802.11a

Test Software Version	MT7662 QA V0.0.2.3		
Frequency	5180 MHz	5200 MHz	5240 MHz
802.11a	2E/29	3D/39	3E/3C

For Client without radar detection function:

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

Test Software Version	MT7662 QA V0.0.2.3		
Frequency	5180 MHz	5200 MHz	5240 MHz
MCS0/Nss1 VHT20	2D/2A	31/32	31/32

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

Test Software Version	MT7662 QA V0.0.2.3	
Frequency	5190 MHz	5230 MHz
MCS0/Nss1 VHT40	1F/20	32/30

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

Test Software Version	MT7662 QA V0.0.2.3
Frequency	5210 MHz
MCS0/Nss1 VHT80	1E/1B

Power Parameters of IEEE 802.11a


Test Software Version	MT7662 QA V0.0.2.3		
Frequency	5180 MHz	5200 MHz	5240 MHz
802.11a	2E/29	2F/30	2E/2F

3.10. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.11.1. Duty Cycle

IEEE 802.11ac MCS0/Nss1 VHT20




Date: 3.JUL.2014 13:12:31

IEEE 802.11ac MCS0/Nss1 VHT40




Date: 3.JUL.2014 13:13:28

IEEE 802.11ac MCS0/Nss1 VHT80



Date: 3.JUL.2014 13:14:10

IEEE 802.11a




Date: 3.JUL.2014 13:12:10

3.12. Test Configurations


3.12.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz ~ 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	1.5m
3	Audio cable	No	1.1m
4	RJ-45 cable*3	No	0.4m
5	RJ-45 cable	No	10m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.1.1. Limit

No restriction limits.

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.1.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.1.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.1.5. Test Deviation

There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.1.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

Temperature	24°C	Humidity	61%
Test Engineer	Benson Peng	Configurations	IEEE 802.11ac

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	38.08	22.88
40	5200 MHz	48.32	33.44
48	5240 MHz	48.64	33.60

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	43.84	36.16
46	5230 MHz	89.60	59.20

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
42	5210 MHz	81.28	74.88

Temperature	24°C	Humidity	61%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a

Configuration IEEE 802.11a / Chain 1 + Chain 2


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	34.56	20.48
40	5200 MHz	43.52	31.52
48	5240 MHz	43.68	30.88

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5180 MHz



Date: 3.JUL.2014 12:28:04

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5200 MHz



Date: 3.JUL.2014 12:16:04



Ref 97 dBμV * Att 0 dB * RBW 300 kHz VBW 1 MHz SWT 20 ms Delta 1 [T1] -0.02 dB 48.64000000 MHz

OBW 33.60000000 MHz Marker 1 [T1] 63.50 dBμV 5.215680000 GHz Temp 1 [T1 00V] 69.83 dBμV 5.223040000 GHz Temp 2 [T1 00V] 70.87 dBμV 5.256640000 GHz

61.89 dBμV 60.475 dBμV 60.475 dBμV 60.475 dBμV

1 PK VIEW

Center 5.24 GHz 8 MHz/ Span 80 MHz

1 PK
VIEW

Ref 97 dBμV * Att 0 dB

* RBW 300 kHz Delta 1 [T1] 0.87 dB
 * VBW 1 MHz SWT 20 ms 43.840000000 MHz

OBW 36.160000000 MHz
 Marker 1 [T1] 54.52 dBμV
 5.168240000 GHz Temp 1 [T1 OBW] 75.81 dBμV
 5.172080000 GHz Temp 2 [T1 OBW] 73.46 dBμV
 5.208240000 GHz


D1 80.040 dBμV D2 54.049 dBμV

F1 F2

Center 5.19 GHz 16 MHz/ Span 160 MHz


Issued Date : Jul. 15, 2014

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 / 5230 MHz




Date: 3.JUL.2014 12:20:03

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 / 5210 MHz




Date: 3.JUL.2014 12:21:22

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5180 MHz




Date: 3.JUL.2014 12:11:59

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5200 MHz



Date: 3.JUL.2014 12:13:03

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5240 MHz



Date: 3.JUL.2014 12:14:29

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) for master limit and 250 mW (24dBm) for client limit provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3. Measurement using a Power Meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	24°C	Humidity	61%
Test Engineer	Benson Peng	Configurations	IEEE 802.11ac/a
Test Date	Jul. 03, 2014		

For Master function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
36	5180 MHz	19.54	18.81	22.20	30.00	Complies
40	5200 MHz	21.23	20.82	24.04	30.00	Complies
48	5240 MHz	21.17	20.93	24.06	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
38	5190 MHz	15.62	15.43	18.54	30.00	Complies
46	5230 MHz	20.82	20.14	23.50	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
42	5210 MHz	15.36	14.53	17.98	30.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
36	5180 MHz	19.41	19.02	22.23	30.00	Complies
40	5200 MHz	21.14	20.97	24.07	30.00	Complies
48	5240 MHz	21.05	20.96	24.02	30.00	Complies

Temperature	24°C	Humidity	61%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac/a
Test Date	Jul. 08, 2014		

For Client without radar detection function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
36	5180 MHz	19.54	18.81	22.20	24.00	Complies
40	5200 MHz	20.57	20.62	23.61	24.00	Complies
48	5240 MHz	20.51	20.85	23.69	24.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
38	5190 MHz	15.62	15.43	18.54	24.00	Complies
46	5230 MHz	20.82	20.14	23.50	24.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
42	5210 MHz	15.36	14.53	17.98	24.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
36	5180 MHz	19.41	19.02	22.23	24.00	Complies
40	5200 MHz	20.18	20.22	23.21	24.00	Complies
48	5240 MHz	20.10	20.43	23.28	24.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.2.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15~5.25 GHz	17 for master limit
	11 for client limit

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Maximum Power Spectral Density (PSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	24°C	Humidity	61%
Test Engineer	Benson Peng	Configurations	IEEE 802.11ac/a
Test Date	Jul. 03, 2014		

For Master function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	8.70	16.18	Complies
40	5200 MHz	10.51	16.18	Complies
48	5240 MHz	10.59	16.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	2.02	16.18	Complies
46	5230 MHz	7.26	16.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210 MHz	-1.54	16.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Configuration IEEE 802.11a / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	8.79	16.18	Complies
40	5200 MHz	10.67	16.18	Complies
48	5240 MHz	10.76	16.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Temperature	24°C	Humidity	61%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac/a
Test Date	Jul. 08, 2014		

For Client without radar detection function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	8.70	10.18	Complies
40	5200 MHz	10.10	10.18	Complies
48	5240 MHz	10.14	10.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = 11 - (6.82 - 6) = 10.18 dBm/MHz

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	2.02	10.18	Complies
46	5230 MHz	7.26	10.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = 11 - (6.82 - 6) = 10.18 dBm/MHz

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210 MHz	-1.54	10.18	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = 11 - (6.82 - 6) = 10.18 dBm/MHz

Configuration IEEE 802.11a / Chain 1 + Chain 2

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	8.79	10.18	Complies
40	5200 MHz	10.17	10.18	Complies
48	5240 MHz	10.13	10.18	Complies


Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82 \text{dBi} > 6 \text{dBi}$, so B1 limit = 11 - (6.82 - 6) = 10.18 dBm/MHz

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

For Master function:


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5240 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 / 5230 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 / 5210 MHz




Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5240 MHz




For Client without radar detection function:


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5240 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 / 5230 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 / 5210 MHz



Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5200 MHz



4.4. Radiated Emissions Measurement

4.4.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1 000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.4.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.4.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	Normal Link
Test Date	Jun. 10, 2014	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.4.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	Normal Link
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	67.83	31.77	40.00	-8.23	57.52	0.98	5.08	31.81	300	104	HORIZONTAL Peak
2	90.14	32.71	43.50	-10.79	54.43	1.13	8.74	31.59	400	95	HORIZONTAL Peak
3	135.73	32.01	43.50	-11.49	50.97	1.38	11.20	31.54	300	259	HORIZONTAL Peak
4	270.56	32.77	46.00	-13.23	49.96	1.99	12.37	31.55	100	38	HORIZONTAL Peak
5	413.15	30.82	46.00	-15.18	43.27	2.53	16.37	31.35	100	200	HORIZONTAL Peak
6	500.45	32.60	46.00	-13.40	44.27	2.82	16.92	31.41	100	88	HORIZONTAL Peak

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	36.79	35.84	40.00	-4.16	52.81	0.71	14.20	31.88	100	82 VERTICAL	QP
2	58.13	33.57	40.00	-6.43	59.16	0.88	5.31	31.78	200	260 VERTICAL	QP
3	89.17	35.45	43.50	-8.05	57.39	1.12	8.54	31.60	125	186 VERTICAL	Peak
4	165.80	32.03	43.50	-11.47	52.63	1.56	9.38	31.54	100	143 VERTICAL	Peak
5	478.14	28.20	46.00	-17.80	39.90	2.72	16.79	31.21	200	339 VERTICAL	Peak
6	500.45	33.27	46.00	-12.73	44.94	2.82	16.92	31.41	125	0 VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.4.9. Results for Radiated Emissions (1GHz~40GHz)

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15544.78	58.91	74.00	-15.09	44.28	10.37	38.78	34.52	168	360	HORIZONTAL Peak
2	15545.86	45.00	54.00	-9.00	30.37	10.37	38.78	34.52	168	354	HORIZONTAL Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15538.62	48.35	54.00	-5.65	33.71	10.37	38.78	34.51	130	210	VERTICAL Average
2	15541.40	60.71	74.00	-13.29	46.08	10.37	38.78	34.52	130	210	VERTICAL Peak

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 40 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	15596.32	48.26	54.00	-5.74	33.72	10.36	38.77	34.59	151	351	HORIZONTAL Average
2	15604.24	60.81	74.00	-13.19	46.30	10.36	38.75	34.60	151	351	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	15596.96	62.64	74.00	-11.36	48.10	10.36	38.77	34.59	121	285	VERTICAL Peak
2	15600.90	50.54	54.00	-3.46	36.02	10.36	38.75	34.59	121	285	VERTICAL Average

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 48 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15718.58	47.51	54.00	-6.49	33.17	10.36	38.72	34.74	155	348	HORIZONTAL Average
2	15727.68	59.59	74.00	-14.41	45.26	10.36	38.72	34.75	155	348	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15714.52	57.59	74.00	-16.41	43.24	10.36	38.72	34.73	135	278	VERTICAL Peak
2	15715.84	50.07	54.00	-3.93	35.72	10.36	38.72	34.73	135	278	VERTICAL Average

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15571.68	45.04	54.00	-8.96	30.45	10.37	38.77	34.55	100	78 HORIZONTAL	Average
2	15574.00	56.43	74.00	-17.57	41.85	10.37	38.77	34.56	100	78 HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15569.64	59.21	74.00	-14.79	44.62	10.37	38.77	34.55	124	336 VERTICAL	Peak
2	15573.84	47.38	54.00	-6.62	32.80	10.37	38.77	34.56	124	336 VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 46 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15685.68	45.63	54.00	-8.37	31.24	10.36	38.73	34.70	100	348	HORIZONTAL Average
2	15693.20	57.36	74.00	-16.64	42.99	10.36	38.72	34.71	100	348	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15692.64	48.47	54.00	-5.53	34.10	10.36	38.72	34.71	120	209	VERTICAL Average
2	15699.76	59.34	74.00	-14.66	44.97	10.36	38.72	34.71	120	209	VERTICAL Peak

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15637.20	44.92	54.00	-9.08	30.45	10.36	38.75	34.64	100	269	HORIZONTAL Average
2	15642.76	57.13	74.00	-16.87	42.66	10.36	38.75	34.64	100	269	HORIZONTAL Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15636.40	56.67	74.00	-17.33	42.20	10.36	38.75	34.64	100	117	VERTICAL Peak
2	15642.96	45.09	54.00	-8.91	30.62	10.36	38.75	34.64	100	117	VERTICAL Average

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 36 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	15537.04	46.17	54.00	-7.83	31.53	10.37	38.78	34.51	100	16 HORIZONTAL	Average
2	15541.02	56.11	74.00	-17.89	41.48	10.37	38.78	34.52	100	16 HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	15537.28	50.89	54.00	-3.11	36.25	10.37	38.78	34.51	129	279 VERTICAL	Average
2	15542.16	65.32	74.00	-8.68	50.69	10.37	38.78	34.52	132	286 VERTICAL	Peak

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 40 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15599.32	57.45	74.00	-16.55	42.91	10.36	38.77	34.59	100	33	HORIZONTAL	Peak
2	15600.76	48.63	54.00	-5.37	34.11	10.36	38.75	34.59	100	33	HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15595.10	61.15	74.00	-12.85	46.60	10.36	38.77	34.58	120	284	VERTICAL	Peak
2	15599.62	50.72	54.00	-3.28	36.18	10.36	38.77	34.59	120	284	VERTICAL	Average

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 48 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15714.68	60.40	74.00	-13.60	46.05	10.36	38.72	34.73	150	360	HORIZONTAL	Peak
2	15719.68	48.05	54.00	-5.95	33.71	10.36	38.72	34.74	150	360	HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15719.58	50.91	54.00	-3.09	36.57	10.36	38.72	34.74	116	122	VERTICAL	Average
2	15724.36	65.14	74.00	-8.86	50.81	10.36	38.72	34.75	116	122	VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5. Band Edge Emissions Measurement

4.5.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.5.3. Test Procedures

- The test procedure is the same as section 4.4.3, only the frequency range investigated is limited to 100MHz around bandedges.

4.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.4.4.

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36, 40, 48 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Channel 36

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5146.60	71.83	74.00	-2.17	66.89	6.13	34.01	35.20	112	71	VERTICAL
2	5150.00	52.94	54.00	-1.06	48.00	6.13	34.01	35.20	112	71	VERTICAL
3	5180.40	111.56			106.53	6.15	34.08	35.20	112	71	VERTICAL
4	5180.60	101.57			96.54	6.15	34.08	35.20	112	71	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5150.00	48.14	54.00	-5.86	43.20	6.13	34.01	35.20	100	146	VERTICAL
2	5150.00	68.90	74.00	-5.10	63.96	6.13	34.01	35.20	100	146	VERTICAL
3	5200.60	104.38			99.31	6.16	34.11	35.20	100	146	VERTICAL
4	5201.20	115.06			109.99	6.16	34.11	35.20	100	146	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5130.80	57.13	74.00	-16.87	52.23	6.12	33.98	35.20	115	199	VERTICAL
2	5150.00	43.78	54.00	-10.22	38.84	6.13	34.01	35.20	115	199	VERTICAL
3	5240.60	105.63			100.47	6.18	34.18	35.20	115	199	VERTICAL
4	5242.40	115.90			110.72	6.20	34.18	35.20	115	199	VERTICAL
5	5350.00	44.57	54.00	-9.43	39.09	6.26	34.42	35.20	115	199	VERTICAL
6	5353.00	57.07	74.00	-16.93	51.59	6.26	34.42	35.20	115	199	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38, 46 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014 ~ Jun. 26, 2014		

Channel 38

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5150.00	52.72	54.00	-1.28	47.78	6.13	34.01	35.20 Average	102	7	VERTICAL
2	5150.00	69.07	74.00	-4.93	64.13	6.13	34.01	35.20 Peak	102	7	VERTICAL
3	5188.00	96.01			90.98	6.15	34.08	35.20 Average	102	7	VERTICAL
4	5188.00	105.90			100.87	6.15	34.08	35.20 Peak	102	7	VERTICAL

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5150.00	52.77	54.00	-1.23	47.83	6.13	34.01	35.20 Average	100	157	VERTICAL
2	5150.00	68.77	74.00	-5.23	63.83	6.13	34.01	35.20 Peak	100	157	VERTICAL
3	5228.80	111.82			106.66	6.18	34.18	35.20 Peak	100	157	VERTICAL
4	5231.80	101.46			96.30	6.18	34.18	35.20 Average	100	157	VERTICAL

Item 3, 4 are the fundamental frequency at 5230 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Channel 42

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5147.60	66.63	74.00	-7.37	61.69	6.13	34.01	35.20	Peak	101	144	VERTICAL
2	5150.00	52.89	54.00	-1.11	47.95	6.13	34.01	35.20	Average	101	144	VERTICAL
3	5202.00	100.74			95.67	6.16	34.11	35.20	Peak	101	144	VERTICAL
4	5212.00	91.01			85.89	6.17	34.15	35.20	Average	101	144	VERTICAL

Item 3, 4 are the fundamental frequency at 5210 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	24°C	Humidity	55%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 36, 40, 48 / Chain 1 + Chain 2
Test Date	Jun. 25, 2014		

Channel 36

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5149.60	70.22	74.00	-3.78	65.28	6.13	34.01	35.20	Peak	112	71 VERTICAL
2	5150.00	53.00	54.00	-1.00	48.06	6.13	34.01	35.20	Average	112	71 VERTICAL
3	5180.80	102.07			97.04	6.15	34.08	35.20	Average	112	71 VERTICAL
4	5182.40	111.78			106.75	6.15	34.08	35.20	Peak	112	71 VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5148.40	65.55	74.00	-8.45	60.61	6.13	34.01	35.20	Peak	100	72 VERTICAL
2	5150.00	48.88	54.00	-5.12	43.94	6.13	34.01	35.20	Average	100	72 VERTICAL
3	5198.40	114.09			109.02	6.16	34.11	35.20	Peak	100	72 VERTICAL
4	5199.20	104.47			99.40	6.16	34.11	35.20	Average	100	72 VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5124.80	56.69	74.00	-17.31	51.83	6.12	33.94	35.20	Peak	130	198 VERTICAL
2	5150.00	44.08	54.00	-9.92	39.14	6.13	34.01	35.20	Average	130	198 VERTICAL
3	5238.80	115.62			110.46	6.18	34.18	35.20	Peak	130	198 VERTICAL
4	5239.40	105.88			100.72	6.18	34.18	35.20	Average	130	198 VERTICAL
5	5350.00	44.35	54.00	-9.65	38.87	6.26	34.42	35.20	Average	130	198 VERTICAL
6	5365.60	58.66	74.00	-15.34	53.13	6.27	34.46	35.20	Peak	130	198 VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.6. Frequency Stability Measurement

4.6.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.6.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.6.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $0^\circ\text{C} \sim 40^\circ\text{C}$.

4.6.4. Test Setup Layout



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.6.7. Test Result of Frequency Stability

Temperature	24°C	Humidity	61%
Test Engineer	Benson Peng	Test Date	Jul. 03, 2014

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5200 MHz
126.50	5200.0542
110.00	5200.0534
93.50	5200.0532
Max. Deviation (MHz)	0.054200
Max. Deviation (ppm)	10.42

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5200 MHz
0	5200.0512
10	5200.0522
20	5200.0534
30	5200.0602
40	5200.0618
Max. Deviation (MHz)	0.061800
Max. Deviation (ppm)	11.88

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
BILOG ANTENNA	Schaffner	CBL6112B	2928	30MHz ~ 2GHz	Dec. 27, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Dec. 17, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 03, 2014	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)

Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
-------------	---------	---------	---------	--------------	---------------	------------------------

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

NCR means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%