TCC

Company Confidential

FCC ID: GMLNPW-3

Amendment A

February 13, 2002

Test Report #: 01-RF-0626



Accredited Laboratory Certificate Number: 1819-01

Ver 1.0

CFR 47 Part 2, 22, and 24 Test Report

Test Report Number: 01-RF-0626 Amendment A

Terminal device:

FCC ID: GMLNPW-3, Model 8265, HW: 3.1, SW: 3.0 (Detailed information is listed in section 4 of the original test report).

Originator: Function: Version/Status: Location: Date:

Test & Certification Center (TCC) - Dallas

Randy Leenerts TCC - Dallas - EMC 1.0 Approved TCC Directories February 13, 2002

Change History:

 Version
 Date

 0.1
 February 7, 2002

 0.2
 February 12, 2002

 1.0
 February 13, 2002

Status02Draft002Draft002Approved

Handled By Randy Leenerts Elizabeth Parish Alan C. Ewing **Comments** In Process Updated Approved

Testing laboratory:	Test & Certification Center (TCC) Dallas	Client:	Nokia Mobile Phones, Inc.
	Nokia Mobile Phones, Inc		Model 8265, FCC ID: GMLNPW-3
	6021 Connection Drive		6021 Connection Drive
	Irving, Texas 75039		Irving, Texas 75039
	U.S.A.		U.S.A.
	Tel. 972-894-5000		Tel. 972-894-5000
	Fax. 972-894-4988	1000	Fax. 972-894-4988

Date and signatures:

For the contents:

and enon

Randy Leenerts, EMC Engineer Technical Review

February 13, 2002

Alan C. Ewing, General Manager Manager Review

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TABLE OF CONTENTS

1. GE	ENERAL	
1.1 1.2	QUALITY SYSTEM	
11.	OCCUPIED BANDWIDTH (EMISSIONS MASKS)	5
11.1 11.2 11.3 11.4	SETUP PASS/FAIL CRITERIA DETAILED TEST RESULTS MEASUREMENT UNCERTAINTY	5 6 6 21
12.	OCCUPIED BANDWIDTH (TRANSMITTER CONDUCTED MEASUREMENTS)	22
12.1 12.2 12.3 12.4	SETUP PASS/FAIL CRITERIA DETAILED TEST RESULTS MEASUREMENT UNCERTAINTY	
15.	FIELD STRENGTH OF SPURIOUS RADIATION	
15.1 15.2 15.3 15.4	SETUP PASS/FAIL CRITERIA DETAILED TEST RESULTS MEASUREMENT UNCERTAINTY	

© No part of this report shall be reproduced out of the context of the report without the written approval of Nokia Mobile Phones, Inc., Dallas Product Creation, TCC – Dallas.

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

1. GENERAL

1.1 Quality System

The quality system in place for TCC-Dallas conforms to ISO/IEC 17025 and has been audited to the standard by A2LA (American Association of Laboratory Accreditation). The appendix of the original report contains the scope of accreditation for A2LA. TCC – Dallas has also been audited using the ISO 9000 Quality System, as part of Nokia Mobile Phones, Inc., by ABS (American Bureau of Shipping) Quality Evaluations Inc.

TCC-Dallas is a recognized laboratory with the Federal Communications Commission in filing applications for Certification under Parts 15 and 18, Registration Number 100060, and Industry Canada, Registration Number IC 661.

1.2 Objective

The objective of this test report amendment is to supplement or amend information provided in the original test report, Test Report No. 01-RF-0026.

The following information are comments/questions from and responses to the Federal Communication Commission.

EMC

1) Internal photograph with antenna clearly notated.

Photographs included in original submission (Internal Photographs, page 5) shows the antenna detail in the upper right quadrant of the picture.

2) Updated occupied BW plots. Those on exhibit are extremely difficult to read. Please scan with higher resolution. Also if possible please use a darker color for the trace.

Refer to Section 11 and Section 12 of this test report amendment.

3) A statement discussing the methods used to account for the burst nature of TDMA signals in your conducted and radiated measurements.

EMI Measurement Receiver is set at a very slow scan rate.

4) Additional radiated spurious data. Use of the substitution method is required.

Refer to Section 15 of this test report amendment.

5) Statement of the emission mode used on page 38. F1D and TDMA are both mentioned on the plot. It is not clear to the FCC that TDMA uses F1D modulation. Please clarify.

The plot shows TDMA modulation. The F1D mask is used on the plot to determine compliance. Refer to Section 11.3 of this test report amendment, page 20.

Ver 1.0

6) A statement clarifying maximum power. The plot on page 38 shows power reference of 30 dBm was used. The FCC understands the power of this unit is 27 dBm. Please clarify the difference and provide a new plot as appropriate.

Refer to Section 11.3 of this test report amendment, page 20.

7) A statement clarifying 50% deviation of the unit. Page 24 states that 50% deviation is 2.5 KHz while deviation plots on page 21 of 85 show a maximum deviation of 12 KHz. Please clarify.

The language in the report in intended to indicate that though 50% modulation (i.e. 6 kHz) is used where reasonable, 2.5 kHz deviation is typically chosen for practical considerations. Using the 2.5 kHz reference mentioned, it is necessary to input nearly 5V into the audio input of the phone. This is well beyond the normal operating range of the handset (which is in the mV range), and higher voltages would risk doing permanent damage to the audio circuitry. The circuitry is sufficiently saturated at this level to demonstrate worst case modulation.

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

5 (46)

11. OCCUPIED BANDWIDTH (EMISSIONS MASKS)

Specification: FCC Part 2.1049(c)(1), 24.238(a)(b)

11.1 Setup

Testing was performed with the EUT connected to a 6dB splitter, 6dB attenuator, filter bank and then to the EMI receiver. The base station simulator was connected to the other port of the splitter to establish a call.

For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with the output level set for +/-2.5kHz deviation (or 50% modulation). With level constant, the signal level was increased 16dB.

For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.



Ver 1.0

6 (46)

11.2 Pass/Fail Criteria

Modulation	Low Limit (kHz)	High Limit (kHz)	
Voice	10.8	13.2	
Wideband Data	7.2	8.8	

11.3 Detailed Test Results

Test Technician / Engineer	Byron Holz/ Mark Severson	
Date of Measurement	December 05, 2001	
Temperature / Humidity	22°C 56%RH	
Test Result	FCC ID: GMLNPW-3 complies with FCC Part 2.1049(c)(1), 24.238(a)(b)	

AMPS Low and Max Power Measurements – no modulation; 836.4 MHz



Max Power:

Ver 1.0



AMPS Min and Max Power – Voice (2500 Hz Sine Wave); F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level

Max Power, Voice Only

Min Power:

TCC

Test & Certification Center (TCC) - Dallas

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

8 (46)



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002 Ve

Ver 1.0

AMPS Min and Max Power – Wideband Data; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Max Power, WBD

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – SAT; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Max Power, SAT Only

FCC ID: GMLNPW-3 Test & Certification Center (TCC) - Dallas Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – ST; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Max Power, ST Only

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – SAT + Voice; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Max Power, SAT+ Voice

Test & Certification Center (TCC) - Dallas FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – SAT + DTMF; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level

25.00 20.00 10.00-0.00 Power (dBm) -10.00 -20.00 -30.00-MANN -40.00--50.00-836.35 836.38 836.40 836.42 836.45 8<u>36.40</u> Freq (MHz) 100.00 Limit EMI

Max Power, SAT+DTMF

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – Voice (2500 Hz Sine Wave); F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level

Min Power, Voice Only



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – Wideband Data; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level

Min Power, WBD



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS Min and Max Power – SAT; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Min Power, SAT Only

Test & Certification Center (TCC) - Dallas	FCC ID: GMLNPW-3 Test Report #: 01-RF-0626	
	February 13, 2002	Ver 1.0

AMPS Min and Max Power – ST; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Min Power, ST Only

Test &

Certification Center (TCC) - Dallas	FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002	Ver 1.0
	rediuary 13, 2002	ver 1.0

AMPS Min and Max Power – SAT + Voice; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level



Max Power, SAT+ Voice

FCC ID: GMLNPW-3Test & Certification Center (TCC) - DallasTest Report #: 01-RF-0626
Amendment A
February 13, 2002Ver 1.0

AMPS Min and Max Power – SAT + DTMF; F3E/F3D mask

100 kHz Span, 300 Hz RBW/VBW, ref to power level

Min Power, SAT+DTMF



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA Min and Max Power – Modulation is TDMA, Mask is FID

200 kHz Span, 300 Hz RBW/VBW, ref to power level

Max Power, TDMA Random Data



Test & Certification Center (TCC) - Dallas Amendment A February 13, 2002

Ver 1.0

Min Power, TDMA Random Data



11.4 Measurement Uncertainty

The measurement uncertainty for this test is +/- 3.7dB for 100kHz - 1000MHz and +/- 5.3dB for 1 - 20GHz.

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

12. OCCUPIED BANDWIDTH (TRANSMITTER CONDUCTED MEASUREMENTS)

Specification: FCC Part 2.1049(c)(1), 24.238(a)(b)

12.1 Setup

Testing was performed with the EUT connected to a 6dB splitter, 6dB attenuator, filter bank and then to the EMI receiver. The base station simulator was connected to the other port of the splitter to establish a call.



12.2 Pass/Fail Criteria

Band	Frequency Range (MHz)	FCC Limits (dBm)
Cellular 800 Low Channel	< 824	-13
Cellular 800 High Channel	> 849	-13
PCS 1900 Low Channel	< 1850	-13
PCS 1900 High Channel	> 1910	-13

Ver 1.0

12.3 Detailed Test Results

Test Technician / Engineer	Mark Severson		
Date of Measurement	November 28, 2001		
Temperature / Humidity	23°C 29%RH		
Test Result	FCC ID: GMLNPW-3 complies with FCC Part 2.1049(c)(1), 24.238(a)(b)		

PCS Band, Call mode, Max Power. Channel 999



Ver 1.0

PCS Band, Call mode, Min Power. Channel 999



Ver 1.0



AMPS (Cellular Band), Call Mode, Max Power, Channel 991

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS (Cellular Band), Call Mode, Max Power, Channel 799



TCC

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0



TDMA (Cellular Band), Call Mode, Max Power, Channel 991

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA (Cellular Band), Call Mode, Max Power, Channel 799



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0



TDMA (PCS Band), Call Mode, Max Power, Channel 2

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA (PCS Band), Call Mode, Max Power, Channel 1998



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS (Cellular Band), Min Power Call Mode, Channel 991



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

AMPS (Cellular Band), Min Power, Call Mode, Channel 799



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA (Cellular Band), Min Power, Call Mode, Channel 991



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA (Cellular Band), Min Power, Call Mode, Channel 799



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA (PCS Band), Min Power, Call Mode, Channel 2



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA (PCS Band), Min Power, Call Mode, Channel 1998



12.4 Measurement Uncertainty

The measurement uncertainty for this test is +/- 3.7dB for 100kHz - 1000MHz and +/- 5.3dB for 1 - 20GHz.

Test & Certification Center (TCC) - Dallas FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

15. FIELD STRENGTH OF SPURIOUS RADIATION

Specification: FCC Part 2.1053

15.1 Setup



15.2 Pass/Fail Criteria

Band	Frequency Range (MHz)	FCC Limit (dBm)
Cellular / PCS	30 – 20000*	-13

* Frequency to be investigated up to the 10th harmonic of the highest clock or frequency used.

Ver 1.0

15.3 Detailed Test Results

Test Technician / Engineer	Michael Sundstrom	
Date of Measurement	November 28, 2001, Feb. 11, 2002	
Temperature / Humidity	23°C, 24°C 29%RH, 23%RH	
Test Result	FCC ID: GMLNPW-3 complies with FCC part 2.1053	

Substitution method according to ANSI/TIA/EIA 603-1 was used for final measurements.

Amps Channel 991:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
824.04	1648.3	-35.5	-13.0	Н
824.04	1648.3	-33.4	-13.0	V
824.04	2472.3	-38.0	-13.0	Н
824.04	2472.5	-34.6	-13.0	V
824.04	3296.1	-35.6	-13.0	Н
824.04	3296.0	-35.1	-13.0	V
824.04	4120.3	-34.1	-13.0	Н
824.04	4120.2	-33.6	-13.0	V
824.04	4944.1	-27.8	-13.0	Н
824.04	4944.2	-28.3	-13.0	V
824.04	5768.3	-28.3	-13.0	Н
824.04	5768.1	-27.3	-13.0	V
824.04	6592.4	-39.5	-13.0	Н
824.04	6592.5	-40.2	-13.0	V
824.04	7415.9	-41.8	-13.0	Н
824.04	7416.5	-42.0	-13.0	V
824.04	8240.9	-40.0	-13.0	Н
824.04	8240.3	-39.9	-13.0	V

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

Amps Channel 384:

Tuned				
Freq	Freq (Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
836.52	1673.3	-39.6	-13.0	Н
836.52	1673.3	-36.4	-13.0	V
836.52	2509.5	-34.7	-13.0	Н
836.52	2509.6	-35.0	-13.0	V
836.52	3345.9	-34.8	-13.0	Н
836.52	3346.0	-35.8	-13.0	V
836.52	4182.6	-32.9	-13.0	Н
836.52	4182.5	-33.4	-13.0	V
836.52	5019.2	-25.2	-13.0	Н
836.52	5019.1	-30.0	-13.0	V
836.52	5855.7	-26.5	-13.0	Н
836.52	5855.7	-26.4	-13.0	V
836.52	6692.2	-38.2	-13.0	Н
836.52	6691.3	-39.9	-13.0	V
836.52	7528.5	-41.8	-13.0	Н
836.52	7527.9	-39.6	-13.0	V
836.52	8365.3	-41.1	-13.0	Н
836.52	8365.1	-40.5	-13.0	V

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

Amps Channel 799:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
848.97	1698.4	-35.8	-13.0	Н
848.97	1698.3	-35.0	-13.0	V
848.97	2547.3	-37.7	-13.0	Н
848.97	2547.4	-35.4	-13.0	V
848.97	3395.9	-34.1	-13.0	Н
848.97	3396.0	-35.2	-13.0	V
848.97	4244.8	-32.3	-13.0	Н
848.97	4244.8	-32.6	-13.0	V
848.97	5093.8	-25.4	-13.0	Н
848.97	5093.8	-27.9	-13.0	V
848.97	5942.8	-26.7	-13.0	Н
848.97	5942.6	-25.6	-13.0	V
848.97	6792.3	-38.6	-13.0	Н
848.97	6791.7	-38.5	-13.0	V
848.97	7641.2	-40.0	-13.0	Н
848.97	7640.6	-41.3	-13.0	V
848.97	8489.9	-38.5	-13.0	Н
848.97	8489.2	-39.6	-13.0	V

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA Cellular Channel 991:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
824.04	1648.3	-36.8	-13.0	Н
824.04	1648.3	-34.7	-13.0	V
824.04	2472.6	-37.4	-13.0	Н
824.04	2472.6	-36.5	-13.0	V
824.04	3296.2	-35.3	-13.0	Н
824.04	3296.2	-35.1	-13.0	V
824.04	4120.2	-33.2	-13.0	Н
824.04	4120.3	-31.8	-13.0	V
824.04	4944.2	-26.3	-13.0	Н
824.04	4944.4	-29.2	-13.0	V
824.04	5768.4	-26.7	-13.0	Н
824.04	5768.4	-26.6	-13.0	V
824.04	6593.1	-45.1	-13.0	Н
824.04	6592.1	-44.1	-13.0	V
824.04	7415.4	-42.8	-13.0	Н
824.04	7417.1	-42.4	-13.0	V
824.04	8239.5	-40.3	-13.0	Н
824.04	8239.9	-38.8	-13.0	V



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA Cellular Channel 384:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
836.52	1673.3	-36.7	-13.0	Н
836.52	1673.3	-35.2	-13.0	V
836.52	2509.8	-33.6	-13.0	Н
836.52	2509.9	-34.8	-13.0	V
836.52	3346.1	-34.8	-13.0	Н
836.52	3346.0	-34.9	-13.0	V
836.52	4182.5	-32.7	-13.0	Н
836.52	4182.6	-33.1	-13.0	V
836.52	5019.2	-23.8	-13.0	Н
836.52	5019.1	-27.7	-13.0	V
836.52	5855.7	-26.8	-13.0	Н
836.52	5855.5	-26.9	-13.0	V
836.52	6692.2	-41.0	-13.0	Н
836.52	6692.1	-37.0	-13.0	V
836.52	7527.8	-42.0	-13.0	Н
836.52	7529.5	-42.7	-13.0	V
836.52	8366.1	-39.9	-13.0	Н
836.52	8365.7	-39.7	-13.0	V



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA Cellular Channel 799:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
848.97	1698.3	-37.9	-13.0	Н
848.97	1698.3	-37.6	-13.0	V
848.97	2546.8	-37.6	-13.0	Н
848.97	2546.9	-35.3	-13.0	V
848.97	3359.9	-34.4	-13.0	Н
848.97	3359.9	-35.0	-13.0	V
848.97	4245.0	-32.1	-13.0	Н
848.97	4244.9	-33.7	-13.0	V
848.97	5093.9	-25.6	-13.0	Н
848.97	5093.8	-27.9	-13.0	V
848.97	5942.8	-26.5	-13.0	Н
848.97	5942.8	-26.4	-13.0	V
848.97	6791.8	-41.3	-13.0	Н
848.97	6791.5	-43.3	-13.0	V
848.97	7641.1	-40.8	-13.0	Н
848.97	7641.5	-39.2	-13.0	V
848.97	8489.7	-40.3	-13.0	Н
848.97	8490.2	-38.8	-13.0	V

FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

TDMA PCS Channel 02:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
1850.04	3700.1	-34.4	-13.0	Н
1850.04	3699.9	-31.9	-13.0	V
1850.04	5550.0	-26.6	-13.0	Н
1850.04	5550.1	-27.5	-13.0	V
1850.04	7400.1	-35.3	-13.0	Η
1850.04	7400.2	-38.0	-13.0	V
1850.04	9250.0	-29.5	-13.0	Н
1850.04	9250.0	-28.3	-13.0	V
1850.04	11100.0	-31.5	-13.0	Н
1850.04	11100.8	-36.3	-13.0	V
1850.04	12950.3	-33.2	-13.0	Н
1850.04	12951.0	-33.6	-13.0	V
1850.04	14801.0	-30.2	-13.0	Н
1850.04	14800.9	-31.0	-13.0	V
1850.04	16649.6	-31.5	-13.0	Н
1850.04	16650.3	-30.1	-13.0	V

Ver 1.0



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA PCS Channel 1001:

Tuned	Freq			
Freq	(Max)	(PK) EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
1880.01	3760.4	-34.0	-13.0	Н
1880.01	3760.4	-34.0	-13.0	V
1880.01	5640.0	-33.2	-13.0	Н
1880.01	5640.0	-33.7	-13.0	V
1880.01	7520.2	-31.7	-13.0	Н
1880.01	7520.1	-29.4	-13.0	V
1880.01	9400.0	-27.2	-13.0	Н
1880.01	9400.7	-31.1	-13.0	V
1880.01	11280.1	-34.4	-13.0	Н
1880.01	11280.1	-36.0	-13.0	V
1880.01	13159.9	-35.2	-13.0	Н
1880.01	13161.4	-32.9	-13.0	V
1880.01	15041.1	-30.6	-13.0	Н
1880.01	15041.5	-31.6	-13.0	V
1880.01	16921.0	-28.4	-13.0	Н
1880.01	16920.5	-28.7	-13.0	V



FCC ID: GMLNPW-3 Test Report #: 01-RF-0626 Amendment A February 13, 2002

Ver 1.0

TDMA PCS Channel 1998:

Tuned	Freq	(PK)		
Freq	(Max)	EMI	FCC Limit	Pol.
(MHz)	(MHz)	(dBm)	(dBm)	
1909.92	3819.9	-29.4	-13.0	Н
1909.92	3819.8	-29.9	-13.0	V
1909.92	5729.6	-29.2	-13.0	Н
1909.92	5729.8	-30.6	-13.0	V
1909.92	7639.6	-18.4	-13.0	Н
1909.92	7639.8	-22.8	-13.0	V
1909.92	9549.6	-26.6	-13.0	Н
1909.92	9549.0	-28.7	-13.0	V
1909.92	11460.5	-35.6	-13.0	Н
1909.92	11458.6	-36.0	-13.0	V
1909.92	13369.0	-31.3	-13.0	Н
1909.92	13369.5	-31.2	-13.0	V
1909.92	15279.3	-32.9	-13.0	Н
1909.92	15280.1	-32.3	-13.0	V
1909.92	17189.4	-28.9	-13.0	Н
1909.92	17189.2	-27.4	-13.0	V

15.4 Measurement Uncertainty

The measurement uncertainty for this test is +/- 5.2dB for 30-300MHz, +/- 5.2dB for 300-1000MHz, +/- 5.6dB for 1-6GHz, and +/-6.8dB for 6 to 18GHz.