

## FCC Test Report

**Report No.:** RFBHQC-WTW-P22070414B

**FCC ID:** MCLT77H747

**Test Model:** T77H747

**Received Date:** 2023/10/16

**Test Date:** 2023/10/25 ~ 2023/10/26

**Issued Date:** 2023/11/20

**Applicant:** HON HAI PRECISION IND. CO., LTD.

**Address:** 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan,  
R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**FCC Registration /  
Designation Number:** 723255 / TW2022



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

|                                                                 |           |
|-----------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                             | <b>3</b>  |
| <b>1 Certificate of Conformity .....</b>                        | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                          | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                               | 5         |
| 2.2 Modification Record .....                                   | 5         |
| <b>3 General Information .....</b>                              | <b>6</b>  |
| 3.1 General Description of EUT .....                            | 6         |
| 3.2 Description of Test Modes .....                             | 7         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail .....   | 8         |
| 3.3 Description of Support Units .....                          | 9         |
| 3.3.1 Configuration of System under Test .....                  | 10        |
| 3.4 General Description of Applied Standards .....              | 11        |
| <b>4 Test Types and Results .....</b>                           | <b>12</b> |
| 4.1 Radiated Emission Measurement .....                         | 12        |
| 4.1.1 Limits of Radiated Emission Measurement .....             | 12        |
| 4.1.2 Test Instruments .....                                    | 13        |
| 4.1.3 Test Procedures .....                                     | 14        |
| 4.1.4 Deviation from Test Standard .....                        | 14        |
| 4.1.5 Test Setup .....                                          | 15        |
| 4.1.6 EUT Operating Conditions .....                            | 15        |
| 4.1.7 Test Results .....                                        | 16        |
| 4.2 Conducted Emission Measurement .....                        | 30        |
| 4.2.1 Limits of Conducted Emission Measurement .....            | 30        |
| 4.2.2 Test Instruments .....                                    | 30        |
| 4.2.3 Test Procedures .....                                     | 31        |
| 4.2.4 Deviation from Test Standard .....                        | 31        |
| 4.2.5 Test Setup .....                                          | 31        |
| 4.2.6 EUT Operating Conditions .....                            | 31        |
| 4.2.7 Test Results .....                                        | 32        |
| 4.3 Frequency Stability .....                                   | 34        |
| 4.3.1 Limits of Frequency Stability Measurement .....           | 34        |
| 4.3.2 Test Setup .....                                          | 34        |
| 4.3.3 Test Instruments .....                                    | 34        |
| 4.3.4 Test Procedure .....                                      | 34        |
| 4.3.5 Deviation from Test Standard .....                        | 34        |
| 4.3.6 EUT Operating Conditions .....                            | 34        |
| 4.3.7 Test Result .....                                         | 35        |
| 4.4 20dB Bandwidth .....                                        | 36        |
| 4.4.1 Limits of 20dB bandwidth Measurement .....                | 36        |
| 4.4.2 Test Setup .....                                          | 36        |
| 4.4.3 Test Instruments .....                                    | 36        |
| 4.4.4 Test Procedures .....                                     | 36        |
| 4.4.5 Deviation from Test Standard .....                        | 36        |
| 4.4.6 EUT Operating Conditions .....                            | 36        |
| 4.4.7 Test Results .....                                        | 37        |
| <b>5 Pictures of Test Arrangements .....</b>                    | <b>38</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b> | <b>39</b> |

### Release Control Record

| Issue No.             | Description       | Date Issued |
|-----------------------|-------------------|-------------|
| RFBHQC-WTW-P22070414B | Original release. | 2023/11/20  |

## 1 Certificate of Conformity

**Product:** NFC module

**Brand:** FOXCONN

**Test Model:** T77H747

**Sample Status:** Engineering Sample

**Applicant:** HON HAI PRECISION IND. CO., LTD.

**Test Date:** 2023/10/25 ~ 2023/10/26

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.225)  
47 CFR FCC Part 15, Subpart C (Section 15.215)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** 2023/11/20  
Claire Kuan / Specialist

**Approved by :**  , **Date:** 2023/11/20  
Wen Yu / Assistant Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.225, 15.215) |                                                                                                 |        |                                                    |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------|--------|----------------------------------------------------|
| FCC Clause                                             | Test Item                                                                                       | Result | Remarks                                            |
| 15.207                                                 | Conducted emission test                                                                         | PASS   | Minimum passing margin is -8.84 dB at 29.69922 MHz |
| 15.225 (a)                                             | The field strength of any emissions within the band 13.553-13.567 MHz                           | PASS   | Minimum passing margin is -68.33 dB at 13.560 MHz  |
| 15.225 (b)                                             | The field strength of any emissions within the bands 13.410-13.553 MHz and 13.567-13.710 MHz    | PASS   | Meet the requirement of limit.                     |
| 15.225 (c)                                             | The field strength of any emissions within the bands 13.110-13.410 MHz and 13.710-14.010 MHz    | PASS   | Meet the requirement of limit.                     |
| 15.225 (d)                                             | The field strength of any emissions appearing outside of the 13.110-14.010 MHz band below 30MHz | PASS   | Minimum passing margin is -24.28 dB at 25.876 MHz  |
| 15.225 (d)                                             | The field strength of any emissions appearing outside of the 13.110-14.010 MHz band above 30MHz | PASS   | Minimum passing margin is -0.9 dB at 149.16 MHz    |
| 15.225 (e)                                             | The frequency tolerance                                                                         | PASS   | Meet the requirement of limit.                     |
| 15.215 (c)                                             | 20dB Bandwidth                                                                                  | PASS   | Meet the requirement of limit.                     |
| 15.203                                                 | Antenna Requirement                                                                             | PASS   | Antenna connector is ACH not a standard connector. |

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency      | Expanded Uncertainty (k=2) ( $\pm$ ) |
|------------------------------------|----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 1.9 dB                               |
| Radiated Emissions up to 1 GHz     | 9kHz ~ 30MHz   | 3.1 dB                               |
|                                    | 30MHz ~ 1GHz   | 5.4 dB                               |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                     |                    |
|---------------------|--------------------|
| Product             | NFC module         |
| Brand               | FOXCONN            |
| Test Model          | T77H747            |
| Status of EUT       | Engineering Sample |
| Power Supply Rating | 5Vdc               |
| Modulation Type     | ASK                |
| Transfer Rate       | 106 kbit/s         |
| Operating Frequency | 13.56MHz           |
| Number of Channel   | 1                  |
| Antenna Type        | Refer to Note      |
| Antenna Connector   | Refer to Note      |
| Accessory Device    | NA                 |
| Cable Supplied      | NA                 |

Note:

1. This report is prepared for FCC class II permissive change. The difference compared with the Report No.: RF160629E05C as the following:

◆ Add one antenna – Antenna No. 7

| Original    |                                            |                     |                   |                       |              |                                  |
|-------------|--------------------------------------------|---------------------|-------------------|-----------------------|--------------|----------------------------------|
| Antenna No. | Brand                                      | Model               | Antenna Gain(dBi) | Frequency range (MHz) | Antenna Type | Connector Type                   |
| 1           | SAA                                        | LX8416-12-000-C     | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |
| 2           | Dexerials                                  | ANT-M041A           | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |
| 3           | Dexerials                                  | ANT-M043A           | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |
| 4           | Dexerials                                  | ANT-M047A           | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |
| 5           | SAA                                        | LX7828-12-000-C     | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |
| 6           | Murata                                     | FLANBPA-0715        | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |
| Newly       |                                            |                     |                   |                       |              |                                  |
| Antenna No. | Brand                                      | Model               | Antenna Gain(dBi) | Frequency range (MHz) | Antenna Type | Connector Type                   |
| 7           | Huizhou Speed Wireless Technology Co., Ltd | F-0W-JV-0191-001-K0 | NA                | 13.56                 | PCB          | ACH connector (with 1.2mm pitch) |

\* Due to radiated measurements are made and the antenna gain is already accounted for this device, so provide an antenna datasheet and/or antenna measurement report is not required. The antenna dimensions and pictures (include antenna wire length if have) are stated in EUT photo exhibit.

2. According to above condition, all test items of new antenna need to be performed. And all data was verified to meet the requirements.
3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

One channel was provided to this EUT:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 1       | 13.56           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |     |    |    | Description |
|--------------------|---------------|-----|----|----|-------------|
|                    | RE            | PLC | FS | EB |             |
| -                  | √             | √   | √  | √  | -           |

Where **RE<sub>≥1G</sub>**: Radiated Emission **PLC**: Power Line Conducted Emission  
**FS**: Frequency Stability **EB**: 20dB Bandwidth measurement

**NOTE:** The EUT's antenna had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Y-plane.

#### Radiated Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| Available Channel | Tested Channel | Modulation Type |
|-------------------|----------------|-----------------|
| 1                 | 1              | ASK             |

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| Available Channel | Tested Channel | Modulation Type |
|-------------------|----------------|-----------------|
| 1                 | 1              | ASK             |

#### Frequency Stability:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| Available Channel | Tested Channel | Modulation Type |
|-------------------|----------------|-----------------|
| 1                 | 1              | ASK             |

#### 20dB Bandwidth:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| Available Channel | Tested Channel | Modulation Type |
|-------------------|----------------|-----------------|
| 1                 | 1              | ASK             |

#### Test Condition:

| Applicable to | Environmental Conditions | Input Power           | Tested By    |
|---------------|--------------------------|-----------------------|--------------|
| RE            | 20deg. C, 70%RH          | 120Vac, 60Hz (System) | Sampson Chen |
| PLC           | 27deg. C, 69%RH          | 120Vac, 60Hz (System) | Sampson Chen |
| FS            | 25deg. C, 60%RH          | 5Vdc                  | Kevin Ko     |
| EB            | 25deg. C, 60%RH          | 5Vdc                  | Kevin Ko     |

### 3.3 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product   | Brand   | Model No.         | Serial No. | FCC ID | Remarks               |
|----|-----------|---------|-------------------|------------|--------|-----------------------|
| A  | Laptop    | Lenovo  | 20U5S01X00<br>L14 | PF-28LKK7  | N/A    | Provided by Lab       |
| B  | Test Tool | FOXCONN | N/A               | N/A        | N/A    | Supplied by applicant |
| C  | Adapter   | Lenovo  | ADLX45YLC3D       | N/A        | N/A    | Provided by Lab       |


| ID | Cable Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks               |
|----|--------------------|------|------------|--------------------|--------------|-----------------------|
| 1  | Data Cable         | 1    | 0.1        | No                 | 0            | Supplied by applicant |
| 2  | DC Cable           | 1    | 1.8        | No                 | 0            | Provided by Lab       |
| 3  | AC Cable           | 1    | 1          | No                 | 0            | Provided by Lab       |

### 3.3.1 Configuration of System under Test

#### For AC Power Conducted Emission test



#### For Radiated Emission test



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.225)**

**FCC Part 15, Subpart C (15.215)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission Measurement

#### 4.1.1 Limits of Radiated Emission Measurement

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209 as below table:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
4. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

##### For Radiated Emission test:

| Description & Manufacturer                    | Model No.            | Serial No.  | Calibrated Date | Calibrated Until |
|-----------------------------------------------|----------------------|-------------|-----------------|------------------|
| Boresight Antenna Tower & Turn Table Max-Full | MF-7802BS            | MF780208530 | N/A             | N/A              |
| Loop Antenna Electro-Metrics                  | EM-6879              | 264         | 2023/2/21       | 2024/2/20        |
| MXA Signal Analyzer Keysight                  | N9020B               | MY60112408  | 2023/3/6        | 2024/3/5         |
| MXE EMI Receiver Keysight                     | N9038A               | MY59050100  | 2023/6/13       | 2024/6/12        |
| Preamplifier EMCi                             | EMC001340            | 980142      | 2023/5/8        | 2024/5/7         |
| RF Coaxial Cable JYEBAO                       | 5D-FB                | LOOPCAB-001 | 2022/12/19      | 2023/12/18       |
|                                               |                      | LOOPCAB-002 | 2022/12/19      | 2023/12/18       |
| Software                                      | ADT_Radiated_V8.7.08 | N/A         | N/A             | N/A              |

##### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Tested Date: 2023/10/25

##### For other test items:

| DESCRIPTION & MANUFACTURER                 | MODEL NO.                     | SERIAL NO.  | CALIBRATED DATE | CALIBRATED UNTIL |
|--------------------------------------------|-------------------------------|-------------|-----------------|------------------|
| Temperature & Humidity Chamber Giant Force | GTH-150-40-SP-AR              | MAA0812-008 | 2022/12/26      | 2023/12/25       |
| DC Power Supply Topward                    | 6603D                         | 795558      | NA              | NA               |
| True RMS Clamp Meter FLUKE                 | 325                           | 31130711WS  | 2023/6/8        | 2024/6/7         |
| MXA Signal Analyzer Keysight               | N9020B                        | MY60112409  | 2023/2/18       | 2024/2/17        |
| Software                                   | ADT_RF Test Software V7.6.5.4 | NA          | NA              | NA               |

##### NOTE:

1. The test was performed in Oven room 2.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. Tested Date: 2023/10/26

#### 4.1.3 Test Procedures

##### **For Radiated Emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak or Peak / Average Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **Note:**

1. The resolution bandwidth of test receiver/spectrum analyzer is 200Hz at frequency below 150kHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 9kHz at frequency 150kHz~30MHz.

##### **For Radiated Emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

##### **Note:**


1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup

##### For Radiated Emission below 30MHz



##### For Radiated Emission 30MHz to 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (NPC300\_PRBSTTool.exe) has been activated to set the EUT under transmission condition continuously at specific channel frequency.


#### 4.1.7 Test Results

|                        |                     |                                          |                       |
|------------------------|---------------------|------------------------------------------|-----------------------|
| <b>Frequency Range</b> | 13.11MHz ~ 14.01MHz | <b>Detector Function &amp; Bandwidth</b> | Quasi-Peak (QP), 9kHz |
|------------------------|---------------------|------------------------------------------|-----------------------|

| Antenna Polarity : Parallel |                 |                         |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | 13.348          | 2.00 QP                 | 40.51          | -38.51      | 1.00               | 186                  | 44.52            | -42.52                   |
| 2                           | 13.478          | 4.42 QP                 | 50.47          | -46.05      | 1.00               | 170                  | 46.97            | -42.55                   |
| 3                           | *13.560         | 15.67 QP                | 84.00          | -68.33      | 1.00               | 160                  | 58.22            | -42.55                   |
| 4                           | 13.667          | 4.43 QP                 | 50.47          | -46.04      | 1.00               | 187                  | 46.99            | -42.56                   |
| 5                           | 13.771          | 1.20 QP                 | 40.51          | -39.31      | 1.00               | 186                  | 43.77            | -42.57                   |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.  
Distance factor@3 m =  $40 \cdot \log(3/30) = -40$  dB




|                 |                     |                               |                       |
|-----------------|---------------------|-------------------------------|-----------------------|
| Frequency Range | 13.11MHz ~ 14.01MHz | Detector Function & Bandwidth | Quasi-Peak (QP), 9kHz |
|-----------------|---------------------|-------------------------------|-----------------------|

| Antenna Polarity : Perpendicular |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | 13.348          | -1.23 QP                | 40.51          | -41.74      | 1.00               | 264                  | 41.29            | -42.52                   |
| 2                                | 13.454          | 1.10 QP                 | 50.47          | -49.37      | 1.00               | 262                  | 43.64            | -42.54                   |
| 3                                | *13.560         | 12.69 QP                | 84.00          | -71.31      | 1.00               | 261                  | 55.24            | -42.55                   |
| 4                                | 13.665          | 0.59 QP                 | 50.47          | -49.88      | 1.00               | 260                  | 43.15            | -42.56                   |
| 5                                | 13.771          | -1.63 QP                | 40.51          | -42.14      | 1.00               | 254                  | 40.94            | -42.57                   |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.  
Distance factor@3 m =  $40 \cdot \log(3/30) = -40$  dB




|                 |                     |                               |                       |
|-----------------|---------------------|-------------------------------|-----------------------|
| Frequency Range | 13.11MHz ~ 14.01MHz | Detector Function & Bandwidth | Quasi-Peak (QP), 9kHz |
|-----------------|---------------------|-------------------------------|-----------------------|

| Antenna Polarity : Ground-parallel |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | 13.358          | 5.68 QP                 | 40.51          | -34.83      | 1.00               | 199                  | 48.20            | -42.52                   |
| 2                                  | 13.421          | 6.97 QP                 | 50.47          | -43.50      | 1.00               | 144                  | 49.50            | -42.53                   |
| 3                                  | *13.560         | 11.18 QP                | 84.00          | -72.82      | 1.00               | 167                  | 53.73            | -42.55                   |
| 4                                  | 13.663          | 4.63 QP                 | 50.47          | -45.84      | 1.00               | 300                  | 47.19            | -42.56                   |
| 5                                  | 13.764          | 2.37 QP                 | 40.51          | -38.14      | 1.00               | 72                   | 44.94            | -42.57                   |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.  
Distance factor@3 m =  $40 \cdot \log(3/30) = -40$  dB




|                 |               |                               |                                 |
|-----------------|---------------|-------------------------------|---------------------------------|
| Frequency Range | 9kHz ~ 150kHz | Detector Function & Bandwidth | Peak (PK) / Average (AV), 200Hz |
|-----------------|---------------|-------------------------------|---------------------------------|

| Antenna Polarity : Parallel |                 |                         |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | 0.009           | 18.41 PK                | 68.52          | -50.11      | 1.00               | 70                   | 60.84            | -42.43                   |
| 2                           | 0.009           | 15.60 AV                | 48.52          | -32.92      | 1.00               | 70                   | 58.03            | -42.43                   |
| 3                           | 0.016           | 11.19 PK                | 63.52          | -52.33      | 1.00               | 167                  | 57.27            | -46.08                   |
| 4                           | 0.016           | 8.94 AV                 | 43.52          | -34.58      | 1.00               | 167                  | 55.02            | -46.08                   |
| 5                           | 0.034           | -0.82 PK                | 56.97          | -57.79      | 1.00               | 274                  | 51.41            | -52.23                   |
| 6                           | 0.034           | -2.92 AV                | 36.97          | -39.89      | 1.00               | 274                  | 49.31            | -52.23                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.  
Distance factor@3 m =  $40 \cdot \log(3/300) = -80$  dB




|                 |               |                               |                                 |
|-----------------|---------------|-------------------------------|---------------------------------|
| Frequency Range | 9kHz ~ 150kHz | Detector Function & Bandwidth | Peak (PK) / Average (AV), 200Hz |
|-----------------|---------------|-------------------------------|---------------------------------|

| Antenna Polarity : Perpendicular |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | 0.010           | 16.34 PK                | 67.60          | -51.26      | 1.00               | 250                  | 60.21            | -43.87                   |
| 2                                | 0.010           | 13.60 AV                | 47.60          | -34.00      | 1.00               | 250                  | 57.47            | -43.87                   |
| 3                                | 0.019           | 10.60 PK                | 62.03          | -51.43      | 1.00               | 37                   | 57.80            | -47.20                   |
| 4                                | 0.019           | 8.24 AV                 | 42.03          | -33.79      | 1.00               | 37                   | 55.44            | -47.20                   |
| 5                                | 0.036           | -1.09 PK                | 56.47          | -57.56      | 1.00               | 57                   | 51.62            | -52.71                   |
| 6                                | 0.036           | -3.32 AV                | 36.47          | -39.79      | 1.00               | 57                   | 49.39            | -52.71                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.  
Distance factor@3 m =  $40 \cdot \log(3/300) = -80$  dB




|                 |               |                               |                                 |
|-----------------|---------------|-------------------------------|---------------------------------|
| Frequency Range | 9kHz ~ 150kHz | Detector Function & Bandwidth | Peak (PK) / Average (AV), 200Hz |
|-----------------|---------------|-------------------------------|---------------------------------|

| Antenna Polarity : Ground-parallel |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | 0.012           | 16.43 PK                | 66.02          | -49.59      | 1.00               | 57                   | 61.04            | -44.61                   |
| 2                                  | 0.012           | 13.80 AV                | 46.02          | -32.22      | 1.00               | 57                   | 58.41            | -44.61                   |
| 3                                  | 0.021           | 8.24 PK                 | 61.16          | -52.92      | 1.00               | 354                  | 56.17            | -47.93                   |
| 4                                  | 0.021           | 6.01 AV                 | 41.16          | -35.15      | 1.00               | 354                  | 53.94            | -47.93                   |
| 5                                  | 0.032           | 0.41 PK                 | 57.50          | -57.09      | 1.00               | 259                  | 52.15            | -51.74                   |
| 6                                  | 0.032           | -1.90 AV                | 37.50          | -39.40      | 1.00               | 259                  | 49.84            | -51.74                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.  
Distance factor@3 m =  $40 \cdot \log(3/300) = -80$  dB




|                 |                 |                               |                                |
|-----------------|-----------------|-------------------------------|--------------------------------|
| Frequency Range | 150kHz ~ 490kHz | Detector Function & Bandwidth | Peak (PK) / Average (AV), 9kHz |
|-----------------|-----------------|-------------------------------|--------------------------------|

| Antenna Polarity : Parallel |                 |                         |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | 0.155           | -21.37 PK               | 43.80          | -65.17      | 1.00               | 344                  | 44.45            | -65.82                   |
| 2                           | 0.155           | -23.57 AV               | 23.80          | -47.37      | 1.00               | 344                  | 42.25            | -65.82                   |
| 3                           | 0.189           | -25.35 PK               | 42.07          | -67.42      | 1.00               | 259                  | 41.93            | -67.28                   |
| 4                           | 0.189           | -28.07 AV               | 22.07          | -50.14      | 1.00               | 259                  | 39.21            | -67.28                   |
| 5                           | 0.269           | -33.31 PK               | 39.01          | -72.32      | 1.00               | 111                  | 37.25            | -70.56                   |
| 6                           | 0.269           | -35.79 AV               | 19.01          | -54.80      | 1.00               | 111                  | 34.77            | -70.56                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.  
Distance factor@3 m =  $40 \cdot \log(3/300) = -80$  dB




|                 |                 |                               |                                |
|-----------------|-----------------|-------------------------------|--------------------------------|
| Frequency Range | 150kHz ~ 490kHz | Detector Function & Bandwidth | Peak (PK) / Average (AV), 9kHz |
|-----------------|-----------------|-------------------------------|--------------------------------|

| Antenna Polarity : Perpendicular |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | 0.175           | -22.63 PK               | 42.74          | -65.37      | 1.00               | 57                   | 44.05            | -66.68                   |
| 2                                | 0.175           | -24.77 AV               | 22.74          | -47.51      | 1.00               | 57                   | 41.91            | -66.68                   |
| 3                                | 0.210           | -25.96 PK               | 41.16          | -67.12      | 1.00               | 76                   | 42.20            | -68.16                   |
| 4                                | 0.210           | -28.15 AV               | 21.16          | -49.31      | 1.00               | 76                   | 40.01            | -68.16                   |
| 5                                | 0.268           | -33.21 PK               | 39.04          | -72.25      | 1.00               | 111                  | 37.31            | -70.52                   |
| 6                                | 0.268           | -35.46 AV               | 19.04          | -54.50      | 1.00               | 111                  | 35.06            | -70.52                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.  
Distance factor@3 m =  $40 \cdot \log(3/300) = -80$  dB




|                 |                 |                               |                                |
|-----------------|-----------------|-------------------------------|--------------------------------|
| Frequency Range | 150kHz ~ 490kHz | Detector Function & Bandwidth | Peak (PK) / Average (AV), 9kHz |
|-----------------|-----------------|-------------------------------|--------------------------------|

| Antenna Polarity : Ground-parallel |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | 0.152           | -21.54 PK               | 43.96          | -65.50      | 1.00               | 321                  | 44.15            | -65.69                   |
| 2                                  | 0.152           | -23.89 AV               | 23.96          | -47.85      | 1.00               | 321                  | 41.80            | -65.69                   |
| 3                                  | 0.184           | -24.97 PK               | 42.31          | -67.28      | 1.00               | 255                  | 42.11            | -67.08                   |
| 4                                  | 0.184           | -27.05 AV               | 22.31          | -49.36      | 1.00               | 255                  | 40.03            | -67.08                   |
| 5                                  | 0.247           | -31.84 PK               | 39.75          | -71.59      | 1.00               | 90                   | 37.83            | -69.67                   |
| 6                                  | 0.247           | -34.11 AV               | 19.75          | -53.86      | 1.00               | 90                   | 35.56            | -69.67                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.  
Distance factor@3 m =  $40 \cdot \log(3/300) = -80$  dB




|                 |                |                               |                       |
|-----------------|----------------|-------------------------------|-----------------------|
| Frequency Range | 490kHz ~ 30MHz | Detector Function & Bandwidth | Quasi-Peak (QP), 9kHz |
|-----------------|----------------|-------------------------------|-----------------------|

| Antenna Polarity : Parallel |                 |                         |                |             |                    |                      |                  |                          |
|-----------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                          | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                           | 0.652           | -2.09 QP                | 31.32          | -33.41      | 1.00               | 112                  | 34.21            | -36.30                   |
| 2                           | 1.254           | -4.70 QP                | 25.63          | -30.33      | 1.00               | 85                   | 34.79            | -39.49                   |
| 3                           | 2.221           | -3.56 QP                | 29.54          | -33.10      | 1.00               | 74                   | 37.85            | -41.41                   |
| 4                           | 3.134           | -8.49 QP                | 29.54          | -38.03      | 1.00               | 104                  | 34.57            | -43.06                   |
| 5                           | 10.121          | -12.42 QP               | 29.54          | -41.96      | 1.00               | 1                    | 29.74            | -42.16                   |
| 6                           | 21.663          | -2.01 QP                | 29.54          | -31.55      | 1.00               | 307                  | 40.90            | -42.91                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.  
Distance factor@3 m =  $40 \cdot \log(3/30) = -40$  dB




|                 |                |                               |                       |
|-----------------|----------------|-------------------------------|-----------------------|
| Frequency Range | 490kHz ~ 30MHz | Detector Function & Bandwidth | Quasi-Peak (QP), 9kHz |
|-----------------|----------------|-------------------------------|-----------------------|

| Antenna Polarity : Perpendicular |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                               | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                | 0.705           | -2.06 QP                | 30.64          | -32.70      | 1.00               | 104                  | 34.65            | -36.71                   |
| 2                                | 1.357           | -8.68 QP                | 24.94          | -33.62      | 1.00               | 164                  | 31.01            | -39.69                   |
| 3                                | 1.988           | -9.72 QP                | 29.54          | -39.26      | 1.00               | 85                   | 31.21            | -40.93                   |
| 4                                | 2.883           | -12.65 QP               | 29.54          | -42.19      | 1.00               | 133                  | 30.13            | -42.78                   |
| 5                                | 11.581          | -9.43 QP                | 29.54          | -38.97      | 1.00               | 220                  | 32.90            | -42.33                   |
| 6                                | 25.876          | 5.26 QP                 | 29.54          | -24.28      | 1.00               | 286                  | 47.44            | -42.18                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.  
Distance factor@3 m =  $40 \cdot \log(3/30) = -40$  dB




|                 |                |                               |                       |
|-----------------|----------------|-------------------------------|-----------------------|
| Frequency Range | 490kHz ~ 30MHz | Detector Function & Bandwidth | Quasi-Peak (QP), 9kHz |
|-----------------|----------------|-------------------------------|-----------------------|

| Antenna Polarity : Ground-parallel |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                  | 0.569           | 4.49 QP                 | 32.50          | -28.01      | 1.00               | 252                  | 40.14            | -35.65                   |
| 2                                  | 0.745           | -1.34 QP                | 30.16          | -31.50      | 1.00               | 81                   | 35.68            | -37.02                   |
| 3                                  | 1.320           | -9.87 QP                | 25.18          | -35.05      | 1.00               | 59                   | 29.75            | -39.62                   |
| 4                                  | 3.020           | -13.25 QP               | 29.54          | -42.79      | 1.00               | 227                  | 29.79            | -43.04                   |
| 5                                  | 7.671           | -13.45 QP               | 29.54          | -42.99      | 1.00               | 130                  | 29.38            | -42.83                   |
| 6                                  | 25.877          | 4.46 QP                 | 29.54          | -25.08      | 1.00               | 255                  | 46.64            | -42.18                   |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.  
Distance factor@3 m =  $40 \cdot \log(3/30) = -40$  dB




|                 |              |                               |                         |
|-----------------|--------------|-------------------------------|-------------------------|
| Frequency Range | 30MHz ~ 1GHz | Detector Function & Bandwidth | Quasi-Peak (QP), 120kHz |
|-----------------|--------------|-------------------------------|-------------------------|

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 108.47          | 36.2 QP                 | 43.5           | -7.3        | 3.00 H             | 356                  | 52.2             | -16.0                    |
| 2                                                    | <b>149.16</b>   | <b>42.6 QP</b>          | <b>43.5</b>    | <b>-0.9</b> | <b>2.00 H</b>      | <b>151</b>           | <b>55.7</b>      | <b>-13.1</b>             |
| 3                                                    | 216.97          | 34.7 QP                 | 46.0           | -11.3       | 1.50 H             | 172                  | 51.2             | -16.5                    |
| 4                                                    | 244.08          | 35.5 QP                 | 46.0           | -10.5       | 1.00 H             | 45                   | 50.0             | -14.5                    |
| 5                                                    | 302.45          | 36.1 QP                 | 46.0           | -9.9        | 1.00 H             | 81                   | 48.4             | -12.3                    |
| 6                                                    | 610.21          | 34.0 QP                 | 46.0           | -12.0       | 1.50 H             | 116                  | 39.0             | -5.0                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.




|                 |              |                               |                         |
|-----------------|--------------|-------------------------------|-------------------------|
| Frequency Range | 30MHz ~ 1GHz | Detector Function & Bandwidth | Quasi-Peak (QP), 120kHz |
|-----------------|--------------|-------------------------------|-------------------------|

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 30.07           | 35.5 QP                 | 40.0           | -4.5        | 1.00 V             | 60                   | 49.3             | -13.8                    |
| 2                                                  | 149.16          | 39.3 QP                 | 43.5           | -4.2        | 2.00 V             | 270                  | 52.4             | -13.1                    |
| 3                                                  | 404.90          | 30.5 QP                 | 46.0           | -15.5       | 1.50 V             | 10                   | 40.5             | -10.0                    |
| 4                                                  | 610.21          | 33.1 QP                 | 46.0           | -12.9       | 1.00 V             | 51                   | 38.1             | -5.0                     |
| 5                                                  | 664.43          | 32.5 QP                 | 46.0           | -13.5       | 1.00 V             | 62                   | 36.8             | -4.3                     |
| 6                                                  | 840.70          | 32.5 QP                 | 46.0           | -13.5       | 2.00 V             | 8                    | 34.6             | -2.1                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

- Note: 1. The lower limit shall apply at the transition frequencies.  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.  
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 Test Instruments

| Description & Manufacturer | Model No.           | Serial No. | Calibrated Date | Calibrated Until |
|----------------------------|---------------------|------------|-----------------|------------------|
| 50 ohm terminal resistance | N/A                 | EMC-04     | 2023/10/20      | 2024/10/19       |
| EMI Test Receiver R&S      | ESCS 30             | 100375     | 2023/5/17       | 2024/5/16        |
| Fixed Attenuator STI       | STI02-2200-10       | 005        | 2023/7/1        | 2024/6/30        |
| LISN R&S                   | ENV216              | 100071     | 2022/10/26      | 2023/10/25       |
| RF Coaxial Cable JYEBAO    | 5D-FB               | COCCAB-001 | 2023/7/1        | 2024/6/30        |
| Software BVADT             | BVADT_Cond_V7.3.7.4 | N/A        | N/A             | N/A              |
| Software BVADT             | BVADT_Cond_V7.3.7.4 | NA         | NA              | NA               |

#### Note:

- The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- The test was performed in Conduction 1.
- Tested Date: 2023/10/25

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note: 1.**Support units were connected to second LISN.

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.


#### 4.2.7 Test Results

|                        |                |                                                     |                                      |
|------------------------|----------------|-----------------------------------------------------|--------------------------------------|
| <b>Frequency Range</b> | 150kHz ~ 30MHz | <b>Detector Function &amp; Resolution Bandwidth</b> | Quasi-Peak (QP) / Average (AV), 9kHz |
|------------------------|----------------|-----------------------------------------------------|--------------------------------------|

| Phase Of Power : Line (L) |                 |                        |                      |       |                       |       |              |       |             |        |
|---------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                           |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                         | 0.15391         | 9.93                   | 38.95                | 22.72 | 48.88                 | 32.65 | 65.79        | 55.79 | -16.91      | -23.14 |
| 2                         | 0.17344         | 9.93                   | 35.24                | 18.61 | 45.17                 | 28.54 | 64.79        | 54.79 | -19.62      | -26.25 |
| 3                         | 0.57969         | 9.95                   | 25.69                | 18.68 | 35.64                 | 28.63 | 56.00        | 46.00 | -20.36      | -17.37 |
| 4                         | 3.73828         | 10.10                  | 23.60                | 15.99 | 33.70                 | 26.09 | 56.00        | 46.00 | -22.30      | -19.91 |
| 5                         | 13.56250        | 10.70                  | 29.84                | 27.19 | 40.54                 | 37.89 | 60.00        | 50.00 | -19.46      | -12.11 |
| 6                         | 29.69922        | 11.53                  | 29.89                | 29.63 | 41.42                 | 41.16 | 60.00        | 50.00 | -18.58      | -8.84  |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
|-----------------|----------------|------------------------------------------|--------------------------------------|

| Phase Of Power : Neutral (N) |                 |                        |                      |       |                       |       |              |       |             |        |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                              |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                            | 0.15000         | 10.00                  | 40.45                | 24.11 | 50.45                 | 34.11 | 66.00        | 56.00 | -15.55      | -21.89 |
| 2                            | 0.58750         | 10.01                  | 26.32                | 19.08 | 36.33                 | 29.09 | 56.00        | 46.00 | -19.67      | -16.91 |
| 3                            | 2.93750         | 10.10                  | 20.63                | 15.27 | 30.73                 | 25.37 | 56.00        | 46.00 | -25.27      | -20.63 |
| 4                            | 12.02344        | 10.50                  | 30.86                | 24.54 | 41.36                 | 35.04 | 60.00        | 50.00 | -18.64      | -14.96 |
| 5                            | 21.15234        | 10.91                  | 19.87                | 15.21 | 30.78                 | 26.12 | 60.00        | 50.00 | -29.22      | -23.88 |
| 6                            | 29.71484        | 11.10                  | 24.76                | 18.20 | 35.86                 | 29.30 | 60.00        | 50.00 | -24.14      | -20.70 |

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 Frequency Stability

#### 4.3.1 Limits of Frequency Stability Measurement

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of 0 degrees to 70 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

Same as Item 4.1.6.

#### 4.3.7 Test Result

| Frequency Stability Versus Temp. |                          |                       |                    |                       |                    |                       |                    |                       |                    |
|----------------------------------|--------------------------|-----------------------|--------------------|-----------------------|--------------------|-----------------------|--------------------|-----------------------|--------------------|
| Temp.<br>(°C)                    | Power<br>Supply<br>(Vdc) | 0 Minute              |                    | 2 Minutes             |                    | 5 Minutes             |                    | 10 Minutes            |                    |
|                                  |                          | Measured<br>Frequency | Frequency<br>Drift | Measured<br>Frequency | Frequency<br>Drift | Measured<br>Frequency | Frequency<br>Drift | Measured<br>Frequency | Frequency<br>Drift |
|                                  |                          | (MHz)                 | %                  | (MHz)                 | %                  | (MHz)                 | %                  | (MHz)                 | %                  |
| 70                               | 5                        | 13.55996              | -0.00029           | 13.55996              | -0.00029           | 13.55995              | -0.00037           | 13.55996              | -0.00029           |
| 60                               | 5                        | 13.55993              | -0.00052           | 13.55993              | -0.00052           | 13.55995              | -0.00037           | 13.55993              | -0.00052           |
| 50                               | 5                        | 13.56005              | 0.00037            | 13.56003              | 0.00022            | 13.56005              | 0.00037            | 13.56005              | 0.00037            |
| 40                               | 5                        | 13.56002              | 0.00015            | 13.56002              | 0.00015            | 13.56                 | 0.00000            | 13.56001              | 0.00007            |
| 30                               | 5                        | 13.56002              | 0.00015            | 13.56002              | 0.00015            | 13.56004              | 0.00029            | 13.56004              | 0.00029            |
| 20                               | 5                        | 13.55994              | -0.00044           | 13.55994              | -0.00044           | 13.55992              | -0.00059           | 13.55992              | -0.00059           |
| 10                               | 5                        | 13.55999              | -0.00007           | 13.55999              | -0.00007           | 13.56                 | 0.00000            | 13.56                 | 0.00000            |
| 0                                | 5                        | 13.56005              | 0.00037            | 13.56005              | 0.00037            | 13.56003              | 0.00022            | 13.56003              | 0.00022            |


| Frequency Stability Versus Voltage |                          |                       |                    |                       |                    |                       |                    |                       |                    |
|------------------------------------|--------------------------|-----------------------|--------------------|-----------------------|--------------------|-----------------------|--------------------|-----------------------|--------------------|
| Temp.<br>(°C)                      | Power<br>Supply<br>(Vdc) | 0 Minute              |                    | 2 Minutes             |                    | 5 Minutes             |                    | 10 Minutes            |                    |
|                                    |                          | Measured<br>Frequency | Frequency<br>Drift | Measured<br>Frequency | Frequency<br>Drift | Measured<br>Frequency | Frequency<br>Drift | Measured<br>Frequency | Frequency<br>Drift |
|                                    |                          | (MHz)                 | %                  | (MHz)                 | %                  | (MHz)                 | %                  | (MHz)                 | %                  |
| 20                                 | 5.75                     | 13.56002              | 0.00015            | 13.56002              | 0.00015            | 13.56                 | 0.00000            | 13.56001              | 0.00007            |
|                                    | 5                        | 13.56002              | 0.00015            | 13.56002              | 0.00015            | 13.56                 | 0.00000            | 13.56001              | 0.00007            |
|                                    | 4.25                     | 13.56002              | 0.00015            | 13.56002              | 0.00015            | 13.56                 | 0.00000            | 13.56001              | 0.00007            |

#### 4.4 20dB Bandwidth

##### 4.4.1 Limits of 20dB BANDWIDTH Measurement

The 20dB bandwidth shall be specified in operating frequency band.

##### 4.4.2 Test Setup



##### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

##### 4.4.4 Test Procedures

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 10Hz RBW and 30Hz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

##### 4.4.5 Deviation from Test Standard

No deviation.

##### 4.4.6 EUT Operating Conditions

Same as Item 4.1.6.



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---