

CERTIFICATION TEST REPORT

Report Number. : S-4791655852-E7V1

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SC-54F

FCC ID : A3LSMA366JPN

EUT Description : GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax
and NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:
2025-04-01

Prepared by:
UL KOREA LTD.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL KOREA LTD. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433

Revision History

Rev.	Issue Date	Revisions	Presented By
V1	2025-04-01	Initial issue	Myeongjun Kwon

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. DECISION RULES AND MEASUREMENT UNCERTAINTY	7
4.1. METROLOGICAL TRACEABILITY	7
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY.....	7
4.4. DECISION RULES.....	7
5. EQUIPMENT UNDER TEST	8
5.1. EUT DESCRIPTION	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.4. WORST-CASE CONFIGURATION AND MODE.....	10
5.5. DESCRIPTION OF TEST SETUP.....	11
6. TEST AND MEASUREMENT EQUIPMENT	13
7. TEST RESULTS SUMMARY	14
8. MEASUREMENT METHODS	15
9. ANTENNA PORT TEST RESULTS	16
9.1. ON TIME AND DUTY CYCLE.....	16
9.2. 20 dB BANDWIDTH.....	17
9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	17
9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	17
9.3. HOPPING FREQUENCY SEPARATION	20
9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	21
9.3.1. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	21
9.4. NUMBER OF HOPPING CHANNELS.....	22
9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	23
9.4.1. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	25
9.4.2. AVERAGE TIME OF OCCUPANCY	27
9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	28
9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	32
9.5. OUTPUT POWER.....	36
9.5.1. BASIC DATA RATE GFSK MODULATION.....	36
9.5.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION	36

9.5.3. ENHANCED DATA RATE 8PSK MODULATION	36
9.5.4. OUTPUT POWER PLOTS	37
9.6. AVERAGE POWER	40
9.6.1. BASIC DATA RATE GFSK MODULATION	40
9.6.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION	40
9.6.3. ENHANCED DATA RATE 8PSK MODULATION	40
9.7. CONDUCTED SPURIOUS EMISSIONS	41
9.7.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	42
9.7.1. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION	46
9.7.2. SPURIOUS EMISSIONS, NON-HOPPING – ANT1	46
9.8. TRANSMITTER ABOVE 1 GHz	52
9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	52
9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION	56
9.9. WORST CASE BELOW 1 GHz	60
10. AC POWER LINE CONDUCTED EMISSIONS	61
10.1. AC Power Line	62

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax and NFC.

MODEL NUMBER: SC-54F

SERIAL NUMBER: R3CXB0VFYTR, R3CXB0VFX0A, R3CXB0VG57H (CONDUCTED); R3CXB0VFYSZ, R3CXB0VFYFL, R3CXB0VFWST (RADIATED)

DATE TESTED: 2025-02-11 – 2025-04-01

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
47 CFR Part 15 Subpart C	Complies

UL KOREA LTD. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL KOREA LTD. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL KOREA LTD. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL KOREA LTD. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL KOREA LTD. By:



Seokhwan Hong
Suwon Lab Engineer
UL KOREA LTD.

Tested By:



Myeongjun Kwon
Suwon Lab Engineer
UL KOREA LTD.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC 47 CFR Part 2.
2. FCC 47 CFR Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2020.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1(3m semi-anechoic chamber)
☐	Chamber 2(3m semi-anechoic chamber)
☒	Chamber 3(3m semi-anechoic chamber)
☐	Chamber 4(3m Full-anechoic chamber)
☐	Chamber 5(3m Full-anechoic chamber)

UL KOREA LTD. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

$$\begin{aligned} \text{AC Corrected Reading (dBuV)} &= \text{Measured Voltage (dBuV)} + \text{Extension Cord} \\ &\text{Loss (dB)} + \text{Cable Loss (dB)} \\ 44.72 \text{ dBuV} &= 34.72 \text{ dBuV} + 9.9 \text{ dB} + 0.1 \text{ dB} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
RF Output Power	0.69 dB
Time	0.60 %
Occupied Bandwidth	0.04 %
Hopping Frequency Separation	2.9×10^3 Hz
Frequency Range	2.5×10^3 Hz
Conducted Spurious Emissions	1.40 dB
Conducted Disturbance, 0.15 to 30 MHz	1.84 dB
Radiated Disturbance, 9 kHz to 30 MHz	2.41 dB
Radiated Disturbance, 30 MHz to 1 GHz	3.69 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.18 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.07 dB

Uncertainty figures are valid to a confidence level of 95%.

4.4. DECISION RULES

Decision rule for statement(s) of conformity is based on Clause 4.4.3 in IEC Guide 115:2023.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a GSM/WCDMA/LTE 5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax and NFC . This test report addresses the DSS(Bluetooth) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak and average conducted output power as follows:

Antenna 1

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 ~ 2 480	Basic GFSK	Peak	12.69	18.58
		Average	12.35	17.17
	Enhanced Pi/4-DPSK	Peak	13.54	22.59
		Average	10.77	11.93
	Enhanced 8PSK	Peak	14.07	25.53
		Average	10.89	12.27

Antenna 2

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 ~ 2 480	Basic GFSK	Peak	11.00	12.59
		Average	10.52	11.28
	Enhanced Pi/4-DPSK	Peak	11.70	14.79
		Average	9.06	8.06
	Enhanced 8PSK	Peak	12.04	16.00
		Average	9.09	8.11

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The internal antenna was Permanently attached.
Therefore, this E.U.T Complies with the requirement of §15.203.**

The radio utilizes a internal antenna, with a maximum gain of:

Frequency Band [MHz]	ANT1 Gain [dBi]	ANT2 Gain [dBi]
DSS 2400 – 2483.5	-2.65	-3.25

“BT/WIFI #1_2.4GHz (SUB4)” and “BT/WIFI #2_2.4GHz (SUB6)” as indicated in antenna specification are written as ANT1 and ANT2 in this report.

5.4. WORST-CASE CONFIGURATION AND MODE

The fundamentals of the EUT were investigated in three orthogonal orientations X, Y and Z. It was determined that below table's orientation was the worst-case orientation.

ANT1	ANT2
X	X

For conducted power test, Diversity was verified and reported. Diversity mode test was performed on each SISO antenna with iPA mode.

Radiated and power line conducted tests were performed with EUT connected to AC power adapter as the worst-case configuration. Radiated harmonics spurious 1~18 GHz Low/Mid/High channels, 18-26GHz were performed with the EUT set at the Diversity mode. Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

For Radiated band-edge and spurious test, tests were performed on each antenna with Diversity mode.

All radiated and power line conducted tests were performed attached with travel adapter for the worst-case condition mode.

GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA800	R37XBMJF8FBDKA	N/A
Data Cable	SAMSUNG	EP-DN980B	N/A	N/A


I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A


TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
Test software enable BT communications.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB 9163	750	2026-07-30
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	2025-09-07
Antenna, Horn, 18 GHz	ETS	3117	00168724	2026-07-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	2026-07-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	2026-07-23
Preamplifier	ETS	3116C-PA	00168841	2025-07-25
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	80108-0004	N/A
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	110367-0003	N/A
Preamplifier, 1000 MHz	Sonoma	310N	341282	2025-07-22
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	2025-07-23
Preamplifier, 18 GHz	B&Z Technologies, LLC	BZR-01001800-231040-182020	28451	2025-07-22
Preamplifier, 18 GHz	B&Z Technologies, LLC	BZR-01001800-231040-181515	23576	2025-07-25
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	2025-07-24
Spectrum Analyzer, 44 GHz	KEYSIGHT	N9040B	MY60080268	2025-12-24
RF Switching Unit	TA Engineering	TA-018S-16	SW-1	N/A
Average Power Sensor	Agilent / HP	U2000A	MY54270007	2025-07-23
Average Power Sensor	Agilent / HP	U2000A	MY54260010	2025-07-23
Bluetooth Tester	TESCOM	MTP300A	MTP300A010266	2025-07-23
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	2025-07-24
Power Splitter	MINI-CIRCUITS	WA1534	UL003	2026-01-03
Power Splitter	MINI-CIRCUITS	WA1534	UL004	2026-01-03
Attenuator	PASTERNAK	PE7087-10	A009	2025-07-23
Attenuator	PASTERNAK	PE7087-10	A001	2025-07-23
EMI Test Receive, 40 GHz	R&S	ESU40	100439	2025-07-23
EMI Test Receive, 40 GHz	R&S	ESU40	100457	2025-07-22
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	2025-07-22
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	2025-07-22
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	2025-07-22
LISN	R&S	ENV216	101836	2025-07-22
Termination	WEINSCHEL	M1406A	T09	2025-07-23
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247(d)	Band Edge / Conducted Spurious Emission	-20 dBc	Conducted	Complies
15.247 (b)(1)	TX conducted output power	< 21 dBm		Complies
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		Complies
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Complies
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 0.4 s		Complies
15.207(a)	AC Power Line conducted emissions	Section 11	Power Line conducted	Complies
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	Complies

8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW: ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION: ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS: ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY: ANSI C63.10, Section 7.8.4

OUTPUT POWER: ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.7

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 7.8.8

Out-of-band EMISSIONS IN RESTRICTED BANDS: ANSI C63.10, Section 7.8.8

AC Power Line Conducted Emission: ANSI C63.10-2020, Section 6.2.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only.

PROCEDURE

ANSI C63.10, Section 11.6: Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS



Mode	On time [msec]	Period [msec]	Duty Cycle X [linear]	Duty Cycle [%]	1/T Minimum VBW [kHz]
GFSK	2.888	3.751	0.7699	76.99	0.35
8DPSK	2.890	3.751	0.7705	77.05	0.35

Note: Since ANT1 and 2 have the same duty cycle, the duty cycle of ANT1 is reported in the table above.

9.2. 20 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. The sweep time is coupled.


RESULTS


9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

Antenna	Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
ANT1	0	2 402	0.945	0.839
	39	2 441	0.943	0.838
	78	2 480	0.935	0.840
ANT2	0	2 402	0.942	0.844
	39	2 441	0.938	0.842
	78	2 480	0.942	0.835
Worst			0.935	0.835

9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

Antenna	Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
ANT1	0	2 402	1.325	1.187
	39	2 441	1.325	1.188
	78	2 480	1.315	1.187
ANT2	0	2 402	1.325	1.186
	39	2 441	1.335	1.200
	78	2 480	1.311	1.192
Worst			1.311	1.186





9.3. HOPPING FREQUENCY SEPARATION

LIMITS

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. The VBW is set to $\text{VBW} \geq \text{RBW}$. The sweep time is coupled.

RESULTS

9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



9.3.1. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



9.4. NUMBER OF HOPPING CHANNELS

LIMITS

FCC §15.247 (a)(1)(iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. The analyzer is set to Max Hold.

RESULTS


Normal Mode: All Channels Observed


9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION





9.4.1. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION





9.4.2. AVERAGE TIME OF OCCUPANCY

LIMITS

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{pulse width}$.


RESULTS

9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal ANT1					
DH1	0.380	32	0.122	0.4	-0.278
DH3	1.637	16	0.262	0.4	-0.138
DH5	2.887	10	0.289	0.4	-0.111
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH ANT1					
DH1	0.380	8	0.030	0.4	-0.370
DH3	1.637	4	0.065	0.4	-0.335
DH5	2.887	3	0.087	0.4	-0.313




DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal ANT2					
DH1	0.380	32	0.122	0.4	-0.278
DH3	1.637	18	0.295	0.4	-0.105
DH5	2.887	9	0.260	0.4	-0.140
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH ANT2					
DH1	0.380	8	0.030	0.4	-0.370
DH3	1.637	5	0.082	0.4	-0.318
DH5	2.887	2	0.058	0.4	-0.342




9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Normal ANT1					
DH1	0.387	32	0.124	0.4	-0.276
DH3	1.639	17	0.279	0.4	-0.187
DH5	2.892	8	0.231	0.4	-0.111
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK AFH ANT1					
DH1	0.387	8	0.031	0.4	-0.369
DH3	1.639	4	0.066	0.4	-0.334
DH5	2.892	2	0.058	0.4	-0.342



DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Normal ANT2					
DH1	0.388	32	0.124	0.4	-0.276
DH3	1.639	13	0.213	0.4	-0.187
DH5	2.892	10	0.289	0.4	-0.111
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK AFH ANT2					
DH1	0.388	8	0.031	0.4	-0.369
DH3	1.639	3	0.049	0.4	-0.351
DH5	2.892	3	0.087	0.4	-0.313



9.5. OUTPUT POWER

LIMITS

§15.247 (b) (1)

The peak conducted output power limit is 0.125 W (21 dBm) since Bluetooth AFH mode can be used at least 20 non-overlapping hopping channels.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

9.5.1. BASIC DATA RATE GFSK MODULATION

Antenna	Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
ANT1	0	2 402	12.030	21.00	-8.970
	39	2 441	12.690		-8.310
	78	2 480	10.840		-10.160
ANT2	0	2 402	10.290		-10.710
	39	2 441	11.000		-10.000
	78	2 480	8.150		-12.850
Worst			12.690		-8.310

9.5.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION


Antenna	Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
ANT1	0	2 402	12.850	21.00	-8.150
	39	2 441	13.540		-7.460
	78	2 480	11.670		-9.330
ANT2	0	2 402	10.980		-10.020
	39	2 441	11.700		-9.300
	78	2 480	8.910		-12.090
Worst			13.540		-7.460


9.5.3. ENHANCED DATA RATE 8PSK MODULATION


Antenna	Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
ANT1	0	2 402	13.210	21.00	-7.790
	39	2 441	14.070		-6.930
	78	2 480	12.160		-8.840
ANT2	0	2 402	11.340		-9.660
	39	2 441	12.040		-8.960
	78	2 480	9.280		-11.720
Worst			14.070		-6.930

9.5.4. OUTPUT POWER PLOTS

PEAK OUTPUT POWER







9.6. AVERAGE POWER

LIMITS

None; for reporting purposes only

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter.
The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

9.6.1. BASIC DATA RATE GFSK MODULATION

Antenna	Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
ANT1	0	2 402	11.746	14.949
	39	2 441	12.347	17.167
	78	2 480	10.459	11.115
ANT2	0	2 402	9.788	9.524
	39	2 441	10.523	11.280
	78	2 480	7.585	5.734

9.6.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION

Antenna	Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
ANT1	0	2 402	10.260	10.617
	39	2 441	10.765	11.926
	78	2 480	8.876	7.720
ANT2	0	2 402	8.325	6.799
	39	2 441	9.061	8.056
	78	2 480	6.112	4.085

9.6.3. ENHANCED DATA RATE 8PSK MODULATION

Antenna	Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
ANT1	0	2 402	10.193	10.454
	39	2 441	10.887	12.266
	78	2 480	9.006	7.955
ANT2	0	2 402	8.352	6.843
	39	2 441	9.090	8.109
	78	2 480	6.138	4.110

9.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The band-edges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

RESULTS


SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON – ANT1




SPURIOUS EMISSIONS, NON-HOPPING – ANT2




0 CHANNEL BANDEDGE




OUT-OF-BAND 0 CHANNEL



OUT-OF-BAND 39 CHANNEL




78 CHANNEL BANDEDGE



OUT-OF-BAND 78 CHANNEL


SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON – ANT2




9.7.1. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

9.7.2. SPURIOUS EMISSIONS, NON-HOPPING – ANT1

SPURIOUS EMISSIONS, NON-HOPPING – ANT1




0 CHANNEL BANDEDGE




OUT-OF-BAND 0 CHANNEL



78 CHANNEL BANDEDGE



OUT-OF-BAND 39 CHANNEL



OUT-OF-BAND 78 CHANNEL