

# RF EXPOSURE EVALUATION

## 1. TEST RESULT CERTIFICATION

<b>Applicant</b>	Midland Radio Corporation
<b>Address</b>	5900 Parretta Drive Kansas City, MO 64120-2134 USA
<b>manufacturer</b>	Midland Radio Corporation
<b>Address</b>	5900 Parretta Drive Kansas City, MO 64120-2134 USA
<b>Factory</b>	Shenzhen Allcomm Electronic Company Limited
<b>Address</b>	Block A, 101A/B, 201, 302,401 of Block B, No. 272 Guangtian Road, Tangxiayong , Yanluo Street, Baoan District, Shenzhen City, Guangdong Province, China
<b>Product Designation:</b>	Mobile GMRS Transceiver
<b>Brand Name:</b>	Midland
<b>Test Model:</b>	MXT105B
<b>FCC ID:</b>	MMAMXT105B
<b>Date of Test:</b>	May 10, 2021~Jul. 30, 2021

## 2. TECHNICAL INFORMATION

A major technical description of EUT is described as following:

<b>Operation Frequency</b>	GMRS: 462.5500MHz-462.7250MHz 462.5625MHz-462.7125MHz
<b>Modulation</b>	FM
<b>Antenna Designation</b>	Detachable
<b>Antenna type</b>	External antenna
<b>Output power</b>	5W
<b>Antenna gain</b>	1.5dBi
<b>Power Supply</b>	DC 12/24V

**Channel list:**

Channel. No	CH. Freq	Rated Power
1	462.5625	5W
2	462.5875	
3	462.6125	
4	<b>462.6375</b>	
5	462.6625	
6	462.6875	
7	462.7125	
8	462.5500	5W
9	462.5750	
10	462.6000	
11	462.6250	
12	<b>462.6500</b>	
13	462.6750	
14	462.7000	
15	462.7250	

### **3.RF EXPOSURE MEASUREMENT**

#### **3.1 INTRODUCTION**

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

The 1992 ANSI/IEEE standard (See Listed limit table) specifies a minimum separation distance of 20 cm for performing reliable field measurements to determine adherence to MPE limits.

If the minimum separation distance between a transmitter and nearby persons is more than 20 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance.

### 3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

#### LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

\*Note:

1. f= Frequency in MHz \* Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

### 3.3 CLASSIFICATION OF THE ASSESSMENT METHODS

According to user manual, The antenna of the product, under normal use condition is at least 42.8cm away from the body of the user. Warning statement to the user for keeping at least 42.8cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

$$S=PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

### 3.4 EUT OPERATION CONDITION

Make the EUT to transmit at Bottom channel, Middle channel and Top channel individually.

### 3.5 TEST RESULTS

Note: report the worst result in this part

Antenna Gain=1.5dBi (Numeric 1.41),  $\pi=3.141$

TEST Frequency (MHz)	Tune-up Tolerance (dBm)	Max tune-up (dBm)	Max tune-up (mW)	Power Density (mW/cm <sup>2</sup> )	Power Density Limit (mW/cm <sup>2</sup> )	Result (Pass/Fail)
462.6375	36.5±0.5	37	5011.87	0.30704614	0.308425	Pass

Note:

1. The output power is refer to **AGC09350210402FE10**.
2. According to the user manual, the minimum separate distance which used for MPE calculate is 42.8cm.