FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: 2BDY8-D115

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ²or S (minutes)				
0.3-3.0	614	1.63	(100)*	6				
3.0-30	1842 / f	4.89 / f	(900 / f)*	6				
30-300	61.4	0.163	1.0	6				
300-1500			F/300	6				
1500-100,000			5	6				

Note: *f* is frequency in MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30 30	
30-300	27.5	0.073	0.2		
300-1500			F/1500	30	
1500-100,000			1.0	30	

Note: f = frequency in MHz

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2	Result
2.4G WIFI	802.11n(H T20)&243 7	20±1	21	125.892 5	1.9907 (2.99dBi)	0.0499	1	Pass
5.2GWIFI	802.11n(H T40)& 5190	11±1	12	15.8489	2.9512 (4.7dBi)	0.009	1	Pass
5.8GWIFI	802.11n(H T20)& 5825	9±1	10	10	2.7353 (4.37dBi)	0.005	1	Pass