For example I the connected state of the connection, we observed present the IDM better noted to IDM desirable manual research, the opposition of the connection connection connection connection connection connection of the conne Disassembly steps
The MANS GUID Committee

Copes the lated lock seeks on the committee

Copes the lated lock seeks on the committee أبييا VIII. Service Support

Pyou encounter difficulties or product defeats in using the product, please central out afterwise for purchase platfore. We will take analysing on feedback, and analysing on the other this produce may placement of the product, the lad to be a family on a general control of the product. The lad out alone you appearance to the product placement of the placement of the product placement of the prod V. Lighting effect control 000 Gear stegle Beak Bullion programming: Enter programming mode, double-Box the corresponding Back Button to dear. ears to entity pering mode). On they carried the control is a seal deadly when the control is a mediate in the control is a mediate in the control is entitle or the control is a mediate in the control is a mediate parameter. As it is asset in the first control is in control in it is control in the control in control in control in control in the control in the control in co If Search the Education's samed "3C200" on the APP and idek to connect. Option call the consider from the bodier. L Vibration Function rot -To temperating enable through the Back Batton function: acade-up the 1990 button, the controller will visite strong above you to temporate enable or disable the function of the Barton inclusion. Residence and Aller Back Declaration temporarily enable or disable the temporarily enable or temporarily enable or disable temporarily enable VL APP collaboration (---) C) Freely press the \$MMAN,\$ better serie, and the ring of nature to the narroal connected state, indicate programming is complete. JC300 1-5-X 取り付け手順 MAI MAI ドンツールのためた: ントローラーの作品ロッドスイッチを知り替 - ウービルルに同じしてくだかい I. Section IX.よく賢問 (QA) 17 ボタンと (十分の上) ボタンを時間に押すと、コードの開始に、現れバードを開発してます。 17 ボタンと (十分の上) ボタンを時間に押すと、コードの開始に、現れバードを開発してます。 17 ボタンと (十分の下) ボタンを開発し戻すと、コードの開催に、薬剤バビードを開発するます。 II. Turboid Millio , 000 000 ワイヤレスコントローラー クイックスタートガイド を担すファドル、コントコータが回転倒すると、100 ボタ の機能を一切的に合物点には解放するとようできます。同様 記述 タランをがクラック。 エットローラが回転倒すると Da3 ボタンの機能を一切的に合併されば解放することがで また。 VI. APP操作案内 で、 協定網に付てコントローターの裏のもさいたくチェットだけ See and 分解学順 SMI ED =ンアールのために VII. 光電インジケータライト III. 振動機度の開発 **6** LCVS DN-1 663-BWLCG, MEMORIALOSER VIII. アフターサービスについて IV. マクロプログラミング機能 8 - 11 ボタンをお店が見るが - フーボー性製剤したも、すべての構造が多いの なったことを引します。 V.スティック絞りを開節 (James) Same of BYWe sell at his, were solvered der Verwendung Jugsich-Ditt austrat.

All Verwendung Schalen für den Contralier aus sell gemit der ihn die erkeine Males, Solviere für den Contralier aus sell gemit der ihn die erkeine Males, Solviere für den sellerzeitig die Manne 1881 – DOSAI on 1—1. One Annagelaustrate beitet some 10 Gebaum die ersonliche einem für Manne 1—1. Dem dem der Propriet uns werder Siller, ihm die Annagelaustrate del solv, um die Volderwang absolute delen. JC200 serie L Verbindung Methode

Cities schellen Sie den Flagssugmedus
den Stick nicht, während er angeschlossen int. Dis Verbindung innen strict in geseicht geseiche, bille Anigem Die der der Gefellem zur Literung. G. Schalter Sie dem Physiosymoton sein. II Aktivieren Sie Glustoeth am Mobilelation und öffnen Sie die AFFStedunter " (Ç CASE L. Gobern Sie die Verbindungsschnithteße ein jelebe AGBBang (+1) © Lüschen Sie die Intermationen zu diesem Contration in der Beildr-Krimmel. Plact Systemeinstellung - Rogler und Sensamn - Regiler absorbalt Wireless-Controller

motion Ets mind other Drebbluten (Natro Muserguterung angeboten

IV. Programmierung Einstellung 2ar Bhannay Auf der Rodesele des Contrellen gibt es 2 programmetale Rücksaten (Infoht 1 von denen jede alle Kombinsten von S21 Funktionstanten programmiert worden kar

Application and the second sec

deservizione di si dei hirutation dei Colodero di solici. Selevizio di si dei hirutation dei Colodero dei Wilchelle dei Elli i giuli figi vini Ed I mach delere in Gelevizione harroni und Ed I mach delere i Soliciande harroni und Ed I mach delere i Soliciande harroni und Scholare i Selevizione harroni und Scholare i Selevizione i an dei Policiande i Colore i Selevizione i Selevi

brates once, it indicates that the continuous filing function to so function keys has been clearbed.

Languaire II List Bilita poo berunde, was erveri languairen Mate-der Signalisad de emprijoti. Albilit 12 Listabilita pro Diskunde, was ervern militaren Minken der Signalisadas emprijoti. Sidned 20 Listabilitat pro Diskunde, was einem sidned lan Elinkon der Signalisaspe emprisati.

II. Turbo Function

VIII. About charging
Under connection status: The signal light feature shorts while charging. After being My stanged, the signal light remains constant to.

What should I do if the compiler care work stop, the carefular does not charge

station to tapic agrantes a verificati.

Perfection a series of control and official and extraction enterests.

In the control and official and offi

PONDs and it in any ween our controller cost benicles weeden have, do Vibration not authors do Commiser note sudjection was done the Statistical Association in autonomy south Agiliar like in Marchania Proclaman, or and done Commiser enforces, versuches this, and the Reference forces the public commission of the Reference and the public commission of the Reference public commission of

reduction: Connect the controller to the device.

© Search for "KeyLinker" in the mobile APP stone, down bad a least of it.

VL APP-Assistenz
Deser Committee van nit sits der Yay, bleier 409 verwender, werden und ermöglich den Michael der Tasten, die Einstellung der kölne Zue der Allystel, der Breiteng der Kille zu der Allystel, der Breiteng der Kille zu der Allystel, der Breiteng der Kille zu der Allystelle der



尺寸: 90*120mm 材质: 128g铜版纸,黑白双面印刷,骑马钉

Installation steps

-

(---

L Connection Method

Metion: Please turn of six time mode, Please do not touch the
postest while connecting.

0

E

montageschritte nans outo Kanede: hen Sie den Verschlasschalter auf der Rückse

natura da Araba en esan terra.

JC209 series

Wireless Controller

Quick Start Guide

Schnellstartanleitung

0,

FCC Requirement

changes or modifications not expressly approved by the party responsible for compliance could void the user' s authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.