



RF Test Report

FCC ID	:	2AJFX-Z60
EUT	:	Dash Cam
MODEL	:	DDPAI Z60
BRAND NAME	:	DDPAI
APPLICANT	:	DDPAI Technology Co., Ltd.
Classification of Test	:	N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Test Report No.: FCCSZ2024-0062-H

Page 2 of 9

Client		Name: DDPAI Technology Co., Ltd. Address: 28F, Building 8A, International Innovation Valley, Nanshan District, Shenzhen, Guangdong Province					
Manufacturer		Name: DDPAI Technology Co., Ltd. Address: 28F, Building 8A, International Innovation Valley, Nanshan District, Shenzhen, Guangdong Province					
Factory		Name: DDPai vision equipment Co.,Ltd Address: Floor 4 & Floor 5& Floor 6, Building 5, Guangda Manufacturing Tangxia Wisdom Post, No.8, Fengbao Road, Tangxia Town, Dongguan City, Guangdong Province, China					
Equipment Ur	Name: Dash Cam Model/Type: DDPAI Z60 Additional Model: Z60、DDPAI Z45、Z45 Brand: DDPAI Serial NO.: N/A Sample NO.:3-1						
Date of Receipt.	2024.08	.23	Date o	f Testing	2024.08.23~2024.10.22		
1	Test Specificatio	on		Test Result			
FCC Part 2 (Section KDB 447498 D04v01		on 2.1091) ,IEEE C95.3		PASS			
Evaluation of Tes	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2024.10.25						
Compiled by:		Reviewed by: Moxiant			Approved by:		
Carvia	nym	2	Mo Xianb	iao		MS	
<u>Cai Jia</u>	nyu nyu	2	Mo Xianb <u>Mo Xianbiac</u>	iao 2	Dc	ang Sanbi	
<u>Cai Jia</u> Name	луµ nyu Signature	Narr	Mo Xianb <u>Mo Xianbiac</u> ne S	iao 2 Signature	<u>Dc</u> Name	ong Sanbi Signature	
Cai Jia Name Other Aspects: No	NYU Nguature ONE.	Nam	Mo Xianbiac Mo Xianbiac ne S	iao 2 Signature	<u>Do</u> Name	ong Sanbi Signature	

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



Test Report No.: FCCSZ2024-0062-H

Page 3 of 9

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. GENERAL PRODUCT INFORMATION	5
2. RF EXPOSURE LIMIT	6
3. CLASSIFICATION	7
4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	7



Page 4 of 9

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED	
FCCSZ2024-0062-H	Original release	2024.10.25	

Test Report No.: FCCSZ2024-0062-H

Page 5 of 9

1. GENERAL PRODUCT INFORMATION

PRODUCT	Dash Cam
BRAND	DDPAI
MODEL	DDPAI Z60
ADDITIONAL MODEL	Z60、DDPAI Z45、Z45
POWER SUPPLY	DC 5V
STANDARDS	FCC Part 2 (Section 2.1091) KDB 447498 D04,IEEE C95.3

Remark:

1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3. EUT photo refer to the report (Report NO.: FCCSZ2024-0062-EUT).

Test Report No.: FCCSZ2024-0062-H

Page 6 of 9

2. RF EXPOSURE LIMIT

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF SOURCE FREQUENCY (MHZ)	THRESHOLD ERP(W)			
0.3 -1.34	1,920 R ²			
1.34 - 30	3,450 R ² F ²			
30 -300	3.83 R ²			
300-1500	0.0128 R ² F			
1500-100,000	19.2R ²			



Page 7 of 9

3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The measured conducted power

Mode	Antenna	Power (dBm)
BT-LE	ANT1	6.27
5.1G WIFI	ANT1	14.76

Page 8 of 9

MAXIMUM PERMISSIBLE EXPOSURE (FCC)

Mode	Frequency (MHz)	Antenna	Max Power (dBm)	Antenna Gain (dBi)	R (cm)	EIRP (dBm)	ERP (dBm)	ERP (W)	Threshold ERP(W)	Ratio
BT-LE	2402-2480	ANT1	6.27	0.8	20	7.07	4.92	0.003	0.77	0.004
5.1G WIFI	5180-5240	ANT1	14.76	1.29	20	16.05	13.9	0.025	0.77	0.032
Sum of ratio = BT-LE + WIFI								0.036		

Note1: This device can operate simultaneously in BT and WIFI. **Note2:** ERP=EIRP-2.15dB

Conclusion:

Therefore, the worst-case situation is 0.036(Sum of Ratios), which is less than "1". This confirmed that the device compliance with FCC RF exposure requirements..

----- End of the Report ------



Page 9 of 9

Important

(1) The test report is invalid without the official stamp of CVC;

(2) Any part photocopies of the test report are forbidden without the written permission from CVC;

(3) The test report is invalid without the signatures of Approval and Reviewer;

- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.

(7) As for the test result "-" or "N" means "not applicable", "/" means "not test", "P" means "pass" and "F" means "fail"

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong,China Post Code: 518110 Tel: 0755-23763060-8805 Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn http://www.cvc.org.cn