

# MPE/RF EXPOSURE REPORT



Evaluation of: Nanit N151 Smart Baby Monitor

To: FCC CFR 47 Part 1.1310

Report Serial No.: UDIS01-U9 Rev A FCC MPE

This report supersedes: NONE

Applicant: UdiSense Inc. (DBA: Nanit)  
244 Fifth Avenue  
Suite # 2702,  
New York, NY 10001  
USA

**Product Function:** Wireless Video Baby Monitor

**Issue Date:** 13<sup>th</sup> August 2018

## **This Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d (\text{mW/cm}^2) = \text{EIRP} / (4 * \pi * d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ { (G (\text{dBi}) / 10)}$$

The calculations in the table below use the highest measured conducted power values together with the antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

### Specification - Maximum Permissible Exposure Limits.

The Limit is defined in Table 1 of FCC §1.1310.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm <sup>2</sup> ) @ Safe Distance
2400 – 2483.5 (BLE)	5.42	3.48	7.29	5.36	0.004	1.0	1.22	0.0037
2400 – 2483.5 (DTS)	5.42	3.48	17.00	50.12	0.035	1.0	3.73	0.0347
5150-5850	4.69	2.94	17.66	58.34	0.03	1.0	3.70	0.0342

Note: For mobile or fixed location transmitters the minimum separation distance is 20cm even if calculations indicate the MPE distance to be less.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)