

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

a)

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	6.5	4.47	27.0	501.19	27	0.245	1
5150-5250	10.5	11.22	20.5	112.20	27	0.137	1
5250-5350	10.5	11.22	16.0	39.81	27	0.049	1
5470-5725	10.5	11.22	15.0	31.62	27	0.039	1
5725-5850	10.5	11.22	26.0	398.11	27	0.488	1

Note: 1. The tune up conducted power was declared by the applicant.

2. The 2.4G Wi-Fi can transmit at the same time with the 5G Wi-Fi.

3. For the 2.4G Wi-Fi, as it can support the beam-forming function, so the directional antenna gain should add the $10\lg 2$, $3.5\text{dBi} + 10\lg 2 = 6.5\text{dBi}$.

4. For the 5G Wi-Fi, as it can support the beam-forming function, so the directional antenna gain should add the $10\lg 4$, $4.5\text{dBi} + 10\lg 4 = 10.5\text{dBi}$.

Simultaneous transmitting consideration (worst case):

The ratio = $\text{MPE}_{2.4\text{G Wi-Fi}}/\text{limit} + \text{MPE}_{5\text{G Wi-Fi}}/\text{limit} = 0.245 + 0.488 = 0.733 < 1.0$, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 27cm from nearby persons.

Result: Compliant.